



**3M General Offices**  
3M Center  
St. Paul, MN 55144-1000  
1-800-364-3577 or (651) 737-6501 (24 hours)

2018-12-27 21:30:02.643

## Safety Data Sheet

---

Purchase Order #: 7-62373  
Customer Number: 0026299440

MSDS COORDINATOR  
FACTORY MOTOR PARTS  
5328 W ROOSEVELT ST  
PHOENIX, AZ 85043-2713  
USA

Dear MSDS COORDINATOR

Enclosed is the Safety Data Sheet (SDS)\* for the product that your company recently purchased from 3M.

Please forward the attached document(s) to the individual in your organization responsible for hazard communication.

If you are a distributor and resell this product, OSHA and EPA require that you transmit this SDS information to your customers at the time of first shipment or whenever you receive revised SDSs from 3M.

3M SDSs are available over the Internet at [www.3m.com/MSDSSearch](http://www.3m.com/MSDSSearch). You may also order a DVD of 3M SDSs by calling 1-800-364-3577.

3M is committed to meeting our customer requirements. Please contact your 3M customer service or sales representative if you have any questions. If you do not know whom to contact, please call the 3M Product Information Center at 1-800-364-3577.

**If you are not currently receiving 3M SDSs by e-mail and would like to do so, please contact our eSDS Administrator at [emsdsadmin@mmm.com](mailto:emsdsadmin@mmm.com) or by calling 651-736-5875.**

\*An Article Information Sheet (AIS) or Article Information Letter (AIL) may be enclosed in place of an SDS if the product is an article which does not require an SDS under the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.





## Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	36-1997-0	<b>Version Number:</b>	2.00
<b>Issue Date:</b>	10/22/18	<b>Supersedes Date:</b>	09/20/16

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ High Power Brake Cleaner, 08880

#### Product Identification Numbers

60-4550-8946-0, 60-4550-9100-3  
7100136846, 7100150166

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive, Brake Cleaner

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Automotive Aftermarket
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

#### 2.1. Hazard classification

Flammable Aerosol: Category 1.  
Gas Under Pressure: Liquefied gas.  
Acute Toxicity (oral): Category 4.  
Serious Eye Damage/Irritation: Category 2B.  
Aspiration Hazard: Category 1.  
Reproductive Toxicity: Category 2.  
Carcinogenicity: Category 2.  
Specific Target Organ Toxicity (single exposure): Category 1.  
Specific Target Organ Toxicity (single exposure): Category 3.

Specific Target Organ Toxicity (repeated exposure): Category 1.

## 2.2. Label elements

### Signal word

Danger

### Symbols

Flame | Gas cylinder | Exclamation mark | Health Hazard |

### Pictograms



### Hazard Statements

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Harmful if swallowed.

Causes eye irritation.

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

Suspected of damaging fertility or the unborn child.

Suspected of causing cancer.

Causes damage to organs:

sensory organs |

Causes damage to organs through prolonged or repeated exposure:

nervous system |

sensory organs |

### Precautionary Statements

#### General:

Keep out of reach of children.

#### Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

#### Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Rinse mouth.

Do NOT induce vomiting.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Specific treatment (see Notes to Physician on this label).

Call a POISON CENTER or doctor/physician if you feel unwell.

#### Storage:

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.

Store in a well-ventilated place.

Store locked up.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

#### Notes to Physician:

This product contains methanol. If there is a reasonable suspicion of methanol poisoning, intravenous (IV) administration with either fomepizole (preferred) or ethanol (if fomepizole is unavailable) should be considered as part of the medical management.

7% of the mixture consists of ingredients of unknown acute oral toxicity.

8% of the mixture consists of ingredients of unknown acute dermal toxicity.

8% of the mixture consists of ingredients of unknown acute inhalation toxicity.

### SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
2-Methylhexane	591-76-4	10 - 30 Trade Secret *
3-Methylhexane	589-34-4	10 - 30 Trade Secret *
Xylene	1330-20-7	10 - 30 Trade Secret *
Ethylbenzene	100-41-4	1 - 10 Trade Secret *
Methyl Alcohol	67-56-1	5 - 10 Trade Secret *
2,3-Dimethylpentane	565-59-3	3 - 7 Trade Secret *
Carbon Dioxide	124-38-9	1 - 5 Trade Secret *
trans-1,3-Dimethylcyclopentane	1759-58-6	1 - 5 Trade Secret *
Heptane	142-82-5	0.5 - 2.5 Trade Secret *
3,3-Dimethylpentane	562-49-2	0.5 - 1.5 Trade Secret *
3-Ethylpentane	617-78-7	0.5 - 1.5 Trade Secret *
Dimethylcyclopentane	2532-58-3	0.5 - 1.5 Trade Secret *
trans-1,2-Dimethylcyclopentane	822-50-4	0.5 - 1.5 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

##### Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

**If Swallowed:**

Do not induce vomiting. Get immediate medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

This product contains methanol. If there is a reasonable suspicion of methanol poisoning, intravenous (IV) administration with either fomepizole (preferred) or ethanol (if fomepizole is unavailable) should be considered as part of the medical management.

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

Use a fire fighting agent suitable for the surrounding fire.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**Hazardous Decomposition or By-Products****Substance**

Carbon monoxide

Carbon dioxide

Toxic Vapor, Gas, Particulate

**Condition**

During Combustion

During Combustion

During Combustion

**5.3. Special protective actions for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material

as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethylbenzene	100-41-4	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin.
Ethylbenzene	100-41-4	OSHA	TWA:435 mg/m3(100 ppm)	
Carbon Dioxide	124-38-9	ACGIH	TWA:5000 ppm;STEL:30000 ppm	
Carbon Dioxide	124-38-9	OSHA	TWA:9000 mg/m3(5000 ppm)	
Xylene	1330-20-7	ACGIH	TWA:100 ppm;STEL:150 ppm	A4: Not class. as human carcin
Xylene	1330-20-7	OSHA	TWA:435 mg/m3(100 ppm)	
Heptane	142-82-5	ACGIH	TWA:400 ppm;STEL:500 ppm	
Heptane	142-82-5	OSHA	TWA:2000 mg/m3(500 ppm)	
Heptane, all isomers	562-49-2	ACGIH	TWA:400 ppm;STEL:500 ppm	
2,3-Dimethylpentane	565-59-3	ACGIH	TWA:400 ppm;STEL:500 ppm	
3-Methylhexane	589-34-4	ACGIH	TWA:400 ppm;STEL:500 ppm	
2-Methylhexane	591-76-4	ACGIH	TWA:400 ppm;STEL:500 ppm	
Heptane, all isomers	617-78-7	ACGIH	TWA:400 ppm;STEL:500 ppm	
Methyl Alcohol	67-56-1	ACGIH	TWA:200 ppm;STEL:250 ppm	SKIN
Methyl Alcohol	67-56-1	OSHA	TWA:260 mg/m3(200 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)****Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Fluoroelastomer

Polymer laminate

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>General Physical Form:</b>	Liquid
<b>Specific Physical Form:</b>	Aerosol
<b>Odor, Color, Grade:</b>	Clear colorless; Solvent odor
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point</b>	<i>No Data Available</i>
<b>Boiling Point</b>	<i>No Data Available</i>
<b>Flash Point</b>	>=15 °F
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	<i>No Data Available</i>
<b>Flammable Limits(UEL)</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	40 psi [ <i>@ 70 °F</i> ]
<b>Vapor Density</b>	>=1.0 [ <i>Ref Std: AIR=1</i> ]
<b>Density</b>	6.5 lb/gal
<b>Specific Gravity</b>	0.78 [ <i>Ref Std: WATER=1</i> ]
<b>Solubility in Water</b>	Nil
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Viscosity</b>	<i>No Data Available</i>



<b>Hazardous Air Pollutants</b>	39.3 % weight [ <i>Test Method</i> :Calculated]
<b>Volatile Organic Compounds</b>	749 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1]
<b>Volatile Organic Compounds</b>	96 % weight [ <i>Test Method</i> :calculated per CARB title 2]
<b>Percent volatile</b>	96 % weight
<b>VOC Less H2O &amp; Exempt Solvents</b>	749 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

Sparks and/or flames

### 10.5. Incompatible materials

Strong acids

Strong oxidizing agents

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

**Skin Contact:**

May be harmful in contact with skin.

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. May cause additional health effects (see below).

**Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion:**

Harmful if swallowed. Chemical (Aspiration) Pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish colored skin (cyanosis), and may be fatal.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:****Single exposure may cause target organ effects:**

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

May cause blindness.

**Prolonged or repeated exposure may cause target organ effects:**

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Ethylbenzene	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE2,000 - 5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE300 - 2,000 mg/kg
3-Methylhexane	Dermal	Rabbit	LD50 3,000 mg/kg
3-Methylhexane	Inhalation-Vapor (4 hours)	Rat	LC50 > 80 mg/l
3-Methylhexane	Ingestion	Rat	LD50 17,000 mg/kg
Xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg

Xylene	Inhalation-Vapor (4 hours)	Rat	LC50 29 mg/l
Xylene	Ingestion	Rat	LD50 3,523 mg/kg
2-Methylhexane	Dermal	Rabbit	LD50 3,000 mg/kg
2-Methylhexane	Inhalation-Vapor (4 hours)	Rat	LC50 > 80 mg/l
2-Methylhexane	Ingestion	Rat	LD50 17,000 mg/kg
Methyl Alcohol	Dermal		LD50 estimated to be 1,000 - 2,000 mg/kg
Methyl Alcohol	Inhalation-Vapor		LC50 estimated to be 10 - 20 mg/l
Methyl Alcohol	Ingestion		LD50 estimated to be 50 - 300 mg/kg
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-Vapor (4 hours)	Rat	LC50 17.4 mg/l
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
2,3-Dimethylpentane	Dermal	Rabbit	LD50 > 2,000 mg/kg
2,3-Dimethylpentane	Inhalation-Vapor (4 hours)	Rat	LC50 > 73.5 mg/l
2,3-Dimethylpentane	Ingestion	Rat	LD50 > 5,000 mg/kg
Carbon Dioxide	Inhalation-Gas (4 hours)	Rat	LC50 > 53,000 ppm
Heptane	Dermal	Rabbit	LD50 3,000 mg/kg
Heptane	Inhalation-Vapor (4 hours)	Rat	LC50 103 mg/l
Heptane	Ingestion	Rat	LD50 > 15,000 mg/kg
3,3-Dimethylpentane	Dermal	Rabbit	LD50 > 2,000 mg/kg
3,3-Dimethylpentane	Inhalation-Vapor (4 hours)	Rat	LC50 > 73.5 mg/l
3,3-Dimethylpentane	Ingestion	Rat	LD50 > 5,000 mg/kg
Dimethylcyclopentane	Ingestion		LD50 estimated to be 300 - 2,000 mg/kg
3-Ethylpentane	Dermal		estimated to be > 5,000 mg/kg
3-Ethylpentane	Inhalation-Dust/Mist		estimated to be > 12.5 mg/l
3-Ethylpentane	Inhalation-Vapor		estimated to be > 50 mg/l
3-Ethylpentane	Ingestion		estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
3-Methylhexane	Rabbit	Minimal irritation
Xylene	Rabbit	Mild irritant
2-Methylhexane	Rabbit	Minimal irritation
Methyl Alcohol	Rabbit	Mild irritant
Ethylbenzene	Rabbit	Mild irritant
2,3-Dimethylpentane	Rabbit	Mild irritant
Heptane	Human	Mild irritant
3,3-Dimethylpentane	Rabbit	Mild irritant

### Serious Eye Damage/Irritation

Name	Species	Value
3-Methylhexane	Rabbit	No significant irritation
Xylene	Rabbit	Mild irritant
2-Methylhexane	Rabbit	No significant irritation

Methyl Alcohol	Rabbit	Moderate irritant
Ethylbenzene	Rabbit	Moderate irritant
2,3-Dimethylpentane	Rabbit	Mild irritant
Heptane	Professional judgement	Moderate irritant
3,3-Dimethylpentane	Rabbit	Mild irritant

### Skin Sensitization

Name	Species	Value
Methyl Alcohol	Guinea pig	Not classified
Ethylbenzene	Human	Not classified

### Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
Xylene	In Vitro	Not mutagenic
Xylene	In vivo	Not mutagenic
Methyl Alcohol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Methyl Alcohol	In vivo	Some positive data exist, but the data are not sufficient for classification
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not sufficient for classification
Heptane	In Vitro	Not mutagenic

### Carcinogenicity

Name	Route	Species	Value
Xylene	Dermal	Rat	Not carcinogenic
Xylene	Ingestion	Multiple animal species	Not carcinogenic
Xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Methyl Alcohol	Inhalation	Multiple animal species	Not carcinogenic
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Xylene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Xylene	Ingestion	Not classified for development	Mouse	NOAEL Not available	during organogenesis
Xylene	Inhalation	Not classified for development	Multiple animal species	NOAEL Not available	during gestation
Methyl Alcohol	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,600 mg/kg/day	21 days
Methyl Alcohol	Ingestion	Toxic to development	Mouse	LOAEL 4,000	during

				mg/kg/day	organogenesis
Methyl Alcohol	Inhalation	Toxic to development	Mouse	NOAEL 1.3 mg/l	during organogenesis
Ethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	prematuring & during gestation
Carbon Dioxide	Inhalation	Not classified for male reproduction	Mouse	LOAEL 350,000 ppm	not available
Carbon Dioxide	Inhalation	Not classified for development	Rat	LOAEL 60,000 ppm	24 hours

**Lactation**

Name	Route	Species	Value
Xylene	Ingestion	Mouse	Not classified for effects on or via lactation

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
3-Methylhexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL 4 mg/l	4 hours
3-Methylhexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	not available
3-Methylhexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Not available	NOAEL Not available	
Xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
Xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Xylene	Inhalation	eyes	Not classified	Rat	NOAEL 3.5 mg/l	not available
Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	eyes	Not classified	Rat	NOAEL 250 mg/kg	not applicable
2-Methylhexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL 4 mg/l	4 hours
2-Methylhexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	not available
2-Methylhexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Not available	NOAEL Not available	
Methyl Alcohol	Inhalation	blindness	Causes damage to organs	Human	NOAEL Not available	occupational exposure
Methyl Alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
Methyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	6 hours
Methyl Alcohol	Ingestion	blindness	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
Methyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Ethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
2,3-Dimethylpentane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Heptane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Heptane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Heptane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
3,3-Dimethylpentane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
Xylene	Inhalation	auditory system	May cause damage to organs through prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Inhalation	heart   endocrine system   gastrointestinal tract   hematopoietic system   muscles   kidney and/or bladder   respiratory system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
Xylene	Ingestion	auditory system	Not classified	Rat	NOAEL 900 mg/kg/day	2 weeks
Xylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
Xylene	Ingestion	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	heart   skin   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   respiratory system	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
Methyl Alcohol	Inhalation	liver	Not classified	Rat	NOAEL 6.55 mg/l	4 weeks
Methyl Alcohol	Inhalation	respiratory system	Not classified	Rat	NOAEL 13.1 mg/l	6 weeks
Methyl Alcohol	Ingestion	liver   nervous system	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years

Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
Ethylbenzene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	auditory system	Not classified	Rat	NOAEL 2.4 mg/l	5 days
Ethylbenzene	Inhalation	endocrine system	Not classified	Mouse	NOAEL 3.3 mg/l	103 weeks
Ethylbenzene	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair   muscles	Not classified	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart   immune system   respiratory system	Not classified	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Ingestion	liver   kidney and/or bladder	Not classified	Rat	NOAEL 680 mg/kg/day	6 months
Carbon Dioxide	Inhalation	heart   bone, teeth, nails, and/or hair   liver   nervous system   kidney and/or bladder   respiratory system	Not classified	Rat	LOAEL 60,000 ppm	166 days
Heptane	Inhalation	liver   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 12 mg/l	26 weeks

#### Aspiration Hazard

Name	Value
3-Methylhexane	Aspiration hazard
Xylene	Aspiration hazard
2-Methylhexane	Aspiration hazard
Ethylbenzene	Aspiration hazard
2,3-Dimethylpentane	Aspiration hazard
Heptane	Aspiration hazard
3,3-Dimethylpentane	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

### Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable

regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information**

**15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:**

**Physical Hazards**

Flammable (gases, aerosols, liquids, or solids)

Gas under pressure

**Health Hazards**

Acute toxicity

Aspiration Hazard

Carcinogenicity

Reproductive toxicity

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Methyl Alcohol	67-56-1	Trade Secret 5 - 10
Ethylbenzene	100-41-4	Trade Secret 1 - 10
Xylene	1330-20-7	Trade Secret 10 - 30
Xylene (Benzene, dimethyl-)	1330-20-7	10 - 30

**15.2. State Regulations**

Contact 3M for more information.

**California Proposition 65**

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Listing</u>
ETHYLBENZENE	100-41-4	Carcinogen
METHANOL	67-56-1	Developmental Toxin

**15.3. Chemical Inventories**

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

**15.4. International Regulations**

Contact 3M for more information.



This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

Health: 2 Flammability: 4 Instability: 0 Special Hazards: None  
Aerosol Storage Code: 3

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	36-1997-0	<b>Version Number:</b>	2.00
<b>Issue Date:</b>	10/22/18	<b>Supersedes Date:</b>	09/20/16

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at [www.3M.com](http://www.3M.com)

