

# Material Safety Data Sheet

B-9 CHEM-DIP CARBURETOR AND PARTS CLEANER

MSDS No. 014

Date of Preparation: 10/29/99

REVISED: 09/21/00

## Section 1 - Chemical Product and Company Identification

**Product Name:** B-9 CHEM-DIP CARBURETOR AND PARTS CLEANER

**Part Number(s):** 0901, 0902, 0905, 0996, 0955 (Blend 2AAM)

**CAS Number:** NOT APPLICABLE TO MIXTURES

**Product Class:** Automotive product

**Manufacturer:** Berryman Products, Inc., 3800 E. Randol Mill Rd., Arlington, TX 76011-5434

**Information Phone No.:** 1-800-433-1704 **Emergency Phone No.:** 1-800-535-5053

## Section 2 - Composition / Information on Ingredients

Ingredient Name	CAS Number	% wt
METHYLENE CHLORIDE (DICHLOROMETHANE)	75-09-2	40-45
MONOCHLOROTOLUENE	25168-05-2	30-35
CRESOLS	Mixture	10-15
MIXED XYLENES	1330-20-7	5-10
SODIUM BICHROMATE	10588-01-9	<4
ETHYL BENZENE	100-41-4	<2

Ingredient	OSHA TWA	ACGIH TWA	ACGIH STEL
METHYLENE CHLORIDE (DICHLOROMETHANE)	125	50	NA
MONOCHLOROTOLUENE	Not established	50	Not established
CRESOLS	5	5	Not established
MIXED XYLENES	100	100	150
SODIUM BICHROMATE	Not established	Not established	Not established
ETHYL BENZENE	100	100	125

## Section 3 - Physical and Chemical Properties

**Physical State:** LIQUID

**Appearance and Odor:** CLEAR, LIGHT BROWN, ANTISEPTIC

**Vapor Density (Air=1):** HEAVIER THAN AIR

**Specific Gravity (@ 20 °C):** 1.126

**Density:** 9.39 lbs/gal

**Boiling Range:** 104-324 °F

**Refractive Index (@ 25 °C):** 1.4848

**% Volatile:** 85

**Evaporation Rate:** SLOWER THAN ETHER

**Vapor Pressure (@ 68 °F):** 350 mm/Hg (Major component)

## Section 4 - Fire-Fighting Measures

**Flash Point:** 210 °F


**Flash Point Method:** CC

**LEL:** 13 % v/v (Major component)

**Flammability Classification:** Class IIIB

**Extinguishing Media:** Carbon dioxide, foam, dry chemicals.

NFPA



**Unusual Fire or Explosion Hazards:** Combustible liquid. Vapors can cause flash fire. Toxic. Poison. Corrosive.

**Special Fire-Fighting Procedures:** Do not release runoff from fire control methods to sewers or waterways. Wear self-contained breathing apparatus pressure demand, MSNA/OSHA (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

### Section 5 - Stability and Reactivity

**Stability:** Stable.

**Polymerization:** Hazardous polymerization will not occur.

**Incompatibilities & Conditions to Avoid:** Isolate from oxidizers, heat, sparks, electric equipment and open flame. May be corrosive to aluminum, magnesium, titanium and their alloys.

**Hazardous Decomposition Products:** Carbon monoxide, carbon dioxide, chlorine containing gases, and hydrogen chloride.

### Section 6 - Health Hazard Information

#### Potential Health Effects

**Primary Entry Routes:** Skin, dermal, inhalation and ingestion.

**Target Organs:** Eyes, skin, respiratory system, CNS, liver and kidneys.

**Effects of Overexposure:** May cause irritation to the eyes, skin, nose, throat and respiratory system. Nausea, headache, light-headedness, dizziness, and dermatitis. Burns and severe corneal damage may occur if direct contact with skin and eyes. Harmful or fatal if swallowed.

**Carcinogenicity:** IARC, NTP, and OSHA list Hexavalent Chromium as a carcinogen.

**Chronic Effects:** May affect liver, kidneys or central nervous system. Can cause nervous system depression. Potential cancer hazard.

#### Emergency and First Aid Procedures

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. Get medical attention immediately.

**Eye Contact:** Immediately flush eyes with plenty of water. Get medical attention IMMEDIATELY.

**Skin Contact:** Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

**Ingestion:** GET MEDICAL ATTENTION IMMEDIATELY. Do not induce vomiting.

### Section 7 - Spill, Leak, and Disposal Procedures

**Spill /Leak Procedures:** Eliminate all sources of ignition. Stop spill at source. Wear appropriate personal protective equipment (Sec. 8). Contain the spill to facilitate clean up with absorbent. Use non-sparking tools and equipment. Transfer to disposal containers. Do not release into sewers or waterways.

**Disposal:** Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

### Section 8 - Exposure Controls / Personal Protection

**Ventilation:** Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

#### Administrative Controls:

**Respiratory Protection:** Respirator not required if airborne concentrations are below OSHA PELs (Sec. 2). If necessary, follow OSHA respirator regulations (29 CFR 1910.134) and wear an MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or non-routine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA.

**Protective Clothing/Equipment:** Wear chemically protective gloves and aprons to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

**Safety Stations:** Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

**Contaminated Equipment:** Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

**Comments:** Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

### Section 9 - Special Precautions and Comments

**Handling Precautions:** Avoid prolonged breathing of vapor and contact with eyes, skin, and clothing. Use in well ventilated area. Wash thoroughly after handling.

**Storage Requirements:** Keep away from heat, sparks and flame. Keep container closed when not in use. Keep away from food.

**California Proposition 65:** This product contains the following chemicals known to the state of California to cause cancer and/or reproductive toxicity: Hexavalent Chromium and Dichloromethane (Methylene chloride).

**DOT Transportation Data (49 CFR 172.101):**

<u>PART NUMBER(s)</u>	<u>SHIPPING NAME</u>	<u>HAZARD CLASS</u>	<u>ID NO.</u>	<u>PACKING GROUP</u>
0996, 0901	Consumer Commodity	ORM-D	N/A	N/A
0902, 0905, 0955	Toxic Liquids Organic, N.O.S., contains (Dichloromethane)	6.1	UN 2810	III

**SARA TITLE III SECTION 313 SUPPLIER NOTIFICATION**

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know-Act of 1986 & of 40CFR 372:

<u>Chemical Name</u>	<u>CAS Number</u>	<u>% wt.</u>
Methylene chloride (Dichloromethane)	75-09-2	40-45
m-Cresol	108-39-4	5-10
Mixed xylenes	1330-20-7	5-10
p-Cresol	106-44-5	<4
Hexavalent chromium (Sodium bichromate)	7440-47-3	<4
Ethyl benzene	100-41-4	<2

**Prepared By:** Morie Stone

**Disclaimer:** All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publications of use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.