# **Permatex.**

# SAFETY DATA SHEET

Revision Date 25-Feb-2015 Version 1

# 1. IDENTIFICATION

**Product identifier** 

Product Name 09117 REAR WINDOW DEFOGGER REPAIR KIT PRS PART 1

Other means of identification

Product Code 390144B Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Coating

Uses advised against No information available

Details of the supplier of the safety data sheet

<u>Manufacturer Address</u> <u>Distributor</u>

ITW PermatexITW Permatex Canada10 Columbus Blvd.35 Brownridge Road, Unit 1Hartford, CT 06106 USAHalton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

# 2. HAZARDS IDENTIFICATION

# Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

#### Label elements

#### **Emergency Overview**

#### Danger

Causes serious eye irritation May cause drowsiness or dizziness Highly flammable liquid and vapor



Appearance Copper Physical state Liquid Odor Alcohol

#### **Precautionary Statements - Prevention**

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

# **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

In case of fire: Use CO2, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

# Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

Not applicable.

Unknown acute toxicity

6.02% of the mixture consists of ingredient(s) of unknown toxicity

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### **Substance**

Chemical Name	CAS No	Weight-%	Trade Secret
SILVER	7440-22-4	30 - 60	*
ETHYL ACETATE	141-78-6	10 - 30	*
ETHANOL	64-17-5	10 - 30	*
PIGMENT ORANGE #13	3520-72-7	1 - 5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

Revision Date 25-Feb-2015

**Description of first aid measures** 

**General advice** Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. If symptoms persist, call a physician. Wash contaminated clothing

before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

**Ingestion** IF SWALLOWED. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person.

Self-protection of the first aider

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

#### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Highly flammable. May be ignited by heat, sparks or flames.

**Explosion data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions In case of fire: Stop leak if safe to do so. Avoid breathing vapors or mists. Avoid contact

with eyes and skin. Use personal protection recommended in Section 8.

**Environmental precautions** 

**Environmental precautions**Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with

inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling.

Wash contaminated clothing before reuse.

#### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static

electricity).

Incompatible materials Strong oxidizing agents. Peroxides. Acids. Alkali.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
SILVER	TWA: 0.1 mg/m <sup>3</sup> dust and fume	TWA: 0.01 mg/m <sup>3</sup>	IDLH: 10 mg/m <sup>3</sup> dust
7440-22-4	_	(vacated) TWA: 0.01 mg/m <sup>3</sup>	TWA: 0.01 mg/m <sup>3</sup> dust
ETHYL ACETATE 141-78-6	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m³ (vacated) TWA: 400 ppm (vacated) TWA: 1400 mg/m³	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m³
ETHANOL 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m³

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective gloves and protective clothing.

**Respiratory protection**Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Tag Closed Cup

Air = 1

#### Information on basic physical and chemical properties

Physical state Liquid
Appearance Copper
Odor Alcohol

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

**pH** Does not apply

Melting point / freezing pointNo information availableBoiling point / boiling range> 38 °C / 100 °FFlash point-10 °C / 14 °F

Evaporation rate No information available

Flammability (solid, gas) No information available Flammability Limit in Air

Upper flammability limit: 11.0%

Lower flammability limit: 2.2%

Vapor pressure Not Determined Vapor density >1

Relative density 1.48

Water solubility Partially soluble

Solubility in other solvents No information available No information available **Partition coefficient** No information available **Autoignition temperature Decomposition temperature** No information available No information available Kinematic viscosity **Dynamic viscosity** No information available **Explosive properties** No information available Oxidizing properties No information available

**Other Information** 

Softening pointNo information availableMolecular weightNo information available

VOC Content (%) 50%

DensityNo information availableBulk densityNo information available

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### **Chemical stability**

Stable under recommended storage conditions.

#### **Possibility of Hazardous Reactions**

None under normal processing.

#### **Conditions to avoid**

Heat, flames and sparks.

#### **Incompatible materials**

Strong oxidizing agents, Peroxides, Acids, Alkali

#### **Hazardous Decomposition Products**

Carbon oxides

# 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

**Inhalation** May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

**Skin contact** May cause skin irritation and/or dermatitis.

**Ingestion** Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
SILVER 7440-22-4	> 2000 mg/kg (Rat)	-	-
ETHYL ACETATE 141-78-6	= 5620 mg/kg (Rat)	> 18000 mg/kg(Rabbit)> 20 mL/kg(Rabbit)	-
ETHANOL 64-17-5	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat)4 h
PIGMENT ORANGE #13 3520-72-7	> 5 g/kg(Rat)	-	-

#### Information on toxicological effects

**Symptoms** No information available.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization Germ cell mutagenicity**No information available.
No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
ETHANOL	A3	Group 1	Known	X
64-17-5		-		
PIGMENT ORANGE #13	-	Group 1	Known	X
3520-72-7		-		

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans Not classifiable as a human carcinogen NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Chronic toxicity May cause adverse effects on the bone marrow and blood-forming system. May cause

adverse liver effects. Contains a known or suspected reproductive toxin.

Target Organ Effects Bladder, blood, Central nervous system, Eyes, kidney, liver, Nasal Septum, Reproductive

System, Respiratory system, Skin.

#### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 3458 mg/kg
ATEmix (dermal) 30407 mg/kg
ATEmix (inhalation-dust/mist) 706.9 mg/l

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

None known

8.46% of the mixture consists of components(s) of unknown hazards to the aquatic environment

# 390144B - 09117 REAR WINDOW DEFOGGER REPAIR KIT PRS PART 1

Chemical Name	Algae/aquatic plants	Fish	Crustacea
SILVER 7440-22-4	-	0.00155 - 0.00293: 96 h Pimephales promelas mg/L LC50 static 0.0062: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.064: 96 h Lepomis macrochirus mg/L LC50 static	0.00024: 48 h Daphnia magna mg/L EC50 Static
ETHYL ACETATE 141-78-6	3300: 48 h Desmodesmus subspicatus mg/L EC50	352 - 500: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 220 - 250: 96 h Pimephales promelas mg/L LC50 flow-through 484: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	560: 48 h Daphnia magna mg/L EC50 Static
ETHANOL 64-17-5	-	12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through	9268 - 14221: 48 h Daphnia magna mg/L LC50 2: 48 h Daphnia magna mg/L EC50 Static 10800: 24 h Daphnia magna mg/L EC50

# Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

# **Mobility**

No information available.

Chemical Name	Partition coefficient
ETHYL ACETATE	0.6
141-78-6	
ETHANOL	-0.32
64-17-5	

#### Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

# Waste treatment methods

Disposal of wastes This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

	Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Г	SILVER	-	Included in waste stream:	5.0 mg/L regulatory level	-
	7440-22-4		F039		
	ETHYL ACETATE	-	Included in waste stream:	-	U112
	141-78-6		F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
SILVER 7440-22-4	Toxic
ETHYL ACETATE	Toxic
141-78-6	Ignitable

# 390144B - 09117 REAR WINDOW DEFOGGER REPAIR KIT PRS PART 1

ETHANOL	Toxic
64-17-5	Ignitable

# 14. TRANSPORT INFORMATION

DOT

**UN/ID no** UN 1993

Proper shipping name: Flammable liquids, n.o.s, (Ethyl acetate, Ethyl alcohol), Limited Quantity (LQ)

Hazard Class 3 Packing Group II

**IATA** 

**UN/ID no** ID 8000

Proper shipping name: Consumer commodity, Limited Quantity (LQ)

Hazard Class 9

**IMDG** 

**UN/ID no** UN 1993

Proper shipping name: Flammable liquids, n.o.s, (Ethyl acetate, Ethyl alcohol), Limited Quantity (LQ)

Hazard Class 3
Packing Group II
EmS-No F-E, S-E

# 15. REGULATORY INFORMATION

**International Inventories** 

**TSCA** Complies Complies **DSL/NDSL** Does not comply **EINECS/ELINCS** Does not comply **ENCS IECSC** Complies Complies **KECL** Complies **PICCS** Complies **AICS** 

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# US Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %		
SILVER - 7440-22-4	1.0		
SARA 311/312 Hazard Categories			
Acute health hazard	Yes		
Chronic Health Hazard	No		
Fire hazard	Yes		
Sudden release of pressure hazard	No		
Reactive Hazard	No		

#### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
SILVER 7440-22-4	-	X	Х	-

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
SILVER 7440-22-4	1 lb	-	RQ 1 lb final RQ RQ 0.454 kg final RQ
ETHYL ACETATE 141-78-6	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

# **US State Regulations**

# **California Proposition 65**

This product contains the following Proposition 65 chemicals Ethyl alcohol is only a considered a Proposition 65 developmental hazard when it is indested as an alcoholic beverage

Chemical Name	California Proposition 65
ETHANOL - 64-17-5	Carcinogen
	Developmental
PIGMENT ORANGE #13 - 3520-72-7	Carcinogen

# **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
SILVER 7440-22-4	Х	X	Х
ETHYL ACETATE 141-78-6	X	X	Х
ETHANOL 64-17-5	X	X	Х

#### **U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

NFPAHealth hazards 2Flammability 3Instability 0-HMISHealth hazards 2Flammability 3Physical hazards 0Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 25-Feb-2015

#### Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

# **Permatex.**

# SAFETY DATA SHEET

Revision Date 25-Feb-2015 Version 1

# 1. IDENTIFICATION

**Product identifier** 

Product Name 09117 REAR WINDOW DEFOGGER REPAIR KIT PRS PART 2

Other means of identification

Product Code 190510AA Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Adhesive

Uses advised against No information available

Details of the supplier of the safety data sheet

<u>Manufacturer Address</u> <u>Distributor</u>

ITW PermatexITW Permatex Canada10 Columbus Blvd.35 Brownridge Road, Unit 1Hartford, CT 06106 USAHalton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

# 2. HAZARDS IDENTIFICATION

# Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Specific target organ toxicity (repeated exposure)	Category 2

#### Label elements

#### **Emergency Overview**

#### Danger

Causes severe skin burns and eye damage

May cause an allergic skin reaction

May cause damage to organs through prolonged or repeated exposure

\_\_\_\_\_\_



Appearance Yellow Physical state Liquid Odor Irritating

#### **Precautionary Statements - Prevention**

Do not breathe dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Contaminated work clothing should not be allowed out of the workplace

#### **Precautionary Statements - Response**

Immediately call a POISON CENTER or doctor/physician

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

If skin irritation or rash occurs: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Immediately call a POISON CENTER or doctor/physician IF SWALLOWED: Rinse mouth. DO NOT induce vomiting In case of fire: Use CO2, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep cool

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

May be harmful if swallowed. May be harmful in contact with skin. Harmful to aquatic life with long lasting effects.

Unknown acute toxicity 48.75241% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substance

Chemical Name	CAS No	Weight-%	Trade Secret
HYDROXYALKYL METHACRYLATE	27813-02-1	15 - 40	*
ALIPHATIC URETHANE METHACRYLATE	3290-92-4	5 - 10	*
ACRYLIC ACID	79-10-7	1 - 5	*
ALUMINUM SILICATE	1302-93-8	1 - 5	*
DIMETHYLBENZYL HYDROPEROXIDE	80-15-9	1 - 5	*
GLASS	65997-17-3	1 - 5	*
2-HYDROXYETHYL METHACRYLATE	868-77-9	1 - 5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

**Description of first aid measures** 

**General advice** Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES:. Immediately flush with plenty of water. After initial flushing, remove any

contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while

rinsing. If symptoms persist, call a physician.

**Skin contact** IF ON SKIN:. Immediately flush eyes or skin with plenty of water for at least 15 minutes

while removing contaminated clothing and shoes. Seek immediate medical attention/advice.

Wash contaminated clothing before reuse.

**Inhalation** IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person.

**Self-protection of the first aider**Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

#### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

None in particular.

**Explosion data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological information.

# 190510AA - 09117 REAR WINDOW DEFOGGER REPAIR KIT PRS PART 2

#### Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel

into suitable containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling.

Wash contaminated clothing before reuse.

# Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible materials Strong oxidizing agents, Strong bases

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACRYLIC ACID	TWA: 2 ppm	(vacated) TWA: 10 ppm	TWA: 2 ppm
79-10-7	S*	(vacated) TWA: 30 mg/m <sup>3</sup> (vacated) S*	TWA: 6 mg/m <sup>3</sup>
ALUMINUM SILICATE 1302-93-8	TWA: 1 mg/m³ respirable fraction	-	-
GLASS 65997-17-3	TWA: 1 fiber/cm3 respirable fibers: length >5 µm, aspect ratio >=3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination TWA: 5 mg/m³ inhalable fraction		-

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

Engineering Controls Showers

Eyewash stations Ventilation systems

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Tight sealing safety goggles.

**Skin and body protection** Wear protective gloves and protective clothing.

appropriate.

# 190510AA - 09117 REAR WINDOW DEFOGGER REPAIR KIT PRS PART 2

**General Hygiene Considerations** 

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

Tag Closed Cup

Butyl acetate = 1

Air = 1

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical state Liquid Appearance Yellow Odor Irritating

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

No information available

pH Does not apply

Melting point / freezing point

Boiling point / boiling range

Flash point

No information available

> 149 °C / 300 °F

> 93 °C / > 199 °F

Evaporation rate < 1

Flammability (solid, gas)

Flammability Limit in Air

Upper flammability limit:

Lower flammability limit:

No information available
No information available

Vapor pressure Not determined

Vapor density >1

Relative density 1.08 @ 80°F Water solubility Insoluble

Solubility in other solvents No information available **Partition coefficient** No information available No information available **Autoignition temperature Decomposition temperature** No information available Kinematic viscosity No information available **Dynamic viscosity** No information available **Explosive properties** No information available Oxidizing properties No information available

**Other Information** 

Softening pointNo information availableMolecular weightNo information available

VOC Content (%) 7%

DensityNo information availableBulk densityNo information available

#### 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### **Chemical stability**

Stable under recommended storage conditions.

#### **Possibility of Hazardous Reactions**

None under normal processing.

#### **Conditions to avoid**

Excessive heat.

#### **Incompatible materials**

Strong oxidizing agents, Strong bases

# 190510AA - 09117 REAR WINDOW DEFOGGER REPAIR KIT PRS PART 2

#### **Hazardous Decomposition Products**

Carbon oxides

# 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

**Inhalation** May be harmful if inhaled.

**Eye contact** Severely irritating to eyes. May cause burns.

**Skin contact** Contact causes severe skin irritation and possible burns.

**Ingestion** May be harmful if swallowed. Can burn mouth, throat, and stomach.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
HYDROXYALKYL METHACRYLATE 27813-02-1	= 11200 mg/kg(Rat)	> 3000 mg/kg(Rabbit)	-
ALIPHATIC URETHANE METHACRYLATE 3290-92-4	= 5660 μL/kg(Rat)	= 16 mL/kg(Rabbit)	-
ACRYLIC ACID 79-10-7	= 193 mg/kg (Rat) = 33500 μg/kg (Rat)	= 280 µL/kg ( Rabbit ) = 295 mg/kg ( Rabbit )	= 11.1 mg/L (Rat) 1 h = 3.6 mg/L (Rat) 4 h
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	= 382 mg/kg ( Rat )	= 0.126 mL/kg(Rabbit)	= 220 ppm (Rat) 4 h
2-HYDROXYETHYL METHACRYLATE 868-77-9	= 5050 mg/kg(Rat)	> 3000 mg/kg(Rabbit)	-

# Information on toxicological effects

**Symptoms** No information available.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization**No information available. **Germ cell mutagenicity**No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
ACRYLIC ACID	-	Group 3	-	-
79-10-7		-		
GLASS	-	Group 3	-	-
65997-17-3		-		

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans Not classifiable as a human carcinogen NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Eyes, Respiratory system, Skin.

#### Numerical measures of toxicity - Product Information

#### The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 2564 mg/kg
ATEmix (dermal) 2826 mg/kg
ATEmix (inhalation-dust/mist) 6.6 mg/l

# 12. ECOLOGICAL INFORMATION

12. ECOLOGICAL IN CRIMATION

# **Ecotoxicity**

None known

81.14791% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
HYDROXYALKYL METHACRYLATE 27813-02-1	-	493: 48 h Leuciscus idus melanotus mg/L LC50 static	-
ALIPHATIC URETHANE METHACRYLATE 3290-92-4	-	144: 96 h Oncorhynchus mykiss mg/L LC50 160: 96 h Pimephales promelas mg/L LC50 112: 96 h Lepomis macrochirus mg/L LC50	-
ACRYLIC ACID 79-10-7	0.17: 96 h Pseudokirchneriella subcapitata mg/L EC50 0.04: 72 h Desmodesmus subspicatus mg/L EC50	222: 96 h Brachydanio rerio mg/L LC50 semi-static	95: 48 h Daphnia magna mg/L EC50 270: 24 h Daphnia magna mg/L LC50 Static
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	-	3.9: 96 h Oncorhynchus mykiss mg/L LC50 static	7: 24 h Daphnia magna mg/L EC50
2-HYDROXYETHYL METHACRYLATE 868-77-9	-	213 - 242: 96 h Pimephales promelas mg/L LC50 flow-through 227: 96 h Pimephales promelas mg/L LC50	-

# Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

#### **Mobility**

No information available.

Chemical Name	Partition coefficient
HYDROXYALKYL METHACRYLATE 27813-02-1	0.97
ACRYLIC ACID 79-10-7	0.38 - 0.46
2-HYDROXYETHYL METHACRYLATE 868-77-9	0.47

# Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

**Contaminated packaging** Do not reuse container.

US EPA Waste Number Not applicable

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
ACRYLIC ACID	-	-	-	U008
79-10-7				
DIMETHYLBENZYL	-	-	-	U096
HYDROPEROXIDE				
80-15-9				

# 190510AA - 09117 REAR WINDOW DEFOGGER **REPAIR KIT PRS PART 2**

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
DIMETHYLBENZYL HYDROPEROXIDE	Toxic
80-15-9	Ignitable

# 14. TRANSPORT INFORMATION

Proper shipping name: Not regulated

Proper shipping name: Not regulated

IMDG

Proper shipping name: Not regulated

# 15. REGULATORY INFORMATION

**International Inventories** 

Complies **TSCA DSL/NDSL** Complies **EINECS/ELINCS** Does not comply **ENCS** Does not comply Complies **IECSC KECL** Complies Does not comply **PICCS** 

Complies **AICS** 

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
ACRYLIC ACID - 79-10-7	1.0
DIMETHYLBENZYL HYDROPEROXIDE - 80-15-9	1.0
SACCHARIN - 81-07-2	1.0

#### SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

#### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ACRYLIC ACID 79-10-7	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	10 lb	-	RQ 10 lb final RQ RQ 4.54 kg final RQ

# **US State Regulations**

#### **California Proposition 65**

This product does not contain any Proposition 65 chemicals

#### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACRYLIC ACID 79-10-7	X	X	X
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	Х	Х	Х
SACCHARIN 81-07-2	X	X	X
SILVER 7440-22-4	X	X	X
WATER 7732-18-5	-	-	X

#### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

NFPAHealth hazards 2Flammability 1Instability 0-HMISHealth hazards 2Flammability 1Physical hazards 0Personal protection B

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)

Revision Date 25-Feb-2015

#### Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

# **Permatex.**

# SAFETY DATA SHEET

Revision Date 03-Feb-2015 Version 1

# 1. IDENTIFICATION

**Product identifier** 

Product Name 09117 REAR WINDOW DEFOGGER REPAIR KIT PRS PART 3

Other means of identification

Product Code PTX394319RR

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Activator

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address <u>Distributor</u>

ITW Permatex Canada
10 Columbus Blvd. 35 Brownridge Road, Unit 1
Hartford, CT 06106 USA Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

# 2. HAZARDS IDENTIFICATION

# Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 2

#### Label elements

#### **Emergency Overview**

#### Danger

Harmful if swallowed

Causes serious eye irritation

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

Highly flammable liquid and vapor



Appearance Green Physical state Liquid Odor Alcoholic

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Wear eye/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

In case of fire: Use CO2, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). Copper compounds.

Unknown acute toxicity

2.38% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substance

Chemical Name	CAS No	Weight-%	Trade Secret
2-PROPANOL	67-63-0	60 - 100	*

# PTX394319RR - 09117 REAR WINDOW DEFOGGER REPAIR KIT PRS PART 3

MINERAL SPIRITS	8052-41-3	1 - 5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

#### **Description of first aid measures**

General advice Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. If symptoms persist, call a physician. Wash contaminated clothing

before reuse.

**Inhalation** IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person.

**Self-protection of the first aider**Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

# Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

#### Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

#### Specific hazards arising from the chemical

Flammable. May be ignited by heat, sparks or flames.

**Explosion data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

# Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

# Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

**Environmental precautions** 

# PTX394319RR - 09117 REAR WINDOW DEFOGGER REPAIR KIT PRS PART 3

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Use a

non-combustible material like vermiculite or sand to soak up the product and place into a

container for later disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Handle in

accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash

contaminated clothing before reuse.

#### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

**Incompatible materials** Strong oxidizing agents.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-PROPANOL	STEL: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm
67-63-0	TWA: 200 ppm	TWA: 980 mg/m <sup>3</sup>	TWA: 400 ppm
		(vacated) TWA: 400 ppm	TWA: 980 mg/m <sup>3</sup>
		(vacated) TWA: 980 mg/m <sup>3</sup>	STEL: 500 ppm
		(vacated) STEL: 500 ppm	STEL: 1225 mg/m <sup>3</sup>
		(vacated) STEL: 1225 mg/m <sup>3</sup>	
MINERAL SPIRITS	TWA: 100 ppm	TWA: 500 ppm	IDLH: 20000 mg/m <sup>3</sup>
8052-41-3		TWA: 2900 mg/m <sup>3</sup>	Ceiling: 1800 mg/m³ 15 min
		(vacated) TWA: 100 ppm	TWA: 350 mg/m <sup>3</sup>
		(vacated) TWA: 525 mg/m <sup>3</sup>	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective gloves and protective clothing.

# PTX394319RR - 09117 REAR WINDOW DEFOGGER **REPAIR KIT PRS PART 3**

Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as Respiratory protection

appropriate.

Handle in accordance with good industrial hygiene and safety practice. **General Hygiene Considerations** 

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Air = 1

#### Information on basic physical and chemical properties

Liquid Physical state **Appearance** Green Odor Alcoholic

**Odor threshold** No information available

**Property** Values Remarks • Method

На Does not apply

No information available Melting point / freezing point Boiling point / boiling range 82 °C / 180 °F

12 °C / 53 °F Flash point

Tag Closed Cup **Evaporation rate** 7.7 Butyl acetate = 1 No information available

Flammability (solid, gas)

Flammability Limit in Air

Upper flammability limit: 12.0% Lower flammability limit: 2.0%

Vapor pressure 32 mm Hg @ 68°F

Vapor density 2.1

Relative density 0.79 @ 77°F Water solubility Soluble in water

Solubility in other solvents No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available No information available Dynamic viscosity **Explosive properties** No information available No information available **Oxidizing properties** 

#### **Other Information**

Softening point No information available Molecular weight No information available

**VOC Content (%)** 96.5

**Density** No information available **Bulk density** No information available

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### **Chemical stability**

Stable under recommended storage conditions.

# **Possibility of Hazardous Reactions**

None under normal processing.

#### Conditions to avoid

Heat, flames and sparks. Take precautionary measures against static discharges.

# PTX394319RR - 09117 REAR WINDOW DEFOGGER REPAIR KIT PRS PART 3

#### **Incompatible materials**

Strong oxidizing agents

#### **Hazardous Decomposition Products**

Carbon oxides

# 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

**Inhalation** May be harmful by inhalation.

**Eye contact** May cause redness and tearing of the eyes.

**Skin contact** May cause skin irritation and/or dermatitis.

**Ingestion** May be harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
2-PROPANOL	= 1870 mg/kg (Rat)	= 4059 mg/kg ( Rabbit )	= 72600 mg/m³ (Rat) 4 h
67-63-0			

#### Information on toxicological effects

**Symptoms** No information available.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available. Germ cell mutagenicity No information available.

<u>Carcinogenicity</u> The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
2-PROPANOL	-	Group 1	-	X
67-63-0				

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Central nervous system, Eyes, kidney, Respiratory system, Skin.

# Numerical measures of toxicity - Product Information

#### The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 1938 mg/kg ATEmix (dermal) 4206 mg/kg ATEmix (inhalation-dust/mist) 75.2 mg/l

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

None known

3.5% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
2-PROPANOL	1000: 96 h Desmodesmus	11130: 96 h Pimephales promelas	13299: 48 h Daphnia magna mg/L
67-63-0	subspicatus mg/L EC50 1000: 72 h	mg/L LC50 static 9640: 96 h	EC50
	Desmodesmus subspicatus mg/L	Pimephales promelas mg/L LC50	
	EC50	flow-through 1400000: 96 h	
		Lepomis macrochirus µg/L LC50	

# Persistence and degradability

No information available.

# PTX394319RR - 09117 REAR WINDOW DEFOGGER **REPAIR KIT PRS PART 3**

#### **Bioaccumulation**

No information available.

#### Mobility

No information available.

Chemical Name	Partition coefficient
2-PROPANOL	0.05
67-63-0	

# Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

**Disposal of wastes** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated packaging Do not reuse container.

**US EPA Waste Number** D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status	
2-PROPANOL	Toxic	
67-63-0	Ignitable	

# 14. TRANSPORT INFORMATION

DOT

Proper shipping name: Isopropyl alcohol, Limited Quantity (LQ)

**Hazard Class** 3 **Packing Group** Ш

**IATA** 

UN/ID no ID 8000

Proper shipping name: Consumer commodity

**Hazard Class** 

**IMDG** 

UN/ID no UN 1219

Proper shipping name: Isopropyl alcohol, Limited Quantity (LQ)

**Hazard Class Packing Group** Ш

EmS-No F-E, S-D

# 15. REGULATORY INFORMATION

**International Inventories** 

**TSCA** Complies **DSL/NDSL** Complies Complies **EINECS/ELINCS** Complies **ENCS** 

# PTX394319RR - 09117 REAR WINDOW DEFOGGER REPAIR KIT PRS PART 3

IECSCCompliesKECLCompliesPICCSCompliesAICSComplies

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %		
2-PROPANOL - 67-63-0	1.0		
SARA 311/312 Hazard Categories	•		
Acute health hazard	Yes		
Chronic Health Hazard	Yes		
Fire hazard	Yes		
Sudden release of pressure hazard	No		
Reactive Hazard	No		

#### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

#### **US State Regulations**

# **California Proposition 65**

This product does not contain any Proposition 65 chemicals

# U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
2-PROPANOL 67-63-0	X	X	Х
MINERAL SPIRITS 8052-41-3	X	X	Х
ORGANO-COPPER COMPOUND 85737-14-0	X	-	Х
ORGANO-COPPER COMPOUND 68084-48-0	X	-	Х
ORGANO-COPPER COMPOUND 22221-10-9	X	-	Х

#### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

PTX394319RR - 09117 REAR WINDOW DEFOGGER REPAIR KIT PRS PART 3

Revision Date 03-Feb-2015

NFPA Health hazards 2 Flammability 3 Instability 0

HMIS Health hazards 2 Flammability 3 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 03-Feb-2015

#### **Disclaimer**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**