

PENRAY FUEL PREP™

Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012. Date of issue: 04/04/2014 Revision date: 04/04/2014 Version: 1.0

SECTION 1: Identification of the subs	stance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	: PENRAY FUEL PREP™ CONCENTRATED DIESEL FUEL CONDITIONER
Product code	: 201201
1.2. Relevant identified uses of the subst	ance or mixture and uses advised against
Use of the substance/mixture	: Fuel Prep.
1.3. Details of the supplier of the safety of	lata sheet
The Penray Companies, Inc. 440 Denniston Ct. 60090 Wheeling, IL T (800) 373-6729 rotto@penray.com	
1.4. Emergency telephone number	
Emergency number	: (800) 373-6729 CHEMTREC (800) 424-9300 CHEMTREC International +1 (703) 527-3887 24 hr
SECTION 2: Hazards identification	
2.1. Classification of the substance or m	ixture
GHS-US classification	
Flammable Liquid 3 Acute toxicity 4 (Inhalation) Skin irritation 2 Eye irritation 2A Carcinogenicity 2 Specific target organ toxicity - Single exposure 3 Aspiration hazard 1	
2.2. Label elements	
GHS-US labelling	
Hazard pictograms (GHS-US)	: GHS02 GHS07 GHS08
Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	: Flammable liquid and vapor. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.
Precautionary statements (GHS-US)	Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash hands thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. If exposed or concerned: Get medical advice/attention. If on skin (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor if you feel unwell. If swallowed: Keep cool. Keep container tightly closed. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.
2.3. Other hazards	
No additional information available	
2.4. Unknown acute toxicity (GHS-US)	
No additional information available	

EN (English)



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Name	Product identifier	%	GHS-US classification
Solvent naphtha, petroleum, heavy aromatic	(CAS No) 64742-94-5	15 - 40	Flam. Liq. 3 Asp. Tox. 1
Kerosene, petroleum	(CAS No) 8008-20-6	10 - 30	Flam. Liq. 3 Skin Irrit. 2 STOT SE 3 Asp. Tox. 1
Solvent naphtha, petroleum, light aromatic	(CAS No) 64742-95-6	10 - 30	Asp. Tox. 1
Pseudocumene	(CAS No) 95-63-6	7 - 13	Flam. Liq. 3 Acute Tox. 4 (Inhalation) Skin Irrit. 2 Eye Irrit. 2A STOT SE 3
Naphthalene	(CAS No) 91-20-3	3 - 7	Acute Tox. 4 (Oral, Dermal) Carc. 2
2-Ethylhexanol	(CAS No) 104-76-7	1 - 5	Flam. Liq. 4 Acute Tox. 4 (Dermal) Skin Irrit. 2 Eye Irrit. 2A
2,6-Di-tert-butylphenol	(CAS No) 128-39-2	0.5 - 1.5	Skin Irrit. 2
Cumene	(CAS No) 98-82-8	0.1 - 1	Flam. Liq. 3 Acute Tox. 4 (Oral) Carc. 2
Naphtha, petroleum, heavy catalytic reformed	(CAS No) 64741-68-0	0.1 - 1	Flam. Liq. 1 Skin Irrit. 2 Muta. 1B Carc. 1B Repr. 2 STOT SE 3 Asp. Tox. 1

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures after inhalation	: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy do, remove contact lenses, if worn. If irritation persists, get medical attention.
First-aid measures after ingestion	: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never g anything by mouth to an unconscious person. Get immediate medical advice/attention.
4.2. Most important symptoms and effe	ts, both acute and delayed
Symptoms/injuries after inhalation	: Harmful if inhaled. May cause drowsiness, dizziness and central nervous system depression. May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking the skin.
Symptoms/injuries after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs ar cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECT	ION 5: Firefighting measure	S
5.1.	Extinguishing media	
Suitabl	e extinguishing media	: Treat for surrounding material.
Unsuita	able extinguishing media	: None known.
5.2.	Special hazards arising from the	e substance or mixture
Fire ha	zard	: Products of combustion may include, and are not limited to: oxides of carbon.
5.3.	Advice for firefighters	
Protect	ion during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool.
04/04/2	714	EN (English) 2/7

EN (English)



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

	ental release me	easures	
6.1. Personal prec	autions, protective	equipment and emergency proc	cedures
General measures			commended in Section 8. Isolate the hazard area and deny entry to ted personnel. Eliminate sources of ignition.
6.2. Methods and	material for contain	ment and cleaning up	
For containment			with inert material (e.g. sand, vermiculite), then place in a suitable ewer or allow to enter waterways. Use appropriate Personal :).
Methods for cleaning up		: Scoop up material and place	e in a disposal container. Provide ventilation.
6.3. Reference to o	other sections		
See section 8 for further	information on protect	ctive clothing and equipment and s	section 13 for advice on waste disposal.
SECTION 7: Handl	ing and storage		
7.1. Precautions for	or safe handling		
Precautions for safe hand	dling	breathing gas/mist/vapors/s	f ignition - No smoking. Avoid contact with skin and eyes. Avoid spray. Do not swallow. Handle and open container with care. Use on using do not eat, drink or smoke. Use only outdoors or in a well-
Hygiene measures		: Launder contaminated clot	hing before reuse. Wash hands before eating, drinking, or smoking.
7.2. Conditions fo	r safe storage, inclu	Iding any incompatibilities	
Storage conditions			ildren. Keep container tightly closed and in a well-ventilated place. . Keep away from heat, sparks, and flame.
7.3. Specific end u	ıse(s)		
Not available.			
SECTION 8: Expos	ure controls/pe	rsonal protection	
8.1. Control paran			
Kerosene, petroleum USA ACGIH		A (m a /m 3)	200 ma/m3
	ACGIH TW/	4 (mg/m²)	200 mg/m ³
Pseudocumene (95-63	3-6)		
USA ACGIH	ACGIH TW/	A (ppm)	25 ppm
Naphthalene (91-20-3))		
USA ACGIH	ACGIH TW/	A (ppm)	10 ppm
		EL (ppm)	15 ppm
USA ACGIH	ACGIH STE		
USA ACGIH USA OSHA		(TWA) (mg/m ³)	50 mg/m ³
	OSHA PEL	(TWA) (mg/m ³) (TWA) (ppm)	50 mg/m ³ 10 ppm
USA OSHA	OSHA PEL	() (č)	
USA OSHA USA OSHA Cumene (98-82-8)	OSHA PEL OSHA PEL	(TWA) (ppm)	10 ppm
USA OSHA USA OSHA Cumene (98-82-8) USA ACGIH	OSHA PEL OSHA PEL ACGIH TW/	(TWA) (ppm) A (ppm)	10 ppm 50 ppm
USA OSHA USA OSHA Cumene (98-82-8)	OSHA PEL OSHA PEL ACGIH TW/	(TWA) (ppm)	10 ppm
USA OSHA USA OSHA Cumene (98-82-8) USA ACGIH	OSHA PEL OSHA PEL ACGIH TW/ OSHA PEL	(TWA) (ppm) A (ppm)	10 ppm 50 ppm
USA OSHA USA OSHA Cumene (98-82-8) USA ACGIH USA OSHA USA OSHA	OSHA PEL OSHA PEL ACGIH TW/ OSHA PEL OSHA PEL	(TWA) (ppm) A (ppm) (TWA) (mg/m ³)	10 ppm 50 ppm 245 mg/m³
USA OSHA USA OSHA Cumene (98-82-8) USA ACGIH USA OSHA USA OSHA S.2. Exposure con	OSHA PEL OSHA PEL ACGIH TW/ OSHA PEL OSHA PEL	(TWA) (ppm) A (ppm) (TWA) (mg/m ³) (TWA) (ppm)	10 ppm 50 ppm 245 mg/m³ 50 ppm 9 keep exposures (airborne levels of dust, fume, vapor, etc.) below
USA OSHA USA OSHA Cumene (98-82-8) USA ACGIH USA OSHA USA OSHA 3.2. Exposure con Appropriate engineering	ACGIH TW/ OSHA PEL ACGIH TW/ OSHA PEL OSHA PEL trols	(TWA) (ppm) A (ppm) (TWA) (mg/m ³) (TWA) (ppm) : Use ventilation adequate to	10 ppm 50 ppm 245 mg/m³ 50 ppm b keep exposures (airborne levels of dust, fume, vapor, etc.) below nits.
USA OSHA USA OSHA Cumene (98-82-8) USA ACGIH USA OSHA USA OSHA 3.2. Exposure con Appropriate engineering	ACGIH TW/ OSHA PEL ACGIH TW/ OSHA PEL OSHA PEL trols	(TWA) (ppm) A (ppm) (TWA) (mg/m³) (TWA) (ppm) : Use ventilation adequate to recommended exposure lin	10 ppm 50 ppm 245 mg/m³ 50 ppm 50 ppm b keep exposures (airborne levels of dust, fume, vapor, etc.) below nits. psure.
USA OSHA USA OSHA Cumene (98-82-8) USA ACGIH USA OSHA USA OSHA 3.2. Exposure con Appropriate engineering Personal protective equip land protection Eye protection	OSHA PEL OSHA PEL ACGIH TW/ OSHA PEL OSHA PEL OSHA PEL trois	(TWA) (ppm) (TWA) (mg/m ³) (TWA) (mg/m ³) (TWA) (ppm) : Use ventilation adequate to recommended exposure lin : Avoid all unnecessary expo : Wear chemically resistant p : Safety glasses or goggles a	10 ppm 50 ppm 245 mg/m³ 50 ppm 50 ppm b keep exposures (airborne levels of dust, fume, vapor, etc.) below nits. osure. orotective gloves. are recommended when using product.
USA OSHA USA OSHA USA OSHA USA ACGIH USA OSHA USA OSHA USA OSHA 3.2. Exposure con Appropriate engineering Personal protective equip Hand protection Eye protection Skin and body protection	OSHA PEL OSHA PEL ACGIH TW/ OSHA PEL OSHA PEL OSHA PEL trois	 (TWA) (ppm) (TWA) (mg/m³) (TWA) (mg/m³) (TWA) (ppm) : Use ventilation adequate to recommended exposure line : Avoid all unnecessary expo : Wear chemically resistant p : Safety glasses or goggles a : Wear suitable protective closed 	10 ppm 50 ppm 245 mg/m³ 50 ppm 50 ppm b keep exposures (airborne levels of dust, fume, vapor, etc.) below nits. osure. porotective gloves. are recommended when using product. othing.
USA OSHA USA OSHA Cumene (98-82-8) USA ACGIH USA OSHA USA OSHA 3.2. Exposure con Appropriate engineering Personal protective equip Hand protection Eye protection	OSHA PEL OSHA PEL ACGIH TW/ OSHA PEL OSHA PEL OSHA PEL trois	(TWA) (ppm) (TWA) (mg/m ³) (TWA) (mg/m ³) (TWA) (ppm) : Use ventilation adequate to recommended exposure lin : Avoid all unnecessary expo : Wear chemically resistant p : Safety glasses or goggles a : Wear suitable protective clo : A NIOSH approved respira exposure limits may be expo	10 ppm 50 ppm 245 mg/m³ 50 ppm 50 ppm b keep exposures (airborne levels of dust, fume, vapor, etc.) below nits. osure. protective gloves. are recommended when using product. othing. tor is recommended in poorly ventilated areas or when permissible meded. Respirator selection must be based on known or anticipated
USA OSHA USA OSHA USA OSHA USA ACGIH USA OSHA USA OSHA USA OSHA 3.2. Exposure con Appropriate engineering Personal protective equip Hand protection Eye protection Skin and body protection	OSHA PEL OSHA PEL ACGIH TW/ OSHA PEL OSHA PEL OSHA PEL trois	 (TWA) (ppm) (TWA) (mg/m³) (TWA) (mg/m³) (TWA) (ppm) : Use ventilation adequate to recommended exposure lini : Avoid all unnecessary expo : Wear chemically resistant p : Safety glasses or goggles a : Wear suitable protective closed : A NIOSH approved respirate exposure limits may be exposure levels, the hazard 	10 ppm 50 ppm 245 mg/m³ 50 ppm 50 ppm b keep exposures (airborne levels of dust, fume, vapor, etc.) below nits. osure. porotective gloves. are recommended when using product. othing.



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 9: Physical and chemical	properties	
9.1. Information on basic physical and		
Physical state	: Liquid	
Colour	: Amber.	
Odour	: Petroleum odor.	
Odour threshold	: No data available.	
pH	: No data available.	
Relative evaporation rate (butylacetate=1)	: No data available.	
Melting point	: No data available.	
Freezing point	: No data available.	
Boiling point	: No data available.	
Flash point	: ~ 49 °C (~ 120 °F)	
Self ignition temperature	: No data available.	
Decomposition temperature	: No data available.	
Flammability (solid, gas)	: Flammable.	
Vapour pressure	: No data available.	
Relative vapour density at 20 °C	: No data available.	
Relative density	: 0.815 - 0.835	
Solubility	: No data available.	
Log Pow	: No data available.	
Log Kow	: No data available.	
Viscosity, kinematic	: No data available.	
Viscosity, dynamic	: No data available.	
Explosive properties	: No data available.	
Oxidising properties	: No data available.	
Explosive limits	: No data available.	
9.2. Other information		
No additional information available		
SECTION 10: Stability and reactivit	ý	
10.1. Reactivity	a for small sea	
No dangerous reaction known under conditions of normal use.		
10.2. Chemical stability Stable under normal storage conditions. May form flammable/explosive vapour-air mixture.		
10.3. Possibility of hazardous reactions		
No dangerous reaction known under conditions		
10.4. Conditions to avoid		
Heat. Incompatible materials. Open flame.		
10.5. Incompatible materials		
Strong oxidizing agents.		
10.6. Hazardous decomposition product	ts	
May include, and are not limited to: oxides of ca		
SECTION 11: Toxicological information	tion	
11.1. Information on toxicological effect		
Acute toxicity	: Harmful if inhaled.	
•	. namma i illiaica.	
FUEL PREP 201201		
LD50 oral rat	> 2000 mg/kg	
LD50 dermal rabbit LC50 inhalation rat (mg/l)	> 2000 mg/kg ~ 18 mg/l/4h	
Solvent naphtha, petroleum, heavy aromat		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000mg/kg	
Kerosene, petroleum (8008-20-6)		
LD50 oral rat	> 5000 mg/kg	
LD50 dormal rabbit	> 2000 mg/kg	

LD50 dermal rabbit

LC50 inhalation rat (mg/l)

> 5.28 mg/l/4h EN (English)

> 2000 mg/kg



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Solvent naphtha, petroleum, light aromatic (6	4742-95-6)
LD50 oral rat	8400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (ppm)	3400 ppm/4h
LC50 inhalation rat (mg/l)	> 5.2 mg/l/4h
Psoudocumono (05-62-6)	
Pseudocumene (95-63-6) LD50 oral rat	3400 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (mg/l)	18 g/m ³ /4h
Naphthalene (91-20-3)	
LD50 oral rat	490 mg/kg
LD50 dermal rabbit	> 20 g/kg
2-Ethylhexanol (104-76-7)	
LD50 oral rat	3730 mg/kg
LD50 dermal rabbit	> 3000 mg/kg
2,6-Di-tert-butylphenol (128-39-2)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	>10000 mg/kg
Cumene (98-82-8)	4400 mailur
LD50 oral rat	1400 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (mg/l)	39000 mg/m³/4 h
Naphtha, petroleum, heavy catalytic reformed	d (64741-68-0)
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.04 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Suspected of causing cancer.
Cumene (98-82-8)	
IARC group	2B
National Toxicity Program (NTP) Status	1
Naphthalene (91-20-3)	
IARC group	2B
National Toxicity Program (NTP) Status	1, 3
Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.
	: May be fatal if swallowed and enters airways.
	 Harmful if inhaled. May cause drowsiness, dizziness and central nervous system depression. May cause respiratory tract irritation.
Symptoms/injuries after skin contact	 Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	 Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/injuries after ingestion	 May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.
SECTION 12: Ecological information	

SECTIO	ON 12: Ecological information	
12.1.	Toxicity	
Ecology -	general	: May cause long-term adverse effects in the aquatic environment.



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

according to the Hazard Communication Standard (CFR29) 1910.1200) HazCom 2012.	
2.2. Persistence and degradability		
FUEL PREP 201201		
Persistence and degradability	Not established.	
12.3. Bioaccumulative potential		
FUEL PREP 201201		
Bioaccumulative potential	Not established.	
12.4. Mobility in soil		
No additional information available		
12.5. Other adverse effects		
No additional information available		
SECTION 13: Disposal consideration	S	
13.1. Waste treatment methods		
Waste disposal recommendations	: This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.	
Additional information	: Handle empty containers with care because residual vapours are flammable.	
SECTION 14: Transport information		
In accordance with DOT		
14.1. UN number		
UN-No.	: UN1993	
14.2. UN proper shipping name		
Proper Shipping Name	: Flammable liquids, n.o.s. (Petroleum, Psuedocumene)	
Department of Transportation Hazard Classes	: 3	
Hazard labels		
Packing group (DOT)	: III	
14.3. Additional information		
Other information	: No supplementary information available.	
Special transport precautions	: Do not handle until all safety precautions have been read and understood.	
SECTION 15: Regulatory information		
15.1. US Federal regulations		
Solvent naphtha, petroleum, heavy aromatic	(64742-94-5)	
Listed on the United States TSCA (Toxic Substa		
Kerosene, petroleum (8008-20-6)		
Listed on the United States TSCA (Toxic Substa	Inces Control Act) inventory	
Solvent naphtha, petroleum, light aromatic (6	\$4742-95-6)	
Listed on the United States TSCA (Toxic Substa	·	
Pseudocumene (95-63-6)		
Listed on the United States TSCA (Toxic Substa	Inces Control Act) inventory	
Listed on SARA Section 313 (Specific toxic cher		
SARA Section 313 - Emission Reporting	1.0 %	
Naphthalene (91-20-3)		
Listed on the United States TSCA (Toxic Substa Listed on SARA Section 313 (Specific toxic cher		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.	

 EPA TSCA Regulatory Flag
 T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

 SARA Section 313 - Emission Reporting
 0.1 %

 2-Ethylbexanol (104-76-7)
 0.1 %

2-Ethylhexanol (104-76-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.	

EN (English)

2,6-Di-tert-butylphenol (128-39-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory



Safety Data Sheet


according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Cumene (98-82-8)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.	
SARA Section 313 - Emission Reporting	1.0 %	
Naphtha, petroleum, heavy catalytic reformed (64741-68-0)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
15.2. US State regulations		
FUEL PREP 201201		
State or local regulations	This product contains chemicals known to the State of California to cause cancer.	

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

IARC	International Agency for Research on Cancer.
	 Carcinogenic to humans; Probably carcinogenic to humans; Possibly carcinogenic to humans; Not classifiable; Probably not carcinogenic to humans.
NTP	National Toxicology Program.
	 Evidence of Carcinogenicity; Known Human Carcinogens; Reasonably anticipated to be Human Carcinogen; Substances delisted from report on Carcinogens; Twelfth Report - Items under consideration.

SECTION 16: Other information		
Indication of changes	:	None.
Date of issue	:	04/04/2014
Other information	:	None.
NFPA health hazard NFPA fire hazard NFPA reactivity		2 2 0



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

