

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012. Revision date: 04/28/2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name : PENRAY WINTER BLEND BIODIESEL FUEL TREATMENT

Product code 203605

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Bio-diesel fuel treatment.

Details of the supplier of the safety data sheet

The Penray Companies, Inc. 440 Denniston Ct. 60090 Wheeling, IL T (800) 373-6729 rotto@penray.com

Emergency telephone number

Emergency number (800) 373-6729

CHEMTREC (800) 424-9300

CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2: Hazards identification

Classification of the substance or mixture

GHS-US classification

Flammable Liquid 3 Acute toxicity 4 (Inhalation) Skin irritation 2 Eye irritation 2A Carcinogenicity 2 Aspiration hazard 1

Label elements

GHS-US labelling

Hazard pictograms (GHS-US)



GHS02

GHS07



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Flammable liquid and vapor. Harmful if inhaled. Causes skin irritation. Causes serious eye

irritation. May be fatal if swallowed and enters airways.

Keep away from heat/sparks/open flames/hot surfaces.- No smoking. Keep container tightly Precautionary statements (GHS-US)

closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash hands thoroughly after handling. Wear protective gloves/eye protection/face protection. Avoid breathing gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. If on skin (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards

No additional information available

Unknown acute toxicity (GHS-US)

40 % of the mixture consists of ingredient(s) of unknown acute toxicity.

SECTION 3: Composition/information on ingredients

Substance 3.1.

Not applicable



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Mixture

Name	Product identifier	%	GHS-US classification
Distillates, petroleum, hydrotreated light naphthenic	(CAS No) 64742-53-6	10 - 30	Not classified
Solvent naphtha, petroleum, heavy aromatic	(CAS No) 64742-94-5	10 - 30	Flam. Liq. 3 Asp. Tox. 1
Solvent naphtha, petroleum, light aromatic	(CAS No) 64742-95-6	2 - 7	Asp. Tox. 1
Pseudocumene	(CAS No) 95-63-6	1 - 5	Flam. Liq. 3 Acute Tox. 4 (Inhalation) Skin Irrit. 2 Eye Irrit. 2A STOT SE 3
Naphthalene	(CAS No) 91-20-3	1 - 5	Acute Tox. 4 (Oral, Dermal) Carc. 2
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	1 - 5	Flam. Liq. 3 Acute Tox. 4 (Dermal, Inhalation) Skin Irrit. 2
Methylxylene	(CAS No) 25551-13-7	1 - 5	Flam. Liq. 3 Skin Irrit. 2 Eye Irrit. 2A
2-Butoxyethanol	(CAS No) 111-76-2	1 - 5	Flam. Liq. 3 Acute Tox. 4 (Oral, Dermalm Inhalation) Skin Irrit. 2 Eye Irrit. 2A
Phenylethane	(CAS No) 100-41-4	0.1 - 1	Flam. Liq. 2 Acute Tox. 4 (Inhalation) Carc. 2
Vinyl acetate	(CAS No) 108-05-4	0.1 - 1	Carc. 2
Cumene	(CAS No) 98-82-8	0.1 - 1	Flam. Liq. 3 Acute Tox. 4 (Oral) Carc. 2
The exact percentage (concentration) of composition has b	een withheld as a trade secret in acco	rdance with paragraph	(i) of §1910.1200.

SECTION 4: First aid measures

Description of first aid measures

First-aid measures after inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to First-aid measures after eye contact do, remove contact lenses, if worn. If irritation persists, get medical attention.

First-aid measures after ingestion If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : Harmful if inhaled. May cause respiratory irritation, headaches and dizziness.

Symptoms/injuries after skin contact Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of

the skin.

Symptoms/injuries after eye contact Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and

tear production, with marked redness and swelling of the conjunctiva.

Symptoms/injuries after ingestion May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and

cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Treat for surrounding material.

Unsuitable extinguishing media : None known.

Special hazards arising from the substance or mixture

: Products of combustion may include, and are not limited to: oxides of carbon. Fire hazard

Advice for firefighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory

protection (SCBA). Use water spray to keep fire-exposed containers cool.

04/28/2014 EN (English) 2/8



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

6.2. Methods and material for containment and cleaning up

For containment

: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up

: Scoop up material and place in a disposal container. Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing gas/mist/vapors/spray. Do not swallow. Handle and open container with care. Use only non-sparking tools. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.

Hygiene measures

: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Store locked up. Keep cool. Keep away from heat, sparks, and flame.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)		
USA ACGIH	ACGIH TWA (mg/m³)	5 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³

Solvent naphtha, petroleum, heavy aromatic (64742-94-5)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.

Solvent naphtha, petroleum, light aromatic (64742-95-6)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.

Pseudocumene (95-63-6)		
USA ACGIH	ACGIH TWA (ppm)	25 ppm

Naphthalene (91-20-3)		
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	ACGIH STEL (ppm)	15 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	50 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm

Xylenes (o-, m-, p- isomers) (1330-20-7)		
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm

Methylxylene (25551-13-7)		
USA ACGIH	ACGIH TWA (ppm)	25 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	125 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	25 ppm

04/28/2014 EN (English) 3/8



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

2-Butoxyethanol (111-76-2)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	240 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm

Phenylethane (100-41-4)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm

Vinyl acetate (108-05-4)		
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	ACGIH STEL (ppm)	15 ppm

Cumene (98-82-8)		
USA ACGIH	ACGIH TWA (ppm)	50 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	245 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm

8.2. Exposure controls

Log Pow

Log Kow

Viscosity, kinematic

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below

recommended exposure limits.

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear chemically resistant protective gloves.

Eye protection : Safety glasses or goggles are recommended when using product.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : A NIOSH approved respirator is recommended in poorly ventilated areas or when permissible

exposure limits may be exceeded. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls : Maintain levels below Community environmental protection thresholds.

Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully

before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid. Clear. **Appearance** Colour : Amber. Odour Petroleum odor. Odour threshold No data available. No data available. Relative evaporation rate (butylacetate=1) : No data available. No data available. Melting point Freezing point : No data available. **Boiling point** : No data available. Flash point ~ 43 °C (~ 110 °F) Self ignition temperature No data available. Decomposition temperature No data available. Flammability (solid, gas) Flammable. Vapour pressure No data available. Relative vapour density at 20 °C No data available. Relative density 0.901 - 0.911 Solubility : No data available.

No data available.No data available.

: No data available.



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Explosive properties : No data available.

Oxidising properties : No data available.

Explosive limits : No data available.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat. Incompatible materials. Open flame.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if inhaled.

203605		
LD50 oral rat	> 2000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat (mg/l)	~ 11 mg/l/4h	

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat (mg/l)	2.18 mg/l/4h	

Solvent naphtha, petroleum, heavy aromatic (64742-94-5)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000mg/kg	
LC50 inhalation rat (mg/l)	> 5.28 mg/l/4h	

Solvent naphtha, petroleum, light aromatic (64742-95-6)		
LD50 oral rat	8400 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat (ppm)	3400 ppm/4h	
LC50 inhalation rat (mg/l)	> 5.2 mg/l/4h	

Pseudocumene (95-63-6)	
LD50 oral rat	3400 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (mg/l)	18 g/m³/4h

Naphthalene (91-20-3)	
LD50 oral rat	490 mg/kg
LD50 dermal rabbit	> 20 g/kg

Xylenes (o-, m-, p- isomers) (1330-20-7)		
LD50 oral rat	4300 mg/kg	
LD50 dermal rabbit	> 1700 mg/kg	
LC50 inhalation rat (ppm)	5000 ppm/4h	
LC50 inhalation rat (mg/l)	47635 mg/l/4h	

Methylxylene (25551-13-7)	
LD50 oral rat	8970 mg/kg

2-Butoxyethanol (111-76-2)	
LD50 oral rat	470 mg/kg

04/28/2014 EN (English) 5/8



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

ccording to the Hazard Communication Standard (CFR29	1910.1200) HazCom 2012.
2-Butoxyethanol (111-76-2)	
LC50 inhalation rat (ppm)	450 ppm/4h
Phenylethane (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15354 mg/kg
LC50 inhalation rat (mg/l)	17.2 mg/l/4h
Vinyl acetate (108-05-4)	
LD50 oral rat	2920 mg/kg
LD50 dermal rabbit	2320 mg/kg
LC50 inhalation rat (mg/l)	11400 mg/m³/4h
Cumene (98-82-8)	
LD50 oral rat	1400 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (mg/l)	39000 mg/m³/4 h
Skin corrosion/irritation	: Causes skin irritation.
Skin corrosion/irritation Serious eye damage/irritation	: Causes skin initiation. : Causes serious eye irritation.
Respiratory or skin sensitisation	Based on available data, the classification criteria are not met.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Suspected of causing cancer.
	. Suspected of causing caricer.
Naphthalene (91-20-3)	
IARC group	2B
National Toxicity Program (NTP) Status	1, 3
Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3
2-Butoxyethanol (111-76-2)	
IARC group	3
National Toxicity Program (NTP) Status	1
Phenylethane (100-41-4)	
IARC group	2B
National Toxicity Program (NTP) Status	1
Vinyl acetate (108-05-4)	
IARC group	2B
	20
Cumene (98-82-8)	T an
IARC group	2B
National Toxicity Program (NTP) Status	1
Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: Harmful if inhaled. May cause respiratory irritation, headaches and dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.
SECTION 12: Ecological information	
12.1. Toxicity	
12.11. TOXICILY	

12. 1	To	Xi	Cit	ty

: May cause long-term adverse effects in the aquatic environment. Ecology - general

Persistence and degradability 12.2.

Persistence and degradability Not established.

04/28/2014 EN (English) 6/8



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

12.3. Bioaccumulative potential

203605

Bioaccumulative potential Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal

regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information : Handle empty containers with care because residual vapours are flammable.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

UN-No. : UN1268

14.2. UN proper shipping name

Proper Shipping Name : Petroleum distillates, n.o.s.

Department of Transportation Hazard Classes : 3

Hazard labels



Packing group (DOT) : III

14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Solvent naphtha, petroleum, heavy aromatic (64742-94-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Solvent naphtha, petroleum, light aromatic (64742-95-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Pseudocumene (95-63-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting 1.0 9

Naphthalene (91-20-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 313 (Specific toxic chemical listings)

EPA TSCA Regulatory Flag T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

SARA Section 313 - Emission Reporting 0.1 %

Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting 1.0 %

Methylxylene (25551-13-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2-Butoxyethanol (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

04/28/2014 EN (English) 7/8



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Phenylethane (100-41-4) Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)	

Vinyl acetate (108-05-4)	ıyl acetate (108-05-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 302 (Specific toxic chemical listings) Listed on SARA Section 313 (Specific toxic chemical listings)		
SARA Section 302 Threshold Planning Quantity (TPQ)	1000	
SARA Section 313 - Emission Reporting	0.1 %	

	Cumene (98-82-8) Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)	
	EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
	SARA Section 313 - Emission Reporting	1.0 %

15.2. US State regulations

203605	
State or local regulations	This product contains chemicals known to the State of California to cause cancer.

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

IARC	International Agency for Research on Cancer.	
	1 - Carcinogenic to humans; 2A - Probably carcinogenic to humans; 2B - Possibly carcinogenic to humans; 3 - Not classifiable; 4 - Probably not carcinogenic to humans.	
NTP	National Toxicology Program.	
	 1 - Evidence of Carcinogenicity; 2 - Known Human Carcinogens; 3 - Reasonably anticipated to be Human Carcinogen; 4 - Substances delisted from report on Carcinogens; 5 - Twelfth Report - Items under consideration. 	

SECTION 16: Other information

NFPA reactivity

Indication of changes : None.

Date of issue : 04/28/2014

Other information : None.

NFPA health hazard : 2

NFPA fire hazard : 2

2 0

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

0

04/28/2014 EN (English) 8/8

