

Date of issue: 07/04/2014

Revision date: 07/04/2014

Version: 1.0

	Date of issue: 07/04/2014 Revision date: 07/04/2014 Version: 1.0
SECTION 1: Identification of t	the substance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	: PENRAY POW-R 365™
Product code	: 207064
1.2. Relevant identified uses of	the substance or mixture and uses advised against
Use of the substance/mixture	: Diesel fuel treatment.
1.3. Details of the supplier of th	e safety data sheet
The Penray Companies, Inc. 440 Denniston Ct. Wheeling, IL 60090 T (800) 373-6729 rotto@penray.com	
1.4. Emergency telephone num	ber
Emergency number	: (800) 373-6729 CHEMTREC (800) 424-9300 CHEMTREC International +1 (703) 527-3887 24 hr
SECTION 2: Hazards identific	ation
2.1. Classification of the substa	ince or mixture
GHS-US classification	
Skin irritation 2 Eye irritation 2A Carcinogenicity 2 Specific target organ toxicity - Single ex Aspiration hazard 1 2.2. Label elements	φosure 3
GHS-US labelling	
Hazard pictograms (GHS-US)	: GHS02 GHS06 GHS06 GHS07 GHS08
Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	 Flammable liquid and vapor. Toxic if inhaled. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.
Precautionary statements (GHS-US)	Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection. Avoid breathing gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.
2.3. Other hazards	
No additional information available	

2.4. Unknown acute toxicity (GHS-US)

5 % of the mixture consists of ingredient(s) of unknown acute toxicity.

EN (English)



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. **Mixture**

Name	Product identifier	%	GHS-US classification
Kerosine, petroleum	(CAS No) 8008-20-6	30 - 60	Flam. Liq. 3 Skin Irrit. 2 STOT SE 3 Asp. Tox. 1
2-Ethylhexyl nitrate	(CAS No) 27247-96-7	10 – 30	Flam. Liq. 4 Acute Tox. 4 (Inhalation)
Solvent naphtha, petroleum, heavy aromatic	(CAS No) 64742-94-5	3 - 7	Flam. Liq. 3 Asp. Tox. 1
2-Butoxyethanol	(CAS No) 111-76-2	3 - 7	Flam. Liq. 3 Acute Tox. 4 (Oral, Dermal) Acute Tox. 3 (Inhalation) Skin Irrit. 2 Eye Irrit. 2A
Solvent naphtha, petroleum, light aromatic	(CAS No) 64742-95-6	1 - 5	Flam. Liq. 3 Skin Irrit. 2 Eye Irrit. 2A Asp. Tox. 1
Pseudocumene	(CAS No) 95-63-6	0.5 - 2	Flam. Liq. 3 Acute Tox. 4 (Inhalation) Skin Irrit. 2 Eye Irrit. 2A STOT SE 3
Naphthalene	(CAS No) 91-20-3	0.5 - 1.5	Acute Tox. 4 (Oral) Carc. 2
Phenylethane	(CAS No) 100-41-4	0.1 - 1	Flam. Liq. 2 Acute Tox. 4 (Inhalation) Skin Irrit. 2 Carc. 2 Asp. Tox. 1
Vinyl acetate	(CAS No) 108-05-4	0.1 - 1	Flam. Liq. 2 Acute Tox. 4 (Inhalation) Carc. 2 STOT SE 3
Cumene	(CAS No) 98-82-8	< 0.1	Flam. Liq. 3 Carc. 2 STOT SE 3 Asp. Tox. 1

* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures after inhalation	: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention.
First-aid measures after skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
First-aid measures after eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.
First-aid measures after ingestion	: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
4.2. Most important symptoms and eff	fects, both acute and delayed
Symptoms/injuries after inhalation	: Toxic if inhaled. May cause drowsiness, dizziness and central nervous system depression. May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.



_

Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting	measures		
5.1. Extinguishing media	l		
Suitable extinguishing media	:	Powder, water spray, foam, carbon di	oxide.
Unsuitable extinguishing media	:	Do not use a heavy water stream.	
5.2. Special hazards aris	ing from the subs	tance or mixture	
Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.			and are not limited to: oxides of carbon.
5.3. Advice for firefighter	S		
Protection during firefighting	:	protection (SCBA). Vapors may be he	ting turn-out gear (full Bunker gear) and respiratory eavier than air and may travel along the ground to a distant ater spray to keep fire-exposed containers cool.
SECTION 6: Accidental	release measu	res	
6.1. Personal precaution	s, protective equip	oment and emergency procedures	
General measures	:	Use personal protection recommende unnecessary and unprotected person	d in Section 8. Isolate the hazard area and deny entry to nel. Eliminate sources of ignition.
6.2. Methods and materia	al for containment	and cleaning up	
For containment	:		material (e.g. sand, vermiculite), then place in a suitable ow to enter waterways. Use appropriate Personal
Methods for cleaning up	:	Scoop up material and place in a disp	osal container. Provide ventilation.
6.3. Reference to other s	ections		
See section 8 for further information	ation on protective o	lothing and equipment and section 13 f	for advice on waste disposal.
SECTION 7: Handling ar	nd storage		
7.1. Precautions for safe	handling		
Precautions for safe handling	Precautions for safe handling : Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing gas/mist/vapors/spray. Do not swallow. Handle and open container with care. Use only non-sparking tools. When using do not eat, drink or smoke. Use only outdoors or in a well- ventilated area.		
Hygiene measures	:	Launder contaminated clothing before	e reuse. Wash hands before eating, drinking, or smoking.
7.2. Conditions for safe s	storage, including	any incompatibilities	
Storage conditions	torage conditions : Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Store locked up. Keep cool. Keep away from heat, sparks, and flame.		
7.3. Specific end use(s)			
Not available.			
SECTION 8: Exposure c	ontrols/persor	al protection	
8.1. Control parameters			
Kerosine, petroleum (8008-2 USA ACGIH	0-6) ACGIH TWA (mg	(m3)	200 mg/m3
USA ACGIH	ACGIH TWA (mg	/m²)	200 mg/m ³
2-Ethylhexyl nitrate (27247-9	6-7)		
USA ACGIH	ACGIH TWA		Not applicable.
USA OSHA	OSHA PEL (TWA	.)	Not applicable.
Solvent naphtha, petroleum, heavy aromatic (64742-94-5)			
USA ACGIH	ACGIH TWA	94742-94-3)	Not applicable.
		Not applicable.	
	· ·		
2-Butoxyethanol (111-76-2)			00
USA ACGIH	ACGIH TWA (ppr	n)	20 ppm
07/04/2014		EN (English)	3/8



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

ccording to the Hazard Communicati	ion Standard (CFR29 2	1910.1200) HazCom 2012.		
2-Butoxyethanol (111-76-2)				
USA OSHA	OSHA PEL (TWA) (mg/m ³) 240 mg/m ³		240 mg/m ³	
USA OSHA	OSHA PEL (TWA	A) (ppm)	50 ppm	
Solvent naphtha, petroleum	, light aromatic (64	1742-95-6)		
USA ACGIH	ACGIH TWA		Not applicable.	
USA OSHA	OSHA PEL (TWA	A)	Not applicable.	
Pseudocumene (95-63-6)				
USA ACGIH	ACGIH TWA (ppr	m)	25 ppm	
Naphthalene (91-20-3)				
USA ACGIH	ACGIH TWA (ppr	m)	10 ppm	
USA ACGIH	ACGIH STEL (pp	m)	15 ppm	
USA OSHA	OSHA PEL (TWA	A) (mg/m³)	50 mg/m ³	
USA OSHA	OSHA PEL (TWA	A) (ppm)	10 ppm	
Phenylethane (100-41-4)				
USA ACGIH	ACGIH TWA (ppr	m)	20 ppm	
USA OSHA	OSHA PEL (TWA	A) (mg/m³)	435 mg/m ³	
USA OSHA	OSHA PEL (TWA	A) (ppm)	100 ppm	
Vinyl acetate (108-05-4)				
USA ACGIH	ACGIH TWA (ppr	m)	10 ppm	
USA ACGIH	ACGIH STEL (pp	m)	15 ppm	
Cumene (98-82-8)				
USA ACGIH	ACGIH TWA (ppr	m)	50 ppm	
USA OSHA	OSHA PEL (TWA	A) (mg/m³)	245 mg/m ³	
USA OSHA	OSHA PEL (TWA	λ) (ppm)	50 ppm	
8.2. Exposure controls				
Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.				
Personal protective equipment : Avoid all unnecessary exposure.				
Hand protection : Wear chemically resistant protective gloves.		gloves.		
Eye protection :		Safety glasses or goggles are recommended when using product.		
		Wear suitable protective clothing.		
Respiratory protection : A NIOSH approved respirator is recommended in poorly ventilated areas or when permissibl exposure limits may be exceeded. Respirator selection must be based on known or anticipat exposure levels, the hazards of the product and the safe working limits of the selected respirator respirator and the safe working limits of the selected respirator respirator and the safe working limits of the selected respirator respirator and the safe working limits of the selected respirator respirator and the safe working limits of the selected respirator respirator and the safe working limits of the selected respirator respirator and the safe working limits of the selected respirator respirator selected respira				
Environmental exposure controls :		Maintain levels below Community environmental protection thresholds.		
Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.				
SECTION 9: Physical ar	nd chemical pr	operties		
9.1. Information on basi				
Physical state		Liquid.		
Appearance : Clear.				
Colour : Amber.				
Odour	:	Petroleum odor.		
Odour threshold	Ddour threshold : No data available.			

pН : No data available. : No data available.

Relative evaporation rate (butylacetate=1)

07/04/2014

EN (English)



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

1			
	Melting point	:	No data available.
	Freezing point	:	No data available.
	Boiling point	:	No data available.
	Flash point	:	~ 50 °C (~ 122 °F)
	Self ignition temperature	:	No data available.
	Decomposition temperature	:	No data available.
	Flammability (solid, gas)	:	Flammable.
	Vapour pressure	:	No data available.
	Relative vapour density at 20 °C	:	No data available.
	Relative density	:	0.835 - 0.855
	Solubility	:	No data available.
	Log Pow	:	No data available.
	Log Kow	:	No data available.
	Viscosity, kinematic	:	No data available.
	Viscosity, dynamic	:	No data available.
	Explosive properties	:	No data available.
	Oxidising properties	:	No data available.
	Explosive limits	:	No data available.

9.2. **Other information**

No additional information available

SECTION 10: Stability and reactive	vity	
10.1. Reactivity		
No dangerous reaction known under conditions of normal use.		
10.2. Chemical stability		
Stable under normal storage conditions. May	y form flammable/explosive vapour-air mixture.	
10.3. Possibility of hazardous reactio	ns	
No dangerous reaction known under condition	ons of normal use.	
10.4. Conditions to avoid		
Heat. Incompatible materials. Open flame.		
10.5. Incompatible materials		
Strong oxidizing agents. Strong reducing age	ents.	
10.6. Hazardous decomposition prod	ucts	
May include, and are not limited to: oxides o	f carbon.	
SECTION 11: Toxicological inform	mation	
11.1. Information on toxicological effe		
Acute toxicity	: Toxic if inhaled.	
-		
POW-R 365		
LD50 oral rat	> 2000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat (mg/l)	>2.0 but ≤10.0 mg/l/4h	
Kerosine, petroleum (8008-20-6)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat (mg/l)	> 5.28 mg/l/4h	
2-Ethylhexyl nitrate (27247-96-7)		
LD50 oral rat	> 2000 mg/kg	
LD50 dermal rabbit	> 4820 mg/kg	
LC50 inhalation rat (mg/l)	> 14 mg/l/4h	
Solvent naphtha, petroleum, heavy aron	natic (64742-94-5)	
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000mg/kg	
07/04/2014	EN (English) 5/8	



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Solvent naphtha, petroleum, heavy aromatic		
LC50 inhalation rat (mg/l)	> 5.28 mg/l/4h	
2-Butoxyethanol (111-76-2)		
LD50 oral rat	470 mg/kg	
LD50 dermal rabbit	220 mg/kg	
LC50 inhalation rat (ppm)	450 ppm/4h	
Solvent naphtha, petroleum, light aromatic (LD50 oral rat		
	8400 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat (ppm)	3400 ppm/4h	
LC50 inhalation rat (mg/l)	> 5.2 mg/l/4h	
Pseudocumene (95-63-6)		
LD50 oral rat	3400 mg/kg	
LD50 dermal rabbit	> 3160 mg/kg	
LC50 inhalation rat (mg/l)	18 g/m³/4h	
Nonhtholono (01.20.2)		
Naphthalene (91-20-3)		
LD50 oral rat LD50 dermal rabbit	490 mg/kg	
LD50 dermai raddit	> 20 g/kg	
Phenylethane (100-41-4)		
LD50 oral rat	3500 mg/kg	
LD50 dermal rabbit	15354 mg/kg	
LC50 inhalation rat (mg/l)	17.2 mg/l/4h	
Vinyl acetate (108-05-4)		
LD50 oral rat	2920 mg/kg	
LD50 dermal rabbit	2320 mg/kg	
	11400 mg/m ³ /4h	
LC50 inhalation rat (mg/m ³)	11400 IIIg/III//4II	
Cumene (98-82-8)		
LD50 oral rat	1400 mg/kg	
LD50 dermal rabbit	> 3160 mg/kg	
LC50 inhalation rat (mg/l)	39000 mg/m³/4 h	
Skin corrosion/irritation	: Causes skin irritation.	
Serious eye damage/irritation	: Causes serious eye irritation.	
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.	
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.	
Carcinogenicity	: Suspected of causing cancer.	
2-Butoxyethanol (111-76-2)		
IARC group	3 - Not classifiable	
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity	
Naphthalene (91-20-3)		
IARC group	2B - Possibly carcinogenic to humans	
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen	
Phenylethane (100-41-4)		
IARC group	2B - Possibly carcinogenic to humans	
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity	
Vinyl acetate (108-05-4)		
IARC group	2B - Possibly carcinogenic to humans	
Cumene (98-82-8)	2D. Dessibly corring and to human	
IARC group	2B - Possibly carcinogenic to humans	
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity	
Reproductive toxicity	Reproductive toxicity : Based on available data, the classification criteria are not met.	
07/04/2014	EN (English) 6/8	



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.
Aspiration hazard	: May be fatal if swallowed and enters airways
Symptoms/injuries after inhalation	: Toxic if inhaled. May cause drowsiness, dizziness and central nervous system depression. May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: May cause long-term adverse effects in the aquatic environment.
12.2. Persistence and degradability	
POW-R 365	
Persistence and degradability	Not established.
12.3. Bioaccumulative potential	
POW-R 365	
Bioaccumulative potential	Not established.
12.4. Mobility in soil	
No additional information available	
12.5. Other adverse effects	
Effect on ozone layer	: No additional information available
Effect on the global warming	: No known ecological damage caused by this product.

SECTION 13: Disposal considerations		
13.1. Waste treatment methods		
Waste disposal recommendations	: This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.	
Additional information	: Handle empty containers with care because residual vapours are flammable.	

SECTION 14: Transport information	
In accordance with DOT	
14.1. UN number	
UN-No.	UN1993
14.2. UN proper shipping name	
Proper Shipping Name	: Flammable liquids, n.o.s. (Petroleum, 2-ethylhexyl nitrate)
Department of Transportation Hazard Classes	: 3
Hazard labels	3
Packing group (DOT)	: 111
14.3. Additional information	
Other information	: No supplementary information available.
Special transport precautions	: Do not handle until all safety precautions have been read and understood.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.


Pseudocumene (95-63-6)			
Listed on SARA Section 313 (Specific toxic ch	emical listings)		
SARA Section 313 - Emission Reporting	1.0 %		
Naphthalene (91-20-3)			
Listed on SARA Section 313 (Specific toxic ch	emical listings)		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.		
SARA Section 313 - Emission Reporting	0.1 %		
Phenylethane (100-41-4)			
Listed on SARA Section 313 (Specific toxic ch	emical listings)		
SARA Section 313 - Emission Reporting	0.1 %		
Vinyl acetate (108-05-4)			
Listed on SARA Section 302 (Specific toxic ch Listed on SARA Section 313 (Specific toxic ch			
SARA Section 302 Threshold Planning Quant	Q) 1000		
SARA Section 313 - Emission Reporting	0.1 %		
Cumene (98-82-8)			
Listed on SARA Section 313 (Specific toxic ch	emical listings)		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.		
SARA Section 313 - Emission Reporting	1.0 %		

15.2. US State regulations

POW-R 365	
State or local regulations	This product contains chemicals known to the State of California to cause cancer.

SECTION 16: Other information

Indication of changes	:	None.
Date of issue	:	07/04/2014
Other information	:	None.
NFPA health hazard	:	2
NFPA fire hazard	:	2
NFPA reactivity	:	0



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

