



SAFETY DATA SHEET

Revision Date 06-Mar-2015

Version 1

1. IDENTIFICATION

Product identifier

Product Name SENSOR-SAFE VALVE COVER AND OIL PAN OEM RTV .5OZ TB CG

Other means of identification

Product Code 22072

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex
10 Columbus Blvd.
Hartford, CT 06106 USA

Distributor

ITW Permatex Canada
35 Brownridge Road, Unit 1
Halton Hills, ON Canada L7G 0C6
Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex
(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

E-mail address mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 2

Label elements

Emergency Overview

Warning

Causes serious eye irritation
May cause an allergic skin reaction
Suspected of causing cancer



Appearance Black

Physical state Paste

Odor Mild

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Contaminated work clothing should not be allowed out of the workplace

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
Specific treatment (see supplemental first aid instructions on this label)
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN: Wash with plenty of soap and water
If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Harmful to aquatic life with long lasting effects

Unknown acute toxicity

25.95% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED	70131-67-8	15 - 40	*
CALCIUM CARBONATE	471-34-1	15 - 40	*
LIMESTONE	1317-65-3	10 - 30	*
SYNTHETIC ISOPARAFFINIC HYDROCARON	64742-47-8	3 - 7	*
VINYL OXIMINOSILANE	2224-33-1	3 - 7	*
2-BUTANONE OXIME	96-29-7	0.1 - 1	*
CARBON BLACK	1333-86-4	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	Get medical advice/attention if you feel unwell.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact	IF ON SKIN: Wash with soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Ingestion	IF SWALLOWED. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO₂), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

None in particular.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin. Use personal protective equipment as required.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

- Methods for containment** Prevent further leakage or spillage if safe to do so.
- Methods for cleaning up** Ensure adequate ventilation. Flood with water to complete polymerization and scrape off floor. Sweep up and shovel into suitable containers for disposal. Slippery, can cause falls if walked on.
- Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

- Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture.
- Incompatible materials** Strong oxidizing agents, Acids, Water

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
CALCIUM CARBONATE 471-34-1	-	-	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
LIMESTONE 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
CARBON BLACK 1333-86-4	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers
 Eyewash stations
 Ventilation systems

Individual protection measures, such as personal protective equipment

- Eye/face protection** Wear safety glasses with side shields (or goggles).
- Skin and body protection** Wear protective gloves and protective clothing.
- Respiratory protection** Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Paste
Appearance	Black
Odor	Mild
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	Not Applicable	Polymerization
Flash point	> 93 °C / > 200 °F	Tag Closed Cup
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	<5 mm Hg @ 80°F	
Vapor density	>1	Air = 1
Relative density	1.44	
Water solubility	Not applicable	Polymerization
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	3.1%
Density	No information available
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity
No data available

Chemical stability
Stable under recommended storage conditions.

Possibility of Hazardous Reactions
None under normal processing.

Conditions to avoid
Excessive heat.

Incompatible materials
Strong oxidizing agents, Acids, Water

Hazardous Decomposition Products

Carbon oxides
 Nitrogen oxides (NOx)
 Formaldehyde
 May release 2-butanone oxime (ethyl methyl ketoxime) at elevated temperature

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.
Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.
Ingestion Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	-	> 16 mL/kg (Rabbit)	> 8750 mg/m ³ (Rat) 7 h
CALCIUM CARBONATE 471-34-1	= 6450 mg/kg (Rat)	-	-
SYNTHETIC ISOPARAFFINIC HYDROCARON 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
2-BUTANONE OXIME 96-29-7	= 930 mg/kg (Rat)	= 0.2 mg/kg (Rabbit)	= 20 mg/L (Rat) 4 h
CARBON BLACK 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
Germ cell mutagenicity No information available.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
CARBON BLACK 1333-86-4	A3	Group 2B	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)
A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)
Group 2B - Possibly Carcinogenic to Humans
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Target Organ Effects Eyes, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 12170 mg/kg
ATEmix (dermal) 10754 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

93.91% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea

SYNTHETIC ISOPARAFFINIC HYDROCARON 64742-47-8	-	45: 96 h Pimephales promelas mg/L LC50 flow-through 2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static	4720: 96 h Den-dronereides heteropoda mg/L LC50
2-BUTANONE OXIME 96-29-7	83: 72 h Desmodemus subspicatus mg/L EC50	777 - 914: 96 h Pimephales promelas mg/L LC50 flow-through 320 - 1000: 96 h Leuciscus idus mg/L LC50 static 760: 96 h Poecilia reticulata mg/L LC50 static	750: 48 h Daphnia magna mg/L EC50
CARBON BLACK 1333-86-4	-	-	5600: 24 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
2-BUTANONE OXIME 96-29-7	0.65

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Do not reuse container.
US EPA Waste Number	Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. TRANSPORT INFORMATION

DOT

Proper shipping name: Not regulated

IATA

Proper shipping name: Not regulated

IMDG

Proper shipping name: Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies

EINECS/ELINCS	Not Listed
ENCS	Not Listed
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
CARBON BLACK - 1333-86-4	Carcinogen
SILICA, QUARTZ - 14808-60-7	Carcinogen
ETHANOL - 64-17-5	Carcinogen Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
LIMESTONE 1317-65-3	X	X	X
ALUMINIUM POWDER 7429-90-5	X	X	X
CARBON BLACK 1333-86-4	X	X	X
SILICA, QUARTZ 14808-60-7	X	X	X

ETHANOL 64-17-5	X	X	X
--------------------	---	---	---

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

<u>NFPA</u>	Health hazards 2	Flammability 1	Instability 0	-
<u>HMIS</u>	Health hazards 2	Flammability 1	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)

Revision Date 06-Mar-2015

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet