

# PENRAY NON-CHLORINATED BRAKE CLEANER

### Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012. Date of issue: 03/28/2014 Revision date: 03/28/2014 Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Product identifier** 

: PENRAY NON-CHLORINATED BRAKE CLEANER ULTRA LOW VOC Product name

Product code : 4705

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Brake Cleaner.

### Details of the supplier of the safety data sheet

The Penray Companies, Inc. 440 Denniston Ct. 60090 Wheeling, IL T (800) 373-6729 rotto@penray.com

**Emergency telephone number** 

**Emergency number** (800) 373-6729

CHEMTREC (800) 424-9300

CHEMTREC International +1 (703) 527-3887 24 hr

### **SECTION 2: Hazards identification**

#### Classification of the substance or mixture

#### **GHS-US** classification

Flammable Liquid 2

Eye irritation 2A

Reproductive toxicity 2 (developmental)

Specific target organ toxicity - Single exposure 3
Specific target organ toxicity - Repeated exposure 2

#### 2.2 Label elements

### **GHS-US** labelling

Hazard pictograms (GHS-US)



GHS07



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Highly flammable liquid and vapor. Causes serious eye irritation. Suspected of damaging the

unborn child. May cause drowsiness or dizziness. May cause damage to organs through

prolonged or repeated.

: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly Precautionary statements (GHS-US)

closed. Ground/Bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash hands thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe gas/mist/vapors/spray. If exposed or concerned: Get medical advice/attention. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Keep cool. Dispose of contents and container in accordance with all local, regional, national and international regulations.

### Other hazards

No additional information available

#### **Unknown acute toxicity (GHS-US)**

No additional information available

### **SECTION 3: Composition/information on ingredients**

### **Substance**

Not applicable



### Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

#### **Mixture**

Name	Product identifier	%	GHS-US classification
Acetone	(CAS No) 67-64-1	60 - 100	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Toluene	(CAS No) 108-88-3	1-5	Flam. Liq. 2 Acute Tox. 4 (Oral) Skin Irrit. 2 Repr. 2 STOT SE 3 STOT RE 2 Asp. Tox. 1
The exact percentage (concentration) of concentration	omposition has been withheld as a trade secret in accorda	nnce with paragraph	n (i) of

#### **SECTION 4: First aid measures**

#### **Description of first aid measures**

First-aid measures after inhalation

: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact

In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

First-aid measures after eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.

First-aid measures after ingestion

If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

#### Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation

: May cause drowsiness, dizziness and central nervous system depression. May cause respiratory irritation.

Symptoms/injuries after skin contact

: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Symptoms/injuries after eye contact

Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Symptoms/injuries after ingestion

: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

### Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

### **SECTION 5: Firefighting measures**

### **Extinguishing media**

Suitable extinguishing media : Powder, water spray, foam, carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

#### Advice for firefighters

Protection during firefighting

: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

#### **SECTION 6: Accidental release measures**

### Personal precautions, protective equipment and emergency procedures

General measures

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

### Methods and material for containment and cleaning up

For containment

: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

: Scoop up material and place in a disposal container. Provide ventilation. Methods for cleaning up

#### Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

### **SECTION 7: Handling and storage**

### **Precautions for safe handling**

Precautions for safe handling

Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Do not breathe gas/mist/vapors/spray. Do not swallow. Handle and open container with care. Use only non-sparking tools. When using do not eat, drink or smoke. Use only outdoors or in a wellventilated area.

03/28/2014 EN (English) 2/6



### Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

#### Conditions for safe storage, including any incompatibilities

: Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Storage conditions

Store locked up. Keep cool. Keep away from heat, sparks, and flame.

#### 7.3. Specific end use(s)

Not available.

### SECTION 8: Exposure controls/personal protection

#### **Control parameters** 8.1.

Acetone (67-64-1)		
USA ACGIH	ACGIH TWA (ppm)	500 ppm
USA ACGIH	ACGIH STEL (ppm)	750 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	2400 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

Toluene (108-88-3)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm

#### **Exposure controls**

: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below Appropriate engineering controls

recommended exposure limits.

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection Wear chemically resistant protective gloves.

Eye protection Safety glasses or goggles are recommended when using product.

Skin and body protection Wear suitable protective clothing.

A NIOSH approved respirator is recommended in poorly ventilated areas or when permissible Respiratory protection

exposure limits may be exceeded. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Maintain levels below Community environmental protection thresholds. Environmental exposure controls

Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully Other information

before eating or smoking. Handle according to established industrial hygiene and safety practices.

### SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Physical state : Liquid Appearance Clear. Colour Colourless. Odour Solvent.

Odour threshold : No data available. No data available pΗ Relative evaporation rate (butylacetate=1) No data available. Melting point : No data available. Freezing point : No data available.

: ~ 56 °C (~ 133 °F) (Acetone) **Boiling point** Flash point ~ -20 °C (~ -4 °F) (Acetone)

Self ignition temperature : No data available. Decomposition temperature : No data available. Flammability (solid, gas) Flammable Vapour pressure No data available. Relative vapour density at 20 °C : No data available. Relative density : 0.790 - 0.796 Solubility : No data available. Log Pow No data available. Log Kow : No data available. : No data available. Viscosity, kinematic

03/28/2014 EN (English) 3/6



### Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Viscosity, dynamic : No data available.

Explosive properties : No data available.

Oxidising properties : No data available.

Explosive limits : No data available.

#### 9.2. Other information

No additional information available

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2. Chemical stability

Stable under normal storage conditions. May form flammable/explosive vapour-air mixture.

### 10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

#### 10.4. Conditions to avoid

Sources of ignition. Incompatible materials.

### 10.5. Incompatible materials

Acids. Amines. Bases. Oxidizers.

#### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

4705		
LD50 oral rat	> 2000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat (mg/l)	> 20 mg/l/4h	

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg
LC50 inhalation rat (mg/l)	50100 mg/m³/8h

Toluene (108-88-3)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	12124 mg/kg
LD50 dermal rabbit	8390 mg/kg
LC50 inhalation rat (mg/l)	28.1 mg/l/4h

Skin corrosion/irritation : Based on available data, the classification criteria are not met.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Based on available data, the classification criteria are not met.

Germ cell mutagenicity : Based on available data, the classification criteria are not met.

Carcinogenicity : Based on available data, the classification criteria are not met.

Toluene (108-88-3)	
IARC group	3

exposure)

Reproductive toxicity : Suspected of damaging the unborn child.

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation : May cause drowsiness, dizziness and central nervous system depression. May cause respiratory

irritation.

Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the

skin.

Symptoms/injuries after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Symptoms/injuries after ingestion : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

03/28/2014 EN (English) 4/6



### Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

#### 12.2. Persistence and degradability

4705

Persistence and degradability Not established.

#### 12.3. Bioaccumulative potential

4705

Bioaccumulative potential Not established.

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal

regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information : Handle empty containers with care because residual vapours are flammable.

## **SECTION 14: Transport information**

In accordance with DOT

### 14.1. UN number

UN-No. : UN1993

### 14.2. UN proper shipping name

Proper Shipping Name : Flammable liquids, n.o.s. (Acetone, Toluene)

Department of Transportation Hazard Classes : 3

Hazard labels



Packing group : II

### 14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.





### Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

### Acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

### Toluene (108-88-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting 1.0 %

### 15.2. US State regulations

State or local regulations	This product contains chemicals known to the State of California to cause cancer, birth
	defects or other reproductive harm.


### SOURCE AGENCY CARCINOGEN CLASSIFICATIONS

IARC	International Agency for Research on Cancer.
	1 - Carcinogenic to humans; 2A - Probably carcinogenic to humans; 2B - Possibly carcinogenic to humans; 3 - Not classifiable; 4 - Probably not carcinogenic to humans.
NTP	National Toxicology Program.
	1 - Evidence of Carcinogenicity;     2 - Known Human Carcinogens;     3 - Reasonably anticipated to be Human Carcinogen;     4 - Substances delisted from report on Carcinogens;     5 - Twelfth Report - Items under consideration.

### **SECTION 16: Other information**

Indication of changes: None.Date of issue: 03/28/2014Other information: None.

NFPA health hazard : 2
NFPA fire hazard : 3
NFPA reactivity : 0



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product



