

# MATERIAL SAFETY DATA SHEET

Trade Name: Johnsens Diesel Fuel Conditioner  
 MSDS NO. 5000  
 Revision Date: 11/13/2007  
 Date Printed: 12/30/2008

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: Johnsens Diesel Fuel Conditioner  
 Synonyms: None  
 Emergency Telephone (24 hr.): CHEMTREC 1-800-424-9300  
 Supplier: Technical Chemical Company, P.O. Box 139, Cleburne, Texas 76033

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight %	OSHA TWA	OSHA STEL	OSHA SKIN
Xylene 1330-20-7	<1	Not Listed	Not Listed	Not Listed
400/500 Base Solvent 64742-47-8	80-95	500 ppm	Not Listed	Not Listed
Solvent Naphtha, light aromatic 64742-95-6	4-8	Not Listed	Not Listed	Not Listed
1,2,4-trimethylenebenzene 95-63-6	<1	Not Listed	Not Listed	Not Listed
Cumene 98-82-8	<1	Not Listed	Not Listed	Not Listed

Component	Weight %	OSHA Z PEL	OSHA Z TWA	OSHA Z Ceiling
Xylene 1330-20-7	<1	Not Listed	Not Listed	Not Listed
400/500 Base Solvent 64742-47-8	80-95	500 ppm	500 ppm	Not Listed
Solvent Naphtha, light aromatic 64742-95-6	4-8	Not Listed	Not Listed	Not Listed
1,2,4-trimethylenebenzene 95-63-6	<1	Not Listed	Not Listed	Not Listed
Cumene 98-82-8	<1	245 mg/m <sup>3</sup> 50 ppm	Not Listed	Not Listed

Component	ACGIH TLV TWA	ACGIH TLV STEL	ACGIH TLV Ceiling
Xylene 1330-20-7	435 mg/m <sup>3</sup> 100 ppm	Not Listed	Not Listed
400/500 Base Solvent 64742-47-8	Not Listed	Not Listed	Not Listed
Solvent Naphtha, light aromatic 64742-95-6	Not Listed	Not Listed	Not Listed
1,2,4-trimethylenebenzene 95-63-6	Not Listed	Not Listed	Not Listed
Cumene 98-82-8	Not Listed	Not Listed	Not Listed

# MATERIAL SAFETY DATA SHEET

Trade Name: Johnsens Diesel Fuel Conditioner  
MSDS NO. 5000  
Revision Date: 11/13/2007  
Date Printed: 12/30/2008

## 3. HAZARDS IDENTIFICATION

**Emergency Overview:** Caution: Combustible. Harmful if inhaled. Harmful or fatal if liquid is aspirated into lungs. Gross inhalation overexposure may cause: Central nervous system depression with dizziness, confusion, incoordination, drowsiness or unconsciousness or death. Keep away from heat, sparks and flame. Avoid breathing vapors. Do not get in eyes, on skin, or on clothing. May cause delayed lung injury. Causes severe eye irritation. May cause severe skin irritation. WARNING: POSSIBLE CANCER HAZARD

**HMIS Classification:** Health: 3 Flammability: 2 Physical Hazard: 0  
**NFPA Rating:** Health: 2 Flammability: 2 Reactivity: 0

## 4. FIRST AID MEASURES

**Eye Contact:** In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

**Ingestion:** If swallowed, do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person.

**Inhalation:** If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

**Skin Contact:** Wash with soap and water. Remove contaminated clothing and shoes, and launder before reuse. Get medical attention if irritation persists.

## 5. FIRE FIGHTING MEASURES

### Flammable Properties

**Flash Point °F(°C):** >155 F  
**Flash Point Method:** TAG Closed Cup  
**Flammable Limits in Air - Lower (%):** .7 vol %  
**Flammable Limits in Air - Upper (%):** 6 vol %  
**Autoignition Temperature °F(°C):** >550 F  
**Extinguishing Media:** Carbon Dioxide, Dry Chemicals, Foam. Water stream may spread fire. Use water spray to keep containers cool that are exposed to heat or flames.

### Protection Of Fire-Fighters:

**Special Fire-Fighting Procedures:** Wear approved positive-pressure self-contained breathing apparatus and protective clothing.  
**Hazardous Combustion Products:** Fumes and Smoke. Carbon Monoxide. Oxides of Carbon. Oxides of Nitrogen.  
**Aerosol Comments:** Not Applicable

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Wear appropriate protective clothing and equipment to prevent skin and eye contact.  
**Spill Procedures:** Wear protective equipment specified.  
**Action to be taken if material is released or spilled:** Increase area ventilation. Remove sources of ignition. Leaking containers should be removed to an isolated, well-ventilated area and transferred to other suitable containers. Wipe, scrape or soak up in an inert material and put in a container for disposal.  
**Environmental Precautions:** Do not allow to enter sanitary drains, sewer or surface and subsurface waters.

## 7. HANDLING AND STORAGE

**Handling and Storage:** Keep away from heat and open flame. Keep containers tightly closed when not in use. Wash thoroughly after handling. Use only with adequate ventilation. Avoid extreme temperatures. Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls:** Exhaust ventilation. Showers. Eyewash stations.  
**Eyes:** Wear safety glasses or goggles to protect against exposure. Chemical goggles; also wear a face shield if splashing hazard exists.  
**Skin Protection:** Avoid skin contact. Wear protective clothing and gloves. Neoprene coated apron or clothing. Nitrile coated apron or clothing.

# MATERIAL SAFETY DATA SHEET

Trade Name: Johnsens Diesel Fuel Conditioner  
MSDS NO. 5000  
Revision Date: 11/13/2007  
Date Printed: 12/30/2008

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Respiratory Protection:** Use an approved NIOSH organic vapor respirator below the TLV. If TLV is exceeded or overexposure is likely, use positive pressure or self contained breathing apparatus.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Colorless to light yellow liquid  
**Odor:** KEROSENE  
**pH Value:** Essentially neutral  
**Vapor Pressure:** .33 mm @ 100 F  
**Vapor Density (Air=1):** 6  
**Boiling Point (°F):** Not determined.  
**Melting/Freezing Point:** Not determined.  
**Solubility in Water:** NEGLIGIBLE  
**Bulk Density at 20°C:** Not Determined  
**Molecular Weight:** Mixture  
**Specific Gravity (H2O=1):** .81 @ 70 F  
**Viscosity:** 1.7 cSt @ 40 C  
**Evaporation Rate:** Not Determined  
**VOC Content(%):** >86%  
**Decomposition Temperature:** Not Known

## 10. STABILITY AND REACTIVITY

**Chemical Stability:** STABLE.  
**Conditions to Avoid:** Keep away from heat, sparks and flame. Do not expose to heat or store at temperatures above 120 F.  
**Materials to Avoid:** Strong oxidizing agents.  
**Hazardous Decomposition Products:** Carbon monoxide. and other asphxiants.  
**Hazardous Polymerization:** WILL NOT OCCUR

## 11. TOXICOLOGICAL INFORMATION

### Toxicological Data:

Component	Route	Species	Dose
Xylene 1330-20-7	Inhalation	Rats	Not known.
400/500 Base Solvent 64742-47-8	Inhalation	Rats	Not known.
Solvent Naphtha, light aromatic 64742-95-6	Inhalation	Rats	Not known.
1,2,4-trimethylenebenzene 95-63-6	Inhalation	Rats	Not known.
Cumene 98-82-8	Inhalation	Rats	Not known.

**Carcinogenicity:**

# MATERIAL SAFETY DATA SHEET

Trade Name: Johnsens Diesel Fuel Conditioner  
 MSDS NO. 5000  
 Revision Date: 11/13/2007  
 Date Printed: 12/30/2008

Component	IARC	NTP	OSHA
Xylene 1330-20-7	Not Listed	Not Listed	Not Listed
400/500 Base Solvent 64742-47-8	Not Listed	Not Listed	Not Listed
Solvent Naphtha, light aromatic 64742-95-6	Not Listed	Not Listed	Not Listed
1,2,4-trimethylenebenzene 95-63-6	Not Listed	Not Listed	Not Listed
Cumene 98-82-8	Not Listed	Not Listed	Not Listed

## 12. ECOLOGICAL INFORMATION

**Remarks:** Ecological testing has not been conducted on this product.

## 13. DISPOSAL CONSIDERATION

**Waste Classification:** Not determined.  
**Waste Management:** Not determined.  
**Disposal Method:** Disposal should be made in accordance with federal, state and local regulations.

## 14. TRANSPORTATION INFORMATION

**U.S. DOT:**  
**Proper Shipping Name:** Not Regulated  
**Hazard Class:** Not Applicable  
**UN/NA Number:** Not Applicable  
**DOT Packing Group:** Not Applicable

**IMDG:**  
**Proper Shipping Name:** Not Regulated  
**Hazard Class:** Not Applicable  
**Hazard Subclass:** Not Applicable  
**UN No.:** Not Applicable  
**Packing Group:** Not Applicable  
**Marine Pollutant:** No

## 15. REGULATORY INFORMATION

**US Federal Regulations:**

Component	SARA 313	SARA 302	TPQ	RQ
Xylene 1330-20-7	Listed.	Not Listed	Not Listed	Not Listed
400/500 Base Solvent 64742-47-8	Not Listed	Not Listed	Not Listed	Not Listed
Solvent Naphtha, light aromatic 64742-95-6	Not Listed	Not Listed	Not Listed	Not Listed
1,2,4-trimethylenebenzene 95-63-6	Not Listed	Not Listed	Not Listed	Not Listed
Cumene 98-82-8	Listed.	Not Listed	Not Listed	Not Listed

# MATERIAL SAFETY DATA SHEET

**Trade Name:** Johnsens Diesel Fuel Conditioner  
**MSDS NO.** 5000  
**Revision Date:** 11/13/2007  
**Date Printed** 12/30/2008  
**SARA 311/312 Hazard Catagories:** Not Determined.

**State Regulations:**

Component	California Prop. 65 Cancer list	California - Prop 65 Developmental Toxicity	California Prop. 65 Reproductive Female	California Prop. 65 Reproductive Male
Xylene 1330-20-7	Not Listed	Not Listed	Not Listed	Not Listed
400/500 Base Solvent 64742-47-8	Not Listed	Not Listed	Not Listed	Not Listed
Solvent Naphtha, light aromatic 64742-95-6	Not Listed	Not Listed	Not Listed	Not Listed
1,2,4-trimethylenebenzene 95-63-6	Not Listed	Not Listed	Not Listed	Not Listed
Cumene 98-82-8	Not Listed	Not Listed	Not Listed	Not Listed

Component	New Jersey Right-to-Know List:
Xylene 1330-20-7	Substance no. 2014
Cumene 98-82-8	Substance no. 0542

**U.S. TSCA:** One or more components of this product is not listed on the TSCA Inventory.  
**Canadian Inventory:** One or more components of this product is not listed on the Canadian DSL or NDSL Inventory.

**Consumer Product Safety Improvement Act of 2008 General Conformity Certification**

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product container.

## 16. OTHER INFORMATION

**General Notes:**  
**Disclaimer:** Do not allow undiluted material or large quantities to reach groundwater, bodies of water or sewer system. The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.