## SUPER X ENGINE CLEANER AND DEGREASER--620

MSDS Number: 620 Revision Date: 10/12/10

Page 1 of 4

### PRODUCT AND COMPANY IDENTIFICATION

### **Manufacturer**

The Penray Companies, Inc.

440 Denniston Ct. Wheeling, IL 60090

Contact: EH&S Manager Telephone Number: 847-459-5000 FAX Number: 847-459-5043

E-Mail: Web

**Product Name:** SUPER X ENGINE CLEANER AND DEGREASER--620

**Revision Date:** 10/12/10 Version: 2 **MSDS Number:** 620

**Common Name:** AEROSOL ENGINE CLEANER AND DEGREASER CONTAINING KEROSENE

EMERGENCY PHONE NUMBER (800) 752-7869

NFPA 704M RATING:

HEALTH:1 FIRE:3 **REACTIVITY: 0** SPECIAL:

O=INSIGNIFICANT 1=SLIGHT 2=MODERATE 3=HIGH 4=EXTREME

## HAZARDS IDENTIFICATION

Route of Entry: Skin absorption and inhalation

**Target Organs:** Lungs, kidneys, liver and nervous system. Inhalation: Respiratory irritation and dizziness

**Skin Contact:** Prolonged contact with skin can cause irritation. Repeated skin contact may cause persistent

irritation and dermatitis

**Eye Contact:** Will cause irritation upon contact.

Ingestion: Product may cause discomfort, nausea, vomiting and diarrhea.

CARCINOGENICITY: Product is not considered a carcinogen by OSHA, NTP or IARC.

MEDICAL CONDITIONS: Pre-existing eye or skin conditions may be aggravated by over-exposure to this product.

## **COMPOSITION/INFORMATION ON INGREDIENTS**

INGREDIENT	CAS NUMBER	PERCENT WEIGHT
KEROSENE 2-BUTOXYETHANOL NONYL PHENOL ETHOXYLATE PROPANE/n-BUTANE Mixture BASE LUBRICATING OILS	8008-20-6 111-76-2 9016-45-9 74-98-6/106-97-8 MIXTURE	5-10% 3-7% 1-5% 10-30% 40-70%

## SUPER X ENGINE CLEANER AND DEGREASER--620

MSDS Number: 620 Revision Date: 10/12/10

Page 2 of 4

4 FIRST AID MEASURES

5

6

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. Seek medical attention. Inhalation

hazard unlikely due to low volatility of product.

**Skin Contact:** Wash area with soap and water, seek medical attention if irritation persists

**Eye Contact:** Immediately flush eyes with plenty of water for 15 minutes. Seek medical attention.

**Ingestion:** DO NOT induce vomiting. Only give CONSCIOUS victim two glasses of water and seek medical

attention. NEVER give UNCONSCIOUS anything by mouth.

FIRE FIGHTING MEASURES

Flammability Classification: Class III Extremely Flammable Aerosol

EXTINGUISHING MEDIA: Carbon Dioxide (CO2) Dry Chemical, Foam.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and can collect in low areas

FIRE FIGHTING INSTRUCTIONS: Containers can build up pressure if exposed to fire. Containers should be cooled with

FIRE FIGHTING EQUIPMENT: Self- contained breathing apparatus with full face piece operated in positive pressure mode.

## ACCIDENTAL RELEASE MEASURES

SPILL/LEAK PROCEDURES: Notify safety personnel ,evacuate all unnecessary personnel and provide adequate ventilation. If feasible, and without risk,clean-up personnel should stop leak. All clean up personnel should wear proper personal protective equipment.

SMALL SPILLS:Clean with inert absorbent and place in recovery drums for disposal.

LARGE SPILLS: Dike to prevent further migration of material. DO NOT release into waterways or sewers. Follow applicable federal and state regulations.

7 HANDLING AND STORAGE

**Handling Precautions:** Wash thoroughly after handling. Do not get into eyes, on skin or on clothing.. Do not

smoke while using this product. Do not use near excessive heat, sparks, or open flame.

Storage Requirements: Store in clean, dry locations away from excessive heat. Store in areas designated for the

storage of Level II aerosols according to

NFPA 30B (Manufacturing and Storage of Aerosol Products.)

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls:** Eye wash station and safety shower.

Strong general ventilation or local exhaust.

**Protective Equipment:** EYE: Chemical splash goggles with indirect or no ventilation.

SKIN: Chemical resistant gloves, such as nitrile.

RESPIRATORY: Organic vapor air purifying respiator if vapors are a nuisance or if the

concentrations are above PEL or TLV.

Exposure Guidelines/Other: Never eat, drink or smoke in work area

## SUPER X ENGINE CLEANER AND DEGREASER--620

Revision Date: 10/12/10 MSDS Number: 620

Page 3 of 4

BT 0..820-0.825

### PHYSICAL AND CHEMICAL PROPERTIES 9

Appearance: Colorless liquid

**Physical State:** liquid **Boiling Point:** BT 220-440 F

Odor: petroleum distillate Freezing/Melting Pt.:

BT 0.4--5.0 mmHG

Solubility: pH: Not soluble in water **Vapor Pressure:** Spec Grav./Density:

Vapor Density: BT 4.5 - 6.2

VOC: <45 % Evap. Rate: >1.0

#### 10 STABILITY AND REACTIVITY

Stability: Material is stable.

Conditions to avoid: Excessive heat and open flame.

Materials to avoid (incompatability): Strong oxidizing agents.

Carbon Monoxide and Carbon Dioxide **Hazardous Decomposition products:** 

**Hazardous Polymerization:** Cannot occur.

#### 11 **TOXICOLOGICAL INFORMATION**

**LD50** 

KEROSENE 28 ml/kg (oral)

#### 12 **ECOLOGICAL INFORMATION**

No data.

#### 13 **DISPOSAL CONSIDERATIONS**

Dispose of in accordance with all applicable state, federal and local regulations.

#### 14 TRANSPORT INFORMATION

DOMESTIC:

CONSUMER COMMODITY ORM-D

**EXPORT:** 

AEROSOL DISPENSERS, CLASS 2.0 UN 1950, LIMITED QUANTITY

## SUPER X ENGINE CLEANER AND DEGREASER--620

MSDS Number: 620 Revision Date: 10/12/10

Page 4 of 4

## 15

## **REGULATORY INFORMATION**

U.S. FEDERAL REGULATIONS

OSHA: Considered to be a hazardous material as defined by 29CFR1910.1200

EPA SARA TITLE III

Section 311-312 (40CFR370): If stored in excess of the threshold quantities, this product should be reported as a(n): IMMEDIATE (acute) HEALTH HAZARD DELAYED (chronic) HEALTH HAZARD FIRE HAZARD SUDDEN RELEASE HAZARD

Section 313(40CFR372) This product contains ingredients which are subject to the reporting requirements of SARA 313: 2-Butoxyethanol

## 16

## **OTHER INFORMATION**

CALIFORNIA PROPOSITION 65: This product does not contain ingredients which are on the current Proposition 65 list.

Notes:

NG= NOT GIVEN BT= BETWEEN

<= LESS THAN

>= GREATER THAN

USERS RESPONSIBILITY; This MSDS provides environmental, health and safety information. This product is to be used in applications consistent with our product literature and container label. Individuals handling this product should be informed to the recommended safety precautions and have access to this MSDS. Please contact your local sales representative of our EH&S Department for further information.

**END OF MSDS** 

**END OF MSDS DOCUMENT**