

Revision date: 09/11/2014

Version:

e Egiobal parts distributors, lic Rev	vision date: 09/11	/2014		Versior
SECTION 1: Identification of the	substance/	mixture and of the cor	npany/undertaking	q
1.1. Product identifier				
Product form	: Mixtu	re		
Trade name	: SANT	ECH PAG OIL CHARGE 4 O	Z.	
Product code	: MT30	27		
1.2. Relevant identified uses of the	substance or	mixture and uses advised a	gainst	
Use of the substance/mixture	: Oil Cl		guinor	
		5		
1.3.Details of the supplier of the saSANTECH INDUSTRIES, INC.1401 VALLEY VIEW LANEIRVING, TX 75061T 817-589-1212	nety data shee	21		
1.4. Emergency telephone number				
Emergency number	: CHEM	ITREC 24 Hour 1-800-424-93	800, 1-703-527-3887 (Int	ternational)
SECTION 2: Hazards identification	on			
2.1. Classification of the substance				
Classification (GHS-US)				
Liquefied gas H280 Acute Tox. 4 (Oral) H302 Full text of H-phrases: see section 16				
2.2. Label elements				
GHS-US labeling Hazard pictograms (GHS-US)				
Signal word (GHS-US) Hazard statements (GHS-US)	: Warn : H280	GHS04 GHS07 ing - Contains gas under pressur - Harmful if swallowed	e; may explode if heated	1
Precautionary statements (GHS-US)	: P264 P270 P301 P330 P410 P501 local, P251	<ul> <li>Wash affected areas thoroug</li> <li>Do not eat, drink or smoke v</li> <li>+P312 - If swallowed: Call a p</li> <li>Rinse mouth</li> <li>+P403 - Protect from sunlight.</li> <li>Dispose of contents/container</li> <li>regional, national, international</li> <li>Pressurized container: Do n</li> </ul>	vhen using this product oison center, doctor if yo Store in a well-ventilate er to appropriate waste al regulations. ot pierce or burn, even a	d place disposal facility, in accordance with
2.3. Other hazards				
Other hazards not contributing to the classification	may o with s	cause cardiac or central nervo	us systems effects. War ntact with skin. (Liquid f	tional misuse and inhalation abuse ning. May Cause frostbite in contac orm can be ejected if the aerosol ca
2.4. Unknown acute toxicity (GHS-L	JS)			
No data available				
SECTION 3: Composition/inform	ation on in	aredients		
3.1. Substance				
Not applicable				
3.2. Mixture				
Name		Product identifier	%	Classification (GHS-US)
Polyalkylene Glycol Alkyl Ether 100		(CAS No) Proprietary	50 - 70	Acute Tox. 4 (Oral), H302
1 1 1 2 Totrofluoroothano		(CAS No) 911 07 2	50 70	Liquofied app. H280

1,1,1,2-Tetrafluoroethane

(CAS No) 811-97-2

50 - 70

Liquefied gas, H280



SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Assure fresh air breathing. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a POISON CENTER/doctor/physician if you feel unwell.
4.2. Most important symptoms and effect	s, both acute and delayed
Symptoms/injuries	: If you feel unwell, seek medical advice. Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/injuries after inhalation	: Coughing. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause drowsiness or dizziness. Slight irritation.
Symptoms/injuries after skin contact	: Blisters. Causes skin irritation. Frostbites. May cause slight irritation . May cause moderate irritation. Red skin.
Symptoms/injuries after eye contact	: May cause slight eye irritation . Slight irritation.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.
4.3. Indication of any immediate medical	attention and special treatment needed
No additional information available	
SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.
5.2. Special hazards arising from the sub	stance or mixture
No additional information available	
5.3. Advice for firefighters	
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: NFPA Aerosol Level 1.
SECTION 6: Accidental release meas	
SECTION 6: Accidental release meas	
6.1. Personal precautions, protective equ General measures	Remove ignition sources.
Jeneral Illeasules	. Nemove ignition sources.
6.1.1. For non-emergency personnel	
Protective equipment	: Gloves. Safety glasses.
Emergency procedures	: Evacuate unnecessary personnel.
6.1.2. For emergency responders	
Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.
6.2. Environmental precautions	
Prevent entry to sewers and public waters. Notify	authorities if liquid enters sewers or public waters.
6.3. Methods and material for containment	nt and cleaning up
For containment	: Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.
Methods for cleaning up	: Store away from other materials.
6.4. Reference to other sections	
See Heading 8. Exposure controls and personal p	protection.
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use.
Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or
	smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.



Hygiene measures	: Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
7.2. Conditions for safe storage, inclu	ding any incompatibilities
Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight.
Storage area	: Store in a well-ventilated place.
7.3. Specific end use(s)	

Follow Label Directions.

	ersonal protection
8.1. Control parameters	
8.2. Exposure controls	
Appropriate engineering controls	: Local exhaust venilation, vent hoods.
Personal protective equipment	: Avoid all unnecessary exposure. Gloves. Safety glasses.
Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Wear appropriate mask.
Other information	: Do not eat, drink or smoke during use.
SECTION 9: Physical and chemic	al properties
9.1. Information on basic physical a	
Physical state	: Gas
Appearance	: Liquid.
Color	: Colourless to light yellow.
Odor	: Characteristic.
Odor threshold	: No data available
рН	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 1 @ 20 deg C
Solubility	: Poorly soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: 98 m²/s @ 40 deg C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available



9.2.	Other information	
VOC co	ontent	: 0%
SECT	ION 10: Stability and reactivity	
10.1.	Reactivity	
	itional information available	
10.2.	Chemical stability	
	ablished.	
10.3.	Possibility of hazardous reactions	
	ablished.	
10.4.	Conditions to avoid	
	unlight. Extremely high or low temperature	9S.
10.5.	Incompatible materials	
	acids. Strong bases.	
10.6.	Hazardous decomposition products	
	me Carbon monoxide. Carbon dioxide.	
SECT	ION 11: Toxicological informati	on
11.1.	Information on toxicological effects	
	mormation on toxicological enects	
Acute to	oxicity	: Harmful if swallowed.
Polya	Ikylene Glycol Alkyl Ether 100 (Propriet	tary)
-	oral rat	500 mg/kg
1,1,1,1	2-Tetrafluoroethane (811-97-2)	
	· /	

LD50 oran at	пулку	
1,1,1,2-Tetrafluoroethane (811-97-2)		
LC50 inhalation rat (mg/l)	00 mg/l/4h (Rat; Litera	ature study)
LC50 inhalation rat (ppm)	9300 ppm/4h (Rat; Lit	terature study)
Skin corrosion/irritation	classified	
Serious eye damage/irritation	classified	
Respiratory or skin sensitization	classified	
Germ cell mutagenicity	classified	
Carcinogenicity	classified	
Reproductive toxicity	classified	
Specific target organ toxicity (single exposure)	classified	
Specific target organ toxicity (repeated exposure)	classified	
Aspiration hazard	classified	
Potential Adverse human health effects and symptoms	ed on available data,	the classification criteria are not met. Harmful if swallowed.
Symptoms/injuries after inhalation	ghing. May cause alle vsiness or dizziness.	ergy or asthma symptoms or breathing difficulties if inhaled. May cause Slight irritation.
Symptoms/injuries after skin contact	ers. Causes skin irrita tion. Red skin.	ation. Frostbites. May cause slight irritation . May cause moderate
Symptoms/injuries after eye contact	cause slight eye irrita	ation . Slight irritation.
Symptoms/injuries after ingestion	lowing a small quant	ity of this material will result in serious health hazard.

SECTION 12: Ecological information	
12.1. Toxicity	
1,1,1,2-Tetrafluoroethane (811-97-2)	
LC50 fish 1	450 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 1	980 mg/l (48 h; Daphnia magna)
12.2. Persistence and degradability	
SANTECH PAG OIL CHARGE 4 OZ.	
Persistence and degradability	Not established.
Polyalkylene Glycol Alkyl Ether 100 (Proprieta	ary)
Persistence and degradability	Not established.
00/44/0044	
26/11/2014	EN (English US) 4/7



1,1,1,2-Tetrafluoroethan			
Persistence and degradability		Not readily biodegradable in water.	
12.3. Bioaccumulative	e potential		
SANTECH PAG OIL CHA	ARGE 4 OZ.		
Bioaccumulative potential		Not established.	
Polyalkylene Glycol Alk	yl Ether 100 (Proprie	tary)	
Bioaccumulative potential		Not established.	
1,1,1,2-Tetrafluoroethan	e (811-97-2)		
BCF other aquatic organis	sms 1	5 - 58 (Estimated value)	
Log Pow		1.06 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method)	
Bioaccumulative potential		Low potential for bioaccumulation (BCF < 500).	
12.4. Mobility in soil			
No additional information av	vailable		
12.5. Other adverse e	ffects		
Other information		: Avoid release to the environment.	
SECTION 13: Dispos			
13.1. Waste treatment		· Dispass in a sofe manner in accordance with least/actional resultations. Dispass of	
Waste disposal recommendations		: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.	
Ecology - waste materials		: Avoid release to the environment.	
SECTION 14: Transp	ort information		
In accordance with ADR / R		N .	
US DOT (ground): U	N1078, Refrigerant ga	ases, n.o.s., 2.2, Limited Quantity	
ICAO/IATA (air): U	N1078, Refrigerant ga	ases, n.o.s., 2.2 , Limited Quantity	
		ases, n.o.s. (1,1,1,2-Tetrafluoroethane, Petroleum Distillates), 2.2	
C		nk instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied authorized to be transported in portable tanks in accordance with the requirements of 173.313 of	
14.2. UN proper shipp	aing nome		
Proper Shipping Name (DC	•	: Refrigerant gases, n.o.s.	
Department of Transportatio Classes		2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115	
Hazard labels (DOT)		: 2.2 - Non-flammable gas	
DOT Symbols		: G - Identifies PSN requiring a technical name	
DOT Special Provisions (49	9 CFR 172.102)	T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.	
DOT Packaging Excentions	(40 CEP 173 vvv)	accordance with the requirements of 173.313 of this subchapter. : 306	
DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx)		: 304	
DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx)		: 314;315	
14.3. Additional informa			
Other information		: No supplementary information available.	
Overland transport No additional information av Transport by sea	vailable		
DOT Vessel Stowage Loca	tion	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.	
26/11/2014		EN (English US) 5/1	

### gpd PAG OIL CHARGE 4 OZ. 8011236

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



#### Air transport DOT Quantity Limitations Passenger aircraft/rail : 75 kg (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 : 150 kg CFR 175.75)

SECTION 15: Regulatory information	DN
15.1. US Federal regulations	
SANTECH PAG OIL CHARGE 4 OZ.	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard Sudden release of pressure hazard
Polyalkylene Glycol Alkyl Ether 100 (Prop	ietary)
Listed on the United States TSCA (Toxic Sub	stances Control Act) inventory
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
1,1,1,2-Tetrafluoroethane (811-97-2)	
Listed on the United States TSCA (Toxic Sub	stances Control Act) inventory
SARA Section 311/312 Hazard Classes	Sudden release of pressure hazard Immediate (acute) health hazard

#### 15.2. International regulations

#### CANADA

SANTECH PAG OIL CHARGE 4 OZ.		
WHMIS Classification	Class A - Compressed Gas	
Polyalkylene Glycol Alkyl Ether 100 (Proprietary)		
Listed on the Canadian DSL (Domestic Sustances List)		
1,1,1,2-Tetrafluoroethane (811-97-2)		
WHMIS Classification	Class A - Compressed Gas	

#### **EU-Regulations**

Polyalkylene Glycol Alkyl Ether 100 (Proprietary)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

Classification according to Regulation (EC) No. 1272/2008 [CLP]

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Xn; R22

Full text of R-phrases: see section 16

15.2.2. National regulations

#### Polyalkylene Glycol Alkyl Ether 100 (Proprietary)

Listed on KECI (Korean Existing Chemicals Inventory) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

#### 15.3. US State regulations

#### Polyalkylene Glycol Alkyl Ether 100 (Proprietary)

U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List Connecticut Right to Know Florida Right to Know Illinois Right to Know Louisiana Right to Know Michigan Right to Know

### gpd PAG OIL CHARGE 4 OZ. 8011236

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



Other information	: None.	
Full text of H-phrases: see section 16:		
Acute Tox. 4 (Oral)	1	Acute toxicity (oral) Category 4
Liquefied gas	(	Gases under pressure Liquefied gas
H280		Contains gas under pressure; may explode if heated
H302	H	Harmful if swallowed
NFPA fire hazard NFPA reactivity	<ul> <li>2 - Intense or continued exprincapacitation or possible remedical attention is given.</li> <li>0 - Materials that will not bur</li> <li>1 - Normally stable, but can</li> </ul>	sidual injury unless prompt n. become unstable at elevated
	temperatures and pressures some release of energy, but	or may react with water with not violently.
HMIS III Rating		
Health	: 2 Moderate Hazard - Temp	orary or minor injury may occur
Flammability	: 0 Minimal Hazard	
,		
Physical	: 1 Slight Hazard	

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.