

Safety Data Sheet (SDS) 8011282, 8011284

Masterchem Premium PAG 100 Viscosity w/ UV Dye

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Masterchem Premium PAG 150 Viscosity w/ UV Dye **PRODUCT DESCRIPTION:** Compressor Lubricant

MANUFACTURER

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC: 800-424-9300

Omega/Santech 1401 Valley View Lane, Suite #100 Irving, TX 75061 Emergency Phone: 972-812-7000

2. HAZARDS IDENTIFICATION

GHS LABEL

This product is not classified as hazardous according to 29CFR 1910.1200.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Poly[oxy(methyl-1,2-ethandiyl)], Alpha-butyl-omega-hydroxy-	>99	9003-13-8

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

INGESTION: Rinse mouth with water. Do not induce vomiting. Seek medical attention if you feel unwell.

INHALATION: Remove to fresh air. If breathing is difficult seek medical attention.

NOTES TO PHYSICIAN: Treat symptomatically.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry Chemical, CO2, Foam. Water Spray.

HAZARDOUS COMBUSTION PRODUCTS: May produce hazardous fumes.

FIRE FIGHTING PROCEDURES: Do not use a water jet.

FIRE FIGHTING EQUIPMENT: In case of fire wear a full-face positive pressuire self contained breathing apparatus and protective suit.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Contain and soak up spill with absorbent material and provide adequate ventilation.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Prevent material from entering drains or watercourses using sand, earth or other appropriate barriers.

LAND SPILL: Prevent contamination of the soil.

GENERAL PROCEDURES: Avoid contact with skin or eyes. Avoid contact with spilled materials. Use appropriate personal protective equipment.



Masterchem Premium PAG 100 Viscosity w/ UV Dye

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Handle in accordance with good industrial hygiene and safety practices.

HANDLING: Use only in a well ventilated area. Avoid breathing (dust, vapor, mist, gas). Avoid contact with eyes, skin, and clothing.

STORAGE: Keep container tightly closed in a dry, well-ventilated place.

STORAGE TEMPERATURE: Store in a cool place below 120°F/49°C under nitrogen blanket as this product is

hydroscopic. For prolonged storage above 60°C, store in rust free container using nitrogen blanket.

STORAGE PRESSURE: Atmospheric.

SPECIAL SENSITIVITY: This is a hydroscopic product. Avoid contact with water.

COMMENTS: Recommended storage container materials are rust free mild steel or stainless steel.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Eye washes and showers for emergency use. **PERSONAL PROTECTIVE EQUIPMENT**

EYES AND FACE: Wear safety glasses with side shields (or goggles) or a face shield.

SKIN: Use chemically resistant gloves; appropriate materials are PVC. Nitrile.

RESPIRATORY: Use appropriate protection if there is risk of breathing the mists or vapors or heated materials.


PROTECTIVE CLOTHING: Wear full protective clothing and chemical resistant gloves to prevent prolonged skin contact.

WORK HYGIENIC PRACTICES: Wash hands, forearms and face before eating, drinking, smoking and using the restroom. Launder contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid **ODOR:** Mild APPEARANCE: Water white to faintly yellow. PHYSICAL STATE COMMENTS: Clear, bright, viscous. pH: ~ 5.5 to 7.5 FLASH POINT AND METHOD: > 210°C COC-ASTM D-92 **AUTOIGNITION TEMPERATURE:** Not Available VAPOR PRESSURE: Not Available VAPOR DENSITY: Not Available **BOILING POINT:** Not Available POUR POINT: -46°C THERMAL DECOMPOSITION: Not Available SOLUBILITY IN WATER: Insoluble in water. **EVAPORATION RATE:** Not Available SPECIFIC GRAVITY: 1.051 at 20°C VISCOSITY #1: 150 cSt at 40°C





STABLE: Yes

STABILITY: Stable under normal conditions.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon. Small amounts of aldehydes, ketones, and alcohols. **INCOMPATIBLE MATERIALS:** Strong oxidizers, strong acids.

11. TOXICOLOGICAL INFORMATION

ACUTE DERMAL LD 50: > 5000 mg/kg Notes: rabbit ORAL LD₅₀: > 5000 mg/kg Notes: rat EYE EFFECTS: Minimal irritation. SKIN EFFECTS: Minimal irritation. REPEATED DOSE EFFECTS: Repeated or prolonged contact may produce defatting of the skin leading to irritation and dermatitis. **IRRITATION:** Not a primary irritant. **NEUROTOXICITY: Not Available GENETIC EFFECTS:** Not Available **REPRODUCTIVE EFFECTS:** Not Available TARGET ORGANS: Not Available **MUTAGENICITY: Not Available** GENERAL COMMENTS: Used materials should be handled with caution. Proper health, safety, and disposal methods should be taken during handling of used materials. Aviod contact with skin and eyes.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Ecotoxicological data have not been determined specifically for this products. The information below is given based on knowledge of the components.

ECOTOXICOLOGICAL INFORMATION: Testing of a similar substance indicates material is non-toxic to aquatic life.

BIOACCUMULATION/ACCUMULATION: Not expected to bio-accumulate.

DISTRIBUTION: Insoluble in water. Adsorbs to soil and has low mobility.

CHEMICAL FATE INFORMATION: Expected to be partially or slowly biodegradable.





Safety Data Sheet (SDS) 8011282, 8011284

Masterchem Premium PAG 100 Viscosity w/ UV Dye

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of contents/container to a licensed contractor or facility in accordance with local, state and federal regulations.

PRODUCT DISPOSAL: The preferred options for disposal include reuse, recycling, co-processing, finding a use for by-product, incineration or other thermal destruction at licensed facilities.

EMPTY CONTAINER: Clean container thoroughly and dispose to licensed disposal contractor.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION) PROPER SHIPPING NAME: Not regulated for Transport ROAD AND RAIL (ADR/RID): NA = Not Applicable AIR (ICAO/IATA): NA = Not Applicable VESSEL (IMO/IMDG): NA = Not Applicable CANADA TRANSPORT OF DANGEROUS GOODS: NA = Not Applicable

15. REGULATORY INFORMATION

UNITED STATES

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: All components listed or exempt.

CANADA

DOMESTIC SUBSTANCE LIST (INVENTORY): All components are listed or exempt.

16. OTHER INFORMATION

REASON FOR ISSUE: Updated to GHS Format with GHS classificationAPPROVED BY: Audris KingTITLE: HS&E ManagerPREPARED BY: Britton Webb









SAFETY DATA SHEET (SDS) LX-10215 PYLAKROME FLUORESCENT YELLOW DYE

REVISION DATE: May 29, 2015

SECTION 1 – PRODUCT IDENTIFICATION

PRODUCT NAME:	.Pylakrome Fluorescent Yellow LX-10215
PRODUCT NUMBER:	•
SYNONYMS:	.Pylakrome Fluorescent Yellow LX-10215
CHEMICAL FAMILY:	.Perylene
CHEMICAL FORMULA:	.Solvent Green 5 (CAS# 78969-59-3)
CAS NUMBER:	.79869-59-3

COMPANY:Omega / Santech 1401 Valley View Lane, Suite #100 Irving, Texas 75061

RECOMMENDED USE:Coloring agent.

FOR ADDITIONAL INFORMATION ABOUT THE SDS: 972-812-7000

SECTION 2 – HAZARDS IDENTIFICATION

The following information is presented in accordance with 29 CFR 1910.1200 (Hazcom 2012) which became effective on May 25, 2012: CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910.1200(d): Combustible dust. LABEL CONTENT IN ACCORDANCE WITH 29 CFR 1910.1200(f): HAZARD PICTOGRAMS:Not Applicable SIGNAL WORD:.....Warning. HAZARD STATEMENT:.....May form combustible dust concentrations in air. PRECAUTIONARY STATEMENTS:Not Applicable.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	PERCENT	CAS NUMBER	TLV-TWA
None as per 29CFR Part 1910.1200.	N/A	N/A	N/A



SAFETY DATA SHEET (SDS) LX-10215

PYLAKROME FLUORESCENT YELLOW DYE

SECTION 4 – FIRST-AID MEASURES

BREATHING (INHALATION):	"If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is
	difficult, give oxygen and call a physician.
SWALLOWING (INGESTION):	.If swallowed, rinse mouth with plenty of water. Seek medical attention. Never give fluids to
	an unconscious person. Induce vomiting.
EYES:	Immediately flush eyes with plenty of water for at least fifteen minutes. Get medical
	attention.
SKIN (DERMAL):	Wash thoroughly with soap and water.
SIGNS AND SYMPTOMS OF EXP	OSURE:Skin may get discolored upon contact with the dye.

SECTION 5 – FIRE-FIGHTING MEASURES

 FLASHPOINT:
 N/A.

 LOWER FLAME LIMIT:
 N/A.

 HIGHER FLAME LIMIT:
 N/A.

 AUTO IGNITION TEMPERATURE: No data available.
 N/A.

 EXTINGUISHING MEDIA:
 In case of fire use water spray, foam, dry chemical or CO₂.

 SPECIAL FIRE FIGHTING PROCEDURES:
 Firefighters should be equipped with self-contained breathing apparatus and protective clothing.

 UNUSUAL FIRE AND EXPLOSION HAZARDS:
 Dusts, when mixed with the right proportions of air and in a source of ignition, have the potential to be explosive.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

HANDLING PRECAUTIONS:	In accordance with good industrial practices, handle with care to avoid contact.
	Spills should be swept up and placed in containers. Spill areas can be washed with water;
	collect waste water for approved disposal method.
WASTE DISPOSAL:	Waste disposal should be in accordance with existing federal, state and local
	environmental regulations.
RCRA HAZARDOUS CLASS:	N/A.
RCRA HAZARDOUS WASTE NUM	BER:Not regulated.

SECTION 7 – HANDLING and STORAGE

STORAGE:	Keep container tightly closed. Store in a cool, dry place.
	In accordance with good industrial practices, handle with care to avoid contact.
	Use local ventilation if dusting is a problem.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION



SAFETY DATA SHEET (SDS) LX-10215

PYLAKROME FLUORESCENT YELLOW DYE

SECTION 9 – PHYSICAL / CHEMICAL PROPERITES

APPEARANCE & ODOR:Greenish powder; odorless.
ODOR THRESHOLD:Not Available
PHYSICAL STATE:Powder.
SOLUBILITY IN WATER:Insoluble.
OTHER SOLUBILITY:Solvent.
BOILING POINT:N/A.
FREEZING POINT:N/A.
MELTING POINT: 207-208 °C
DECOMPOSITION TEMPERATURE: 235 °C, 90 kJ/kg (DSC (DIN 51007))
FLASH POINT:N/A.
AUTO IGNITION TEMPERATURE: No data available.
FLAMMABILITY (SOLID/GAS):Not flammable (may form combustible dust-air mixtures)
UPPER FLAMMABILITY LIMIT:N/A.
LOWER FLAMMABILITY LIMITN/A.
VAPOR PRESSURE:N/A.
VAPOR DENSITY (AIR=1):N/A.
PARTITION COEFFICIENT (n-ocatnol/water):Not Available
SPECIFIC GRAVITY:Not Available
pH: 7.0 - 8.0
VOLATILITY INCLUDING WATER: N/A.
VISCOSITY:Not Available.
BULK DENSITY:~ 330 kg/m3

SECTION 10 – STABILITY and REACTIVITY

REACTIVITY:	No dangerous reactions known under normal conditions of use
STABILITY:	Stable.
HAZARDOUS DECOMP.:	Carbon monoxide, carbon dioxide, oxides of nitrogen, sulfur, and other potentially toxic
	fumes.
INCOMPATIBILITY:	Oxidizing and reducing agents may destroy color.
POLYMERIZATION:	None expected.
CONDITIONS TO AVOID:	None.

SECTION 11 – TOXICOLOGICAL INFORMATION

Toxic Ingredient	Percentage of Formula	CAS#	De Minimis Level
N/A	N/A	N/A	N/A
	Solid particles (powder/dust) or	n the eye may cause par	n and irritation.
	May cause skin irritation.		
GESTION:	Ingestion may cause irritation.		
HALATION:			
MMON ROUTES OF EXP	OSURE: Ingestion	. Inhalation. Skin & Eves	i.
	Y:Based on the ingredients, there		
RONIC EFFECT:	u		
	Rat (Oral): > 5,000 mg/kg.	.	
	May be slightly irritating to the		
	EXPOSURE:Skin may	the second se	the state the state of the stat



SAFETY DATA SHEET (SDS)

LX-10215

PYLAKROME FLUORESCENT YELLOW DYE

SECTION 12 – ECOLOGICAL INFORMATION

ECOTOXICITY:	.Fish (48 h): > 100 mg/l, Leuciscus idus melanotus (static).; There is a high probability that
	the product is not acutely harmful to aquatic organisms.
PERSISTENCE & DEGRADABILIT	Y:Colourants are by their nature very stable and are therefore not
	readily biodegradable under conditions prevailing in surface water or in effluent treatment plants. The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical seperation.
BIOACCUMULATIVE POTENTIAL	:No Data Available.
MOBILITY IN THE ENVIRONMEN	I :The substance will not evaporate into the atmosphere from the water
	surface.

SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:Waste disposal should be in accordance with existing federal, state and local environmental regulations. RCRA HAZARDOUS CLASS:N/A.

RCRA HAZARDOUS NUMBER: Not regulated.

SECTION 14 – TRANSPORTATION INFORMATION

The information listed below is offered to supplement the data which may also be found on the product's label. Depending on the packaging quantities and packaging instructions, the item may be subject to specific regulatory exceptions.

DOT TRANSPORTATION INFORMATION

DOT SHIPPING NAME:Non-hazardous powdered dye; Item # 154800. HAZARD CLASS:N/A. UN CODE:N/A. NA NUMBER:.....N/A. PACKAGING GROUP :.....N/A. SPECIAL PROVISIONS:.....None. REPORTABLE QUANTITY:.....N/A. VESSEL STOWAGE:N/A. EMERGENCY RESPONSE PAGE: .N/A.

SECTION 15 - REGULATIONS

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29CFR 1910.1200

TSCA STATUS:This product is registered under the regulations of the Toxic Substances Control Act (TSCA). RCRA HAZARDOUS CLASS:N/A. RCRA HAZARDOUS NUMBER:.....Not regulated. CERCLA REPORTABLE QUANTITY:N/A. CERCLA HAZARDOUS SUBSTANCE:.....Not regulated. SARA 312:N/A. SARA SECTION 313:.....SARA Title III Section 313: This product is not reportable for SARA 313.

OSHA CRITERIA:No carcinogenicity unless listed in Section 3 or 11 of the Safety Data Sheet.



SAFETY DATA SHEET (SDS) LX-10215 PYLAKROME FLUORESCENT YELLOW DYE

STATE REGULATIONS

REGULATED COMPONENT CAS #	COMPONENT CONCENTRATION	STATE REGISTRATION
N/A	N/A	N/A

SECTION 16 – OTHER INFORMATION

HMIS Information :

Health:	1
Flammability:	1
Reactivity:	0
Personal Protection:	SD

DISCLAIMER:Omega / Santech believes all the information and data given is accurate as of the date of preparation and is offered in good faith. This information is given without warranty or representation solely for your consideration, investigation, and verification. Since conditions of use are beyond our control, Omega / Santech expressly disclaims all liability for the use or handling of this product. All risks of use are assumed by end-users.