

ITW Permatex
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924 (ChemTel)
 International Emergency: 00+ 1+ 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 135EA HEAVY DUTY RUBBERIZED UNDERCOATING 16OZ AE
Item No: 81833
Product Type: Undercoating

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
PETROLEUM GASES, LIQUEFIED, SWEETENED 68476-86-8	15-40	Not listed	Not listed
ASPHALT, OXIDIZED 64742-93-4	10-30	5 mg/m ³	Not listed
TOLUENE 108-88-3	7-13	20 ppm	200 ppm
STODDARD SOLVENT 8052-41-3	5-10	100 ppm	500 ppm; 2900 mg/m ³
TALC 14807-96-6	3-7	2 mg/m ³	20 mppcf

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye, skin and respiratory irritation. Excessive inhalation causes headache, dizziness, nausea, and incoordination. Long term exposure to high concentrations of vapor may cause lung, liver or kidney damage. Aspiration hazard if swallowed.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation. Overexposure may cause eye and skin redness. Swallowing: This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage. Aspiration into the lungs can cause chemical pneumonia which can be fatal.

Component	Weight%	NTP	ACGIH Carcinogens	IARC Carcinogen
PETROLEUM GASES, LIQUEFIED, SWEETENED 68476-86-8	15-40	Not Listed		
ASPHALT, OXIDIZED 64742-93-4	10-30	Not Listed		Group 3, Vol. 35, Supp. 7 1987
TOLUENE 108-88-3	7-13	male rat-no evidence; female rat-no evidence; male mice- no, female mice-no	A4 - Not Classifiable as a Human Carcinogen	Group 3; Monograph 71, 1999; Monograph 47, 1989
STODDARD SOLVENT 8052-41-3	5-10	Not Listed		
TALC 14807-96-6	3-7	male rat-some evidence, female rat- clear evidence, male mice-no evidence, female mice-no evidence	A4- Not classifiable as a human carcinogen	Group 3 Supplement 7, 1987 Monograph 42, 1987

Aggravated Medical Condition: Persons with preexisting respiratory, liver, kidney, eye or skin diseases may be adversely affected.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.

Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.

4. FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): Extremely flammable per aerosol flame projection test
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.
Hazardous Products of Combustion: Oxides of carbon, Oxides of sulfur
Unusual Fire/Explosion Hazards: Contents under pressure. Exposure to temperatures over 120 degrees F. may cause bursting or venting. Use equipment or shielding to protect personnel from bursting containers.

Lower Explosive Limit: n/d
Upper Explosive Limit: n/d

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C). Exposure to high temperatures may cause container to burst.
Handling: Do not use near heat, sparks or open flame. Do not puncture or incinerate container. Vapors may accumulate readily and may ignite explosively. Avoid contact with skin and eyes. Use in a well ventilated area to prevent irritation by vapors. Intentionally concentrating and inhaling the vapor may be harmful or fatal. Wash hands before eating and smoking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.
Skin: Neoprene or nitrile gloves recommended.
Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection: An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Black liquid
Odor: Solvent
Boiling Point: >100°F
pH: Does not apply
Solubility in Water: Nil
Specific Gravity: 1.03
VOC(Wt.%): 39.5%
Vapor Pressure: n/d
Vapor Density (Air=1): >1
Evaporation Rate: <1 (butyl acetate =1)

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: Will not occur
Incompatibilities: Strong oxidizers
Conditions to Avoid: Keep away from heat, sparks and open flame. - No smoking
Hazardous Products of Combustion: Oxides of carbon, Oxides of sulfur

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

Product Name: 135EA HEAVY DUTY RUBBERIZED
UNDERCOATING 16OZ AE

Item No. 81833

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash.

US EPA Waste Number: D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

U.S. Department of Transportation - DOT - 49 CFR (Ground)

DOT Shipping Name: Aerosols, Limited Quantity

Hazard Class: Class 2.1

UN/ID Number: UN 1950

IATA (Air)

Proper Shipping Name: Consumer Commodity

Class or Division: Class 9

UN/ID Number: ID 8000

IMDG (Vessel)

Proper Shipping Name: Aerosols, Limited Quantity

Hazard Class: Class 2.1

UN Number: UN 1950

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

Toluene

California Proposition 65: WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 4, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 4, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

(HMIS is a registered trademark of the National Paint and Coatings Association)

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106
Telephone No.: 1-87-Permatex (877) 376-2839

Revision Date: December 04, 2012

Revision Number: 1