

ITW Permatex
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924 (ChemTel)
 International Emergency: +01-813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: THE RIGHT STUFF FOR IMPORTS POWERBEAD 7.5 OZ AE
Item No: 85144
Product Type: Elastomeric rubber (pressurized)

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	40-50	Not listed	Not listed
CALCIUM CARBONATE 471-34-1	20-30	10 mg/m ³	Not listed
GARNET MINERAL 1302-62-1	20-30	Not listed	Not listed
VINYL OXIMINOSILANE 2224-33-1	<7	Not listed	Not listed
MODIFIED SILICON DIOXIDE 68611-44-9	<5	Not listed	Not listed
STEARIC ACID 57-11-4	<2	Not listed	Not listed
2-BUTANONE OXIME 96-29-7	0.5-2.0	Not listed	Not listed
NITROGEN 7727-37-9	0.5-2.0	Not listed	Not listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation. May irritate lips, gums, tongue, mouth, nose and throat. When this product is exposed to moisture, butanone oxime may be formed. Note: This product does not contain microcrystalline silica.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: 2-Butanone oxime produced during cure is toxic and irritates eyes, nose and throat. Overexposure may cause eye and skin redness. Overexposure to nitrogen propellant (only released if can is punctured) may cause headache, drowsiness, dizziness, excitation, excess salivation, vomiting, unconsciousness.

Aggravated Medical Condition: None known.

4. FIRST AID MEASURES

Ingestion: Rinse mouth. If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.

Skin Contact: Wipe off material with paper towel or cloth Wash off with soap and water If skin irritation persists, call a physician

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): >200°F TCC

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.

Special Fire-Fighting Procedures: ***Warning: This container is pressurized with nitrogen. Do not remove rubber plug. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

Hazardous Products of Combustion: Formaldehyde, Silica fume, Oxides of nitrogen, Methyl ethyl ketone, possibly methyl ethyl ketoxime

Unusual Fire/Explosion Hazards: Contents under pressure. Heated cans may burst. Use equipment or shielding to protect personnel from bursting containers.

5. FIRE FIGHTING MEASURES

Lower Explosive Limit: Not determined
Upper Explosive Limit: Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Wipe or scrape up spill material. Maintain good ventilation for large spills. Place scrap material in a well-ventilated area and allow to cure to rubber. Clean up spills thoroughly as residue is slippery.

7. HANDLING AND STORAGE

Storage: Store in a dry area below 90 degrees F. Keep container closed when not in use. Exposure to high temperatures may cause container to burst.
Handling: Avoid contact with skin and eyes. Do not inhale vapors. Do not wear contact lenses. Wash hands before eating and smoking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.
Skin: Neoprene or nitrile gloves recommended.
Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection: An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.
Comments: When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor concentrations below the OSHA permissible limit for formaldehyde

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Grey paste
Odor: Mild
Boiling Point: Not applicable, polymeric material
pH: Does not apply
Solubility in Water: Polymerized
Specific Gravity: 1.45
VOC(Wt.%): <3%
Vapor Pressure: <5 mm Hg @ 80°F
Vapor Density (Air=1): 3.0
Evaporation Rate: <1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: Will not occur
Incompatibilities: Strong oxidizers, Polymerized by contact with moisture, Acids, Iron Heat. Exposure to moisture.
Conditions to Avoid: Formaldehyde, Silica fume, Oxides of nitrogen, Methyl ethyl ketone, possibly methyl ethyl ketoxime
Hazardous Products of Combustion:

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)
U.S. Department of Transportation - DOT - 49 CFR (Ground)

Product Name: THE RIGHT STUFF FOR IMPORTS
POWERBEAD 7.5 OZ AE

Item No. 85144

14. TRANSPORTATION INFORMATION

DOT Shipping Name: Aerosols, Limited Quantity
Hazard Class: Class 2.2
UN/ID Number: UN 1950

IATA (Air)

Proper Shipping Name: Consumer Commodity (Not more than 1 liter)
Class or Division: Class 9
UN/ID Number: ID 8000

IMDG (Vessel)

Proper Shipping Name: Aerosols, Limited Quantity
Hazard Class: Class 2.2
UN Number: UN 1950

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

California Proposition 65: No California Prop 65 chemicals are known to be present.

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

HMIS is a registered trademark of the National Paint and Coatings Association

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106
Telephone No.: 1-87-Permatex (877) 376-2839

Revision Date: July 25, 2012

Revision Number: 8