

Valvoline™ Advanced Full Synthetic SAE 5W-30 Motor Oil

Version: 4.0 Revision Date: 06/12/2023 Print Date: 06/21/2023

SECTION 1. IDENTIFICATION

Product name : Valvoline™ Advanced Full Synthetic SAE 5W-30

Motor Oil

Product code : 881164

Manufacturer or supplier's details

Company name of supplier : Valvoline Global Operations

Address : 100 Valvoline Way

Lexington, KY 40509

United States of America (USA)

Telephone : 1-800-TEAMVAL (1-800-832-6825)

E-mail address : SDS@valvolineglobal.com

Emergency telephone

number

: +1-800-VALVOLINE (+1-800-825-8654)

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS



Valvoline™ Advanced Full Synthetic SAE 5W-30 Motor Oil

Version: 4.0 Revision Date: 06/12/2023 Print Date: 06/21/2023

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	>= 40 - < 50
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	>= 30 - < 40
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	>= 5 - < 10

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

No symptoms known or expected.

Notes to physician : No hazards which require special first aid measures.

Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.



Valvoline™ Advanced Full Synthetic SAE 5W-30 Motor Oil

Version: 4.0 Revision Date: 06/12/2023 Print Date: 06/21/2023

Unsuitable extinguishing

media

High volume water jet

Hazardous combustion

products

carbon dioxide and carbon monoxide

Further information Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Refer to protective measures listed in sections 7 and 8.

Use personal protective equipment.

: If the product contaminates rivers and lakes or drains inform Environmental precautions

respective authorities.

Methods and materials for containment and cleaning up Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Conditions for safe storage Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid No materials to be especially mentioned.

Further information on

storage stability

: No decomposition if stored and applied as directed.



Valvoline™ Advanced Full Synthetic SAE 5W-30 Motor Oil

Version: 4.0 Revision Date: 06/12/2023 Print Date: 06/21/2023

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Eye protection : Safety glasses

Skin and body protection : Protective suit

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : amber



Valvoline™ Advanced Full Synthetic SAE 5W-30 Motor Oil

Version: 4.0 Revision Date: 06/12/2023 Print Date: 06/21/2023

Odour : mild

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 626 °F / 330 °C

(1,013.333333 hPa)

Calculated Phase Transition Liquid/Gas

Flash point : $> 394 \, ^{\circ}\text{F} \, / > 201 \, ^{\circ}\text{C}$

Method: Cleveland open cup see user defined free text

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

6 %(V)

Calculated Explosive Limit

Lower explosion limit / Lower

flammability limit

1 %(V)

Calculated Explosive Limit

Vapour pressure : 1.3333333 hPa (68 °F / 20 °C)

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 0.847 g/cm3

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Decomposition temperature : No data available



Valvoline™ Advanced Full Synthetic SAE 5W-30 Motor Oil

Version: 4.0 Revision Date: 06/12/2023 Print Date: 06/21/2023 06/21/2023

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 63.17 mm2/s (104 °F / 40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

No hazards to be specially mentioned.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg



Valvoline™ Advanced Full Synthetic SAE 5W-30 Motor Oil

Version: 4.0 Revision Date: 06/12/2023 Print Date: 06/21/2023

Skin corrosion/irritation

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation Result : Slight, transient irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation Result : Slight, transient irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation Result : Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation
Assessment : No eye irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation
Assessment : No eye irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation
Assessment : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.



Valvoline™ Advanced Full Synthetic SAE 5W-30 Motor Oil

Version: 4.0 Revision Date: 06/12/2023 Print Date: 06/21/2023

Carcinogenicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

IARC No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

No aspiration toxicity classification



Valvoline™ Advanced Full Synthetic SAE 5W-30 Motor Oil

Version: 4.0 Revision Date: 06/12/2023 Print Date: 06/21/2023

Further information

Product:

: No data available Remarks

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

: Not classified based on available information. Acute aquatic toxicity

Chronic aquatic toxicity Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

: NOEC (Fish): 10 mg/l

aquatic invertebrates (Chronic toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment

Not classified based on available information. Acute aquatic toxicity

Not classified based on available information. Chronic aquatic toxicity

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Ecotoxicology Assessment

Acute aquatic toxicity Not classified based on available information.

Chronic aquatic toxicity Not classified based on available information.

Valvoline... Global

SAFETY DATA SHEET

Valvoline™ Advanced Full Synthetic SAE 5W-30 Motor Oil

Version: 4.0 Revision Date: 06/12/2023 Print Date: 06/21/2023

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

: NOEC (Fish): 10 mg/l

aquatic invertebrates (Chronic toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Persistence and degradability

No data available

Bioaccumulative potential

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n-

octanol/water

: log Pow: Expected > 7

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential Regulation: 40 CFR Protection of Environment; Part 82

Protection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was

manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +

B).



Valvoline™ Advanced Full Synthetic SAE 5W-30 Motor Oil

Version: 4.0 Revision Date: 06/12/2023 Print Date: 06/21/2023

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

Valvoline, Global

SAFETY DATA SHEET

Valvoline™ Advanced Full Synthetic SAE 5W-30 Motor Oil

Version: 4.0 Revision Date: 06/12/2023 Print Date: 06/21/2023

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY 64742-54-7 PARAFFINIC

Pennsylvania Right To Know

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY
PARAFFINIC
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY
PARAFFINIC
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY
PARAFFINIC
PROPRIETARY SUBSTANCE OF OLOA 55603 - 0-276105
HIGHLY REFINED MINERAL OIL (C15 - C50)
Not Assigned
Not Assigned

Maine Chemicals of High Concern

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY 64742-54-7 PARAFFINIC

Vermont Chemicals of High Concern

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY 64742-54-7 PARAFFINIC



Valvoline™ Advanced Full Synthetic SAE 5W-30 Motor Oil

Version: 4.0 Revision Date: 06/12/2023 Print Date: 06/21/2023

Washington Chemicals of High Concern

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY 64742-54-7

PARAFFINIC

California List of Hazardous Substances

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY 64742-54-7

PARAFFINIC

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY 64742-54-7

PARAFFINIC

California Permissible Exposure Limits for Chemical Contaminants

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY 64742-54-7

PARAFFINIC

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY 64742-54-7

PARAFFINIC

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY 64742-54-7

PARAFFINIC

The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AIIC : Not in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)



Valvoline™ Advanced Full Synthetic SAE 5W-30 Motor Oil

Version: 4.0 Revision Date: 06/12/2023 Print Date: 06/21/2023

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:

Health 0 Instability

Special hazard

HMIS® IV:

HEALTH	1	0
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -



Valvoline™ Advanced Full Synthetic SAE 5W-30 Motor Oil

Version: 4.0 Revision Date: 06/12/2023 Print Date: 06/21/2023

Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA -National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD -Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 06/12/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Internal information: R0252918