

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 001
Date Prepared: 05/10/99
Date Printed: 07/24/99
MSDS No: 503.0240649-003.001

PYROIL AP-16B PEN OIL BONUS 12-14.4 OZ

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: PYROIL AP-16B PEN OIL BONUS 12-14.4 OZ
Product Code: 80250080
General or Generic ID: LUBRICANT

Company

The Valvoline Company
P.O. Box 14000
Lexington, KY 40512

Telephone Numbers

Emergency: 1-800-274-5263
Information: 1-606-357-7847

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
KEROSENE	8008-20-6	74.0- 84.0
ALIPHATIC PETROLEUM DISTILLATES	64742-65-0	6.0- 16.0
CARBON DIOXIDE	124-38-9	0.0- 10.0
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	0.0- 8.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin

May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage.

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

Symptoms of Exposure

stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), and death.

Target Organ Effects

Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals, and may aggravate preexisting disorders of these organs in humans: blood abnormalities, liver abnormalities, anemia, spleen damage, testis damage, kidney damage, lung damage.

Continued On Next Page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 002
Date Prepared: 05/10/99
Date Printed: 07/24/99
MSDS No: 503.0240649-003.001

PYROIL AP-16B PEN OIL BONUS 12-14.4 OZ

Developmental Information

This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

Cancer Information

Ethylene glycol monobutyl ether has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal.

Other Health Effects

No data

Primary Route(s) of Entry

Inhalation, Skin contact.

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing

Do not induce vomiting. This material is an aspiration hazard. If individual is drowsy or unconscious, place on left side with the head down. Seek medical attention. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Note to Physicians

No data

5. FIRE FIGHTING MEASURES

Flash Point

160.0 F (71.1 C) TCC

Explosive Limit

(for component) Lower .7 Upper 10.6 %

Continued On Next Page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 003
Date Prepared: 05/10/99
Date Printed: 07/24/99
MSDS No: 503.0240649-003.001

PYROIL AP-16B PEN OIL BONUS 12-14.4 OZ

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Fire and Explosion Hazards

Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Extinguishing Media

regular foam, carbon dioxide, dry chemical.

Fire Fighting Instructions

Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Health - 1, Flammability - 2, Reactivity - 0

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Absorb liquid on vermiculite, floor absorbent, or other absorbent material and transfer to hood.

Large Spill

Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal. Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. All five gallon pails and larger metal containers including tank cars and tank trucks should be grounded and/or bonded when material is transferred.

Continued On Next Page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 004
Date Prepared: 05/10/99
Date Printed: 07/24/99
MSDS No: 503.0240649-003.001

PYROIL AP-16B PEN OIL BONUS 12-14.4 OZ

Storage

Not applicable

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin Protection

Wear resistant gloves such as: neoprene, nitrile rubber, To prevent repeated or prolonged skin contact, wear impervious clothing and boots..

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Component

KEROSENE (8008-20-6)

No exposure limits established

ALIPHATIC PETROLEUM DISTILLATES (64742-65-0)

OSHA VPEL 5.000 mg/m³ - TWA Oil Mist

ACGIH TLV 5.000 mg/m³ - TWA Oil Mist

CARBON DIOXIDE (124-38-9)

OSHA VPEL 10000.000 ppm - TWA

OSHA VPEL 30000.000 ppm - STEL

ACGIH TLV 5000.000 ppm - TWA

ACGIH TLV 30000.000 ppm - STEL

ETHYLENE GLYCOL MONOBUTYL ETHER (111-76-2)

OSHA VPEL 25.000 ppm - TWA ((Skin))

ACGIH TLV 25.000 ppm - TWA ((Skin))

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

(for component) > 300.0 F (148.8 C) @ 760.00 mmHg

Continued On Next Page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 005
Date Prepared: 05/10/99
Date Printed: 07/24/99
MSDS No: 503.0240649-003.001

PYROIL AP-16B PEN OIL BONUS 12-14.4 OZ

Vapor Pressure

(for component) 5.000 mmHg @ 77.00 F

Specific Vapor Density

> 1.000 @ AIR=1

Specific Gravity

.830 @ 77.00 F

Liquid Density

6.920 lbs/gal @ 77.00 F
.830 kg/l @ 25.00 C

Percent Volatiles (Including Water)

85.0 - 100.0 %

Volatile Organic Compounds (VOC) (Maximum)

720.000 g/l
6.010 lbs/gal

Evaporation Rate

FASTER THAN ETHYL ETHER

Appearance

No data

State

LIQUID

Physical Form

No data

Color

No data

Odor

No data

pH

Not applicable

Flame Propagation

> 18.000 IN

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Chemical Stability

Stable.

Continued On Next Page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 006
Date Prepared: 05/10/99
Date Printed: 07/24/99
MSDS No: 503.0240649-003.001

PYROIL AP-16B PEN OIL BONUS 12-14.4 OZ

Incompatibility

Avoid contact with: strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations.

4. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:
AEROSOLS, 2.1, UN 1950

Container/Mode:
CASES/SURFACE - NO EXCEPTIONS

NOS Component:
None

RQ (Reportable Quantity) - 49 CFR 172.101

Not applicable

15. REGULATORY INFORMATION

US Federal Regulations

TSCA (Toxic Substances Control Act) Status

TSCA (UNITED STATES) The intentional ingredients of this product are listed.

CERCLA RQ - 40 CFR 302.4

None

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate(X) Delayed(X) Fire(X) Reactive() Sudden Release of
Pressure()

Continued On Next Page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 007
Date Prepared: 05/10/99
Date Printed: 07/24/99
MSDS No: 503.0240649-003.001

PYROIL AP-16B PEN OIL BONUS 12-14.4 OZ

SARA 313 Components - 40 CFR 372.65 Section 313 Component(s)	CAS Number
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2

International Regulations
Inventory Status
Not determined

State and Local Regulations
California Proposition 65
None

New Jersey RTK Label Information

KEROSENE	8008-20-6
CARBON DIOXIDE	124-38-9
2-BUTOXY ETHANOL	111-76-2

Pennsylvania RTK Label Information

KEROSINE (PETROLEUM)	8008-20-6
CARBON DIOXIDE	124-38-9
ETHANOL, 2-BUTOXY-	111-76-2

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.