

POWER SPORT BATTERY

Safety Data Sheet

Issuing Date 01-Nov-2014 Revision Date 02-Mar-2015 Revision Number 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Flooded Motorcycle Batteries: High Performance, Conventional Flooded

Series

DRY CHARGE CONVENTIONAL POWER SPORT

Recommended Use Dry Charged Battery, Vented Battery

Supplier Address: Walmart Inc., 702 SW 8th Street Bentonville, AR 72716

1-888-405-3513

EMERGENCY CONTACT: INFOTRAC 1-800-535-5053

2. HAZARDS IDENTIFICATION

Emergency Overview

NOTE: Under normal conditions of battery use, internal components will not present a health hazard. The following information is provided for battery acid and lead exposure that may occur during battery production or container breakage or under extreme heat conditions such as fire.

In case of rupture:

Corrosive

The product causes burns of eyes, skin and mucous membranes

Appearance: No information available, Physical State: Solid. Odor: Odorless

Potential Health Effects

Principle Routes of Exposure Skin contact.

Acute Toxicity

Chronic Effects

Main Symptoms

Eyes Corrosive to the eyes and may cause severe damage including blindness.

Skin Causes burns.

Inhalation Harmful by inhalation. Contact with moist mucous membranes of the respiratory

system can cause caustic condition resulting in burns.

Ingestion Harmful if swallowed. Can burn mouth, throat, and stomach.

Lead compounds may be absorbed by ingestion, by inhalation and through the

skin. Lead may damage kidney function, the blood forming system and the

reproductive system. Avoid repeated exposure.

Severe exposures can lead to shock, circulatory collapse, and death Lead poisoning is characterized by a metallic taste in the mouth, loss of appetite

indigestion, nausea, vomiting, constipation, sleep disturbances and overall

weakness

Aggravated Medical Conditions None known.

Environment Hazard See Section 12 for additional Ecological Information

COMPOSITION/INFORMATION ON INGREDIENTS 3.

Chemical Name	CAS-No	Weight %
Inorganic Lead/Lead Compounds	7439-92-1	85-90
Tin (Sn)	7440-31-5	<0.2
Antimony (Sb)	7440-36-0	1-3
Arsenic(As)	7440-38-2	0.04-0.06
Case Material: Polypropylene (PP)	9003-07-0	~10

4. FIRST AID MEASURES

General Advice First aid is upon rupture of sealed battery.

Immediate medical attention is required. Rinse immediately with plenty of water, also **Eye Contact**

under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not

rub affected area.

Immediate medical attention is required. Wash off immediately with soap and plenty **Skin Contact**

of water removing all contaminated clothes and shoes.

Move to fresh air. Call a physician or Poison Control Center immediately. If not Inhalation

breathing, give artificial respiration. If breathing is difficult, give oxygen.

Immediate medical attention is required. Call a physician or Poison Control Center Ingestion immediately. Do NOT induce vomiting. Drink plenty of water. Never give anything by

mouth to an unconscious person. Remove from exposure, lie down.

Notes to Physician Treat symptomatically.

Protection of First-aiders Use personal protective equipment. Avoid contact with skin, eyes and clothing.

5. FIRE-FIGHTING MEASURES

Flammable Properties Not flammable. Flash Point Not determined.

Use extinguishing measures that are appropriate to local Suitable Extinguishing Media

circumstances and the surrounding environment.

Uniform Fire Code Corrosive: Acid-Liquid

Hazardous Combustion Products Hazardous metal fumes and oxides.

Explosion Data Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

The product causes burns of eyes, skin and mucous

membranes. Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion

do not breathe fumes.

Protective Equipment and Precautions for Firefighters

Specific Hazards Arising from the Chemical

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Use personal protective equipment. Do not touch damaged containers or spilled

material unless wearing appropriate protective clothing. Do not get in eyes, on skin,

or on clothing.

Environmental Precautions Refer to protective measures listed in Sections 7 and 8.

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up In case of rupture: Use personal protective equipment. Dam up. Soak up with inert

absorbent material. Take up mechanically and collect in suitable container for

disposal. Clean contaminated surface thoroughly.

Other Information Refer to protective measures listed in Sections 7 and 8.

7. HANDLING AND STORAGE

Handling Handle in accordance with good industrial hygiene and safety practice.

Storage Keep containers tightly closed in a dry, cool and well-ventilated place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

NFPA

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lead 7439-92-1	TWA: 0.05 mg/m3	TWA: 50 µg/m3 Action Level: 30 µg/m3 Poison, See 29 CFR 1910.1025	IDLH: 100 mg/m3 TWA: 0.050 mg/m3
Tin 7440-31-5	TWA: 2 mg/m3	TWA: 2 mg/m3 Sn except oxides (vacated) TWA: 2 mg/m3	IDLH: 100 mg/m3 TWA: 2 mg/m3

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value.

OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits.

NIOSH IDLH: Immediately Dangerous to Life or Health.

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965

F.2d 962 (11th Cir., 1992).

Engineering Measures Showers

Eyewash stations Ventilation systems

Personal Protective Equipment

Eye/Face Protection Skin and Body ProtectionTightly fitting safety goggles.
Wear protective gloves/clothing.

are exceeded or irritation is experienced, ventilation and evacuation may be required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance No information available, Black. Odor Odorless. **Odor Threshold Physical State** No information available Solid

Hq No information available

Auto-ignition No information Flash Point No information available.

Temperature available

No data available

Boiling information Nο **Decomposition Temperature** No information available Point/Range available

Melting Point/Range No information available

No information Flammability Limits in Air No information available **Explosion Limits** available

information No Water Solubility Immiscible in water Solubility available

Evaporation Rate No information available **Vapor Pressure**

Partition Coefficient: Vapor Density No data available

noctanol/water

10. STABILITY AND REACTIVITY

Stability Stable under recommended storage conditions.

Incompatible Products Incompatible with strong acids and bases. Incompatible with oxidizing agents.

Conditions to Avoid Exposure to air or moisture over prolonged periods.

Hazardous Decomposition Products Thermal decomposition can lead to release of toxic/corrosive gases and vapors

Hazardous Polymerization Hazardous polymerization does not occur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

Irritation Causes severe irritation and or burns

Component Information

Chemical Name LD50 Oral		LD50 Dermal	LC50 Inhalation	
Sulfuric acid	= 2140 mg/kg (Rat)	-	= 510 mg/m3(Rat) 2 h	

Chronic Toxicity

Lead compounds may be absorbed by ingestion, by inhalation and through the skin. Lead may **Chronic Toxicity**

damage kidney function, the blood forming system and the reproductive system. Avoid repeated

exposure.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Lead	A3	Group 2A	Reasonably Anticipated	X
PP		Group 3	·	

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity	Product is or contains a chemical which is a known or suspected reproductive hazard.	
Developmental Toxicity	Contains ingredients that have suspected developmental hazards. Inorganic lead compounds can cause developmental damage.	
Target Organ Effects	None known.	

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Lead		LC50: 0.44 mg/L (96 h semi-static) Cyprinus carpio LC50: 1.17 mg/L (96 h flow-through) Oncorhynchus mykiss LC50: 1.32 mg/L (96 h static) Oncorhynchus mykiss		EC50: 600 µg/L (48 h) water flea

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261). Should not be released into the environment.

Contaminated Packaging Do not re-use empty containers.

US EPA Waste Number D002 D008

Chemical			RCRA - D	RCRA - U
	RCRA	RCRA - Basis for Listing	Series	Series
Name		_	Wastes	Wastes

|--|

California Hazardous Waste Codes 792

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California EHW	California Carc	California Hazardous Waste	California Waste - Part 2
Lead			Toxic	TCLP (for CA Toxicity): 5.0 mg/L
Calcium	Ignitable Reactive			

14. TRANSPORT INFORMATION

Note: Exempt from hazardous materials regulations per 49CFR173.159 (d).

DOT Description NOT REGULATED NON-SPILLABLE BATTERY

TDG Description Not regulated NON-SPILLABLE BATTERY

MEX Description Not regulated NON-SPILLABLE BATTERY

ICAO Description Not regulated NON-SPILLABLE BATTERY

IATA Description Not regulated NON-SPILLABLE BATTERY

IMDG/IMO Description Not regulated NON-SPILLABLE BATTERY

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL Not determined

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Lead	7439-92-1	85-90	0.1

SARA 311/312 Hazard Categories Acute

Health Hazard
Chronic Health Hazard
Fire Hazard
Sudden Release of Pressure Hazard

Yes

Yes

No

No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable	CWA - Toxic	CWA - Priority	CWA - Hazardous
	Quantities	Pollutants	Pollutants	Substances
Lead		X	X	

Clean Air Act. Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:

Chemical Name	CAS-No	Weight %	HAPS data	VOC Chemicals	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Lead	7439-92-1	85-90				

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs
Lead	10 lb	

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Lead	7439-92-1	Carcinogen Developmental Female Reproductive Male Reproductive

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Lead	X	X	X	X	X
Tin	X	Х	Х		
Calcium	Χ	X	X		

International Regulations

Mexico - Grade Minimum risk, Grade 0

Chemical Name	Carcinogen Status	Exposure Limits
Lead	A3	Mexico: TWA= 0.15 mg/m3
Tin		Mexico: TWA 2 mg/m3 Mexico: STEL 4 mg/m3

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR)

and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

D2A Very toxic materials E Corrosive material



Chemical Name	NPRI
Lead	X

LegendNPRI - National Pollutant Release Inventory

16. OTHER INFORMATION