



# FVP Speed Detailer & Protectant

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Revision Date: 07/01/2015

Date of issue: 07/01/2015

Version: 1.0

### SECTION 1: IDENTIFICATION

#### Product Identifier

Product Form: Mixture

Product Name: FVP Speed Detailer & Protectant

Product Code: FVPSDP-22

#### Intended Use of the Product

Protectant

#### Name, Address, and Telephone of the Responsible Party

##### Company

Factory Motor Parts

1380 Corporate Center Curve, Suite 200

Eagan, MN 55121

(866) 387-3343

[www.FVPparts.com](http://www.FVPparts.com)

#### Emergency Telephone Number

Emergency Number : 1-800-535-5053 INFOTRAC

### SECTION 2: HAZARDS IDENTIFICATION

#### Classification of the Substance or Mixture

##### Classification (GHS-US)

Not classified

#### Label Elements

GHS-US Labeling No labeling applicable

#### Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. May cause an allergic reaction in sensitive individuals.

Unknown Acute Toxicity (GHS-US) Not available

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Isopropyl alcohol	(CAS No) 67-63-0	2.95	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Dimethylol-5,5-dimethylhydantoin	(CAS No) 6440-58-0	0.4	Acute Tox. 4 (Oral), H302
Polytetrafluoroethylene	(CAS No) 9002-84-0	0.01	Not classified
2-Butoxyethanol	(CAS No) 111-76-2	0.00345 - 0.00405	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 2 (Dermal), H310 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319

Full text of H-phrases: see section 16

### SECTION 4: FIRST AID MEASURES

#### Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Call a POISON CENTER or doctor/physician if you feel unwell.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

# FVP Speed Detailer & Protectant

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

### **Most Important Symptoms and Effects Both Acute and Delayed**

**General:** None expected under normal conditions of use.

**Inhalation:** May cause respiratory irritation.

**Skin Contact:** May cause mild skin irritation.

**Eye Contact:** May cause slight irritation to eyes.

**Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** None expected under normal conditions of use.

### **Indication of Any Immediate Medical Attention and Special Treatment Needed**

If you feel unwell, seek medical advice (show the label where possible).

## **SECTION 5: FIRE-FIGHTING MEASURES**

### **Extinguishing Media**

**Suitable Extinguishing Media:** Use extinguishing media appropriate for surrounding fire.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### **Special Hazards Arising From the Substance or Mixture**

**Fire Hazard:** Not flammable.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### **Advice for Firefighters**

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. Do not breathe fumes from fires or vapors from decomposition. Do not allow run-off from firefighting to enter drains or water courses.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>).

### **Reference to Other Sections**

Refer to section 9 for flammability properties.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **Personal Precautions, Protective Equipment and Emergency Procedures**

**General Measures:** No special measures required.

#### **For Non-Emergency Personnel**

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### **For Emergency Personnel**

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Evacuate unnecessary personnel. Stop leak if safe to do so. Ventilate area.

### **Environmental Precautions**

Prevent entry to sewers and public waters.

### **Methods and Material for Containment and Cleaning Up**

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Contact competent authorities after a spill.

### **Reference to Other Sections**

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

## **SECTION 7: HANDLING AND STORAGE**

### **Precautions for Safe Handling**

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

# FVP Speed Detailer & Protectant

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### **Conditions for Safe Storage, Including Any Incompatibilities**

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers. Reducing agents. Acetaldehyde. Chlorine. Ethylene oxide. Isocyanates.

**Specific End Use(s)** Protectant

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **Control Parameters**

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

<b>Isopropyl alcohol (67-63-0)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	200 ppm
<b>USA ACGIH</b>	ACGIH STEL (ppm)	400 ppm
<b>USA ACGIH</b>	ACGIH chemical category	Not Classifiable as a Human Carcinogen
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	400 ppm
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	400 ppm
<b>USA NIOSH</b>	NIOSH REL (STEL) (mg/m <sup>3</sup> )	1225 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (STEL) (ppm)	500 ppm
<b>USA IDLH</b>	US IDLH (ppm)	2000 ppm (10% LEL)
<b>Alberta</b>	OEL STEL (mg/m <sup>3</sup> )	984 mg/m <sup>3</sup>
<b>Alberta</b>	OEL STEL (ppm)	400 ppm
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	492 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA (ppm)	200 ppm
<b>British Columbia</b>	OEL STEL (ppm)	400 ppm
<b>British Columbia</b>	OEL TWA (ppm)	200 ppm
<b>Manitoba</b>	OEL STEL (ppm)	400 ppm
<b>Manitoba</b>	OEL TWA (ppm)	200 ppm
<b>New Brunswick</b>	OEL STEL (mg/m <sup>3</sup> )	1230 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL STEL (ppm)	500 ppm
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	983 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL TWA (ppm)	400 ppm
<b>Newfoundland &amp; Labrador</b>	OEL STEL (ppm)	400 ppm
<b>Newfoundland &amp; Labrador</b>	OEL TWA (ppm)	200 ppm
<b>Nova Scotia</b>	OEL STEL (ppm)	400 ppm
<b>Nova Scotia</b>	OEL TWA (ppm)	200 ppm
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	1228 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL STEL (ppm)	500 ppm
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	983 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL TWA (ppm)	400 ppm
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	1228 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL STEL (ppm)	500 ppm
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	983 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL TWA (ppm)	400 ppm
<b>Ontario</b>	OEL STEL (ppm)	400 ppm
<b>Ontario</b>	OEL TWA (ppm)	200 ppm
<b>Prince Edward Island</b>	OEL STEL (ppm)	400 ppm
<b>Prince Edward Island</b>	OEL TWA (ppm)	200 ppm
<b>Québec</b>	VECD (mg/m <sup>3</sup> )	1230 mg/m <sup>3</sup>

# FVP Speed Detailer & Protectant

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Québec	VECD (ppm)	500 ppm
Québec	VEMP (mg/m <sup>3</sup> )	985 mg/m <sup>3</sup>
Québec	VEMP (ppm)	400 ppm
Saskatchewan	OEL STEL (ppm)	400 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm
Yukon	OEL STEL (mg/m <sup>3</sup> )	1225 mg/m <sup>3</sup>
Yukon	OEL STEL (ppm)	500 ppm
Yukon	OEL TWA (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
Yukon	OEL TWA (ppm)	400 ppm
<b>Polytetrafluoroethylene (9002-84-0)</b>		
Québec	VEMP (mg/m <sup>3</sup> )	2.5 mg/m <sup>3</sup> (decomposition products; determine quantitatively the decomposition products in the air and express the results as Fluorides)
<b>2-Butoxyethanol (111-76-2)</b>		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	240 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA OSHA	Limit value category (OSHA)	prevent or reduce skin absorption
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	24 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	5 ppm
USA IDLH	US IDLH (ppm)	700 ppm
Alberta	OEL TWA (mg/m <sup>3</sup> )	97 mg/m <sup>3</sup>
Alberta	OEL TWA (ppm)	20 ppm
British Columbia	OEL TWA (ppm)	20 ppm
Manitoba	OEL TWA (ppm)	20 ppm
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	121 mg/m <sup>3</sup>
New Brunswick	OEL TWA (ppm)	25 ppm
Newfoundland & Labrador	OEL TWA (ppm)	20 ppm
Nova Scotia	OEL TWA (ppm)	20 ppm
Nunavut	OEL STEL (mg/m <sup>3</sup> )	360 mg/m <sup>3</sup>
Nunavut	OEL STEL (ppm)	75 ppm
Nunavut	OEL TWA (mg/m <sup>3</sup> )	120 mg/m <sup>3</sup>
Nunavut	OEL TWA (ppm)	25 ppm
Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	360 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (ppm)	75 ppm
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	120 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (ppm)	25 ppm
Ontario	OEL TWA (ppm)	20 ppm
Prince Edward Island	OEL TWA (ppm)	20 ppm
Québec	VEMP (mg/m <sup>3</sup> )	97 mg/m <sup>3</sup>
Québec	VEMP (ppm)	20 ppm
Saskatchewan	OEL STEL (ppm)	30 ppm
Saskatchewan	OEL TWA (ppm)	20 ppm
Yukon	OEL STEL (mg/m <sup>3</sup> )	720 mg/m <sup>3</sup>
Yukon	OEL STEL (ppm)	150 ppm
Yukon	OEL TWA (mg/m <sup>3</sup> )	240 mg/m <sup>3</sup>
Yukon	OEL TWA (ppm)	50 ppm

# FVP Speed Detailer & Protectant

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### **Exposure Controls**

**Appropriate Engineering Controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

**Personal Protective Equipment:** Not generally required. The use of personal protective equipment may be necessary as conditions warrant.

**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical goggles or safety glasses.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

#### **Information on Basic Physical and Chemical Properties**

<b>Physical State</b>	: Liquid
<b>Appearance</b>	: Light Blue
<b>Odor</b>	: Pleasant
<b>Odor Threshold</b>	: Not available
<b>pH</b>	: 5
<b>Evaporation Rate</b>	: Not available
<b>Melting Point</b>	: Not available
<b>Freezing Point</b>	: Not available
<b>Boiling Point</b>	: > 100 °C (212 °F)
<b>Flash Point</b>	: > 100 °C (212 °F)
<b>Auto-ignition Temperature</b>	: Not available
<b>Decomposition Temperature</b>	: Not available
<b>Flammability (solid, gas)</b>	: Not available
<b>Lower Flammable Limit</b>	: Not available
<b>Upper Flammable Limit</b>	: Not available
<b>Vapor Pressure</b>	: Not available
<b>Relative Vapor Density at 20 °C</b>	: Not available
<b>Relative Density</b>	: Not available
<b>Specific Gravity</b>	: 0.995 (at 20°C)
<b>Solubility</b>	: Soluble.
<b>Partition Coefficient: N-Octanol/Water</b>	: Not available
<b>Viscosity</b>	: Not available
<b>Explosion Data – Sensitivity to Mechanical Impact</b>	: Not expected to present an explosion hazard due to mechanical impact.
<b>Explosion Data – Sensitivity to Static Discharge</b>	: Not expected to present an explosion hazard due to static discharge.

### **SECTION 10: STABILITY AND REACTIVITY**

**Reactivity:** Hazardous reactions will not occur under normal conditions.

**Chemical Stability:** Stable under normal conditions.

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Incompatible materials.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers. Reducing agents. Acetaldehyde. Chlorine. Ethylene oxide. Isocyanates.

**Hazardous Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides. Hydrocarbons.

### **SECTION 11: TOXICOLOGICAL INFORMATION**

#### **Information on Toxicological Effects - Product**

**Acute Toxicity:** Not classified

**ID50 and IC50 Data:** Not available

**Skin Corrosion/Irritation:** Not classified

# FVP Speed Detailer & Protectant

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**pH:** 5

**Serious Eye Damage/Irritation:** Not classified

**pH:** 5

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** Not classified

**Teratogenicity:** Not classified

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** May cause respiratory irritation.

**Symptoms/Injuries After Skin Contact:** May cause mild skin irritation.

**Symptoms/Injuries After Eye Contact:** May cause slight irritation to eyes.

**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** None expected under normal conditions of use.

### **Information on Toxicological Effects - Ingredient(s)**

#### **ID50 and IC50 Data:**

<b>Isopropyl alcohol (67-63-0)</b>	
<b>ID50 Oral Rat</b>	4710 mg/kg
<b>ID50 Dermal Rabbit</b>	4059 mg/kg
<b>IC50 Inhalation Rat</b>	72.6 mg/l/4h (Exposure time: 4 h)
<b>Dimethylol-5,5-dimethylhydantoin (6440-58-0)</b>	
<b>ID50 Oral Rat</b>	1572 mg/kg
<b>2-Butoxyethanol (111-76-2)</b>	
<b>ID50 Oral Rat</b>	470 mg/kg
<b>ID50 Dermal Rat</b>	220 mg/kg
<b>ID50 Dermal Rabbit</b>	99 mg/kg
<b>IC50 Inhalation Rat</b>	450 ppm/4h
<b>ATE US (vapors)</b>	3.84 mg/l/4h
<b>Isopropyl alcohol (67-63-0)</b>	
<b>IARC Group</b>	3
<b>Polytetrafluoroethylene (9002-84-0)</b>	
<b>IARC Group</b>	3
<b>2-Butoxyethanol (111-76-2)</b>	
<b>IARC Group</b>	3

## **SECTION 12: ECOLOGICAL INFORMATION**

**Toxicity** No additional information available

<b>Isopropyl alcohol (67-63-0)</b>	
<b>IC50 Fish 1</b>	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
<b>EC50 Daphnia 1</b>	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>EC50 Other Aquatic Organisms 1</b>	1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)
<b>IC 50 Fish 2</b>	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
<b>EC50 Other Aquatic Organisms 2</b>	1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
<b>Dimethylol-5,5-dimethylhydantoin (6440-58-0)</b>	
<b>IC50 Fish 1</b>	514 mg/l (Freshwater [96h static] Species: Oncorhynchus mykiss)
<b>2-Butoxyethanol (111-76-2)</b>	
<b>IC50 Fish 1</b>	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
<b>EC50 Daphnia 1</b>	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>IC 50 Fish 2</b>	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)

# FVP Speed Detailer & Protectant

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### Persistence and Degradability

#### FVP Speed Detailer & Protectant

Persistence and Degradability Not established.

### Bioaccumulative Potential

#### FVP Speed Detailer & Protectant

Bioaccumulative Potential Not established.

#### **Isopropyl alcohol (67-63-0)**

Log Pow 0.05 (at 25 °C)

#### **2-Butoxyethanol (111-76-2)**

Log Pow 0.81 (at 25 °C)

**Mobility in Soil** Not available

### Other Adverse Effects

**Other Information:** Avoid release to the environment.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

**Sewage Disposal Recommendations:** Do not empty into drains; dispose of this material and its container in a safe way.

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

## **SECTION 14: TRANSPORT INFORMATION**

In Accordance With ICAO/IATA/DOT/TDG/IMDG

**UN Number** Not regulated for transport

**UN Proper Shipping Name** Not regulated for transport

### Transport Hazard Class(es)

**Additional Information** Not available

**Transport by sea** Not regulated for transport

**Air transport** Not regulated for transport

**Marine Pollutant** No

## **SECTION 15: REGULATORY INFORMATION**

### US Federal Regulations

#### **Isopropyl alcohol (67-63-0)**

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on United States SARA Section 313

**EPA TSCA Regulatory Flag** T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

**SARA Section 313 - Emission Reporting** 1.0 % (only if manufactured by the strong acid process, no supplier notification)

#### **Dimethylol-5,5-dimethylhydantoin (6440-58-0)**

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### **Polytetrafluoroethylene (9002-84-0)**

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### **2-Butoxyethanol (111-76-2)**

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### US State Regulations

#### **Isopropyl alcohol (67-63-0)**

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic

U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)

U.S. - Connecticut - Volatile Substances

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations

# FVP Speed Detailer & Protectant

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)  
U.S. - Idaho - Occupational Exposure Limits - TWAs  
RTK - U.S. - Massachusetts - Right To Know List  
U.S. - Massachusetts - Toxics Use Reduction Act  
U.S. - Michigan - Occupational Exposure Limits - STELs  
U.S. - Michigan - Occupational Exposure Limits - TWAs  
U.S. - Minnesota - Hazardous Substance List  
U.S. - Minnesota - Permissible Exposure Limits - STELs  
U.S. - Minnesota - Permissible Exposure Limits - TWAs  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual  
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances  
U.S. - New Jersey - Environmental Hazardous Substances List  
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - New Jersey - Special Health Hazards Substances List  
U.S. - New York - Occupational Exposure Limits - TWAs  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour  
U.S. - Oregon - Permissible Exposure Limits - TWAs  
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
RTK - U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour  
U.S. - Tennessee - Occupational Exposure Limits - STELs  
U.S. - Tennessee - Occupational Exposure Limits - TWAs  
U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions  
U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term  
U.S. - Vermont - Permissible Exposure Limits - STELs  
U.S. - Vermont - Permissible Exposure Limits - TWAs  
U.S. - Washington - Permissible Exposure Limits - STELs  
U.S. - Washington - Permissible Exposure Limits - TWAs

### **Polytetrafluoroethylene (9002-84-0)**

RTK - U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term

### **2-Butoxyethanol (111-76-2)**

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute  
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)  
U.S. - Colorado - Groundwater Quality Standards  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)  
U.S. - Idaho - Occupational Exposure Limits - TWAs  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2  
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2  
RTK - U.S. - Massachusetts - Right To Know List  
U.S. - Michigan - Occupational Exposure Limits - Skin Designations  
U.S. - Michigan - Occupational Exposure Limits - TWAs  
U.S. - Minnesota - Chemicals of High Concern



# FVP Speed Detailer & Protectant

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

U.S. - Minnesota - Hazardous Substance List  
U.S. - Minnesota - Permissible Exposure Limits - Skin Designations  
U.S. - Minnesota - Permissible Exposure Limits - TWAs  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual  
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - New Jersey - Special Health Hazards Substances List  
U.S. - New York - Occupational Exposure Limits - Skin Designations  
U.S. - New York - Occupational Exposure Limits - TWAs  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour  
U.S. - Oregon - Permissible Exposure Limits - Skin Designations  
U.S. - Oregon - Permissible Exposure Limits - TWAs  
RTK - U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour  
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual  
U.S. - Tennessee - Occupational Exposure Limits - Skin Designations  
U.S. - Tennessee - Occupational Exposure Limits - TWAs  
U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term  
U.S. - Vermont - Permissible Exposure Limits - Skin Designations  
U.S. - Vermont - Permissible Exposure Limits - TWAs  
U.S. - Washington - Permissible Exposure Limits - Skin Designations  
U.S. - Washington - Permissible Exposure Limits - STELs  
U.S. - Washington - Permissible Exposure Limits - TWAs  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

### Canadian Regulations

#### FVP Speed Detailer & Protectant

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
----------------------	---

#### Isopropyl alcohol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

#### Dimethylol-5,5-dimethylhydantoin (6440-58-0)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
----------------------	---

#### Polytetrafluoroethylene (9002-84-0)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
----------------------	---

#### 2-Butoxyethanol (111-76-2)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

# FVP Speed Detailer & Protectant

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

### SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 07/01/2015

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.


#### GHS Full Text Phrases:

Acute Tox. 2 (Dermal)	Acute toxicity (dermal) Category 2
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
Skin Sens. 1B	Skin sensitization Category 1B
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H310	Fatal in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness

**NFPA Health Hazard** : 0 - Exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials.

**NFPA Fire Hazard** : 1 - Must be preheated before ignition can occur.

**NFPA Reactivity** : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



#### Party Responsible for the Preparation of This Document

Factory Motor Parts

Phone Number: (866) 387-3343

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

NA GHS SDS

