



SAFETY DATA SHEET

1. Identification

Product identifier Gunk Carburetor Parts Cleaner - Non Chlorinated

Other means of identification

SDS number M4815NC
Part No. M4815NC, M4819NC
Tariff code 3814.00.1000

Recommended use Carburetor Cleaner

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Blaster LLC
Address 8500 Sweet Valley Drive Valley View, Ohio 44125 - USA T
Telephone (216)901-5800 821-7643
F (216)901-5801
Website www.blastercorp.com
E-mail

Emergency phone number

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1
Health hazards Acute toxicity, dermal Category 4
Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2A
Carcinogenicity Category 2
Reproductive toxicity Category 2
Specific target organ toxicity, single exposure Category 3 narcotic effects
Specific target organ toxicity, repeated exposure Category 2
Aspiration hazard Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

| | |
|--|---|
| Response | If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. |
| Storage | Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Hazard(s) not otherwise classified (HNOC) | Combustible. |
| Supplemental information | NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The container label may not include the OSHA label elements listed in this document. Always carefully review the entire SDS and the product label prior to use in the workplace. |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|------------------------------------|--------------------------|------------|-----------|
| Acetone | | 67-64-1 | 70 - < 80 |
| ISOPARAFFINIC PETROLEUM DISTILLATE | | 64742-47-8 | 10 - < 20 |
| Carbon Dioxide | | 124-38-9 | 5 - < 10 |
| Xylene | | 1330-20-7 | 5 - < 10 |
| Ethylbenzene | | 100-41-4 | 3 - < 5 |

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

| | |
|---|--|
| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell. |
| Skin contact | Remove contaminated clothing. Wash with plenty of soap and water. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse. |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. |
| Ingestion | Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. |
| Most important symptoms/effects, acute and delayed | Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed. |
| General information | IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. |

5. Fire-fighting measures

| | |
|--|--|
| Suitable extinguishing media | Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. |

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol. Combustible.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value |
|-------------------------------|------|------------|
| Acetone (CAS 67-64-1) | PEL | 2400 mg/m3 |
| | | 1000 ppm |
| Carbon Dioxide (CAS 124-38-9) | PEL | 9000 mg/m3 |
| | | 5000 ppm |
| Ethylbenzene (CAS 100-41-4) | PEL | 435 mg/m3 |
| | | 100 ppm |

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value |
|---|------|-----------------------|
| ISOPARAFFINIC PETROLEUM DISTILLATE (CAS 64742-47-8) | PEL | 400 mg/m ³ |
| | | 100 ppm |
| Xylene (CAS 1330-20-7) | PEL | 435 mg/m ³ |
| | | 100 ppm |

US. ACGIH Threshold Limit Values

| Components | Type | Value |
|----------------------------------|------|-----------|
| Acetone (CAS 67-64-1) | STEL | 500 ppm |
| | TWA | 250 ppm |
| Carbon Dioxide (CAS 124-38-9) | STEL | 30000 ppm |
| | TWA | 5000 ppm |
| Ethylbenzene (CAS 100-41-4) | TWA | 20 ppm |
| | | |
| Xylene (CAS 1330-20-7) | STEL | 150 ppm |
| | TWA | 100 ppm |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value |
|----------------------------------|------|-------------------------|
| Acetone (CAS 67-64-1) | TWA | 590 mg/m ³ |
| | | 250 ppm |
| Carbon Dioxide (CAS 124-38-9) | STEL | 54000 mg/m ³ |
| | | 30000 ppm |
| | TWA | 9000 mg/m ³ |
| | | 5000 ppm |
| Ethylbenzene (CAS 100-41-4) | STEL | 545 mg/m ³ |
| | | 125 ppm |
| | TWA | 435 mg/m ³ |
| | | 100 ppm |
| Xylene (CAS 1330-20-7) | STEL | 655 mg/m ³ |
| | | 150 ppm |
| | TWA | 435 mg/m ³ |
| | | 100 ppm |

Biological limit values

ACGIH Biological Exposure Indices

| Components | Value | Determinant | Specimen | Sampling Time |
|--------------------------------|----------|---|------------------------|---------------|
| Acetone (CAS 67-64-1) | 25 mg/l | Acetone | Urine | * |
| Ethylbenzene (CAS 100-41-4) | 0.15 g/g | Sum of mandelic acid and phenylglyoxylic acid | Creatinine in urine | * |
| | | Methylhippuric acids | | |
| Xylene (CAS 1330-20-7) | 1.5 g/g | | | * |

* - For sampling details, please see the source document.

| | |
|--|--|
| Appropriate engineering controls | Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower. |
| Individual protection measures, such as personal protective equipment | |
| Eye/face protection | Chemical respirator with organic vapor cartridge and full facepiece. |
| Skin protection | |
| Hand protection | Wear appropriate chemical resistant gloves. Nitrile, butyl rubber or neoprene gloves are recommended. |
| Other | Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. |
| Respiratory protection | Chemical respirator with organic vapor cartridge and full facepiece. Chemical respirator with organic vapor cartridge and full facepiece if threshold limits are exceeded. |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |
| General hygiene considerations | Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |

9. Physical and chemical properties

| | |
|---|---|
| Appearance | Clear. Liquid |
| Physical state | Liquid. |
| Form | Aerosol. |
| Color | Colorless |
| Odor | Solvent.odor |
| Odor threshold | Not available. |
| pH | Not available. |
| Melting point/freezing point | -132.38 °F (-91.32 °C) estimated |
| Initial boiling point and boiling range | 133 °F (56.11 °C) |
| Flash point | -20.0 °F (-28.9 °C) Pensky-Martens Closed Cup |
| Evaporation rate | > 1 BuAc |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | 2.3 % estimated |
| Flammability limit - upper (%) | 11.7 % estimated |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | 4878.91739 hPa estimated |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Not available. |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | 869 °F (465 °C) estimated |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Density | 6.67 lbs/gal |
| Explosive properties | Not explosive. |

| | |
|--------------------------------------|---------------------|
| Heat of combustion (NFPA 30B) | 27.4 kJ/g estimated |
| Oxidizing properties | Not oxidizing. |
| Percent volatile | 100 % |
| Specific gravity | 0.8 |
| VOC | < 10 % w/w |

10. Stability and reactivity

| | |
|---|---|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| Conditions to avoid | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Strong acids. Strong oxidizing agents. Aluminum. Halogens. |
| Hazardous decomposition products | No hazardous decomposition products are known. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|--|
| Inhalation | May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful. |
| Skin contact | Harmful in contact with skin. Causes skin irritation. |
| Eye contact | Causes serious eye irritation. |
| Ingestion | Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. |

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Harmful in contact with skin.

| Components | Species | Test Results |
|-----------------------------|---------|-----------------------|
| Acetone (CAS 67-64-1) | | |
| Acute | | |
| Inhalation | | |
| LC50 | Rat | 50.1 mg/l, 8 Hours |
| Oral | | |
| LD50 | Rat | 5800 mg/kg |
| Ethylbenzene (CAS 100-41-4) | | |
| Acute | | |
| Oral | | |
| LD50 | Rat | 3500 mg/kg |
| Xylene (CAS 1330-20-7) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | 12130 mg/kg, 24 Hours |
| Inhalation | | |
| LC50 | Rat | 6350 mg/l, 4 Hours |
| Oral | | |
| LD50 | Rat | 3523 - 8600 mg/kg |

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization**Respiratory sensitization** Not a respiratory sensitizer.**Skin sensitization** This product is not expected to cause skin sensitization.**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.**Carcinogenicity** Suspected of causing cancer.**IARC Monographs. Overall Evaluation of Carcinogenicity**

Ethylbenzene (CAS 100-41-4)

2B Possibly carcinogenic to humans.

Xylene (CAS 1330-20-7)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging fertility or the unborn child.**Specific target organ toxicity - single exposure** May cause drowsiness and dizziness.**Specific target organ toxicity - repeated exposure** May cause damage to organs through prolonged or repeated exposure.**Aspiration hazard** May be fatal if swallowed and enters airways.**Chronic effects** May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.**12. Ecological information****Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Components | Species | Test Results |
|---|---------|--|
| Acetone (CAS 67-64-1) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) 10294 - 17704 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) 4740 - 6330 mg/l, 96 hours |
| Ethylbenzene (CAS 100-41-4) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) 1.37 - 4.4 mg/l, 48 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) 7.5 - 11 mg/l, 96 hours |
| ISOPARAFFINIC PETROLEUM DISTILLATE (CAS 64742-47-8) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) 2.9 mg/l, 96 hours |
| Xylene (CAS 1330-20-7) | | |
| Aquatic | | |
| Fish | LC50 | Bluegill (Lepomis macrochirus) 7.711 - 9.591 mg/l, 96 hours |

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.**Bioaccumulative potential****Partition coefficient n-octanol / water (log Kow)**

| | |
|--------------|------------|
| Acetone | -0.24 |
| Ethylbenzene | 3.15 |
| Xylene | 3.12 - 3.2 |

Mobility in soil No data available.**Other adverse effects** The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

| | |
|--|--|
| Disposal instructions | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Local disposal regulations | Dispose in accordance with all applicable regulations. |
| Hazardous waste code | D001: Waste Flammable material with a flash point <140 F The waste code should be assigned in discussion between the user, the producer and the waste disposal company. |
| Waste from residues / unused products | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| Contaminated packaging | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. |

14. Transport information

DOT

| | |
|-------------------------------------|--|
| UN number | UN1950 |
| UN proper shipping name | Aerosols, flammable, (each not exceeding 1 L capacity), Limited Quantity |
| Transport hazard class(es) | |
| Class | 2.1 |
| Subsidiary risk | - |
| Label(s) | 2.1 |
| Packing group | Not available. |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Special provisions | N82 |
| Packaging exceptions | 306 |
| Packaging non bulk | None |
| Packaging bulk | None |

IATA


| | |
|-------------------------------------|---|
| UN number | UN1950 |
| UN proper shipping name | Aerosol, flammable, Limited Quantity |
| Transport hazard class(es) | |
| Class | 2.1 |
| Subsidiary risk | - |
| Packing group | Not available. |
| Environmental hazards | No. |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |

IMDG


| | |
|-------------------------------------|---|
| UN number | UN1950 |
| UN proper shipping name | Aerosols, Limited Quantity |
| Transport hazard class(es) | |
| Class | 2 |
| Subsidiary risk | - |
| Packing group | Not available. |
| Environmental hazards | |
| Marine pollutant | No. |
| EmS | F-D, S-U |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

DOT; IMDG



IATA



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

| | |
|-----------------------------|---------|
| Acetone (CAS 67-64-1) | Listed. |
| Ethylbenzene (CAS 100-41-4) | Listed. |
| Xylene (CAS 1330-20-7) | Listed. |

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

| | |
|-------------------------------------|--|
| Classified hazard categories | Flammable (gases, aerosols, liquids, or solids) Acute toxicity (any route of exposure) Skin corrosion or irritation Serious eye damage or eye irritation Carcinogenicity Reproductive toxicity Specific target organ toxicity (single or repeated exposure) Aspiration hazard |
|-------------------------------------|--|

SARA 313 (TRI reporting)

| Chemical name | CAS number | % by wt. |
|---------------|------------|----------|
| Ethylbenzene | 100-41-4 | 3 - < 5 |
| Xylene | 1330-20-7 | 5 - < 10 |

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylbenzene (CAS 100-41-4)
Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Acetone (CAS 67-64-1) Low priority

US state regulations

California Proposition 65



WARNING: This product can expose you to Ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1)
Ethylbenzene (CAS 100-41-4)
Xylene (CAS 1330-20-7)

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| Taiwan | Taiwan Chemical Substance Inventory (TCSI) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| | |
|----------------------|---|
| Issue date | 05-06-2015 |
| Revision date | 03-02-2023 |
| Version # | 07 |
| HMIS® ratings | Health: 3* Flammability: 4 Physical hazard: 0 |
| NFPA ratings | Health: 2 Flammability: 4 Instability: 0 |

NFPA ratings



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.