

PENRAY ®	according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012
	Date of issue: 12/31/2014 Revision date: 12/31/2014 Version: 1.0
	the substance/mixture and of the company/undertaking
1.1. Product identifier Product name	: PENRAY FUEL INJECTOR CLEANER
Product code	: 2112
	the substance or mixture and uses advised against
Jse of the substance/mixture	: Fuel System cleaner.
I.3. Details of the supplier of the penray Companies, Inc. The Penray Companies, Inc. 440 Denniston Ct. Wheeling, IL 60090 Γ (800) 373-6729 otto@penray.com 14	
I.4. Emergency telephone num Emergency number	: (800) 373-6729
	CHEMTREC (800) 424-9300 CHEMTREC International +1 (703) 527-3887 24 hr
SECTION 2: Hazards identific	ation
2.1. Classification of the substa	ance or mixture
Flammable Liquid 2 Skin irritation 2 Carcinogenicity 2 Specific target organ toxicity - Single e Aspiration hazard 1	xposure 3
2.2. Label elements	
GHS-US labelling	
Hazard pictograms (GHS-US)	HS02 GHS07 GHS08
Signal word (GHS-US)	: Danger
lazard statements (GHS-US)	 Highly flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.
Precautionary statements (GHS-US)	Keep away from heat/sparks/open flames/hot surfaces.– No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection. Wash hands thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. If on skin (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.
2.3. Other hazards	
lo additional information available	
.4. Unknown acute toxicity (G	HS-US)
percent of the mixture consists of ing	redient(s) of unknown acute toxicity.

SECTION 3: Composition/information on ingredients

Substance 3.1.

Not applicable

12/31/2014

EN (English)

Page 1



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

.2. Mixture			
Name	Product identifier	%	GHS-US classification
Kerosine, petroleum	(CAS No) 8008-20-6	60 - 100	Flam. Liq. 3 Skin Irrit. 2 STOT SE 3 Asp. Tox. 1
Polyolefin alkyl phenol alkyl amine	Propriatary	1 - 2	Skin Irrit. 2 Eye Irrit. 2A
Benzene, 1,2,4-trimethyl-	(CAS No) 95-63-6	0.5 - 1.5	Flam. Liq. 3 Acute Tox. 4 (Inhalation) Skin Irrit. 2 Eye Irrit. 2A STOT SE 3
Naphthalene	(CAS No) 91-20-3	< 0.5	Acute Tox. 4 (Oral) Carc. 2
Cumene	(CAS No) 98-82-8	< 0.1	Flam. Liq. 3 Acute Tox. 4 (Oral) Carc. 2 STOT SE 3 Asp. Tox. 1
Ethylbenzene	(CAS No) 100-41-4	< 0.1	Flam. Liq. 2 Acute Tox. 4 (Inhalation) Skin Irrit. 2 Carc. 2
Toluene	(CAS No) 108-88-3	< 0.1	Flam. Liq. 2 Skin Irrit. 2 Repr. 2 (developmental) STOT RE 2 Asp. Tox. 1
Benzene	(CAS No) 71-43-2	< 0.1	Flam. Liq. 2 Acute Tox. 4 (Oral) Skin Irrit. 2 Eye Irrit. 2A Muta. 1B Carc. 1A STOT RE 1 Asp. Tox. 1
Furan	(CAS No) 110-00-9	< 0.1	Flam. Liq. 1 Acute Tox. 4 (Oral) Acute Tox. 3 (Inhalation) Skin Irrit. 2 Muta. 2 Carc. 1B STOT RE 2
Propylene oxide	(CAS No) 75-56-9	< 0.1	Flam. Liq. 1 Acute Tox. 3 (Inhalation) Acute Tox. 4 (Oral, Dermal) Eye Irrit. 2A Muta. 1B Carc. 2 STOT SE 3
Acetaldehyde	(CAS No) 75-07-0	< 0.1	Flam. Liq. 1 Eye Irrit. 2A Carc. 2 STOT SE 3

* The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

difficult,
clothing ists.
s, if worn.
ət



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

4.2.	Most important symptoms and effect	s, both acute and delayed
Sympton	ms/injuries after inhalation	: May cause respiratory tract irritation. May cause drowsiness, dizziness and central nervous system depression.
Sympton	ms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Sympton	ms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Sympton	ms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.
4.3.	Indication of any immediate medical	attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECT	ION 5: Firefighting measures	
5.1.	Extinguishing media	
Suitabl	e extinguishing media	: Powder, water spray, foam, carbon dioxide.
Unsuita	able extinguishing media	: Do not use a heavy water stream.
5.2.	Special hazards arising from the su	bstance or mixture
Fire ha	zard	: Products of combustion may include, and are not limited to: oxides of carbon, aldehydes, hydrocarbons.
5.3.	Advice for firefighters	
Protect	ion during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

SECTI	ON 6: Accidental release measu	ires
6.1.	Personal precautions, protective equi	pment and emergency procedures
General	measures :	Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.
6.2.	Methods and material for containment	t and cleaning up
For cont	ainment :	Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
Methods	s for cleaning up	Scoop up material and place in a disposal container. Provide ventilation.
6.3.	Reference to other sections	
See sec	tion 8 for further information on protective of	clothing and equipment and section 13 for advice on waste disposal.
SECTI	ON 7: Handling and storage	

7.1.	Precautions for safe handling	
Precauti	ons for safe handling	Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. Handle and open container with care. Use only non-sparking tools. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.
Hygiene	measures	: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.
7.2.	Conditions for safe storage, including	any incompatibilities
Storage	conditions	Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Store locked up. Keep cool. Keep away from heat, sparks, and flame.
7.3.	Specific end use(s)	

```
Not available.
```

SECTION 8: Exposure c	ontrols/personal protection	
8.1. Control parameters		
Kerosine, petroleum (8008-2	0-6)	
USA ACGIH	ACGIH TWA (mg/m³)	200 mg/m ³
Polyolefin alkyl phenol alkyl	amine (Propriatary)	
ACGIH	Not applicable	
OSHA	Not applicable	
	1	

Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Benzene, 1,2,4-trimet			
ACGIH	Not applicable		
OSHA	Not applicable		
Naphthalene (91-20-3)		
USA ACGIH	ACGIH TWA (ppm)	10 ppm	
USA ACGIH	ACGIH STEL (ppm)	15 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m ³)	50 mg/m³	
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm	
Cumene (98-82-8)			
USA ACGIH	ACGIH TWA (ppm)	50 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m ³)	245 mg/m ³	
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm	
Ethylbenzene (100-41	-4)	<u>.</u>	
USA ACGIH	ACGIH TWA (ppm)	20 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³	
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm	
Toluene (108-88-3)	·	<u>.</u>	
USA ACGIH	ACGIH TWA (ppm)	20 ppm	
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm	
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm	
Benzene (71-43-2)			
USA ACGIH	ACGIH TWA (ppm)	0.5 ppm	
USA ACGIH	ACGIH STEL (ppm)	2.5 ppm	
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm	
USA OSHA	OSHA PEL (STEL) (ppm)	5 ppm	
USA OSHA	OSHA PEL (Ceiling) (ppm)	25 ppm	
Furan (110-00-9)			
ACGIH	Not applicable		
OSHA	Not applicable		
Propylene oxide (75-5	56-9)		
USA ACGIH	ACGIH TWA (ppm)	2 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m ³)	240 mg/m ³	
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm	
Acetaldehyde (75-07-	0)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	360 mg/m ³	
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm	

8.2. Exposure controls	
Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear chemically resistant protective gloves.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Respiratory protection	: A NIOSH approved respirator is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and	d chemical properties
Physical state	: Liquid
Appearance	: Clear
Color	: Amber
Odor	: Petroleum odor
Odor threshold	: No data available
рН	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 22 °C (71 °F)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.864 - 0.869
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECT	ION 10: Stability and reactivity			
	10.1. Reactivity			
No dan	No dangerous reaction known under conditions of normal use.			
10.2.	Chemical stability			
Stable under normal storage conditions. May form flammable/explosive vapor-air mixture.				
10.3.	Possibility of hazardous reactions			
No dan	No dangerous reaction known under conditions of normal use.			
10.4.	Conditions to avoid			
Heat. Ir	Heat. Incompatible materials. Open flame.			
10.5.	Incompatible materials			
Strong	Strong oxidizing agents.			
10.6.	Hazardous decomposition products			
May include, and are not limited to: oxides of carbon, aldehydes, hydrocarbons.				
SECT	ION 11: Toxicological information			
11.1.	Information on toxicological effects			
Acute to	oxicity : Not classified.			



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

2112			
LD50 oral rat	> 2000 mg/kg		
LD50 dermal rabbit	> 2000 mg/kg		
LC50 inhalation rat	No data available		
Kerosine, petroleum (8008-20-6)			
LD50 oral rat	> 5000 mg/kg		
LD50 dermal rabbit	> 2000 mg/kg		
LC50 inhalation rat	> 5.28 mg/l/4h		
Benzene, 1,2,4-trimethyl- (95-63-6)			
LD50 oral rat	3280 mg/kg		
LD50 dermal rabbit	> 3160 mg/kg		
LC50 inhalation rat 18 g/m ³ /4h			
Naphthalene (91-20-3)			
LD50 oral rat	490 mg/kg		
LD50 dermal rabbit	> 20 g/kg		
Cumene (98-82-8)			
LD50 oral rat	1400 mg/kg		
LD50 dermal rabbit	>3160 mg/kg		
LC50 inhalation rat	39000 mg/m ³ /4h		
Ethylbenzene (100-41-4)	2500 malla		
	3500 mg/kg		
LD50 dermal rabbit	15354 mg/kg		
LC50 inhalation rat	17.2 mg/l/4h		
Toluene (108-88-3)			
LD50 oral rat	> 5000 mg/kg		
LD50 dermal rabbit	8390 mg/kg		
LD50 dermal rat	12124 mg/kg		
LC50 inhalation rat	28.1 mg/l/4h		
Benzene (71-43-2)			
LD50 oral rat	930 mg/kg		
LD50 dermal rabbit	> 9.4 ml/kg		
LC50 inhalation rat	13050-14380 ppm/4h		
Furan (110-00-9)			
LC50 inhalation rat	3398 ppm/1h		
Propylene oxide (75-56-9)			
LD50 oral rat	520 mg/kg		
LD50 dermal rabbit	1244 mg/kg		
LC50 inhalation rat	4000 ppm/4h		
Acetaldehyde (75-07-0)			
LD50 oral rat	1930 mg/kg		
LC50 inhalation rat	13300 ppm/4h		
Skin corrosion/irritation	: Causes skin irritation.	_	
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.		
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.		
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.		
Carcinogenicity	: Suspected of causing cancer.		
Naphthalene (91-20-3)			
IARC group	2B - Possibly carcinogenic to humans		
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen		
Cumene (98-82-8)			
IARC group	2B - Possibly carcinogenic to humans		
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity		
12/31/2014	EN (English)	6/9	
12/31/2014		D/M	



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Ethylbenzene (100-41-4)			
IARC group	2B - Possibly carcinogenic to humans		
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity		
Toluene (108-88-3)			
IARC group	3 - Not classifiable		
Benzene (71-43-2)			
IARC group	1 - Carcinogenic to humans		
National Toxicology Program (NTP) Status 1 - Evidence of Carcinogenicity, 2 - Known Human Carcinogens			
	In OSHA Specifically Regulated Carcinogen list		
Furan (110-00-9)			
IARC group	2B - Possibly carcinogenic to humans		
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen		
Propylene oxide (75-56-9)			
IARC group	2B - Possibly carcinogenic to humans		
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen		
Acetaldehyde (75-07-0)			
IARC group	1 - Carcinogenic to humans (associated with consumption of alcoholic beverages), 2B - Possibly carcinogenic to humans		
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen		
Reproductive toxicity	: Based on available data, the classification criteria are not met.		
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.		
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.		
Aspiration hazard	: May be fatal if swallowed and enters airways.		
Symptoms/injuries after inhalation	: May cause respiratory tract irritation. May cause drowsiness, dizziness and central nervous system depression.		
Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting ar of the skin.			
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.		
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.		

SECTION 12: Ecological informa	tion
12.1. Toxicity	
Ecology - general	: May cause long-term adverse effects in the aquatic environment.
12.2. Persistence and degradability	
2112	
Persistence and degradability	Not established.
12.3. Bioaccumulative potential	
2112	
Bioaccumulative potential	Not established.
12.4. Mobility in soil	
No additional information available	
12.5. Other adverse effects	
Effect on the global warming	: No known ecological damage caused by this product.
SECTION 13: Disposal considera	itions
13.1. Waste treatment methods	
Waste disposal recommendations	: This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.
Additional information	: Handle empty containers with care because residual vapors are flammable.



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 14: Transport information	
In accordance with DOT	
UN-No.(DOT)	: UN1993
Proper Shipping Name (DOT)	: Flammable liquids, n.o.s. (Petroleum, Benzene, 1,2,4-trimethyl-)
Department of Transportation (DOT) Hazard Classes	: 3
Hazard labels (DOT)	
Packing group (DOT)	: 11
Additional information	
Other information	: No supplementary information available.
Special transport precautions	: Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.


Benzene, 1,2,4-trimethyl- (95-63-6)				
Listed on United States SARA Section 313				
SARA Section 313 - Emission Reporting	ARA Section 313 - Emission Reporting 1.0 %			
Naphthalene (91-20-3)				
Listed on United States SARA Section 313				
EPA TSCA Regulatory Flag	T - T - ir	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.		
SARA Section 313 - Emission Reporting	0.1 %	0.1 %		
Cumene (98-82-8)				
Listed on United States SARA Section 313				
EPA TSCA Regulatory Flag	T - T - ir	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.		
SARA Section 313 - Emission Reporting 1.0 %				
Ethylbenzene (100-41-4)				
Listed on United States SARA Section 313				
SARA Section 313 - Emission Reporting	0.1 %			
Toluene (108-88-3)				
Listed on United States SARA Section 313				
SARA Section 313 - Emission Reporting 1.0 %				
Benzene (71-43-2)				
Listed on United States SARA Section 313				
SARA Section 313 - Emission Reporting	SARA Section 313 - Emission Reporting 0.1 %			
Furan (110-00-9)				
Listed on the United States SARA Section 302 Listed on United States SARA Section 313				
SARA Section 302 Threshold Planning Quantity (TPQ)		500		
SARA Section 313 - Emission Reporting		0.1 %		
Propylene oxide (75-56-9)				
Listed on the United States SARA Section 302 Listed on United States SARA Section 313				
EPA TSCA Regulatory Flag		T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.		
SARA Section 302 Threshold Planning Quantity (TPQ)	10000		
SARA Section 313 - Emission Reporting 0.1 %				

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Acetaldehyde (75-07-0)			
Listed on United States SARA Section 313			
EPA TSCA Regulatory Flag T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.			
SARA Section 313 - Emission Reporting 0.1 %			
15.2. US State regulations			
2112			

Indication of changes	: None.
Date of issue	: 12/31/2014
Other information	: None.
NFPA health hazard	: 2
NFPA fire hazard	: 3
NFPA reactivity	: 0



Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.





Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 07/24/2014 Revision date: 07/24/2014

Version: 1.0

1.1.	Product identifier		
Product name		: PENRAY INTAKE VALVE DEPOSIT CLEANER	
CAS N	lo	: 2312	
1.2.	Relevant identified uses of the substance or mixture and uses advised against		
Use of	the substance/mixture	: Fuel System cleaner.	
1.3.	Details of the supplier of the safety data sheet		
440 De Wheel T (800	enray Companies, Inc. enniston Ct. ing, IL 60090) 373-6729 <u>penray.com</u>		
1.4.	Emergency telephone number	er de la constant de	
Emerg	ency number	: (800) 373-6729 CHEMTREC (800) 424-9300 CHEMTREC International +1 (703) 527-3887 24 hr	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable Liquid 2 Acute toxicity 4 (Dermal, Inhalation) Skin irritation 2 Carcinogenicity 2 Reproductive toxicity 2 (developmental) Specific target organ toxicity - Repeated exposure 2 Aspiration hazard 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)

Signal word (GHS-US) Hazard statements (GHS-US)

Precautionary statements (GHS-US)

- HS02 GHS07 GHS08
- : Danger
- : Highly flammable liquid and vapor. Harmful in contact with skin or if inhaled. Causes skin irritation. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.
- : Keep away from heat/sparks/open flames/hot surfaces.– No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use only outdoors or in a well- ventilated area. Wash hands thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe gas/mist/vapors/spray. If exposed or concerned: Get medical advice/attention. If on skin (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

No additional information available





Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. **Mixture**

Name	Product identifier	%	GHS-US classification
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	60 - 100	Flam. Liq. 3 Acute Tox. 4 (Dermal, Inhalation) Skin Irrit. 2
Ethylbenzene	(CAS No) 100-41-4	7 - 30	Flam. Liq. 2 Acute Tox. 4 (Inhalation) Skin Irrit. 2 Carc. 2 Asp. Tox. 1
Toluene	(CAS No) 108-88-3	7 - 13	Flam. Liq. 2 Skin Irrit. 2 Repr. 2 STOT SE 3 STOT RE 2 Asp. Tox. 1
Solvent naphtha, petroleum, light aromatic	(CAS No) 64742-95-6	0.5 - 1.5	Flam. Liq. 3 Skin Irrit. 2 Eye Irrit. 2A Asp. Tox. 1
Cumene	(CAS No) 98-82-8	< 0.1	Flam. Liq. 3 Carc. 2 STOT SE 3 Asp. Tox. 1
Benzene	(CAS No) 71-43-2	< 0.1	Flam. Liq. 2 Acute Tox. 4 (Oral) Skin Irrit. 2 Eye Irrit. 2A Muta. 1B Carc. 1A STOT RE 1 Asp. Tox. 1
Naphthalene	(CAS No) 91-20-3	< 0.1	Acute Tox. 4 (Oral) Carc. 2
Furan	(CAS No) 110-00-9	< 0.1	Flam. Liq. 1 Acute Tox. 3 (Inhalation) Acute Tox. 4 (Oral) Skin Irrit. 2 Muta. 2 Carc. 1B STOT RE 2
Propylene oxide	(CAS No) 75-56-9	< 0.1	Flam. Liq. 1 Acute Tox. 3 (Inhalation) Acute Tox. 4 (Oral, Dermal) Eye Irrit. 2A Muta. 1B Carc. 2 STOT SE 3
Acetaldehyde	(CAS No) 75-07-0	< 0.1	Flam. Liq. 1 Eye Irrit. 2A Carc. 2 STOT SE 3

* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures after inhalation	: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.
First-aid measures after ingestion	: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

4.2. Most important symptoms and effe	cts, both acute and delayed
Symptoms/injuries after inhalation	: Harmful if inhaled. May cause drowsiness, dizziness and central nervous system depression. May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Harmful in contact with skin. Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	 May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

. ,		
SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media	: Powder, water spray, foam, carbon dioxide.	
Unsuitable extinguishing media	: Do not use a heavy water stream.	
5.2. Special hazards arising from the s	substance or mixture	
Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon, aldehydes, hydrocarbons.	
5.3. Advice for firefighters		
Protection during firefighting	Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.	
SECTION 6: Accidental release me	asures	
6.1. Personal precautions, protective e	equipment and emergency procedures	
General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.	
6.2. Methods and material for contain	nent and cleaning up	
For containment	 Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE). 	
Methods for cleaning up	: Scoop up material and place in a disposal container. Provide ventilation.	
6.3. Reference to other sections		
See section 8 for further information on protect	tive clothing and equipment and section 13 for advice on waste disposal.	
SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Precautions for safe handling	Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Do not breathe gas/mist/vapors/spray. Do not swallow. Handle and open container with care. Use only non-sparking tools. When using do not eat, drink or smoke. Use only outdoors or in a well- ventilated area.	
Hygiene measures	: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.	
7.2. Conditions for safe storage, inclu	ding any incompatibilities	
Storage conditions	: Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Store locked up. Keep cool. Keep away from heat, sparks, and flame.	
7.3. Specific end use(s)		
Not available.		
SECTION 8: Exposure controls/personal protection		

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Xylenes (o-, m-, p- isomers) (1330-20-7)		
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m ³



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Xylenes (o-, m-, p- isomers) (1330-20-7)			
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm	
Ethylbenzene (100-41 USA ACGIH	ACGIH TWA (ppm)	20 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³	
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm	
Toluene (108-88-3)			
USA ACGIH	ACGIH TWA (ppm)	20 ppm	
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm	
USA OSHA	OSHA PEL (STEL) (ppm)	150 ppm	
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm	
Solvent naphtha, pet	roleum, light aromatic (64742-95-6)		
USA ACGIH	ACGIH TWA	Not applicable.	
USA OSHA	OSHA PEL (TWA)	Not applicable.	
Cumene (98-82-8)			
USA ACGIH	ACGIH TWA (ppm)	50 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m ³)	245 mg/m ³	
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm	
Bonzono (71-42-2)	1		
Benzene (71-43-2) USA ACGIH	ACGIH TWA (ppm)	0.5 ppm	
USA ACGIH	ACGIH STEL (ppm)	2.5 ppm	
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm	
USA OSHA	OSHA PEL (STEL) (ppm)	5 ppm	
USA OSHA	OSHA PEL (Ceiling) (ppm)	25 ppm	
034 03114		25 μμπ	
Naphthalene (91-20-3	3)		
USA ACGIH	ACGIH TWA (ppm)	10 ppm	
USA ACGIH	ACGIH STEL (ppm)	15 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m ³)	50 mg/m ³	
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm	
Furan (110-00-9)			
USA ACGIH	ACGIH TWA	Not applicable.	
USA OSHA	OSHA PEL (TWA)	Not applicable.	
Propylene oxide (75-	56-9)		
USA ACGIH	ACGIH TWA (ppm)	2 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m ³)	240 mg/m ³	
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm	
Acetaldehyde (75-07-	0)		
USA ACGIH	ACGIH Ceiling (ppm)	25 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m ³)	360 mg/m ³	
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm	



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

8.2. Exposure controls	
Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear chemically resistant protective gloves.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: A NIOSH approved respirator is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

OF CHOM 3. I Hysical and chemical	properties		
9.1. Information on basic physical and chemical properties			
Physical state	: Liquid.		
Appearance	: Clear.		
Color	: Amber.		
Odor	: Petroleum odor.		
Odor threshold	: No data available.		
рН	: No data available.		
Relative evaporation rate (butylacetate=1)	: No data available.		
Melting point	: No data available.		
Freezing point	: No data available.		
Boiling point	: No data available.		
Flash point	: ~ 22 °C (~ 71 °F)		
Self ignition temperature	: No data available.		
Decomposition temperature	: No data available.		
Flammability (solid, gas)	: Flammable.		
Vapor pressure	: No data available.		
Relative vapor density at 20 °C	: No data available.		
Relative density	: 0.864 - 0.869		
Solubility	: No data available.		
Log Pow	: No data available.		
Log Kow	: No data available.		
Viscosity, kinematic	: No data available.		
Viscosity, dynamic	: No data available.		
Explosive properties	: No data available.		
Oxidising properties	: No data available.		
Explosive limits	: No data available.		

Other information 9.2.

No additional information available

SECTI	ON 10: Stability and reactivity			
10.1.	Reactivity			
No dang	No dangerous reaction known under conditions of normal use.			
10.2.	Chemical stability			
Stable ur	Stable under normal storage conditions. May form flammable/explosive vapor-air mixture.			
10.3.	Possibility of hazardous reactions			
No dang	No dangerous reaction known under conditions of normal use.			
10.4.	Conditions to avoid			
Heat. Incompatible materials. Open flame.				



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

cording to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.			
0.5. Incompatible materials			
Acids. Bases. Strong oxidizing agents.			
0.6. Hazardous decomposition products			
May include, and are not limited to: oxid	lay include, and are not limited to: oxides of carbon, aldehydes, hydrocarbons.		
SECTION 11: Toxicological in	formation		
1.1. Information on toxicologica			
Acute toxicity	: Harmful in contact with skin or if inhaled.		
-			
2312			
LD50 oral rat	> 2000 mg/kg		
LD50 dermal rabbit	>1000 but <2000 mg/kg		
LC50 inhalation rat	>10.0 but ≤20.0 mg/l/4h (Calculated using ATE values)		
Xylenes (o-, m-, p- isomers) (1330-2	0-7)		
LD50 oral rat	4300 mg/kg		
LD50 dermal rabbit	> 1700 mg/kg		
LC50 inhalation rat	5000 ppm/4 h		
Ethylbenzene (100-41-4)			
LD50 oral rat	3500 mg/kg		
LD50 dermal rabbit	15354 mg/kg		
LC50 inhalation rat	17.2 mg/l/4h		
Toluene (108-88-3)	5000 malla		
LD50 oral rat	> 5000 mg/kg		
LD50 dermal rat LD50 dermal rabbit	12124 mg/kg		
LC50 inhalation rat	8390 mg/kg 28.1 mg/l/4h		
	20.1 mg//4m		
Solvent naphtha, petroleum, light a			
LD50 oral rat	8400 mg/kg		
LD50 dermal rabbit	> 2000 mg/kg		
LC50 inhalation rat	3400 ppm/4h		
LC50 inhalation rat	> 5.2 mg/l/4h		
Cumene (98-82-8)			
LD50 oral rat	1400 mg/kg		
LD50 dermal rabbit	> 3160 mg/kg		
LC50 inhalation rat	39000 mg/m³/4 h		
Benzene (71-43-2)			
LD50 oral rat	930 mg/kg		
LD50 dermal rabbit	> 9.4 mL/kg		
LC50 inhalation rat	13050 - 14380 ppm/4h		
Naphthalene (91-20-3) LD50 oral rat	400 mg/kg		
LD50 dermal rabbit	490 mg/kg > 20 g/kg		
LC50 inhalation rat	> 20 g/kg > 340 mg/m ³ /4 h		
Furan (110-00-9)			
LC50 inhalation rat	3398 ppm/1h		
Propylene oxide (75-56-9)			
LD50 oral rat	520 mg/kg		
LD50 dermal rabbit	1244 mg/kg		
LC50 inhalation rat	4000 ppm/4h		
Acetaldehyde (75-07-0) LD50 oral rat	1930 mg/kg		
LC50 inhalation rat	13300 ppm/4h		
	13000 ppin/4in		



Safety Data Sheet

ccording to the Hazard Communication Standard (CFR29	9 1910.1200) HazCom 2012.
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Suspected of causing cancer.
Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3 - Not classifiable
Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity
Toluene (108-88-3)	
IARC group	3 - Not classifiable
Cumene (98-82-8)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity
Benzene (71-43-2)	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity, 2 - Known Human Carcinogens
	In OSHA Specifically Regulated Carcinogen list
Naphthalene (91-20-3)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
Furan (110-00-9)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
Propylene oxide (75-56-9)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
Acetaldehyde (75-07-0)	
IARC group	1 - Carcinogenic to humans, 2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen
Reproductive toxicity	: Suspected of damaging the unborn child.
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: Harmful if inhaled. May cause drowsiness, dizziness and central nervous system depression. May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Harmful in contact with skin. Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting. Symptoms/injuries after ingestion

SECTIO	ON 12: Ecological information	
12.1.	Toxicity	
Ecology -	general	May cause long-term adverse effects in the aquatic environment.
12.2.	Persistence and degradability	
2312		
Persiste	Persistence and degradability Not established.	



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

12.3. Bioaccumulative potential	
2312	
Bioaccumulative potential	Not established.
12.4. Mobility in soil	
No additional information available	
12.5. Other adverse effects	
Effect on ozone layer	: No additional information available
Effect on the global warming	: No known ecological damage caused by this product.
SECTION 13: Disposal consideration	ns
13.1. Waste treatment methods	
Waste disposal recommendations	: This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.
Additional information	: Handle empty containers with care because residual vapors are flammable.
SECTION 14: Transport information	
In accordance with DOT	
14.1. UN number	
UN-No.	: 3295
14.2. UN proper shipping name	
Proper Shipping Name	: Hydrocarbons, liquid, n.o.s. (Xylene, Ethylbenzene, Toluene)
Department of Transportation Hazard Classes	: 3
Hazard labels	
Packing group	: 11
14.3. Additional information	
Other information	: No supplementary information available.
Special transport precautions	: Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Xylenes (o-, m-, p- isomers) (1330-20-7)		
Listed on SARA Section 313 (Specific toxic chemical listings)		
SARA Section 313 - Emission Reporting	1.0 %	
Ethylbenzene (100-41-4)		
Listed on SARA Section 313 (Specific toxic chemical listings)		
SARA Section 313 - Emission Reporting 0.1 %		
Toluene (108-88-3)		
Listed on SARA Section 313 (Specific toxic chemical listings)		
SARA Section 313 - Emission Reporting 1.0 %		
Cumene (98-82-8)		
Listed on SARA Section 313 (Specific toxic chemical listings)		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.	
SARA Section 313 - Emission Reporting	1.0 %	




Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Benzene (71-43-2)		
Listed on SARA Section 313 (Specific toxic chemical listings)		
SARA Section 313 - Emission Reporting 0.1 %		
Nanhthalono (01-20-2)		
Naphthalene (91-20-3)		
Listed on SARA Section 313 (Specific toxic chemical list		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.	
SARA Section 313 - Emission Reporting	0.1 %	
Furan (110-00-9)		
Listed on SARA Section 302 (Specific toxic chemical listings) Listed on SARA Section 313 (Specific toxic chemical listings)		
SARA Section 302 Threshold Planning Quantity (TPQ) 500		
SARA Section 313 - Emission Reporting	0.1 %	
Propylene oxide (75-56-9)		
Listed on SARA Section 302 (Specific toxic chemical listings) Listed on SARA Section 313 (Specific toxic chemical listings)		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.	
SARA Section 302 Threshold Planning Quantity (TPQ)	10000	
SARA Section 313 - Emission Reporting 0.1 %		
Acetaldehyde (75-07-0)		
Listed on SARA Section 313 (Specific toxic chemical listings)		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.	
SARA Section 313 - Emission Reporting	0.1 %	

15.2. US State regulations

2312	
State or local regulations	This product contains chemicals known to the State of California to cause cancer, birth
	defects or other reproductive harm.

SECTION 16: Other information		
Indication of changes	:	None.
Date of issue	:	07/24/2014
Other information	:	None.
NFPA health hazard NFPA fire hazard NFPA reactivity	::	2 3 0



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product





Date of issue: 04/30/2014 Revision date: 04/30/2014 Version: 1.0

Date	of issue. 04/30/2014 Revision date. 04/30/2014 Version: 1.0
SECTION 1: Identification of the s	ubstance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	: PENRAY F.I. AIR INTAKE CLEANER
Product code	: 2412
1.2. Relevant identified uses of the su	ubstance or mixture and uses advised against
Use of the substance/mixture	: Fuel system cleaner.
1.3. Details of the supplier of the safe	ety data sheet
The Penray Companies, Inc. 440 Denniston Ct. 60090 Wheeling, IL T (800) 373-6729 rotto@penray.com	
1.4. Emergency telephone number	
Emergency number	: (800) 373-6729 CHEMTREC (800) 424-9300 CHEMTREC International +1 (703) 527-3887 24 hr
SECTION 2: Hazards identification	n
2.1. Classification of the substance of	r mixture
GHS-US classification	
Flammable Liquid 3 Skin irritation 2 Serious eye damage 1 Carcinogenicity 2 Specific target organ toxicity - Single exposur Aspiration hazard 1	re 3
2.2. Label elements	
GHS-US labelling	
Hazard pictograms (GHS-US)	HS02 HS02 HS05 HS07 HS08
Signal word (GHS-US) Hazard statements (GHS-US)	: Danger : Flammable liquid and vapor. Causes skin irritation. Causes serious eye damage. May cause
Tiazard statements (GFIS-05)	drowsiness or dizziness. May be fatal if swallowed and enters airways.
Precautionary statements (GHS-US)	: Keep away from heat/sparks/open flames/hot surfaces.– No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection. Wash hands thoroughly after handling. Avoid breathing gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. If on skin (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor. Do NOT induce vomiting. Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.
2.3. Other hazards	
No additional information available	
SECTION 3: Composition/informa	tion on ingredients
3.1. Substance	
Not applicable	



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Name	Product identifier	%	GHS-US classification
Kerosene, petroleum	(CAS No) 8008-20-6	30 - 60	Flam. Liq. 3 Skin Irrit. 2 STOT SE 3 Asp. Tox. 1
Isopropyl alcohol	(CAS No) 67-63-0	15 - 40	Flam. Liq. 2 Eye Irrit. 2A STOT SE 3
Solvent naphtha, petroleum, light aromatic	(CAS No) 64742-95-6	7 - 13	Asp. Tox. 1
Alkylphenol polyoxyalkyl alkylamine	Proprietary	7 - 13	Eye Dam. 1
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	1 - 5	Flam. Liq. 3 Acute Tox. 4 (Dermal, Inhalation) Skin Irrit. 2
Benzene, 1,2,4-trimethyl-	(CAS No) 95-63-6	1 - 5	Flam. Liq. 3 Acute Tox. 4 (Inhalation) Skin Irrit. 2 Eye Irrit. 2A STOT SE 3
1,3,5-Trimethylbenzene	(CAS No) 108-67-8	1 - 5	Flam. Liq. 3 Skin Irrit. 2 Eye Irrit. 2A STOT SE 3 Asp. Tox. 1
n-Propylbenzene	(CAS No) 103-65-1	1 - 5	Flam. Liq. 3 STOT SE 3 Asp. Tox. 1
Cumene	(CAS No) 98-82-8	0.1 - 1	Flam. Liq. 3 Acute Tox. 4 (Oral) Carc. 2
Naphthalene	(CAS No) 91-20-3	0.1 - 1	Acute Tox. 4 (Oral, Dermal) Carc. 2

SECTION 4: First aid measures Description of first aid measures 4.1. First-aid measures after inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell. In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing First-aid measures after skin contact and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists. First-aid measures after eye contact In case of contact, immediately flush eves with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately. First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention. Most important symptoms and effects, both acute and delayed 42 Symptoms/injuries after inhalation May cause drowsiness, dizziness and central nervous system depression. May cause respiratory tract irritation. Symptoms/injuries after skin contact Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. Symptoms/injuries after eye contact Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns. Symptoms/injuries after ingestion May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECT	ION 5: Firefighting measures	
5.1.	Extinguishing media	
Suitable	e extinguishing media	: Powder, water spray, foam, carbon dioxide.
Unsuita	ble extinguishing media	: Do not use a heavy water stream.
5.2.	Special hazards arising from the s	ubstance or mixture
Fire ha	zard	: Products of combustion may include, and are not limited to: oxides of carbon.
5.3.	Advice for firefighters	
Protect	ion during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 6: Accidenta		· · · ·	
		oment and emergency procedures	
General measures		• • • •	ed in Section 8. Isolate the hazard area and deny entry to anel. Eliminate sources of ignition.
6.2. Methods and mate	erial for containment	and cleaning up	
For containment	:		material (e.g. sand, vermiculite), then place in a suitable low to enter waterways. Use appropriate Personal
Methods for cleaning up	:	Scoop up material and place in a disp	posal container. Provide ventilation.
6.3. Reference to other	r sections		
See section 8 for further inform	mation on protective of	clothing and equipment and section 13	for advice on waste disposal.
SECTION 7: Handling	and storage		
7.1. Precautions for sa	fe handling		
Precautions for safe handling	:	breathing gas/mist/vapors/spray. Do	No smoking. Avoid contact with skin and eyes. Avoid not swallow. Handle and open container with care. Use onl ot eat, drink or smoke. Use only outdoors or in a well-
Hygiene measures	:	Launder contaminated clothing before	e reuse. Wash hands before eating, drinking, or smoking.
		any incompatibilities	
Storage conditions	:	Keep out of the reach of children. Ke Store locked up. Keep cool. Keep aw	ep container tightly closed and in a well-ventilated place. ay from heat, sparks, and flame.
7.3. Specific end use(s	;)		
Not available.			
SECTION 8: Exposure	controls/persor	nal protection	
8.1. Control parameter	S		
Kerosene, petroleum (8008	8-20-6)		
USA ACGIH	ACGIH TWA (mg	/m³)	200 mg/m ³
Isopropyl alcohol (67-63-0))		•
USA ACGIH	ACGIH TWA (pp	m)	200 ppm
USA ACGIH	ACGIH STEL (pp	m)	400 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
USA OSHA	OSHA PEL (TWA	(ppm)	400 ppm
Solvent naphtha, petroleur		1742-95-6)	Netenslieble
	ACGIH TWA	<u> </u>	Not applicable.
USA OSHA	OSHA PEL (TWA	()	Not applicable.
Alkylphenol polyoxyalkyl a	alkylamine (Propriet	ary)	
USA ACGIH	ACGIH TWA		Not applicable.
USA OSHA	OSHA PEL (TWA	A)	Not applicable.
Xylenes (o-, m-, p- isomers	s) (1330-20-7)		
USA ACGIH	ACGIH TWA (pp	m)	100 ppm
USA ACGIH	ACGIH STEL (pp	m)	150 ppm
USA OSHA	OSHA PEL (TWA	A) (mg/m³)	435 mg/m ³
USA OSHA	OSHA PEL (TWA	A) (ppm)	100 ppm
Benzene, 1,2,4-trimethyl- (95-63-6)		•
USA ACGIH	ACGIH TWA (pp	m)	25 ppm
			I
1,3,5-Trimethylbenzene (10			
USA ACGIH	ACGIH TWA	<u>\</u>	Not applicable.
USA OSHA	OSHA PEL (TWA	A)	Not applicable.



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

n-Propylbenzene (103-65-1)			
USA ACGIH	ACGIH TWA	Not applicable.	
USA OSHA	OSHA PEL (TWA)	Not applicable.	
Cumene (98-82-8)			
USA ACGIH	ACGIH TWA (ppm)	50 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m ³)	245 mg/m ³	
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm	
Naphthalene (91-20-3)			
USA ACGIH	ACGIH TWA (ppm)	10 ppm	
USA ACGIH	ACGIH STEL (ppm)	15 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m³)	50 mg/m ³	
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm	
8.2. Exposure controls			

Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear chemically resistant protective gloves.
Eye protection	: Wear approved eye (properly fitted dust- or splash-proof chemical safety goggles) / face (face shield) protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: A NIOSH approved respirator is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Ph	ysical and chemical properties

9.1. Information on basic physical	and chemical properties
Physical state	: Liquid.
Appearance	: Clear.
Colour	: No data available.
Odour	: Petroleum odor.
Odour threshold	: No data available.
рН	: No data available.
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: No data available.
Flash point	: ~26 °C (~78 °F)
Self ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: Flammable.
Vapour pressure	: No data available.
Relative vapour density at 20 °C	: No data available.
Relative density	: 0.811 - 0.823
Solubility	: No data available.
Log Pow	: No data available.
Log Kow	: No data available.
Viscosity, kinematic	: No data available.
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

	· · · · · · · · · · · · · · · · · · ·			
9.2. Other information				
No additional information available				
SECTION 10: Stability and reactivity				
10.1. Reactivity				
-	normal usa			
No dangerous reaction known under conditions of	normal use.			
10.2. Chemical stability				
Stable under normal storage conditions. May form	flammable/explosive vapour-air mixture.			
10.3. Possibility of hazardous reactions				
No dangerous reaction known under conditions of	normal use.			
10.4. Conditions to avoid				
Heat. Incompatible materials. Open flame.				
10.5. Incompatible materials				
Strong oxidizing agents.				
10.6. Hazardous decomposition products				
May include, and are not limited to: oxides of carbo	on.			
SECTION 11: Toxicological informatic	n			
11.1. Information on toxicological effects				
Acute toxicity	: Not classified			
2412				
LD50 oral rat	> 2000 mg/kg			
LD50 dermal rat	> 2000 mg/kg			
LC50 inhalation rat (mg/l)	> 20 mg/l/4h			
Kerosene, petroleum (8008-20-6)				
LD50 oral rat	> 5000 mg/kg			
LD50 dermal rabbit	> 2000 mg/kg			
LC50 inhalation rat (mg/l)	> 5.28 mg/l/4h			
Isopropyl alcohol (67-63-0)				
LD50 oral rat	4396 mg/kg			
LD50 dermal rat	12800 mg/kg			
LD50 dermal rabbit	12870 mg/kg			
LC50 inhalation rat (mg/l)	72.6 mg/l/4h			
Solvent naphtha, petroleum, light aromatic (6	4742-95-6)			
LD50 oral rat	8400 mg/kg			
LD50 dermal rabbit	> 2000 mg/kg			
LC50 inhalation rat (ppm)	3400 ppm/4h			
LC50 inhalation rat (mg/l)	> 5.2 mg/l/4h			
Vidence (c. m. m. isomere) (4220-20-7)	-			
Xylenes (o-, m-, p- isomers) (1330-20-7)	4200 malka			
LD50 oral rat LD50 dermal rabbit	4300 mg/kg			
	> 1700 mg/kg 5000 ppm/4h			
LC50 inhalation rat (ppm) LC50 inhalation rat (mg/l)	47635 mg/l/4h			
	47000 mg//40			
Benzene, 1,2,4-trimethyl- (95-63-6)				
LD50 oral rat	3400 mg/kg			
LD50 dermal rabbit	> 3160 mg/kg			
LC50 inhalation rat (mg/l)	18 g/m³/4h			
1,3,5-Trimethylbenzene (108-67-8)				
LC50 inhalation rat (mg/l)	24 g/m³/4 h			
n-Propylbenzene (103-65-1)				
LD50 oral rat	6040 mg/kg			
LC50 inhalation rat (ppm)	65000 ppm/2h			
Cumene (98-82-8)				
LD50 oral rat	1400 mg/kg			
LD50 dermal rabbit	> 3160 mg/kg			
LC50 inhalation rat (mg/m ³)	39000 mg/m ³ /4 h			
	·			



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Naphthalene (91-20-3)	
LD50 oral rat	490 mg/kg
LD50 dermal rabbit	> 20 g/kg
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Suspected of causing cancer.

Isopropyl alcohol (67-63-0)			
IARC group	3		
Xylenes (o-, m-, p- isomers) (1330-20-7)			
IARC group	3		
Cumene (98-82-8)			
IARC group	2B		
National Toxicity Program (NTP) Status	1		
Naphthalene (91-20-3)			
IARC group	2B		
National Toxicity Program (NTP) Status	1, 3		
Reproductive toxicity	: Based on available data, the classification criteria are not met.		
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.		
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.		
Aspiration hazard	: May be fatal if swallowed and enters airways.		
Symptoms/injuries after inhalation	: May cause drowsiness, dizziness and central nervous system depression. May cause respiratory tract irritation.		
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.		
Symptoms/injuries after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.		
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.		

SECTION 12: Ecological information

12.1.	Toxicity	
Ecology	- general :	May cause long-term adverse effects in the aquatic environment.
12.2.	Persistence and degradability	
2412		
Persist	ence and degradability	Not established.
12.3.	Bioaccumulative potential	
2412		
Bioacci	umulative potential	Not established.
12.4.	Mobility in soil	
No additi	onal information available	
12.5.	Other adverse effects	
No additi	onal information available	
SECTI	ON 13: Disposal considerations	
13.1.	Waste treatment methods	
Waste di	sposal recommendations :	This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.
Additiona	al information :	Handle empty containers with care because residual vapours are flammable.
SECTI	ON 14: Transport information	
In accord	ance with DOT	
14.1.	UN number	

14.1.	UN HUITIBEI	
UN-No.		

: UN1993



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.


14.0 LIN proper chipping neme	
14.2. UN proper shipping name Proper Shipping Name	: Flammable liquids, n.o.s. (Petroleum, Isopropanol)
Department of Transportation Hazard Classes	
Hazard labels	
	3
Packing group (DOT)	: 111
14.3. Additional information	
Other information	: No supplementary information available.
Special transport precautions	: Do not handle until all safety precautions have been read and understood.
SECTION 15: Regulatory information	
15.1. US Federal regulations	
Karasana natralaum (2002 20 6)	
Kerosene, petroleum (8008-20-6) Listed on the United States TSCA (Toxic Subst	ances Central Act) inventory
Isopropyl alcohol (67-63-0)	
Listed on the United States TSCA (Toxic Subst Listed on SARA Section 313 (Specific toxic che	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 %
Solvent naphtha, petroleum, light aromatic (64742-95-6)
Listed on the United States TSCA (Toxic Subst	
Xylenes (o-, m-, p- isomers) (1330-20-7)	
Listed on the United States TSCA (Toxic Subst	ances Control Act) inventory
Listed on SARA Section 313 (Specific toxic che	
SARA Section 313 - Emission Reporting	1.0 %
Benzene, 1,2,4-trimethyl- (95-63-6)	
Listed on the United States TSCA (Toxic Subst	ances Control Act) inventory
Listed on SARA Section 313 (Specific toxic che	mical listings)
SARA Section 313 - Emission Reporting	1.0 %
1,3,5-Trimethylbenzene (108-67-8)	
Listed on the United States TSCA (Toxic Subst	ances Control Act) inventory
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
n-Propylbenzene (103-65-1)	
Listed on the United States TSCA (Toxic Subst	ances Control Act) inventory
Cumene (98-82-8)	
Listed on the United States TSCA (Toxic Subst Listed on SARA Section 313 (Specific toxic che	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 %
Naphthalene (91-20-3)	
Listed on the United States TSCA (Toxic Subst Listed on SARA Section 313 (Specific toxic che	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	0.1 %
15.2. US State regulations	
2412	
State or local regulations	This product contains chemicals known to the State of California to cause cancer.



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:		
IARC	International Agency for Research on Cancer.	
	 Carcinogenic to humans; Probably carcinogenic to humans; Possibly carcinogenic to humans; Not classifiable; Probably not carcinogenic to humans. 	
NTP	National Toxicology Program.	
	 Evidence of Carcinogenicity; Known Human Carcinogens; Reasonably anticipated to be Human Carcinogen; Substances delisted from report on Carcinogens; Twelfth Report - Items under consideration. 	

SECTION 16: Other information				
Indication of changes	:	None.		
Date of issue	:	04/30/2014		
Other information	:	None.		
NFPA health hazard NFPA fire hazard NFPA reactivity	:	3 2 0		



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

