NITE()	Page: 1
SAFETY DATA SHEET	Revision Date: 11/25/2015
	Print Date: 4/11/2016
	SDS Number: 000000264892
Pyroil™ FUEL INJECTOR & CARBURETOR CLEANER	Version: 1.0
PYAFI12P	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Pyroil™ FUEL INJECTOR & CARBURETOR

CLEANER

Relevant identified uses of the substance or mixture and uses advised against

Details of the supplier of the safety data sheet	Emergency telephone number CHEMTREC DIRECT 1-800-424-9300
Niteo Products, LLC P.O. Box 191629 Dallas TX 75219 United States of America	Product Information 1-844-696-4836

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Skin irritation : Category 2

Specific target organ systemic toxicity - single

exposure

: Category 3 (Central nervous system)

Aspiration hazard : Category 1

GHS Label element

Hazard pictograms :







Signal Word : Danger

Hazard Statements : Flammable liquid and vapor.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause drowsiness or dizziness.

Precautionary Statements : Prevention:

Keep away from heat/sparks/open flames/hot surfaces. No

NITE()	Page: 2
SAFETY DATA SHEET	Revision Date: 11/25/2015
	Print Date: 4/11/2016
	SDS Number: 000000264892
Pyroil™ FUEL INJECTOR & CARBURETOR CLEANER	Version: 1.0
PYAFI12P	

smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/ attention.

Take off contaminated clothing and wash before reuse.

In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
KEROSENE	8008-20-6	Flam. Liq. 3; H226	97.22
		Skin Irrit. 2; H315	
		CTOT CE 2. H226	
		STOT SE 3; H336	
		Asp. Tox. 1; H304	

NITEC)	Page: 3
SAFETY DATA SHEET	Revision Date: 11/25/2015
	Print Date: 4/11/2016
	SDS Number: 000000264892
Pyroil™ FUEL INJECTOR & CARBURETOR CLEANER	Version: 1.0
PYAFI12P	

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Call a POISON CENTRE or doctor/physician if exposed or

you feel unwell.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : Move to fresh air.

If unconscious place in recovery position and seek medical

advice.

Consult a physician after significant exposure.

In case of skin contact : Remove contaminated clothing. If irritation develops, get

medical attention.

If on skin, rinse well with water.

Wash contaminated clothing before re-use.

If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Obtain medical attention.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this

material.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Lung irritation confusion

irregular heartbeat Convulsions

May be fatal if swallowed and enters airways.

NITE()	Page: 4
SAFETY DATA SHEET	Revision Date: 11/25/2015
	Print Date: 4/11/2016
	SDS Number: 000000264892
Pyroil™ FUEL INJECTOR & CARBURETOR CLEANER	Version: 1.0
PYAFI12P	

Causes skin irritation.

May cause drowsiness or dizziness.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Never use welding or cutting torch on or near drum (even

empty) because product (even just residue) can ignite

explosively.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Aldehydes

carbon dioxide and carbon monoxide

Hydrocarbons

Nitrogen oxides (NOx)

sulfur oxides

Specific extinguishing

methods

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

> be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and : Evacuate personnel to safe areas. Remove all sources of ignition.

NITE()	Page: 5
SAFETY DATA SHEET	Revision Date: 11/25/2015
	Print Date: 4/11/2016
	SDS Number: 000000264892
Pyroil™ FUEL INJECTOR & CARBURETOR CLEANER	Version: 1.0
PYAFI12P	

Ensure adequate ventilation.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

Other information : Comply with all applicable federal, state, and local regulations.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Open drum carefully as content may be under pressure.

Avoid formation of aerosol.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Container hazardous when empty.

Take precautionary measures against static discharges. Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

: Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

No smoking.

NITE()	Page: 6
SAFETY DATA SHEET	Revision Date: 11/25/2015
	Print Date: 4/11/2016
	SDS Number: 000000264892
Pyroil™ FUEL INJECTOR & CARBURETOR CLEANER	Version: 1.0
PYAFI12P	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
KEROSENE	8008-20-6	TWA	200 mg/m3 Non-aerosol (as total hydrocarbon vapor)	ACGIH
		SKIN_DES		ACGIH
				ACGIH
		REL	100 mg/m3	NIOSH/GUID E

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection

In the case of vapour formation use a respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by airpurifying respirators is limited. Use a positive pressure, airsupplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection

Remarks The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Not required under normal conditions of use. Wear splash-Eye protection

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection Wear as appropriate:

Impervious clothing

Safety shoes

Flame-resistant clothing

NITE()	Page: 7
SAFETY DATA SHEET	Revision Date: 11/25/2015
	Print Date: 4/11/2016
	SDS Number: 000000264892
Pyroil™ FUEL INJECTOR & CARBURETOR CLEANER	Version: 1.0
PYAFI12P	

Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear. Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not eat or drink. When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 680 °F / 360 °C

Calculated Phase Transition Liquid/Gas

Flash point : 120.00 °F / 48.89 °C

Calculated Flash Point

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 10 hPa (37.8 °C)

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : No data available

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

NITEC PRODUCTS	Page: 8
SAFETY DATA SHEET	Revision Date: 11/25/2015
	Print Date: 4/11/2016
	SDS Number: 000000264892
Pyroil™ FUEL INJECTOR & CARBURETOR CLEANER	Version: 1.0
PYAFI12P	

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

Conditions to avoid : excessive heat

Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

carbon dioxide and carbon monoxide

Hydrocarbons

Nitrogen oxides (NOx)

Sulphur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure

Inhalation Skin contact

Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Components: KEROSENE:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 420

Acute inhalation toxicity : LC 50 (Rat): > 5.28 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

NITEC PRODUCTS	Page: 9
SAFETY DATA SHEET	Revision Date: 11/25/2015
	Print Date: 4/11/2016
	SDS Number: 000000264892
Pyroil™ FUEL INJECTOR & CARBURETOR CLEANER	Version: 1.0
PYAFI12P	

Assessment: Not classified as acutely toxic by inhalation

under GHS.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Skin corrosion/irritation

Causes skin irritation.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation and/or dermatitis.

Components:

KEROSENE:

Result: Irritating to skin.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

KEROSENE:

Result: Slightly irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

KEROSENE:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

KEROSENE:

May be fatal if swallowed and enters airways.

NITEO PRODUCTS	Page: 10
SAFETY DATA SHEET	Revision Date: 11/25/2015
	Print Date: 4/11/2016
	SDS Number: 000000264892
Pyroil™ FUEL INJECTOR & CARBURETOR CLEANER	Version: 1.0
PYAFI12P	

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components: KEROSENE:

Remarks: Skin

Remarks: Central nervous system

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 2; Toxic to aquatic life.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 2; Toxic to aquatic life with

long lasting effects.

Components:

KEROSENE:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l

Exposure time: 96 h Test Type: semi-static test Test substance: WAF

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Water flea (Daphnia magna)): 1.4 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

NITEC PRODUCTS	Page: 11
SAFETY DATA SHEET	Revision Date: 11/25/2015
	Print Date: 4/11/2016
	SDS Number: 000000264892
Pyroil™ FUEL INJECTOR & CARBURETOR CLEANER	Version: 1.0
PYAFI12P	

Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): 1 - 3

mg/l

Exposure time: 72 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 201

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

(Water flea (Daphnia magna)): 0.89 mg/l

Exposure time: 21 d

End point: Reproduction Test Test Type: semi-static test Test substance: WAF

Method: OECD Test Guideline 211

Persistence and degradability

Components:

KEROSENE:

Biodegradability : Biodegradation: 58.6 %

Exposure time: 28 d

Method: OECD Test Guideline 301F

Bioaccumulative potential

Components:

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with

long lasting effects.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

NITE COLUMN TERMINATION OF THE PROPERTY OF THE	Page: 12
SAFETY DATA SHEET	Revision Date: 11/25/2015
	Print Date: 4/11/2016
	SDS Number: 000000264892
Pyroil™ FUEL INJECTOR & CARBURETOR CLEANER	Version: 1.0
PYAFI12P	

Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT /
		02,100	11712711120	OKOO!	LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods	

U.S. DOT - RAIL

Not dangerous goods	

U.S. DOT - INLAND WATERWAYS

Not dangerous goods	

TRANSPORT CANADA - ROAD

Not dangerous goods	

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

UN	1993	FLAMMABLE LIQUID, N.O.S.	3	III	MARINE
		(KEROSENE)			POLLUTANT:(
					KEROSENE)LÌ
					MITED
					QUANTITY

NITE()	Page: 13
SAFETY DATA SHEET	Revision Date: 11/25/2015
	Print Date: 4/11/2016
	SDS Number: 000000264892
Pyroil™ FUEL INJECTOR & CARBURETOR CLEANER	Version: 1.0
PYAFI12P	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

UN	1993	Flammable liquid, n.o.s.	3	III
		(KEROSENE)		
		·		

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

UN	1993	Flammable liquid, n.o.s.	3	III
		(KEROSENE)		

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

UN	1993	LIQUIDO INFLAMABLE, N.E.P. (KEROSENE)	3	III

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	yes

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
NAPHTHALENE	91-20-3	100	214132.762313

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard

SARA 313

Component(s)SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65 Proposition 65 warnings are not required for this product

based on the results of a risk assessment.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

NITE()	Page: 14
SAFETY DATA SHEET	Revision Date: 11/25/2015
	Print Date: 4/11/2016
	SDS Number: 000000264892
Pyroil™ FUEL INJECTOR & CARBURETOR CLEANER	Version: 1.0
PYAFI12P	

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI: On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 11/25/2015



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class II

Full text of H-Statements

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

NITE()	Page: 15
SAFETY DATA SHEET	Revision Date: 11/25/2015
	Print Date: 4/11/2016
	SDS Number: 000000264892
Pyroil™ FUEL INJECTOR & CARBURETOR CLEANER	Version: 1.0
PYAFI12P	

Sources of key data used to compile the Safety Data Sheet

Internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

Cefic, the European Chemical Industry Council.

ESIS European Chemical Substances Information System

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Niteo's Environmental Health and Safety Department (1-844-696-4836).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement: Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

NITE()	Page: 16
SAFETY DATA SHEET	Revision Date: 11/25/2015
	Print Date: 4/11/2016
	SDS Number: 000000264892
Pyroil™ FUEL INJECTOR & CARBURETOR CLEANER	Version: 1.0
PYAFI12P	

HMIS : Hazardous Materials Identification System NFPA : National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System