

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 001
Date Prepared: 10/29/97
Date Printed: 03/13/99
MSDS No: 503.0328421-C01.001

PYROIL TBC-13B THROT BOD BONUS 12-15.6

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: PYROIL TBC-13B THROT BOD BONUS 12-15.6

Product Code: 80250023

General or Generic ID: CARBURETOR CLEANER

Company

The Valvoline Company
P.O. Box 14000
Lexington, KY 40512

Telephone Numbers

Emergency: 1-800-274-5263

Information: 1-606-357-7847

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
XYLENE	1330-20-7	45.0- 45.0
METHYL ALCOHOL	67-56-1	30.0- 30.0
ACETONE	67-64-1	17.0- 27.0
CARBON DIOXIDE	124-38-9	1.0- 8.0
ETHYLBENZENE	100-41-4	9.0- 9.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Additional symptoms of eye exposure may include: blurred vision

Skin

May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage.

Inhalation

Breathing of vapor or mist is possible.

Symptoms of Exposure

stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), and death.

Target Organ Effects

Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals, and may aggravate pre-existing disorders of these organs in humans: liver abnormalities, anemia, spleen damage, nervous system damage, eye damage, kidney damage, lung damage, brain damage. Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans, and may aggravate pre-existing disorders of these organs: liver abnormalities, eye damage

Continued On Next Page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 002
Date Prepared: 10/29/97
Date Printed: 03/13/99
MSDS No: 503.0328421-001.001

PYROIL TBC-13B THROT BOD BONUS 12-15.6

Developmental Information

No data

Cancer Information

No data

Other Health Effects

No data

Primary Route(s) of Entry

Inhalation, Skin absorption, Skin contact.

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing

Call a physician or poison control center immediately for instructions. This material contains both methanol and petroleum distillates. Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis which can be fatal.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Note to Physicians

This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis.

5. FIRE FIGHTING MEASURES

Flash Point

No data

Continued On Next Page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 003
Date Prepared: 10/29/97
Date Printed: 05/13/99
MSDS No: 503.0328421-001.001

PYROIL TBC-13B THROT BOD BONUS 12-15.6

Explosive Limit

(for component) Lower 1.0 Upper 36.0 %

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Fire and Explosion Hazards

Material is highly volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Extinguishing Media

regular foam, carbon dioxide, dry chemical.

Fire Fighting Instructions

Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Health - 3, Flammability - 4, Reactivity - 0

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

Large Spill

Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal. Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. All five gallon pails and larger metal containers including tank cars and tank trucks should be grounded and/or bonded when material is transferred.

Continued On Next Page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 004

Date Prepared: 10/29/97

Date Printed: 03/13/99

MSDS No: 503.0328421-001.001

PYROIL TBC-13B THROT BOD BONUS 12-15.6

Storage

Not applicable

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin Protection

Other protective equipment: not required under normal conditions of use. Wear resistant gloves such as: neoprene.

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Component

XYLENE (1330-20-7)

OSHA VPEL 100.000 ppm - TWA
OSHA VPEL 150.000 ppm - STEL
ACGIH TLV 100.000 ppm - TWA
ACGIH TLV 150.000 ppm - STEL

METHYL ALCOHOL (67-56-1)

OSHA VPEL 200.000 ppm - TWA ((Skin))
OSHA VPEL 250.000 ppm - STEL ((Skin))
ACGIH TLV 200.000 ppm - TWA ((Skin))
ACGIH TLV 250.000 ppm - STEL ((Skin))

ACETONE (67-64-1)

OSHA VPEL 750.000 ppm - TWA
OSHA VPEL 1000.000 ppm - STEL
ACGIH TLV 750.000 ppm - TWA
ACGIH TLV 1000.000 ppm - STEL

CARBON DIOXIDE (124-38-9)

OSHA VPEL 10000.000 ppm - TWA
OSHA VPEL 30000.000 ppm - STEL
ACGIH TLV 5000.000 ppm - TWA
ACGIH TLV 30000.000 ppm - STEL

ETHYLBENZENE (100-41-4)

OSHA VPEL 100.000 ppm - TWA
OSHA VPEL 125.000 ppm - STEL
ACGIH TLV 100.000 ppm - TWA
ACGIH TLV 125.000 ppm - STEL

Continued On Next Page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 005
Date Prepared: 10/29/97
Date Printed: 03/13/99
MSDS No: 503.0328421-001.001

PYROIL TBC-13B THROT BOD BONUS 12-15.6

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point
(for component) 133.0 F (56.1 C) @ 760 mmHg

Vapor Pressure
(for component) 135.000 mmHg @ 68.00 F

Specific Vapor Density
No data

Specific Gravity
.827 @ 77.00 F

Liquid Density
6.890 lbs/gal @ 77.00 F
.827 kg/l @ 25.00 C

Percent Volatiles (Including Water)
No data

Volatile Organic Compounds (VOC) (Maximum)
75.000 %

Evaporation Rate
No data

Appearance
No data

State
LIQUID

Physical Form
No data

Color
CLEAR

Odor
SOLVENT

pH
No data

Flame Propagation
> 18.000 IN

10. STABILITY AND REACTIVITY

Hazardous Polymerization
Product will not undergo hazardous polymerization.

Continued On Next Page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 006
Date Prepared: 10/29/97
Date Printed: 03/13/99
MSDS No: 503.0328421-001.001

PYROIL TBC-13B THROT BOD BONUS 12-15.6

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Chemical Stability

Stable. Avoid heat, open flame, and prolonged storage at elevated temperatures.

Incompatibility

Avoid contact with: strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:
CONSUMER COMMODITY, ORM-D

Container/Mode:
CASES/SURFACE - ORM-D EXCEPTION

NOS Component:
METHYL ALCOHOL
ACETONE

RQ (Reportable Quantity) - 49 CFR 172.101

Product Quantity (lbs) Component

222	XYLENES (O-, M-, P- ISOMERS)
11696	ETHYLBENZENE
16682	METHANOL
22708	ACETONE

15. REGULATORY INFORMATION

US Federal Regulations

TSCA (Toxic Substances Control Act) Status

TSCA (UNITED STATES) The intentional ingredients of this product are listed.

Continued On Next Page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 007
Date Prepared: 10/23/97
Date Printed: 03/13/99
MSDS No: 503.0328421-001.001

PYROIL TBC-13B THROT BOD BONUS 12-15.6

CERCLA RQ - 40 CFR 302.4

Component	Component
XYLENES (O-, M-, P- ISOMERS)	100
METHYL ALCOHOL	5000
ACETONE	5000
ETHYLBENZENE	1000

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate(X) Delayed(X) Fire(X) Reactive() Sudden Release of Pressure()

SARA 313 Components - 40 CFR 372.65

Section 313 Component(s)	CAS Number	Max %
XYLENE (MIXED ISOMERS)	1330-20-7	45.00
METHANOL	67-56-1	29.97
ETHYLBENZENE	100-41-4	9.00

International Regulations

Inventory Status

Not determined

State and Local Regulations

California Proposition 65

None

New Jersey RTK Label Information

XYLENES	1330-20-7
METHYL ALCOHOL	67-56-1
ACETONE	67-64-1
CARBON DIOXIDE	124-38-9
ETHYL BENZENE	100-41-4

Pennsylvania RTK Label Information

BENZENE, DIMETHYL-	1330-20-7
METHANOL	67-56-1
2-PROPANONE	67-64-1
CARBON DIOXIDE	124-38-9
BENZENE, ETHYL-	100-41-4

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.