		Page: 1
SAFETY DATA SHEET		Revision Date: 09/07/2018
		Print Date: 10/29/2018
		SDS Number: R0076417
Valvoline™ General Purpose Amber Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV609		Version: 1.3

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ General Purpose Amber Grease
™ Trademark, Valvoline or its subsidiaries, registered in various countries


Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-832-6825) SDS@valvoline.com	Emergency telephone number 1-800-VALVOLINE (1-800-825-8654) Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825) Product Information 1-800-TEAMVAL (1-800-832-6825)
---	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin irritation : Category 2
Eye irritation : Category 2A
Specific target organ systemic toxicity - single exposure : Category 3 (Respiratory system)

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.

SAFETY DATA SHEET

Revision Date: 09/07/2018

Print Date: 10/29/2018

SDS Number: R0076417

Valvoline™ General Purpose Amber Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 VV609

Version: 1.3

Precautionary Statements

: **Prevention:**

Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
 Wash skin thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/ eye protection/ face protection.

Response:

IF ON SKIN: Wash with plenty of soap and water.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If skin irritation occurs: Get medical advice/ attention.
 If eye irritation persists: Get medical advice/ attention.
 Take off contaminated clothing and wash before reuse.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity:
 9.9999 %

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (<3 % DMSO EXTRACT)	64742-65-0	Not a hazardous substance or mixture.	>=80.00 - < 90.00
ASPHALTIC RESIN		Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT SE 3; H335	>=20.00 - < 30.00
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT	64742-52-5	This material is not considered hazardous under the OSHA	>=5.00 - < 10.00



SAFETY DATA SHEET

Revision Date: 09/07/2018

Print Date: 10/29/2018

SDS Number: R0076417

Version: 1.3

Valvoline™ General Purpose Amber Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 VV609

		Hazard Communication Standard (HazCom 2012).	
--	--	--	--

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
 Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.
- If inhaled : Move to fresh air.
 If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
 If on skin, rinse well with water.
 Wash contaminated clothing before re-use.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
 Remove contact lenses.
 Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
 Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
 acne

**SAFETY DATA SHEET**

Revision Date: 09/07/2018

Print Date: 10/29/2018

SDS Number: R0076417

Version: 1.3

Valvoline™ General Purpose Amber Grease
™ Trademark, Valvoline or its subsidiaries, registered in various countries
VV609

stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
Aldehydes
Ketones
Nitrogen oxides (NO_x)
Sulphur oxides

Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

SAFETY DATA SHEET

Revision Date: 09/07/2018

Print Date: 10/29/2018

SDS Number: R0076417

Version: 1.3

Valvoline™ General Purpose Amber Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 VV609

- Environmental precautions : Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (<3 % DMSO EXTRACT)	64742-65-0	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3	NIOSH REL

SAFETY DATA SHEET

Revision Date: 09/07/2018

Print Date: 10/29/2018

SDS Number: R0076417

Version: 1.3

Valvoline™ General Purpose Amber Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 VV609

			Mist	
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT	64742-52-5	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection
 Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear as appropriate:
 Impervious clothing
 Safety shoes
 Choose body protection according to the amount and

**SAFETY DATA SHEET**

Revision Date: 09/07/2018

Print Date: 10/29/2018

SDS Number: R0076417

Version: 1.3

Valvoline™ General Purpose Amber Grease
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
VV609

concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
Wear resistant gloves (consult your safety equipment
supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Physical state : liquid

Colour : amber

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 698 °F / 370 °C

Flash point : 491 °F / 255 °C

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : Not applicable

Relative density :
No data available

Density : 0.902 g/cm³ (20 °C)

Solubility(ies)
Water solubility : negligible

Solubility in other solvents : No data available

**SAFETY DATA SHEET**

Revision Date: 09/07/2018

Print Date: 10/29/2018

SDS Number: R0076417

Version: 1.3

Valvoline™ General Purpose Amber Grease
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
VV609

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : > 315 °C

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm²/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide
Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate (Rat): 34,014 mg/kg

Acute inhalation toxicity : Acute toxicity estimate (Rat): 1,560 mg/l
Exposure time: 4 h

SAFETY DATA SHEET

Revision Date: 09/07/2018

Print Date: 10/29/2018

SDS Number: R0076417

Version: 1.3

Valvoline™ General Purpose Amber Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 VV609

Acute dermal toxicity : Acute toxicity estimate (Rabbit): 8,261 mg/kg

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (<3 % DMSO EXTRACT):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:

Acute oral toxicity : LD50 (Rat): > 5 g/kg

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
 Assessment: Not classified as acutely toxic by inhalation under GHS.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
 Assessment: Not classified as acutely toxic by dermal absorption under GHS.
 Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Causes skin irritation.

Product:

Result : Irritating to skin.

Remarks : May cause skin irritation and/or dermatitis.

Result : Repeated exposure may cause skin dryness or cracking.

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (<3 % DMSO EXTRACT):

Result : Slight, transient irritation

ASPHALTIC RESIN:

Result : Irritating to skin.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:

Species : Rabbit
 Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Result : Irritating to eyes.

SAFETY DATA SHEET

Revision Date: 09/07/2018

Print Date: 10/29/2018

SDS Number: R0076417

Version: 1.3

Valvoline™ General Purpose Amber Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 VV609

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.
 Causes serious eye irritation.

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (<3 % DMSO EXTRACT):

Result : Slight, transient irritation

ASPHALTIC RESIN:

Result : Irritating to eyes.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:

Species : Rabbit

Result : Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (<3 % DMSO EXTRACT):

Genotoxicity in vitro : Test Type: Ames test

Result: negative

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

**SAFETY DATA SHEET**

Revision Date: 09/07/2018

Print Date: 10/29/2018

SDS Number: R0076417

Version: 1.3

Valvoline™ General Purpose Amber Grease
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
VV609

Product:

Assessment : May cause respiratory irritation.

Components:**ASPHALTIC RESIN:**

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Further information**Product:**

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test

SAFETY DATA SHEET

Revision Date: 09/07/2018

Print Date: 10/29/2018

SDS Number: R0076417

Version: 1.3

 Valvoline™ General Purpose Amber Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 VV609

 Test substance: WAF
 Method: OECD Test Guideline 201

 Toxicity to daphnia and other aquatic invertebrates
 (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
 Exposure time: 21 d
 Test Type: semi-static test
 Test substance: WAF
 Method: OECD Test Guideline 211

Persistence and degradability

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:

 Biodegradability : Result: Inherently biodegradable
 Biodegradation: 31 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301F

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS
Disposal methods

 General advice : Do not dispose of waste into sewer.
 Do not contaminate ponds, waterways or ditches with
 chemical or used container.
 Send to a licensed waste management company.

 Dispose of in accordance with all applicable local, state and
 federal regulations.

 Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Empty containers should be taken to an approved waste
 handling site for recycling or disposal.
 Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION
International transport regulations



SAFETY DATA SHEET

Revision Date: 09/07/2018

Print Date: 10/29/2018

SDS Number: R0076417

Version: 1.3

Valvoline™ General Purpose Amber Grease
™ Trademark, Valvoline or its subsidiaries, registered in various countries
VV609

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID



SAFETY DATA SHEET

Revision Date: 09/07/2018

Print Date: 10/29/2018

SDS Number: R0076417

Version: 1.3

Valvoline™ General Purpose Amber Grease
™ Trademark, Valvoline or its subsidiaries, registered in various countries
VV609

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Skin corrosion or irritation
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

- TSCA : On TSCA Inventory
- KECI : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- AICS : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- ENCS : Not in compliance with the inventory
- DSL : All components of this product are on the Canadian DSL

TSCA list

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

Revision Date: 09/07/2018


Print Date: 10/29/2018

SDS Number: R0076417

Version: 1.3

Valvoline™ General Purpose Amber Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 VV609

Revision Date: 09/07/2018

NFPA:	HMIS III:						
<p style="text-align: center;">Flammability</p>  <p style="text-align: center;">Special hazard.</p>	<table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: yellow; color: black;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification
 Combustible Liquid Class IIIB

Full text of H-Statements


- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.

Sources of key data used to compile the Safety Data Sheet
 Valvoline internal data including own and sponsored test reports
 The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

- ACGIH : American Conference of Industrial Hygienists
- BEI : Biological Exposure Index
- CAS : Chemical Abstracts Service (Division of the American Chemical Society).
- CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
- FG : Food grade
- GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

	Page: 16
SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 10/29/2018
	SDS Number: R0076417
Valvoline™ General Purpose Amber Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV609	Version: 1.3

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the “International Air Transport Association” (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the “International Civil Aviation Organization”

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System