

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 001
Date Prepared: 01/14/02
Date Printed: 02/04/03
MSDS No: 503.0278955-001.012

PYROIL WHITE LITHIUM GREASE 12/11 OZ

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: PYROIL WHITE LITHIUM GREASE 12/11 OZ
SAP Material No: PYWLG11
General or Generic ID: LITHIUM COMPLEX GREASE

Company

The Valvoline Company
P.O. Box 14000
Lexington, KY 40512

Telephone Numbers

Emergency: 1-800-274-5263
Information: 1-859-357-7206

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
HEPTANE	142-82-5	77.0- 87.0
CARBON DIOXIDE	124-38-9	0.0- 8.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Can cause eye irritation. Additional symptoms of eye exposure may include: blurred vision

Skin

May cause mild skin irritation. Prolonged or repeated contact may dry and crack the skin.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing of vapor or mist is possible.

Symptoms of Exposure

stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), and death.

Target Organ Effects

Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals, and may aggravate preexisting disorders of these organs in humans: effects on hearing, central nervous system damage.

Continued On Next Page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 002
Date Prepared: 01/14/02
Date Printed: 02/04/03
MSDS No: 503.0278955-001.012

PYROIL WHITE LITHIUM GREASE 12/11 OZ

Developmental Information

No data

Cancer Information

No data

Other Health Effects

No data

Primary Route(s) of Entry

Inhalation, Skin contact.

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Note to Physicians

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin.

5. FIRE FIGHTING MEASURES

Flash Point

-20.0 F (-28.8 C) TCC

Explosive Limit

(for component) Lower 1.1 Upper 10.0 %

Continued On Next Page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 003
Date Prepared: 01/14/02
Date Printed: 02/04/03
MSDS No: 503.0278955-001.012

PYROIL WHITE LITHIUM GREASE 12/11 OZ

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Fire and Explosion Hazards

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Extinguishing Media

regular foam, carbon dioxide, dry chemical.

Fire Fighting Instructions

Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Health - 1, Flammability - 4, Reactivity - 0

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Allow to evaporate. Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Ventilate area.

Large Spill

Allow to evaporate. Persons not wearing protective equipment should be excluded from area until leak has been repaired. Eliminate all ignition sources (flares, flames, including pilot lights, electrical sparks).

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Not applicable

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Not required under normal conditions of use.

Skin Protection

Not required under normal conditions of use., Other protective equipment: not required under normal conditions of use..

Continued On Next Page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 004
Date Prepared: 01/14/02
Date Printed: 02/04/03
MSDS No: 503.0278955-001.012

PYROIL WHITE LITHIUM GREASE 12/11 OZ

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Component

HEPTANE (142-82-5)

OSHA VPEL 400.000 ppm - TWA
OSHA VPEL 500.000 ppm - STEL
ACGIH TLV 400.000 ppm - TWA
ACGIH TLV 500.000 ppm - STEL

CARBON DIOXIDE (124-38-9)

OSHA VPEL 10000.000 ppm - TWA
OSHA VPEL 30000.000 ppm - STEL
ACGIH TLV 5000.000 ppm - TWA
ACGIH TLV 30000.000 ppm - STEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

(for component) 200.0 F (93.3 C) @ 760 mmHg

Vapor Pressure

(for component) 40.000 mmHg @ 68.00 F

Specific Vapor Density

> 1.000 @ AIR=1

Specific Gravity

.680 @ 77.00 F

Liquid Density

5.670 lbs/gal @ 77.00 F
.680 kg/l @ 25.00 C

Percent Volatiles (Including Water)

70.0 - 85.0 %

Volatile Organic Compounds (VOC) (Maximum)

581.000 g/l
4.850 lbs/gal

Continued On Next Page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 005
Date Prepared: 01/14/02
Date Printed: 02/04/03
MSDS No: 503.0278955-001.012

PYROIL WHITE LITHIUM GREASE 12/11 OZ

Evaporation Rate

FASTER THAN ETHYL ETHER

Appearance

No data

State

LIQUID

Physical Form

No data

Color

No data

Odor

No data

pH

Not applicable

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Ventilate area of spill. Allow material to evaporate.

Continued On Next Page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 006
Date Prepared: 01/14/02
Date Printed: 02/04/03
MSDS No: 503.0278955-001.012

PYROIL WHITE LITHIUM GREASE 12/11 OZ

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:
AEROSOLS,2.1,UN 1950

Container/Mode:
CASES/SURFACE - NO EXCEPTIONS

NOS Component:
None

RQ (Reportable Quantity) - 49 CFR 172.101
Not applicable

15. REGULATORY INFORMATION

US Federal Regulations

TSCA (Toxic Substances Control Act) Status

TSCA (UNITED STATES) The intentional ingredients of this product are listed.

CERCLA RQ - 40 CFR 302.4

None

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate(X) Delayed(X) Fire() Reactive() Sudden Release of
Pressure()

SARA 313 Components - 40 CFR 372.65

None

International Regulations

Inventory Status

Not determined

State and Local Regulations

California Proposition 65

None

New Jersey RTK Label Information

N-HEPTANE 142-82-5
CARBON DIOXIDE 124-38-9

Pennsylvania RTK Label Information

HEPTANE (N-) 142-82-5
CARBON DIOXIDE 124-38-9

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 007
Date Prepared: 01/14/02
Date Printed: 02/04/03
MSDS No: 503.0278955-001.012

PYROIL WHITE LITHIUM GREASE 12/11 OZ

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.
