



Material Safety Data Sheet

Copyright, 2006, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3M(TM) Super Red Putty, P.N. 05972
MANUFACTURER: 3M
DIVISION: Automotive Aftermarket

ADDRESS: 3M Center
 St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 10/02/2006
Supersedes Date: 12/02/2005

Document Group: 10-2852-1

Product Use:

Specific Use: Glazing Putty for Automotive Pinholes and Scratches

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
TALC	14807-96-6	10 - 40
N-BUTYL ACETATE	123-86-4	10 - 40
BARIUM SULFATE	7727-43-7	10 - 40
OXIDIZED SOYBEAN OIL	68152-81-8	3 - 7
NITROCELLULOSE	9004-70-0	3 - 7
XYLENE	1330-20-7	1 - 5
TOLUENE	108-88-3	1 - 5
ISOPROPYL ALCOHOL	67-63-0	1 - 5
IRON OXIDE	1332-37-2	1 - 5
BIS(2-ETHYLHEXYL)PHTHALATE	117-81-7	1 - 5
BUTYL ALCOHOL	71-36-3	1 - 5
KAOLIN	1332-58-7	<2
ETHYL ALCOHOL	64-17-5	<1
QUARTZ SILICA	14808-60-7	<= 0.013552

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Paste

Odor, Color, Grade: Smooth red paste with sweet ester odor

General Physical Form: Liquid

Immediate health, physical, and environmental hazards: Flammable liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. Contains a chemical or chemicals which can cause cancer. May cause target organ effects. Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

May be absorbed through skin and cause target organ effects.

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

During grinding, scraping, sanding:

Fibrosis: Signs/symptoms may include breathlessness, chronic dry cough, phlegm production, wheezing, and changes in lung function tests.

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

May be absorbed following inhalation and cause target organ effects.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Central Neuropathy: Signs/symptoms may include irritability, memory impairment, personality changes, sleep disorders, and decreased ability to concentrate.

Blood Effects: Signs/symptoms may include generalized weakness and fatigue, skin pallor, changes in blood clotting time, internal bleeding, and/or hemoglobinemia.

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

NOTE: This product contains ethanol. In IARC published Monograph No. 44, entitled, "Alcohol Drinking", the carcinogenicity of ethanol was determined based on chronic exposure to ethanol through human consumption of alcoholic beverages. This is not an expected effect during the foreseeable use of this product.

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Class Description</u>	<u>Regulation</u>
BIS(2-ETHYLHEXYL)PHTHALATE	117-81-7	Anticipated human carcinogen	National Toxicology Program Carcinogens
ETHYL ALCOHOL	64-17-5	Group 1	International Agency for Research on Cancer
QUARTZ SILICA	14808-60-7	Group 1	International Agency for Research on Cancer
QUARTZ SILICA	14808-60-7	Known human carcinogen	National Toxicology Program Carcinogens

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature	<i>No Data Available</i>
Flash Point	65 °F [<i>Test Method: SETAFLASH</i>]
Flammable Limits - LEL	1.0 %
Flammable Limits - UEL	7.6 %
OSHA Flammability Classification:	Class IB Flammable Liquid

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Water may not effectively extinguish fire; however, it should be used to keep fire-exposed

containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Flammable liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Cover spill area with a fire-extinguishing foam. An aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Contents may be under pressure, open carefully. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Ground containers securely when transferring contents. Wear low static or properly grounded shoes. Avoid breathing of vapors, mists or spray. Avoid static discharge. Avoid eye contact with vapors, mists, or spray. Keep out of the reach of children. Avoid breathing of dust created by cutting, sanding, grinding or machining. Avoid contact with oxidizing agents.

7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Keep container in well-ventilated area. Keep container tightly closed. Store away from oxidizing agents.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Provide appropriate local exhaust ventilation on open containers. Provide appropriate local exhaust for cutting, grinding, sanding or machining. If exhaust ventilation is not available, use appropriate respiratory protection. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Safety Glasses with side shields, Indirect Vented Goggles.

8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Neoprene.

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray. Avoid breathing of dust created by cutting, sanding, grinding or machining.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges and P95 particulate prefilters.

Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
BARIUM SULFATE	ACGIH	TWA	10 mg/m3	
BARIUM SULFATE	OSHA	TWA, respirable	5 mg/m3	Table Z-1
BARIUM SULFATE	OSHA	TWA, Vacated, as dust	10 mg/m3	
BARIUM SULFATE	OSHA	TWA, as total dust	15 mg/m3	Table Z-1
BIS(2-ETHYLHEXYL)PHTHALATE	ACGIH	TWA	5 mg/m3	Table A3
BIS(2-ETHYLHEXYL)PHTHALATE	OSHA	TWA	5 mg/m3	Table Z-1A
BIS(2-ETHYLHEXYL)PHTHALATE	OSHA	STEL	10 mg/m3	Table Z-1A
BUTYL ALCOHOL	ACGIH	TWA	20 ppm	
BUTYL ALCOHOL	OSHA	CEIL, Vacated	50 ppm	Skin Notation*
BUTYL ALCOHOL	OSHA	TWA	100 ppm	Table Z-1
ETHYL ALCOHOL	ACGIH	TWA	1000 ppm	Table A4
ETHYL ALCOHOL	OSHA	TWA	1000 ppm	Table Z-1
ISOPROPYL ALCOHOL	ACGIH	TWA	200 ppm	Table A4
ISOPROPYL ALCOHOL	ACGIH	STEL	400 ppm	Table A4
ISOPROPYL ALCOHOL	OSHA	TWA	400 ppm	Table Z-1A
ISOPROPYL ALCOHOL	OSHA	STEL	500 ppm	Table Z-1A
KAOLIN	ACGIH	TWA, respirable	2 mg/m3	Table A4
KAOLIN	OSHA	TWA, respirable	5 mg/m3	Table Z-1
KAOLIN	OSHA	TWA, Vacated, as dust	10 mg/m3	
KAOLIN	OSHA	TWA, as total dust	15 mg/m3	Table Z-1
N-BUTYL ACETATE	ACGIH	TWA	150 ppm	
N-BUTYL ACETATE	ACGIH	STEL	200 ppm	
N-BUTYL ACETATE	OSHA	TWA	150 ppm	Table Z-1A
N-BUTYL ACETATE	OSHA	STEL	200 ppm	Table Z-1A
QUARTZ SILICA	ACGIH	TWA, respirable	0.025 mg/m3	Table A2
QUARTZ SILICA	OSHA	TWA, respirable	0.1 mg/m3	Table Z-1A
STEARATES	ACGIH	TWA, as total dust	10 mg/m3	Table A4
TALC	ACGIH	TWA, respirable	2 mg/m3	Table A4
TALC	CMRG	TWA, as respirable dust	0.5 mg/m3	
TALC	OSHA	TWA, respirable	2 mg/m3	Table Z-1A
TOLUENE	ACGIH	TWA	50 ppm	Skin Notation*; Table A4
TOLUENE	CMRG	STEL	75 ppm	Skin Notation*

TOLUENE	OSHA	TWA, Vacated	100 ppm	
TOLUENE	OSHA	STEL, Vacated	150 ppm	
TOLUENE	OSHA	TWA	200 ppm	Table Z-2
TOLUENE	OSHA	CEIL	300 ppm	Table Z-2
XYLENE	ACGIH	TWA	100 ppm	Table A4
XYLENE	ACGIH	STEL	150 ppm	Table A4
XYLENE	OSHA	TWA	100 ppm	Table Z-1A
XYLENE	OSHA	STEL	150 ppm	Table Z-1A

* Substance(s) refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

VAC Vacated PEL: Vacated Permissible Exposure Limits [PEL] are enforced as the OSHA PEL in some states. Check with your local regulatory agency.

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Paste
Odor, Color, Grade:	Smooth red paste with sweet ester odor
General Physical Form:	Liquid
Autoignition temperature	<i>No Data Available</i>
Flash Point	65 °F [<i>Test Method: SETAFLASH</i>]
Flammable Limits - LEL	1.0 %
Flammable Limits - UEL	7.6 %
Boiling point	277 °F
Density	1.73 g/ml
Vapor Density	4.00 [<i>Ref Std: AIR=1</i>]
Vapor Pressure	<=27 psia [<i>@ 131.0000000000 °F</i>] [<i>Details: MITS data</i>]
Specific Gravity	1.680 - 1.730 [<i>Ref Std: WATER=1</i>]
pH	<i>Not Applicable</i>
Melting point	<i>No Data Available</i>
Solubility in Water	Negligible
Evaporation rate	7.80 [<i>Ref Std: ETHER=1</i>]
Volatile Organic Compounds	3.66 lb/gal [<i>Test Method: calculated SCAQMD rule 443.1</i>]
Percent volatile	25.75 %
VOC Less H2O & Exempt Solvents	438.5 g/l [<i>Test Method: calculated SCAQMD rule 443.1</i>]
Viscosity	80000 - 125000 centipoise

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: Heat; Sparks and/or flames

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified
Toxic Vapor, Gas, Particulate	Not Specified

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of waste product in a permitted hazardous waste facility.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

ID Number(s):
60-9800-0820-9

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
XYLENE	1330-20-7	1 - 5
BIS(2-ETHYLHEXYL)PHTHALATE	117-81-7	1 - 5
TOLUENE	108-88-3	1 - 5
BUTYL ALCOHOL	71-36-3	1 - 5

This material contains a chemical which requires export notification under TSCA Section 12[b]:

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Regulation</u>	<u>Status</u>
BIS(2-ETHYLHEXYL)PHTHALATE	117-81-7	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable
BIS(2-ETHYLHEXYL)PHTHALATE (ALKYL PHTHALATES)	117-81-7	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable
N-BUTYL ACETATE	123-86-4	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable

STATE REGULATIONS

Contact 3M for more information.

CALIFORNIA PROPOSITION 65

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Classification</u>
BIS(2-ETHYLHEXYL)PHTHALATE	117-81-7	*Male reproductive toxin
BIS(2-ETHYLHEXYL)PHTHALATE	117-81-7	**Carcinogen
BIS(2-ETHYLHEXYL)PHTHALATE	117-81-7	*Developmental Toxin
SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE)	NONE	**Carcinogen
TOLUENE	108-88-3	*Developmental Toxin

* WARNING: contains a chemical or chemicals which can cause birth defects or other reproductive harm.

** WARNING: contains a chemical which can cause cancer.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

WHMIS: Hazardous

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 2 **Flammability:** 3 **Reactivity:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:

Copyright was modified.

Section 8: Exposure guidelines ingredient information was modified.

Section 16: Reason for reissue heading was deleted.

Section 16: Reason for reissue phrase was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com