



**3M General Offices**  
3M Center  
St. Paul, MN 55144-1000  
1-800-364-3577 or (651) 737-6501 (24 hours)

2018-09-25 21:31:54.043

## Safety Data Sheet

---

Purchase Order #: 7-60793  
Customer Number: 0026299440

MSDS COORDINATOR  
FACTORY MOTOR PARTS  
5328 W ROOSEVELT  
PHOENIX, AZ 85043-2713  
USA

Dear MSDS COORDINATOR

Enclosed is the Safety Data Sheet (SDS)\* for the product that your company recently purchased from 3M.

Please forward the attached document(s) to the individual in your organization responsible for hazard communication.

If you are a distributor and resell this product, OSHA and EPA require that you transmit this SDS information to your customers at the time of first shipment or whenever you receive revised SDSs from 3M.

3M SDSs are available over the Internet at [www.3m.com/MSDSSearch](http://www.3m.com/MSDSSearch). You may also order a DVD of 3M SDSs by calling 1-800-364-3577.

3M is committed to meeting our customer requirements. Please contact your 3M customer service or sales representative if you have any questions. If you do not know whom to contact, please call the 3M Product Information Center at 1-800-364-3577.

**If you are not currently receiving 3M SDSs by e-mail and would like to do so, please contact our eSDS Administrator at [emsdsadmin@mmm.com](mailto:emsdsadmin@mmm.com) or by calling 651-736-5875.**

\*An Article Information Sheet (AIS) or Article Information Letter (AIL) may be enclosed in place of an SDS if the product is an article which does not require an SDS under the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.





## Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	25-3522-7	<b>Version Number:</b>	6.03
<b>Issue Date:</b>	08/07/18	<b>Supersedes Date:</b>	03/08/18

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Brand Super Trim Adhesive, PN 08090

#### Product Identification Numbers

60-4550-3687-5, 60-4550-5561-0  
7000000530

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive, Adhesive Aerosol

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Automotive Aftermarket
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

#### 2.1. Hazard classification

Flammable Aerosol: Category 1.  
Gas Under Pressure: Liquefied gas.  
Serious Eye Damage/Irritation: Category 2B.  
Reproductive Toxicity: Category 1B.  
Simple Asphyxiant.  
Specific Target Organ Toxicity (single exposure): Category 3.  
Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

**Signal word**

Danger

**Symbols**

Flame | Gas cylinder | Exclamation mark | Health Hazard |

**Pictograms****Hazard Statements**

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes eye irritation.

May cause drowsiness or dizziness.

May damage fertility or the unborn child.

May displace oxygen and cause rapid suffocation.

Causes damage to organs through prolonged or repeated exposure:

nervous system |

sensory organs |

**Precautionary Statements****General:**

Keep out of reach of children.

**Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

**Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Call a POISON CENTER or doctor/physician if you feel unwell.

**Storage:**

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

34% of the mixture consists of ingredients of unknown acute oral toxicity.

34% of the mixture consists of ingredients of unknown acute dermal toxicity.

32% of the mixture consists of ingredients of unknown acute inhalation toxicity.

### SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Methyl Acetate	79-20-9	30 - 40 Trade Secret *
Dimethyl Ether	115-10-6	25 - 35 Trade Secret *
Cyclohexane	110-82-7	10 - 20 Trade Secret *
Polychloroprene	9010-98-4	1 - 10 Trade Secret *
Non-hazardous components (NJTSRN 04499600-7374)	Trade Secret*	1 - 10 Trade Secret *
Thermoplastic Rubbers	Trade Secret*	< 10 Trade Secret *
Toluene	108-88-3	3 - 7 Trade Secret *
Hydrotreated Heavy Naphtha (Petroleum)	64742-48-9	1 - 5 Trade Secret *
Antioxidant	Trade Secret*	1 - 5 Trade Secret *
Benzene, ethenyl-, polymer with 1,3-butadiene and 2-methyl-1,3-butadiene, hydrogenated	Trade Secret*	1 - 5 Trade Secret *

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

##### Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

##### Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

##### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Formaldehyde	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin
Toluene	108-88-3	OSHA	TWA:200 ppm;CEIL:300 ppm	
Cyclohexane	110-82-7	ACGIH	TWA:100 ppm	
Cyclohexane	110-82-7	OSHA	TWA:1050 mg/m3(300 ppm)	
Dimethyl Ether	115-10-6	AIHA	TWA:1880 mg/m3(1000 ppm)	
Methyl Acetate	79-20-9	ACGIH	TWA:200 ppm;STEL:250 ppm	
Methyl Acetate	79-20-9	OSHA	TWA:610 mg/m3(200 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Fluoroelastomer

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

<b>General Physical Form:</b>	Liquid
<b>Specific Physical Form:</b>	Aerosol
<b>Odor, Color, Grade:</b>	Yellow to amber color, mild solvent smell
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point</b>	<i>Not Applicable</i>
<b>Boiling Point</b>	<i>Not Applicable</i>
<b>Flash Point</b>	-42 °F
<b>Evaporation rate</b>	1.9 [Ref Std:ETHER=1]
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	<i>No Data Available</i>
<b>Flammable Limits(UEL)</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	<i>Not Applicable</i>
<b>Vapor Density</b>	>=1 [Ref Std:AIR=1]
<b>Density</b>	0.835 g/ml
<b>Specific Gravity</b>	0.835 [Ref Std:WATER=1]
<b>Solubility in Water</b>	Negligible
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Viscosity</b>	<i>Not Applicable</i>
<b>Hazardous Air Pollutants</b>	0.50449 lb HAPS/lb solids [Test Method:Calculated]
<b>Volatile Organic Compounds</b>	53.4 % weight [Test Method:calculated per CARB title 2]
<b>Volatile Organic Compounds</b>	446 g/l [Test Method:calculated SCAQMD rule 443.1]
<b>Percent volatile</b>	85.4 % weight [Test Method:Estimated]
<b>VOC Less H2O &amp; Exempt Solvents</b>	628 g/l [Test Method:calculated SCAQMD rule 443.1]

**SECTION 10: Stability and reactivity****10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

**10.2. Chemical stability**

Stable.

**10.3. Possibility of hazardous reactions**

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

Heat  
Sparks and/or flames

**10.5. Incompatible materials**

Strong acids  
Strong oxidizing agents

**10.6. Hazardous decomposition products**

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.



## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

##### Inhalation:

May be harmful if inhaled.

Simple Asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal.

May cause additional health effects (see below).

##### Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

##### Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

##### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

#### Additional Health Effects:

##### Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

##### Prolonged or repeated exposure may cause target organ effects:

Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision.

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Olfactory Effects: Signs/symptoms may include decreased ability to detect odors and/or complete loss of smell.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

##### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or

the data are not sufficient for classification.

### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Methyl Acetate	Dermal	Rat	LD50 > 2,000 mg/kg
Methyl Acetate	Inhalation-Vapor (4 hours)	Rat	LC50 > 49 mg/l
Methyl Acetate	Ingestion	Rat	LD50 > 5,000 mg/kg
Dimethyl Ether	Inhalation-Gas (4 hours)	Rat	LC50 164,000 ppm
Cyclohexane	Dermal	Rat	LD50 > 2,000 mg/kg
Cyclohexane	Inhalation-Vapor (4 hours)	Rat	LC50 > 32.9 mg/l
Cyclohexane	Ingestion	Rat	LD50 6,200 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
Polychloroprene	Dermal		LD50 estimated to be > 5,000 mg/kg
Polychloroprene	Ingestion	Rat	LD50 > 20,000 mg/kg
Non-hazardous components (NJTSRN 04499600-7374)	Dermal		LD50 estimated to be > 5,000 mg/kg
Non-hazardous components (NJTSRN 04499600-7374)	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Antioxidant	Dermal		LD50 estimated to be > 5,000 mg/kg
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation-Vapor		LC50 estimated to be 20 - 50 mg/l
Hydrotreated Heavy Naphtha (Petroleum)	Dermal	Rabbit	LD50 > 3,000 mg/kg
Antioxidant	Ingestion	Rat	LD50 > 34,000 mg/kg
Hydrotreated Heavy Naphtha (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
Methyl Acetate	Rabbit	No significant irritation
Cyclohexane	Rabbit	Mild irritant
Toluene	Rabbit	Irritant
Polychloroprene	Human	No significant irritation
Hydrotreated Heavy Naphtha (Petroleum)	Rabbit	Irritant

### Serious Eye Damage/Irritation

Name	Species	Value
Methyl Acetate	Rabbit	Moderate irritant
Cyclohexane	Rabbit	Mild irritant
Toluene	Rabbit	Moderate irritant
Polychloroprene	Professional judgement	No significant irritation
Hydrotreated Heavy Naphtha (Petroleum)	Rabbit	No significant irritation

### Skin Sensitization

Name	Species	Value
Methyl Acetate	Human	Not classified

Toluene	Guinea pig	Not classified
Hydrotreated Heavy Naphtha (Petroleum)	Guinea pig	Not classified

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Methyl Acetate	In Vitro	Not mutagenic
Methyl Acetate	In vivo	Not mutagenic
Dimethyl Ether	In Vitro	Not mutagenic
Dimethyl Ether	In vivo	Not mutagenic
Cyclohexane	In Vitro	Not mutagenic
Cyclohexane	In vivo	Some positive data exist, but the data are not sufficient for classification
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Hydrotreated Heavy Naphtha (Petroleum)	In vivo	Not mutagenic
Hydrotreated Heavy Naphtha (Petroleum)	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Dimethyl Ether	Inhalation	Rat	Not carcinogenic
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Hydrotreated Heavy Naphtha (Petroleum)	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Dimethyl Ether	Inhalation	Not classified for development	Rat	NOAEL 40,000 ppm	during organogenesis
Cyclohexane	Inhalation	Not classified for female reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Not classified for male reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Not classified for development	Rat	NOAEL 6.9 mg/l	2 generation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesis

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methyl Acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Methyl Acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Methyl Acetate	Inhalation	blindness	Not classified		NOAEL Not available	
Methyl Acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
Dimethyl Ether	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 10,000 ppm	30 minutes
Dimethyl Ether	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 100,000 ppm	5 minutes
Cyclohexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Cyclohexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
Hydrotreated Heavy Naphtha (Petroleum)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methyl Acetate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	28 days
Methyl Acetate	Inhalation	endocrine system   hematopoietic system   liver   immune system   kidney and/or bladder	Not classified	Rat	NOAEL 6.1 mg/l	28 days
Dimethyl Ether	Inhalation	hematopoietic	Not classified	Rat	NOAEL	2 years

		system			25,000 ppm	
Dimethyl Ether	Inhalation	liver	Not classified	Rat	NOAEL 20,000 ppm	30 weeks
Cyclohexane	Inhalation	liver	Not classified	Rat	NOAEL 24 mg/l	90 days
Cyclohexane	Inhalation	auditory system	Not classified	Rat	NOAEL 1.7 mg/l	90 days
Cyclohexane	Inhalation	kidney and/or bladder	Not classified	Rabbit	NOAEL 2.7 mg/l	10 weeks
Cyclohexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 24 mg/l	14 weeks
Cyclohexane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 8.6 mg/l	30 weeks
Toluene	Inhalation	auditory system   nervous system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.6 mg/l	90 days
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	bone, teeth, nails, and/or hair   blood   liver   muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days

**Aspiration Hazard**

Name	Value
Cyclohexane	Aspiration hazard

Toluene	Aspiration hazard
Hydrotreated Heavy Naphtha (Petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

### Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

### EPCRA 311/312 Hazard Classifications:

#### Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

Gas under pressure

#### Health Hazards

Reproductive toxicity

Serious eye damage or eye irritation

Simple Asphyxiant

Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Toluene	108-88-3	Trade Secret 3 - 7
Cyclohexane	110-82-7	Trade Secret 10 - 20

**15.2. State Regulations**

Contact 3M for more information.

**California Proposition 65**

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Listing</u>
Ethylbenzene	100-41-4	Carcinogen
Toluene	108-88-3	Developmental Toxin

**15.3. Chemical Inventories**

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

**15.4. International Regulations**

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

**SECTION 16: Other information**

**NFPA Hazard Classification**

**Health:** 1 **Flammability:** 4 **Instability:** 0 **Special Hazards:** None  
**Aerosol Storage Code:** 2

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Document Group:** 25-3522-7 **Version Number:** 6.03  
**Issue Date:** 08/07/18 **Supersedes Date:** 03/08/18

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at [www.3M.com](http://www.3M.com)

