

MATERIAL SAFETY DATA SHEET

MATERIAL IDENTITY: SUPERCLEAN TIRE GLOSS

Section 1 - Product Identification

Manufacturer: SuperClean Brands, LLC
1380 Corporate Center Curve, Suite 107
Eagan, MN 55121

Telephone: (651) 365-7500

Facsimile: (651) 365-7599

Transportation Emergency (for immediate information about a chemical or to seek assistance from a manufacturer): 1-800-424-9300

Date Updated: March 10, 2011

Section 2 - Hazardous Ingredients

INGREDIENTS	CAS #	% range	TLV	PEL
Hydrotreated middle distillate	64742-46-7	NA	(Mist) 5 mg/m ³	(Mist) 5 mg/m ³
Polydimethylsiloxane	63148-62-9	NA	NE	NE

Balance of formula is not hazardous as defined by OSHA

Section 3 - Physical Data

Form:	Liquid	pH:	NA
Color:	Clear	pH (1% vol):	NA
Odor:	Slight	Solubility in Water:	Insoluble
Specific Gravity (Water = 1):	0.82 - 0.83	Vapor Density (Air=1):	ND
Boiling Point °F:	>400	% VOC by weight (EPA 59.203(f)(1)):	<3
Evaporation Rate (Water = 1):	NE	Vapor pressure:	ND

Section 4 - Fire and Explosion Information

Flash Point (Method) F: >200F (TCC)

Unusual Fire & Explosion Hazards: Smoke may be generated while burning. Carbon monoxide, carbon dioxide, and other oxides may be generated as products of combustion.

Extinguishing Agents: Carbon dioxide, dry chemical, or foam. Water stream may spread fire, use water spray only to cool containers exposed to fire. If leak or spill has not ignited, use water spray to disperse the vapors.

Fire fighting methods: Evacuate area and fight fire from a safe distance. Use water spray to cool adjacent structures and to protect personnel. Shut off source of leak if possible. Fire fighters must wear MSHA/NIOSH approved positive pressure breathing apparatus with full face mask and full protective equipment.

Section 5 - Health Hazard Data - Signs and Symptoms of Overexposure

Probable Routes of Entry: Eyes, skin, inhalation. See section 11: other effects for toxicity information.

Eyes: Contact with eyes may cause slight irritation with mild redness and dryness.

Skin: Prolonged or repeated contact may result in contact dermatitis, dryness, redness, or chapping.

Inhalation: Not expected to present a hazard at ambient temperature and normal use. Overexposure by inhalation of misted product may lead irritation in respiratory tract. Severe overexposure may lead to drowsiness, dullness, dizziness, nausea, and headache.

Ingestion: Ingestion is not expected to be a primary route of exposure. Do not ingest. Material may cause irritation to mouth, throat and stomach. Coughing, choking, gagging, and vomiting may develop. Note: Aspiration is a secondary hazard that should be expected and can lead to chemical pneumonitis. Loss of consciousness and convulsions followed by death may result.

Repeated exposure effects: Redness, drying, chapping

Medical Conditions

Aggravated by Exposure: Pre-existing disorders usually not aggravated.

MATERIAL SAFETY DATA SHEET

MATERIAL IDENTITY: SUPERCLEAN TIRE GLOSS

Section 12 - Ecological Information

Hydrotreated middle distillate No data
 Polydimethylsiloxane No data

Section 13 - Hazard Rating - HMIS

0 = minimal 1 = slight 2 = moderate 3 = serious 4 = severe
 Health: 1 Reactivity: 0 Fire: 1 Personal protection equipment: A (glasses if splashing occurs)

Section 14 - Regulatory Information

• Chemical Inventory Status - part 1 •

Ingredient	TSCA	EC	Japan	Australia
Hydrotreated middle distillate	Yes	Yes	Yes	Yes
Polydimethylsiloxane	Yes	ND	ND	ND

• Chemical Inventory Status - part 2 •

Ingredient	Korea	-----Canada----- DSL	NDSL	Philippines
Hydrotreated middle distillate	Yes	Yes	No	Yes
Polydimethylsiloxane	ND	Yes	No	ND

• Federal, State & Int'l Regulations – part 1 •

Ingredient	---- SARA 302 ---- RQ	TPQ	----- SARA 313 ----- List	Chemical Catg.
Hydrotreated middle distillate	No	No	No	No
Polydimethylsiloxane	No	No	No	No

• Federal, State & Int'l Regulations - part 2 •

Ingredient	CERCLA	RCRA 261.33	TSCA 8(D)
Hydrotreated middle distillate	No	ND	ND
Polydimethylsiloxane	No	ND	ND


Chemical Weapons Convention: No TSCA 12(b): No CDTA: No
 SARA 311/312: Acute: yes Chronic: No Fire: No Pressure: No Reactivity: No

Section 15 - Shipping Name

Not DOT regulated.

Section 16 – WHMIS

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Class	Description	Symbol
D2B	Material causing other toxic effects	

ABBREVIATIONS:
 > = GREATER THAN NE = NOT ESTABLISHED NDA = NO DATA AVAILABLE
 ND = NO DATA <= LESS THAN BCF = BIOCONCENTRATION FACTOR
 NA = NOT APPLICABLE ~ = APPROXIMATELY

The data and recommendations presented herein are based upon our research and the research of others, and are believed to be accurate. However, no warranty of guarantee of their accuracy is made; and the products are distributed without any warranty, expressed or implied, including the limited warranties of merchantability of fitness for a particular purpose. The supplier makes no warranties, expressed or implied to the vendee, the vendee's employees or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, adequacy or furnishing of such information. Employers should use this information only as a supplement to other information and must make independent determinations of suitability to assure proper use, safety, and health of employees.