

according to Regulation (EC) No 1907/2006

**Divinol Test Fluid GS** Revision date:

26.04.2019 Article No.: 29120 Page 1 of 9

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

29120 Divinol Test Fluid GS

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

See technical information

### 1.3. Details of the supplier of the safety data sheet

Zeller+Gmelin GmbH & Co. KG Company name:

Schlossstr. 20 Street: D-73054 Eislingen Place: +49 (0) 7161 / 802-0 Telephone:

info@zeller-gmelin.de e-mail:

Uwe Allmendinger

Telephone: +49 (0) 7161 / 802-297 Contact person:

produktsicherheit@zeller-gmelin.de e-mail:

Internet: www.zeller-gmelin.de

Produktsicherheit / Product Safety Responsible Department: 1.4. Emergency telephone Germany: +49 (0) 7161 / 802-400

In England and Wales: NHS Direct: 0845 4647 or 111 In Scotland: NHS 24 - 08454 <u>number:</u>

24 24 24 In Republic of Ireland: 01 809 2166

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

## Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3 Aspiration hazard: Asp. Tox. 1

Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 3

**Hazard Statements:** 

Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

## Regulation (EC) No. 1272/2008

### Hazard components for labelling

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

hydrocarbons, C10-C12, isoalkanes, <2% aromatics

Danger Signal word:

Pictograms:







#### **Hazard statements**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

Telefax: +49 (0) 7161 / 802-290



according to Regulation (EC) No 1907/2006

Revision date: Divinol Test Fluid GS
26.04.2019 Article No.: 29120 Page 2 of 9

smoking.

P261 Avoid breathing mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P403+P235 Store in a well-ventilated place. Keep cool.

#### Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

#### 2.3. Other hazards

Results of PBT and vPvB assessment: not applicable.

### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### Chemical characterization

Solvent-based mixture.

### **Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification	•	•	
64742-48-9	hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			25 - <= 100 %
	919-857-5	649-327-00-6	01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
	hydrocarbons, C10-C12, isoalkanes, <2% aromatics			10 - < 20 %
	923-037-2		01-2119471991-29	
	Flam. Liq. 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H304 H411 EUH066			
128-37-0	2,6-di-tert-butyl-p-cresol			0.1 - < 0.3 %
	204-881-4		01-2119565113-46	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			

Full text of H and EUH statements: see section 16.

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### **General information**

When in doubt or if symptoms are observed, get medical advice. If unconscious place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

# After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

# After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunken in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting.

## 4.2. Most important symptoms and effects, both acute and delayed

When in doubt or if symptoms are observed, get medical advice.

### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

# **SECTION 5: Firefighting measures**



according to Regulation (EC) No 1907/2006

Revision date: Divinol Test Fluid GS
26.04.2019 Article No.: 29120 Page 3 of 9

#### 5.1. Extinguishing media

### Suitable extinguishing media

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO2).

### Unsuitable extinguishing media

Full water jet.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide Carbon dioxide (CO2). Do not inhale explosion and combustion gases.

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into soil/subsoil.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Clean contaminated articles and floor according to the environmental legislation.

#### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### 6.4. Reference to other sections

See protective measures under point 7 and 8.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Use personal protection equipment. Do not eat, drink or smoke when using this product. Provide fresh air. Handle and open container with care. Conditions to avoid: generation/formation of aerosols.

#### Advice on protection against fire and explosion

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Vapours of flammable solvents can accumulate in the gas phase of closed container, especially during heat treatment. Therefore keep away from fire and sources of ignition. Provide earthing of containers, equipment, pumps and ventilation facilities. Use non-sparking tools. Recommendation: Wear anti-static footwear and clothing

### 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Protect against: Frost. Keep away from heat. Protect against direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

## 7.3. Specific end use(s)

Observe technical data sheet.

#### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
128-37-0	2,6-Di-tert-butyl-p-cresol	_	10		TWA (8 h)	WEL



according to Regulation (EC) No 1907/2006

Revision date: Divinol Test Fluid GS
26.04.2019 Article No.: 29120 Page 4 of 9

#### **DNEL/DMEL values**

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
128-37-0 2,6-di-tert-butyl-p-cresol					
Worker DNEL, long-term		inhalation	systemic	5,8 mg/m³	
Consumer DNEL, long-term		inhalation	systemic	1,74 mg/m³	
Worker DNEL, long-term		dermal	systemic	8,3 mg/kg bw/day	
Consumer DNEL, long-term		dermal	systemic	5 mg/kg bw/day	

#### **PNEC values**

CAS No	Substance	
Environmental compartment Value		Value
128-37-0 2,6-di-tert-butyl-p-cresol		
Freshwater 4 mg/l		4 mg/l
Marine water 0,4 mg/l		0,4 mg/l
Secondary poisoning 16,7 mg/kg		16,7 mg/kg
Soil 1,04 mg/kg		1,04 mg/kg

#### 8.2. Exposure controls

#### Appropriate engineering controls

See chapter 7. No additional measures necessary.

### Protective and hygiene measures

When using do not eat, drink, smoke, sniff.

#### Eye/face protection

Eye glasses with side protection.

#### Hand protection

Wear suitable gloves. Recommended glove articles: DIN EN 374. Suitable material: NBR (Nitrile rubber). Breakthrough time (maximum wearing time): > 120 min (Thickness of the glove material: 0.4 mm). Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

# Skin protection

Protective clothing.

#### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Suitable respiratory protection apparatus: Filtering Half-face mask (DIN EN 149), e.g. FFAP / Full-/half-/quarter-face masks (DIN EN 136/140) + Combination filtering device (EN 14387), e.g. AP.

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains.

# SECTION 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: clear
Odour: mild

Test method

pH-Value: not applicable

Changes in the physical state

Melting point: not determined
Initial boiling point and boiling range: > 150 °C

Pour point: < -20 °C DIN ISO 3016



according to Regulation (EC) No 1907/2006

Revision date: Divinol Test Fluid GS
26.04.2019 Article No.: 29120 Page 5 of 9

2 hPa

Flash point: > 38 °C EN ISO 13736

Lower explosion limits:0,7 vol. %Upper explosion limits:6,0 vol. %Ignition temperature:not determinedDecomposition temperature:No information available.

(at 20 °C)

Vapour pressure:

Density (at 15 °C): 0,77 g/cm³ DIN EN ISO 12185

Water solubility: insoluble
Partition coefficient: not determined
Viscosity / dynamic: not determined

Viscosity / kinematic: 1,27 mm²/s DIN 51562

(at 20 °C)

Flow time: not determined Vapour density: not determined Evaporation rate: not determined

## 9.2. Other information

No information available.

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

No information available.

### 10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

### 10.4. Conditions to avoid

Heat.

#### 10.5. Incompatible materials

No information available.

## 10.6. Hazardous decomposition products

No information available.

# **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

### **Acute toxicity**

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

Revision date: Divinol Test Fluid GS
26.04.2019 Article No.: 29120 Page 6 of 9

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-48-9	hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 >5000,0 mg/kg	Rat		
	dermal	LD50 >5000,0 mg/kg	Rabbit		
128-37-0	2,6-di-tert-butyl-p-cresol				
	oral	LD50 >2930,0 mg/kg	Rat		
	dermal	LD50 >2000,0 mg/kg	Rabbit		

### Irritation and corrosivity

Based on available data, the classification criteria are not met.

### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause drowsiness or dizziness. (hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

### STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

### **Aspiration hazard**

May be fatal if swallowed and enters airways. (hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics; hydrocarbons, C10-C12, isoalkanes, <2% aromatics)

### Practical experience

#### Other observations

Keeping to the general worker's protection rules and the industrial hygienics, there is no risk in handling this product through the personnel. Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

There are no data available on the mixture itself.

## 12.2. Persistence and degradability

There are no data available on the mixture itself.

# 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
128-37-0	2,6-di-tert-butyl-p-cresol	5,10

### 12.4. Mobility in soil

No data available

### 12.5. Results of PBT and vPvB assessment

No data available

### 12.6. Other adverse effects

No data available

### **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods



according to Regulation (EC) No 1907/2006

Revision date: Divinol Test Fluid GS

26.04.2019 Article No.: 29120 Page 7 of 9

### Advice on disposal

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

### Waste disposal number of waste from residues/unused products

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and mother liquors; hazardous waste

### Contaminated packaging

Non-contaminated packages may be recycled. Consult the appropriate local waste disposal expert about waste disposal.

## **SECTION 14: Transport information**

### Land transport (ADR/RID)

**14.1. UN number:** UN 3295

14.2. UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S.

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Classification code: F1
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

# Marine transport (IMDG)

**14.1. UN number:** UN 3295

14.2. UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S.

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Marine pollutant:

Special Provisions:

Limited quantity:

Excepted quantity:

EmS:

NO

223

5 L

E1

EnS:

F-E, S-D

# Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 3295

14.2. UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S.

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Special Provisions:

Revision No: 3,0 - Replaces version: 2

Print date: 29.04.2019



according to Regulation (EC) No 1907/2006

Revision date: Divinol Test Fluid GS
26.04.2019 Article No.: 29120 Page 8 of 9

Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1

IATA-packing instructions - Passenger:355IATA-max. quantity - Passenger:60 LIATA-packing instructions - Cargo:366IATA-max. quantity - Cargo:220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No data available

14.7. Transport in bulk according to Annex | of Marpol and the IBC Code

No data available

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### EU regulatory information

2010/75/EU (VOC): 99,8 % (768,5 g/l)

Information according to 2012/18/EU P5c FLAMMABLE LIQUIDS

(SEVESO III):

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### SECTION 16: Other information

### Changes

This data sheet contains changes from the previous version in section(s): 2,3,4,5,6,7,8,9,10,11,12,13,14,15,16.

#### Abbreviations and acronyms

ADR: Accord européen relatif au transport international des marchandises dangereuses par route (European

Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations concerning the International Carriage of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

CAS: Chemical Abstracts Service (a division of the American Chemical Society)

DNEL/DMEL: Derived No-Effect Level / Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average

STEL (EC): Short Term Exposure Limit

ATE: Acute Toxicity Estimate

LD50: Lethal Dose, 50% (median lethal dose)

LC50: Lethal Concentration, 50% (median lethal concentration)

EC50: half maximal Effective Concentration

ErC50: EC50 in terms of reduction of growth rate

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

VwVwS: Verwaltungsvorschrift wassergefährdende Stoffe



according to Regulation (EC) No 1907/2006

Revision date: Divinol Test Fluid GS
26.04.2019 Article No.: 29120 Page 9 of 9

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Asp. Tox. 1; H304	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

	, and the state of
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

### **Further Information**

Safety Data Sheet according to COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

\_\_\_\_\_

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)