



27262 PAG YF Refrigeration Lubricant 46

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 02/29/2016

Revision date: 02/29/2016

Supersedes: 09/11/2014

Version: 2.1

SECTION 1: Identification

1.1. Identification

Trade name : 27262 PAG YF Refrigeration Lubricant 46
Product code : 27262

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Polyalkylene Glycol based lubricant for use in air conditioning systems.

1.3. Details of the supplier of the safety data sheet

Tire Seal, Inc.
3574 Corona Street
Lake Worth, Florida 33461 - USA
T 561-582-2245 - F 561-582-1499
www.supercool.ac

1.4. Emergency telephone number

Emergency number : USA PHONE:1-800-373-7542, INT'L: 1-484-951-2432
DGA/AAG ENVIRONMENTAL CONTRACT: DGA4000-048

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Not classified

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS08

GHS09

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H227 - Combustible liquid
H302 - Harmful if swallowed
H317 - May cause an allergic skin reaction
H320 - Causes eye irritation
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P264 - Wash hands, forearms and face thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P272 - Contaminated work clothing must not be allowed out of the workplace
P280 - Wear protective gloves/protective clothing/eye protection/face protection

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

27262 PAG YF Refrigeration Lubricant 46

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
2,6-di-tert-butyl-p-cresol	(CAS No) 128-37-0	0.1 - 1	Acute Tox. 4 (Oral), H302
2,6-diisopropylphenyl isocyanate	(CAS No) 28178-42-9	0.7 - 0.7	Acute Tox. 4 (Oral), H302

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container closed when not in use.
- Incompatible products : Strong bases. Strong acids.

27262 PAG YF Refrigeration Lubricant 46

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Incompatible materials : Sources of ignition. Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2,6-di-tert-butyl-p-cresol (128-37-0)

ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (Butylated hydroxytoluene (BHT); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction and vapor)
-------	--------------------------------	--

Not applicable

2,6-diisopropylphenyl isocyanate (28178-42-9)

Not applicable

8.2. Exposure controls

Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: The use of gloves impervious to the specific material handled is advised to prevent skin contact. Suggested protective material: Nitrile, 4.5 mil thickness, tested at 3.5 ml and above with no breakthrough time after 240 minutes.
Eye protection	: Chemical goggles or safety glasses.
Respiratory protection	: Where there is potential for airborne exposure above the exposure limit an approved air purifying respirator equipped with Type P2 - Medium efficiency particle filters may be used.
Other information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear.
Color	: Colorless to Yellowish
Odor	: Characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 200 °C Calculated
Flash point	: 174 °C Closed Cup
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Solubility	: Unknown.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: 41.4 - 50.6 cSt @40°C
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

27262 PAG YF Refrigeration Lubricant 46

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

2,6-di-tert-butyl-p-cresol (128-37-0)	
LD50 oral rat	890 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value; >6000 mg/kg bodyweight; Rat)
LD50 dermal rat	> 2000 mg/kg (Rat; Literature study; OECD 402: Acute Dermal Toxicity; >2000 mg/kg bodyweight; Rat; Experimental value)
ATE US (oral)	890.000 mg/kg body weight

2,6-diisopropylphenyl isocyanate (28178-42-9)	
LD50 oral rat	1414 mg/kg (Rat)
LC50 inhalation rat (mg/l)	0.047 mg/l/4h (Rat)
ATE US (oral)	1414.000 mg/kg body weight
ATE US (vapors)	0.047 mg/l/4h
ATE US (dust, mist)	0.047 mg/l/4h

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Based on available data, the classification criteria are not met
Carcinogenicity : Not classified

2,6-di-tert-butyl-p-cresol (128-37-0)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified
Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure) : Not classified
Specific target organ toxicity (repeated exposure) : Not classified
Aspiration hazard : Not classified
Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Toxic to aquatic life.

27262 PAG YF Refrigeration Lubricant 46

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2,6-di-tert-butyl-p-cresol (128-37-0)	
LC50 fish 1	>= 0.57 mg/l (LC0; EU Method C.1; 96 h; Brachydanio rerio; Semi-static system; Fresh water; Experimental value)
EC50 Daphnia 1	0.48 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	0.199 mg/l (LC50; ECOSAR v1.00; 96 h; Pisces)
EC50 Daphnia 2	0.15 mg/l (NOEC; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)

12.2. Persistence and degradability

27262 PAG YF Refrigeration Lubricant 46	
Persistence and degradability	Not established.
2,6-di-tert-butyl-p-cresol (128-37-0)	
Persistence and degradability	Not readily biodegradable in water. Biodegradable in the soil. Adsorbs into the soil. Low potential for mobility in soil. Photooxidation in the air.
Biochemical oxygen demand (BOD)	0.51 g O ₂ /g substance
Chemical oxygen demand (COD)	2.27 g O ₂ /g substance
ThOD	2.977 g O ₂ /g substance
BOD (% of ThOD)	0.17
2,6-diisopropylphenyl isocyanate (28178-42-9)	
Persistence and degradability	Biodegradability in water: no data available.

12.3. Bioaccumulative potential

27262 PAG YF Refrigeration Lubricant 46	
Bioaccumulative potential	Not established.
2,6-di-tert-butyl-p-cresol (128-37-0)	
BCF fish 1	230 - 2500 (BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 56 days; Cyprinus carpio; Flow-through system; Fresh water; Experimental value)
Log Pow	5.1 (Experimental value)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).
2,6-diisopropylphenyl isocyanate (28178-42-9)	
Bioaccumulative potential	No bioaccumulation data available.

12.4. Mobility in soil

2,6-di-tert-butyl-p-cresol (128-37-0)	
Log Koc	Koc,PCKOCWIN v1.66; 23030; Calculated value; log Koc; PCKOCWIN v1.66; 4.362; Calculated value
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT
Not regulated for transport

TDG

No additional information available

27262 PAG YF Refrigeration Lubricant 46

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

No additional information available

15.2. International regulations

CANADA

27262 PAG YF Refrigeration Lubricant 46

WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

Revision date : 02/29/2016

Other information : None.


Full text of H-phrases: see section 16:

H302	Harmful if swallowed
------	----------------------

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



SDS US (GHS HazCom 2012)

This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of Tire Seal, Inc. The data on this sheet related only to the specific material designed herein. Tire Seal, Inc. assumes no legal responsibility for the use or reliance upon these data.