

Material Safety Data Sheet

Section 1: Product & Company Identification

Product Name: K&W® Permanent Metallic™ Block Seal

Product Number (s): 401016

Manufactured By:

CRC Industries, Inc.

885 Louis Drive

Warminster, PA 18974

www.crcindustries.com

General Information
Technical Assistance
(800) 521-3168
Customer Service
(800) 272-8963
24-Hr Emergency (CHEMTREC)
(800) 424-9300

Section 2: Hazards Identification

Emergency Overview

Appearance & Odor: Reddish brown, lumpy liquid, practically odorless

CAUTION

Irritant

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

Potential Health Effects:

EYE: Causes moderate irritation to the eyes.

SKIN: Causes moderate irritation to the skin.

INHALATION: Spray mist would be irritating to the respiratory system.

INGESTION: May cause irritation to the mouth, esophagus and stomach.

CHRONIC EFFECTS: None known

TARGET ORGANS: None known

Medical Conditions Aggravated by Exposure:

Unknown

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Name: K&W® Permanent Metallic™ Product Number (s):

Block Seal

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Water	7732-18-5	55 - 65
Sodium silicate	1344-09-8	30 - 40
Iron oxide	1309-37-1	< 1

Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician

if irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If

breathing is difficult give oxygen. Call a physician.

Ingestion: If swallowed, DO NOT induce vomiting. Get medical attention immediately.

Note to Physicians: None

Section 5: Fire-Fighting Measures

<u>Flammable Properties:</u> As defined by OSHA, this product is nonflammable.

Flash Point: None (TCC) Upper Explosive Limit: None Autoignition Temperature: None Lower Explosive Limit: None

Suitable Extinguishing Media: This material will not burn. Use extinguishing media appropriate for the surrounding

fire.

Products of Combustion: NA

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for

protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed

containers cool and to knock down vapors which may result from product

decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush

into sewers or storm drains. This product is harmful to aquatic life.

Product Name: K&W® Permanent Metallic™

Block Seal

Product Number (s):

Methods for Containment & Clean-up: Dike area

Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Avoid contact with eyes, skin and clothing. Keep container closed when not in use. Properly

clean any spilled residue with a wet cloth.

Storage Procedures: Store in a cool dry area out of direct sunlight. Store in closed container. Do not store near

acids.

Aerosol Storage Level: NA

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

	OSHA ACGIH		GIH	OTHER			
COMPONENT	TWA	STEL	TWA	STEL	TWA	SOURCE	UNIT
Water	NE	NE	NE	NE	NE		
Sodium silicate	NE	NE	NE	NE	NE		
Iron oxide	10*	NE	5*	NE	NE		mg/m ³
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

^{*} Exposure values apply to dust or respirable fraction. These values would not apply to the liquid mixture product. These would only apply to this product if it were dried to a powder or residue.

Engineering Controls: Area should have ventilation to provide fresh air. Use local exhaust to prevent accumulation

of vapors. Use mechanical means if necessary to maintain vapor levels below the exposure

guidelines. If working in a confined space, follow applicable OSHA regulations

Respiratory Protection: None required for normal work where adequate ventilation is provided. Use a self-contained

breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid

contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile or neoprene. Also, use full protective clothing if there

is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid
Color: reddish brown
Odor: practically odorless
Specific Gravity: 1.37
Initial Boiling Point: 212 F

Product Name: K&W® Permanent Metallic™ Product Number (s):

Block Seal

Freezing Point: ND Vapor Pressure: ND

Vapor Density: > 1 (air = 1) Evaporation Rate: < 1 (ether = 1)

Solubility: Complete

pH: 11.5

Volatile Organic Compounds: wt %: 0 g/L: 0 lbs./qal: 0

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: None

Incompatible Materials: Acids, ammonium salts

Hazardous Decomposition Products: Hydrogen

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

ACUTE EFFECTS

Component	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Sodium silicate	LD50	1153 mg/kg	Oral	Rat
Iron oxide	LD50	> 10,000 mg/kg	Oral	Rat

CHRONIC EFFECTS

Carcinogenicity:

Component Result

OSHA: None listed NAC: None listed NTP: None listed

Mutagenicity: No data

Other: None

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: sodium silicate – 96 Hr LC50 water flea: 247 ppm

Persistence / Degradability: This material is not persistent in aquatic systems, but its high pH when undiluted is

acutely harmful to aquatic life.

Bioaccumulation / Accumulation: No information available.

Block Seal

Mobility in Environment: No information available.

Section 13: Disposal Considerations

Disposal: This material is not a RCRA hazardous waste. (See 40 CFR Part 261.20 – 261.33)

Wastes should be collected and properly disposed. Do not dump into bodies of water, on the ground or

in a septic system.

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

Section 14: Transport Information

Proper shipping description:

US DOT (ground): Not regulated.

Special Provisions: None

Section 15: Regulatory Information

U.S. Federal

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: None

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories: Fire Hazard No

Reactive Hazard No
Release of Pressure No
Acute Health Hazard Yes
Chronic Health Hazard No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting

requirements of Section 313 of Title III of the Superfund Amendments and

Reauthorization Act of 1986 and 40 CFR Part 372:

None

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

Product Name: K&W® Permanent Metallic™ Product Number (s):

Block Seal

State Regulations

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of

California to cause cancer, birth defects or other reproductive harm: NONE

State Right to Know:

New Jersey: 1309-37-1 Pennsylvania: 1309-37-1 Massachusetts: 1309-37-1 Rhode Island: 1309-37-1

Additional Regulatory Information: None

Section 16: Other Information

NFPA: Health: 1 Flammability: 0 Reactivity: 0

HMIS: Health: 1 Flammability: 0 Reactivity: 0 PPE: B

Prepared By: Michelle Rudnick

CRC #: 902

Revision Date: 11/28/2005

Changes since last revision: MSDS reformatted in accordance with ANSI Z400.1-2004

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS: Chemical Abstract Service NA: Not Applicable Not Determined Parts per Million ND: ppm: Tag Closed Cup Not Established TCC: NE: PMCC: Pensky-Martens Closed Cup g/L: grams per Liter PPE: Personal Protection Equipment pounds per gallon lbs./gal:

TWA: Time Weighted Average STEL: Short Term Exposure Limit

OSHA: Occupational Safety and Health Administration

ACGIH American Association of Governmental Industrial Hygienists

NIOSH National Institute of Occupational Safety & Health