

# SAFETY DATA SHEET

Revision Date 20-Mar-2018 Version 4

# 1. IDENTIFICATION

**Product identifier** 

Product Name 771 NICKEL ANTI-SEIZE LUBRICANT 8OZ BT

Other means of identification

Product Code 77124

Recommended use of the chemical and restrictions on use

Recommended Use Lubricant.

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer AddressMay Also Be Distributed by:ITW PermatexITW Permatex Canada6875 Parkland Blvd.35 Brownridge Road, Unit 1Solon, OH 44139 USAHalton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

24-hour emergency phone number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

# 2. HAZARDS IDENTIFICATION

# Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1
Carcinogenicity	Category 2

#### Label elements

#### **Emergency Overview**

## Signal word Warning

May cause an allergic skin reaction Suspected of causing cancer



Revision Date 20-Mar-2018

Appearance Silver Physical state Paste Odor Petroleum

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wash face, hands and any exposed skin thoroughly after handling

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

#### **Precautionary Statements - Storage**

Store locked up

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

- Note L: The classification as a carcinogen 1 does not apply. The substance contains less than 3 % DMSO extract as measured by IP 346. This note applies only to certain complex oil derived substances in Annex I

Unknown acute toxicity

34.5 % of the mixture consists of ingredient(s) of unknown toxicity

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substance(s)

Chemical Name	CAS No	Weight-%
DISTILLATES (PETROLEUM),	64741-96-4	30 - 60
SOLVENT-REFINED HEAVY		
NAPHTHENIC		
NICKEL	7440-02-0	5 - 10
ALUMINIUM POWDER	7429-90-5	1 - 5

#### 4. FIRST AID MEASURES

#### **Description of first aid measures**

**General advice** Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

**Skin contact** IF ON SKIN:. Wash with soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Revision Date 20-Mar-2018

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

# 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

Water.

Specific hazards arising from the chemical

None in particular.

**Explosion data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

Environmental precautions

**Environmental precautions**See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel

into suitable containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

#### 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

\_\_\_\_\_

BT

#### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Store locked up.

Incompatible materials Strong oxidizing agents

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
NICKEL	TWA: 1.5 mg/m³ inhalable fraction	TWA: 1 mg/m <sup>3</sup>	IDLH: 10 mg/m³ IDLH: 10 mg/m³ Ni
7440-02-0		(vacated) TWA: 1 mg/m <sup>3</sup>	TWA: 0.015 mg/m <sup>3</sup> TWA: 0.015
			mg/m³ except Nickel carbonyl Ni
ALUMINIUM POWDER	TWA: 1 mg/m³ respirable fraction	TWA: 15 mg/m³ total dust	TWA: 10 mg/m <sup>3</sup> total dust
7429-90-5		TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 5 mg/m <sup>3</sup> respirable dust
		(vacated) TWA: 15 mg/m <sup>3</sup> total dust	TWA: 5 mg/m <sup>3</sup> Al
		(vacated) TWA: 5 mg/m³ respirable	_
		fraction (vacated) TWA: 5 mg/m <sup>3</sup> Al	
		Aluminum	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

**Respiratory protection**Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical state Paste
Appearance Silver
Odor Petroleum

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No information available
Melting point / freezing point
Rolling point / boiling range
No information available
No information available

**Boiling point / boiling range**No information available **Flash point**No information available

> 204 °C / > 399 °F

**Evaporation rate** < 1 Butyl acetate = 1

Flammability (solid, gas) No information available Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available

Relative density 1.12 Water solubility Negligible

Solubility in other solvents No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available Dynamic viscosity No information available No information available **Explosive properties Oxidizing properties** No information available

## **Other Information**

Softening pointNo information availableMolecular weightNo information available

VOC Content (%) 0

DensityNo information availableBulk densityNo information available

## 10. STABILITY AND REACTIVITY

#### Reactivity

Stable under normal conditions

#### Chemical stability

Stable under recommended storage conditions

#### Possibility of Hazardous Reactions

None under normal processing.

Hazardous polymerization does not occur.

#### Conditions to avoid

Excessive heat.

#### Incompatible materials

Strong oxidizing agents

#### **Hazardous Decomposition Products**

Carbon oxides Metal oxides

## Information on likely routes of exposure

**Inhalation** May cause irritation of respiratory tract.

**Eye contact** Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

**Skin contact** May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.

**Ingestion** Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
NICKEL	> 9000 mg/kg (Rat)	=	-
7440-02-0			

## Information on toxicological effects

Revision Date 20-Mar-2018

**Symptoms** No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** May cause sensitization by skin contact.

Germ cell mutagenicity No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
DISTILLATES	A2	Group 1	Known	X
(PETROLEUM),		•		
SOLVENT-REFINED				
HEAVY NAPHTHENIC				
64741-96-4				
NICKEL	-	Group 2B	Reasonably Anticipated	X
7440-02-0		·	, ,	

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Central Vascular System (CVS), Nasal Cavities, Respiratory system, Skin, Eyes.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 73761 mg/kg

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

37 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

#### Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

#### **Mobility**

No information available.

#### Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number Not applicable

# 77124 - 771 NICKEL ANTI-SEIZE LUBRICANT 8OZ

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status	
NICKEL	Toxic powder	
7440-02-0	Ignitable powder	
ALUMINIUM POWDER	Ignitable powder	
7429-90-5		

## **14. TRANSPORT INFORMATION**

DOT

Proper shipping name: Not regulated

<u>IATA</u>

Proper shipping name: Not regulated

**IMDG** 

Proper shipping name: Not regulated

# 15. REGULATORY INFORMATION

**International Inventories** 

**TSCA** Complies **DSL/NDSL** Complies Complies **EINECS/ELINCS** Complies **ENCS IECSC** Complies Complies **KECL** Complies **PICCS** Complies **AICS** 

## Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %	
NICKEL - 7440-02-0	0.1	
ALUMINIUM POWDER - 7429-90-5	1.0	

## SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

## **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
NICKEL 7440-02-0	-	X	Х	-

## **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
NICKEL	100 lb	-	RQ 100 lb final RQ
7440-02-0			RQ 45.4 kg final RQ

# **US State Regulations**

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name <u>California Proposition 65</u>	
NICKEL - 7440-02-0	Carcinogen

#### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
GRAPHITE	X	X	X
7782-42-5			
NICKEL	X	X	X
7440-02-0			
ALUMINIUM POWDER	X	X	X
7429-90-5			

#### **U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

## **WHMIS Hazard Class**

D2B - Toxic materials

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

Health hazards 2 Flammability 1 Instability 0 NFPA

HMIS Health hazards 2 Flammability 1 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

**Revision Date** 20-Mar-2018

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**