

Revision Date 23-Apr-2018

SAFETY DATA SHEET

Version 8

1. IDENTIFICATION		
Product identifier Product Name	2AR FORM A GASKET #2 SEALANT 1.50Z	
Product Name	ZAR FORM A GASKET #2 SEALANT 1.502	
Other means of identification		
Product Code	80015	
Recommended use of the chemical	and restrictions on use	
Recommended Use	Sealant.	
Uses advised against	No information available	
Details of the supplier of the safety	data sheet	
Manufacturer Address	May Also Be Distributed by:	
ITW Permatex	ITW Permatex Canada	
6875 Parkland Blvd.	101-2360 Bristol Circle	
Solon, OH 44139 USA	Oakville, ON Canada L6H 6M5	
	Telephone: (800) 924-6994	
24-hour emergency phone number	Chem-Tel: 800-255-3924	
	International Emergency:	
	00+1+ 813-248-0585	
	Contract Number: MIS0003453	
E-mail address	mail@permatex.com	
	2. HAZARDS IDENTIFICATION	

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1
Carcinogenicity	Category 2

Label elements

Emergency Overview			
Signal word			
Danger			
May cause an allergic skin reaction Suspected of causing cancer			

Appearance Black Physical state Paste Odor Alcohol **Precautionary Statements - Prevention** Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves **Precautionary Statements - Response** IF exposed or concerned: Get medical advice/attention Specific treatment (see supplemental first aid instructions on this label) IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse **Precautionary Statements - Storage** Store locked up **Precautionary Statements - Disposal** Dispose of contents/container to an approved waste disposal plant Hazards not otherwise classified (HNOC) Not applicable

Other Information

- Not applicable

Unknown acute toxicity

1.14 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance(s)

Chemical Name	CAS No	Weight-%
ROSIN	8050-09-7	10 - 30
ETHANOL	64-17-5	5 - 10
2-PROPANOL	67-63-0	1 - 5
METHANOL	67-56-1	0.1 - 1
METHYL ISOBUTYL KETONE	108-10-1	0.1 - 1

4. FIRST AID MEASURES

Description of first aid measures

General advice	Get medical advice/attention if you feel unwell.	
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.	
Skin contact	IF ON SKIN:. Wash skin with soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.	
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.	
Ingestion	IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an	

	unconscious person. Call a physician.			
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.			
Most important symptoms and effects, both acute and delayed				
Symptoms	See section 2 for more information.			
Indication of any immediate medica	al attention and special treatment needed			
Note to physicians	Treat symptomatically.			
	5. FIRE-FIGHTING MEASURES			
<u>Suitable extinguishing media</u> Carbon dioxide (CO2), Dry chemical,	Foam			
Unsuitable extinguishing media None.				
Specific hazards arising from the c None in particular.	hemical			
<u>Explosion data</u> Sensitivity to Mechanical Impact Sensitivity to Static Discharge	None. None.			
Protective equipment and precaution As in any fire, wear self-contained bre protective gear.	ons for firefighters Pathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full			
	6. ACCIDENTAL RELEASE MEASURES			
Personal precautions, protective ed	quipment and emergency procedures			
Personal precautions	Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin. Use personal protective equipment as required.			
Environmental precautions				
Environmental precautions	See Section 12 for additional Ecological Information.			
Methods and material for containm	ent and cleaning up			
Methods for containment	Prevent further leakage or spillage if safe to do so.			
Methods for cleaning up	Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.			
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.			
	7. HANDLING AND STORAGE			
Precautions for safe handling				
Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.			

Conditions for safe storage, including any incompatibilities

.

Storage Conditions

Store in a well-ventilated place. Keep cool.

Strong oxidizing agents

Incompatible materials

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ROSIN	-	(vacated) TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³ Formaldehyde
8050-09-7		Formaldehyde	
ETHANOL	STEL: 1000 ppm	TWA: 1000 ppm	IDLH: 3300 ppm
64-17-5		TWA: 1900 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1900 mg/m ³
		(vacated) TWA: 1900 mg/m ³	
2-PROPANOL	STEL: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm
67-63-0	TWA: 200 ppm	TWA: 980 mg/m ³	TWA: 400 ppm
		(vacated) TWA: 400 ppm	TWA: 980 mg/m ³
		(vacated) TWA: 980 mg/m ³	STEL: 500 ppm
		(vacated) STEL: 500 ppm	STEL: 1225 mg/m ³
		(vacated) STEL: 1225 mg/m ³	
METHANOL	STEL: 250 ppm	TWA: 200 ppm	IDLH: 6000 ppm
67-56-1	TWA: 200 ppm	TWA: 260 mg/m ³	TWA: 200 ppm
	S*	(vacated) TWA: 200 ppm	TWA: 260 mg/m ³
		(vacated) TWA: 260 mg/m ³	STEL: 250 ppm
		(vacated) STEL: 250 ppm	STEL: 325 mg/m ³
		(vacated) STEL: 325 mg/m ³	
		(vacated) S*	
METHYL ISOBUTYL KETONE	STEL: 75 ppm	TWA: 100 ppm	IDLH: 500 ppm
108-10-1	TWA: 20 ppm	TWA: 410 mg/m ³	TWA: 50 ppm
		(vacated) TWA: 50 ppm	TWA: 205 mg/m ³
		(vacated) TWA: 205 mg/m ³	STEL: 75 ppm
		(vacated) STEL: 75 ppm	STEL: 300 mg/m ³
		(vacated) STEL: 300 mg/m ³	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls	Showers	
	Eyewash stations	
	Ventilation systems	

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.
Respiratory protection	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Paste
Appearance	Black
Odor	Alcohol

Odor threshold	No information available		
Property	Values No information available	Remarks • Method	
pH Molting point (freezing point	No information available		
Melting point / freezing point	82 °C / 180 °F		
Boiling point / boiling range		ASTM D 4359	
Flash point	Does not apply 7.7	Fther = 1	
Evaporation rate	No information available		
Flammability (solid, gas)	NO INICITIATION AVAILABLE		
Flammability Limit in Air			
Upper flammability limit:	No information available		
Lower flammability limit:	No information available		
Vapor pressure	33 mm Hg @ 68°F	A:- 4	
Vapor density	2.0	Air = 1	
Relative density	1.5		
Water solubility	Partially soluble		
Solubility in other solvents	No information available		
Partition coefficient	No information available		
Autoignition temperature	No information available		
Decomposition temperature	No information available		
Kinematic viscosity	No information available		
Dynamic viscosity	No information available		
Explosive properties	No information available		
Oxidizing properties	No information available		
Other Information			
Softening point Molecular weight VOC Content (%)	No information available No information available 11% No information available		
Density Bulk density	No information available		
Durk density			

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products Carbon oxides Aldehydes Carboxylic acids

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation

May cause irritation of respiratory tract.

Eye contact

Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact

Ingestion

May cause skin irritation and/or dermatitis. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ROSIN	= 7600 mg/kg (Rat) = 3000 mg/kg	> 2500 mg/kg (Rabbit)	= 1.5 mg/L (Rat) 4 h
8050-09-7	(Rat)		
ETHANOL	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
64-17-5			
2-PROPANOL	5050 mg/kg	12800 mg/kg	= 72600 mg/m ³ (Rat) 4 h
67-63-0			
METHANOL	= 6200 mg/kg (Rat)	= 15800 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h = 64000
67-56-1		· · ·	ppm (Rat)4 h
METHYL ISOBUTYL KETONE	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	= 8.2 mg/L (Rat) 4 h
108-10-1		· ·	

Ingestion may cause irritation to mucous membranes.

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	No information	on available.			
Germ cell mutagenicity	No information available.				
Carcinogenicity	The table be	low indicates whether each	agency has listed any ing	gredient as a carcinogen.	
Chemical Name	ACGIH	IARC	NTP	OSHA	
ETHANOL 64-17-5	A3	-	Known	Х	
METHYL ISOBUTYL KETONE 108-10-1	A3	Group 2B	-	X	
Group 1 - Carcinogenic to Group 2B - Possibly Carc NTP (National Toxicolo Known - Known Carcinog OSHA (Occupational Sa X - Present	ncy for Research on Cance o Humans inogenic to Humans gy Program) ien ifety and Health Administra	tion of the US Department o			
Chronic toxicity		dverse effects on the bone effects. Contains a known			
Target Organ Effects	Blood, Central nervous system, Eyes, Liver, Reproductive System, Respiratory system, Skin, Thyroid.				
The following values are ATEmix (oral) ATEmix (dermal)	calculated based on ch 11332 mg/k 12237 mg/k	0	ument .		

12. ECOLOGICAL INFORMATION

Ecotoxicity

2.425 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

102.2 mg/l

Persistence and degradability

ATEmix (inhalation-dust/mist)

No information available.

Bioaccumulation

No information available.

<u>Mobility</u>

No information available.

Chemical Name	Partition coefficient
ETHANOL	-0.32
64-17-5	
2-PROPANOL	0.05
67-63-0	
METHANOL	-0.77
67-56-1	
METHYL ISOBUTYL KETONE	1.19
108-10-1	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Do not reuse container.
US EPA Waste Number	Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ETHANOL	Toxic
64-17-5	Ignitable
2-PROPANOL	Toxic
67-63-0	Ignitable
METHANOL	Toxic
67-56-1	Ignitable

14. TRANSPORT INFORMATION

DOT Proper shipping name:	Not regulated
IATA Proper shipping name:	Not regulated
IMDG Proper shipping name:	Not regulated

15. REGULATORY INFORMATION				
International Inventories				
TSCA	Complies			
DSL/NDSL	Complies			
EINECS/ELINCS	Complies			
ENCS	Not determined			
IECSC	Complies			
KECL	Complies			
PICCS	Complies			
AICS	Complies			

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances ENCS - Japan Existing and New Chemical Substances IECSC - China Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances AICS - Australian Inventory of Chemical Substances

US Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
2-PROPANOL - 67-63-0	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

<u>CERCLA</u>

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
METHANOL	5000 lb	-	RQ 5000 lb final RQ
67-56-1			RQ 2270 kg final RQ
METHYL ISOBUTYL KETONE	5000 lb	-	RQ 5000 lb final RQ
108-10-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
ETHANOL - 64-17-5	Carcinogen
	Developmental
CRYSTALLINE SILICA - 14808-60-7	*Carcinogen
TITANIUM DIOXIDE - 13463-67-7	*Carcinogen (airborne, unbound particles of respirable size)
METHANOL - 67-56-1	Developmental
CARBON BLACK - 1333-86-4	*Carcinogen (airborne, unbound particles of respirable size)
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen
	Developmental

• *The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product

• Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage

• Ethanol has been shown to be a reproductive toxin only when consumed as an alcoholic beverage

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
KAOLIN	Х	Х	Х
1332-58-7			
ETHANOL	Х	X	Х

64-17-5			
2-PROPANOL	X	X	X
67-63-0			
CRYSTALLINE SILICA	X	Х	X
14808-60-7			
TITANIUM DIOXIDE	X	Х	X
13463-67-7			
METHANOL	X	Х	X
67-56-1			
CARBON BLACK	X	Х	X
1333-86-4			
METHYL ISOBUTYL KETONE	X	X	X
108-10-1			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 1	Instability 0	-
HMIS	Health hazards 2	Flammability 1	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 23-Apr-2018

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet