

ITW Permatex  
 10 Columbus Blvd.  
 Hartford, CT 06106 USA  
 Telephone: 1-87-Permatex  
 (877) 376-2839  
 Emergency: 800-255-3924 (ChemTel)  
 International Emergency: +01-813-248-0585

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** 122GA CHAIN LUBE 5 OZ AE  
**Item No:** 80075  
**Product Type:** Aerosol lubricant

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC 64742-53-6	30-60	5 mg/m <sup>3</sup> TWA ACGIH	Not listed
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC 64742-52-5	10-30	Not listed	Not listed
PETROLEUM GASES, LIQUEFIED, SWEETENED 68476-86-8	10-30	Not listed	Not listed

### 3. HAZARDS IDENTIFICATION

**Toxicity:** Exposure to vapors or mist may result in irritation of the respiratory tract. Intentional misuse by concentrating and inhaling the vapor may be harmful or fatal. Harmful if swallowed. May cause eye and skin irritation. Prolonged exposure may cause liver and kidney effects and may affect the central nervous system.

**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation

**Signs and Symptoms of Exposure:** Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation. May cause pain, redness or swelling of the eyes and excessive blinking and tear production. Skin redness.

**Aggravated Medical Condition:** Preexisting pulmonary and dermatological disorders.

### 4. FIRST AID MEASURES

**Ingestion:** Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.

**Skin Contact:** Wash off with soap and water. If skin irritation persists, call a physician.

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

### 5. FIRE FIGHTING MEASURES

**Flash Point °F(C°):** Flammable aerosol based on flame projection test

**Recommended Extinguishing Media:** Carbon dioxide, Dry chemical, Foam

**Special Fire-Fighting Procedures:** Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

**Hazardous Products of Combustion:** Oxides of carbon

**Unusual Fire/Explosion Hazards:** Contents under pressure. Exposure to temperatures over 120 degrees F. may cause bursting or venting. Keep containers cool.

**Lower Explosive Limit:** Not determined

**Upper Explosive Limit:** Not determined

## 6. ACCIDENTAL RELEASE MEASURES

**Spill Procedures:** Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

## 7. HANDLING AND STORAGE

**Storage:** Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C).  
**Handling:** Do not use near heat, sparks or open flame. Do not inhale vapors. Avoid contact with skin and eyes. Wash hands before eating and smoking.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Eyes:** Safety glasses.  
**Skin:** Neoprene or nitrile gloves recommended.  
**Ventilation:** General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.  
**Respiratory Protection:** An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Brown liquid  
**Odor:** Mild  
**Boiling Point:** >500°F  
**pH:** Does not apply  
**Solubility in Water:** Nil  
**Specific Gravity:** 0.87-0.97  
**VOC(Wt.%):** 15.6%  
**Vapor Pressure:** Not determined  
**Vapor Density (Air=1):** >1  
**Evaporation Rate:** <1 (butyl acetate = 1)

## 10. STABILITY AND REACTIVITY

**Chemical Stability:** Stable at normal conditions  
**Hazardous Polymerization:** Will not occur  
**Incompatibilities:** Strong oxidizers  
**Conditions to Avoid:** Keep away from heat, sparks and open flame. - No smoking.  
**Hazardous Products of Combustion:** Oxides of carbon

## 11. TOXICOLOGICAL INFORMATION

See Section 3

## 12. ECOLOGICAL INFORMATION

No data available

## 13. DISPOSAL CONSIDERATIONS

**Recommended Method of Disposal:** Disposal should be made in accordance with federal, state and local regulations. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash.  
**US EPA Waste Number:** D001 as per 40CFR 261.21

## 14. TRANSPORTATION INFORMATION

**DOT (49CFR 172)**

**U.S. Department of Transportation - DOT - 49 CFR (Ground)**

**DOT Shipping Name:** Aerosols, Limited Quantity  
**Hazard Class:** Class 2.1  
**UN/ID Number:** UN 1950

**IATA (Air)**

**Proper Shipping Name:** Consumer Commodity (Not more than 1 liter)  
**Class or Division:** Class 9  
**UN/ID Number:** ID 8000

**IMDG (Vessel)**

**Proper Shipping Name:** Aerosols, Limited Quantity  
**Hazard Class:** Class 2.1

**Product Name:** 122GA CHAIN LUBE 5 OZ AE

**Item No.** 80075

**UN Number:** UN 1950

**Marine Pollutant:** None

## 15. REGULATORY INFORMATION

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

**California Proposition 65:** No California Prop 65 chemicals are known to be present.

**TSCA Inventory Status:** All components of this product are listed (or exempt) on the EPA TSCA inventory.

## 16. OTHER INFORMATION

**Estimated NFPA Rating:** HEALTH 1, FLAMMABILITY 4, REACTIVITY 0.

**Estimated HMIS Classification:** HEALTH 1, FLAMMABILITY 4, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

HMIS is a registered trademark of the National Paint and Coatings Association

**Prepared By:** Denise Boyd, Manager-Environmental, Health & Safety

**Company:** ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106

**Telephone No.:** 1-87-Permatex (877) 376-2839

**Revision Date:** April 26, 2012

**Revision Number:** 5