SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: PENTOSIN PENTO HIGH PERFORMANCE II 5W-40

PRODUCT NUMBER:

TRADE NAME: PENTOSIN PENTO HIGH

PERFORMANCE II 5W-40

GENERAL USE: Automotive Motor Oil

CHEMICAL FAMILY: Blend of Base Mineral Oils Organo

Calcium and Organo Zinc additives.

PRODUCT DESCRIPTION:

Brown colored liquid with characteristic odor.

MANUFACTURED FOR

CRP Industries TELEPHONE NUMBER (General Inquiries)

609-578-4100

ADDRESS (NUMBER, STREET, P.O. BOX)

35 Commerce Drive

(CITY, STATE AND ZIP CODE)

Cranbury NJ 08512 USA



January 11, 2011 **EFFECTIVE DATE:** DATE OF EXPIRATION: January 10, 2014

New Issue SUPERSEDES DATE:

CHEMTEL 24-HOUR EMERGENCY TELEPHONE NUMBERS

1-800-255-3924 North America (Toll Free)

813-248-0585 International and Local Calls

SECTION 2 - HAZARDS IDENTIFICATION

COUNTRY

ChemTel

EMERGENCY OVERVIEW

OSHA HAZARDS: None. WHMIS Hazard Classes: None. Do not breathe vapors or mists. Do not get in eyes. May irritate skin, especially upon prolonged contact; Avoid contact with skin and clothing. Wash thoroughly after handling. Aspirant hazard if ingested then requritated.

CANADA (WHMIS) SYMBOL(S) USA (DOT)

GHS HAZARD SYMBOLS

None None None

HMIS HAZARD RATINGS

HEALTH: 0 = INSIGNIFICANT, 1 = SLIGHT, 2 = MODERATE FLAMMABILITY: 3 = HIGH, 4 = EXTREME * - CHRONIC HEALTH HAZARD

0 PHYSICAL HAZARD: 0

REQUIRED PERSONAL PROTECTIVE EQUIPMENT:

HMIS PERSONAL PROTECTIVE EQUIPMENT LETTER:

B





Wear safety glasses and impervious gloves. See Section 8 for details on **Personal Protective Equipment.**

1

POTENTIAL HEALTH EFFECTS

ACUTE EXPOSURE EFFECTS

INHALATION:

Irritation of the respiratory tract may occur from inhalation of product mists, especially with prolonged exposure. Mineral oil content can produce chemical pneumonitis.

SKIN:

Irritation and itching may occur and prolonged contact may cause dermatitis. The problem may be exacerbated by liquid becoming trapped against the skin by contaminated clothing and shoes; skin absorption can occur in these cases.

Tearing, redness and pain may occur; chemical conjunctivitis may result, especially in cases where the eyes are not promptly rinsed.

Ingestion may result in nausea, vomiting, and gastrointestinal irritation, especially in cases of ingestion of large quantities. Vomiting and subsequent aspiration of product into the lungs may lead to pneumonitis.

CHRONIC EXPOSURE EFFECTS

Dermatitis may occur from chronic or prolonged skin exposure. Eye irritation may occur with chronic/prolonged eye exposure to product.

CARCINOGENICITY:

NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO CALIFORNIA, Prop.65? ESIS NOTATION?

PRODUCT NAME: PENTOSIN PENTO HIGH PERFORMANCE II 5W-40

PRODUCT NUMBER:

SECTION 3 - HAZARDOUS INGREDIENTS				
Hazardous Components	% (by Weight)	CAS#		
Calcium (long chain alkyl) salicylate	<2.5%	990001-09-5		
Zinc-Dialkyldithiophosphate	<2.5%	68649-42-3		

NOTES: This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS). Hazard symbols and risk phrases are based on maximum listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200) or the Canadian Workplace Hazardous Materials Information System (WHMIS) and are considered trade secrets under relevant US and Canadian Federal Laws.

SECTION 4 - FIRST AID MEASURES

INHALATION:

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, use mouth-to-mouth resuscitation.

EYES:

Rinse eyes with cool potable water for 5 minutes, then remove contact lenses if present. Wash for at least 10 more minutes with cool potable water lifting upper and lower lids occasionally. Seek medical attention if irritation persists.

SKIN

Wash contact areas with soap and water. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury. If heated product causes burns, seek medical assistance.

INGESTION:

Contact medical authorities immediately. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs naturally, have victim lean forward to avoid aspiration of regurgitant. Give 1-2 glasses of water to victim if victim is conscious and able to swallow and seek immediate medical assistance. Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES

DATA RELATED TO FIRE:

FLASH POINT: >464°F / >240°C AUTO-IGNITION TEMPERATURE: NE

FLAMMABLE/EXPLOSIVE LIMITS: LOWER: NE UPPER: NE

SENSITIVITY TO MECHANICAL IMPACT/ STATIC DISCHARGE: None

GENERAL HAZARDS:

Product is minimally combustible at elevated temperatures. Irritating and/or harmful vapors may be emitted under fire conditions.

SUITABLE EXTINGUISHING MEDIA:

CO2, Dry Chemical, or water spray mists.

UNSUITABLE EXTINGUISHING MEDIA:

Choose extinguishing media with respect to total fire hazard; avoid water streams as this will spread fire.

FIRE FIGHTING PROCEDURES:

Prevent product runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use protective equipment and self-contained breathing apparatus (SCBA), and should fire based on total fire hazards. Use of water spray or fog to cool fire exposed surfaces and prevent the rupture of containers is acceptable if runoff control is implemented.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Product containers will rupture and leak from heat; released product will pose a slip and fall hazard to fire-fighting personnel. Use water spray or fog to cool fire-exposed containers where runoff control is implemented.

HAZARDOUS COMBUSTION PRODUCTS:

Carbon monoxide and dioxide, hydrocarbon compounds, smoke, soot, fumes, - fire conditions only.

PRODUCT NAME: PENTOSIN PENTO HIGH PERFORMANCE II 5W-40

PRODUCT NUMBER:

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Stop leak if you can do it without risk. Small Spills: Absorb with earth, sand or other noncombustible material and transfer to containers for later disposal. Recover by pumping or with suitable absorbent. Large Spills: Prepare earthen or manufactured dikes ahead of spill; prevent discharge or entry into bodies of water, sewers, basements or confined areas. For large spills or spills on water, contact local authorities and the National Response Center toll-free at (800)424-8802. Avoid direct discharge to watercourses.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Handling: Prevent small spills and leakage to avoid slip hazard. Wear personal protective equipment. Keep containers tightly closed. Do not store with incompatible materials. KEEP OUT OF THE REACH OF CHILDREN.

Storage: Do not store in open or unlabelled containers.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION				
Component	CAS#	ACGIH Exposure Limits (mg/m³ unless otherwise noted)	OSHA Exposure Limits (mg/m³ unless otherwise noted)	
Calcium (long chain alkyl) salicylate	990001-09-5	NE	NE	
Zinc-Dialkyldithiophosphate	68649-42-3	NE	NE	

PERSONAL PROTECTION

RESPIRATORY PROTECTION:

Not required for normal work situations where adequate ventilation is provided. Use NIOSH European EN-149 approved self contained, positive pressure respirators or Self-Contained Breathing Apparatus (SCBA) for emergencies and in situations where air may be displaced by vapors. Follow OSHA Std. 29CFR 1910.134.

PROTECTIVE GLOVES:

Use impervious gloves if there is prolonged or repeated contact of liquid with skin. Solvex gloves recommended.

EYE PROTECTION:

Safety glasses with side shields required.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

No skin protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

ENGINEERING CONTROLS:

Eyewash fountain or emergency eyewash bottle should be present in work area. Personal protective clothing and use of equipment must be in accordance with 29CFR 1910.132 and 29CFR 1910.133.

WORK / HYGIENIC PRACTICES:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES			
APPEARANCE AND ODOR	VAPOR PRESSURE		
Brown colored liquid with charecteristic odor.	NE		
ODOR THRESHOLD	SPECIFIC GRAVITY (WATER = 1)		
NA	0.846 g/cm ³ at 20°C, 68°F		
FREEZING / MELTING POINT	BOILING POINT		
-42°C, -44°F	>200°C, >392°F		
SOLUBILITY IN WATER	COEFFICIENT OF WATER / OIL DISTRIBUTION		
Insoluble	Not Determined but favors oil.		
рН	SOLUBILITY IN ORGANIC SOLVENTS		
NA	Variable, dependent upon solvent		
FLASH POINT	VISCOSITY		
>464°F / >240°C	168 mm²/s (DIN EN ISO 3104) - Kinematic		

PRODUCT NAME: PENTOSIN PENTO HIGH PERFORMANCE II 5W-40 PRODUCT NUMBER: SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES (Continued) VAPOR DENSITY (AIR = 1) FLAMMABLE LIMITS LEL: NE UEL: NE AUTOIGNITION TEMPERATURE EVAPORATION RATE (Butyl Acetate = 1) Not Determined VOLATILE ORGANIC COMPOUND (VOC) INFORMATION Not Known. SECTION 10 - STABILITY AND REACTIVITY CONDITIONS TO AVOID: STABILITY Stable under normal conditions. Excessive heat. Oxidizers. INCOMPATIBILITY (MATERIALS TO AVOID): Incompatible with strong oxidizing agents. HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Carbon monoxide and dioxide, hydrocarbon compounds, smoke, soot, fumes, - fire conditions only. HAZARDOUS POLYMERIZATION: CONDITIONS TO AVOID: Will not occur. None related to hazardous polymerization. SECTION 11 - TOXICOLOGICAL INFORMATION **Complete Product** Oral LD₅₀ Not Known - ingested product is aspirant hazard if regurgitated. Dermal LD₅₀ Not Known but capable of producing mild irritation. Inhalation LC₅₀ Not Known - ingested product is aspirant hazard if regurgitated. Mild irritant to eyes; possible mild irritant to skin. Irritation / Sensitization No ingredients have been identified by IARC, NTP, OSHA, or ECHA to be carcinogens. Carcinogenicity Mutagenicity Not Known Reproductive Toxicity Not Known Teratogenicity Not Known **Product Components** LC50 of Ingredient LD50 of Ingredient CAS# Component (Inhalation, Rat - unless otherwise (Oral, Rat - unless otherwise specified) specified) Calcium (long chain alkyl) salicylate NE ΝE 990001-09-5 Zinc-Dialkyldithiophosphate 68649-42-3 NE NE **SECTION 12 - ECOLOGICAL INFORMATION** Water hazard class 2 (Self-assessment): hazardous for aquatic organisms. Do not allow product to reach ground water, water bodies or sewage system. SECTION 13 - DISPOSAL CONSIDERATIONS WASTE DISPOSAL METHOD: Recycling of used/waste product is preferable to simple disposal. Product is suitable for supervised incineration at very high temperatures to prevent formation of undesirable combustion products. End user bears the responsibility to discard unused or waste product in accordance with local, state, and federal laws and regulations. **SECTION 14 - TRANSPORT INFORMATION** PROPER SHIPPING NAME: Not regulated

DOT HAZARD CLASS / Pack Group: Not regulated IATA HAZARD CLASS / Pack Group: Not regulated REFERENCE: 49 CFR, IATA, IMDG, RID/ADR 2009 IMDG HAZARD CLASS: Not regulated UN / NA IDENTIFICATION NUMBER: RID/ADR Dangerous Goods Code: None Not regulated LABEL: Not regulated TDG Class / Pack Group: Not regulated HAZARD SYMBOLS: Hazard Identification Number (HIN): Not regulated None

Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EU, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

PRODUCT NAME: PENTOSIN PENTO HIGH PERFORMANCE II 5W-40

PRODUCT NUMBER:

SECTION 15 - REGULATORY INFORMATION

TSCA (USA - Toxic Substance Control Act): Components listed under section 8(b).

SARA TITLE III (USA - Superfund Amendments and Reauthorization Act):

Acute Health: NO Chronic Health: NO Fire: NO Sudden Release of Pressure: NO

Reactive: NO

SARA 313 REPORTABLE INGREDIENTS: No ingredients are reportable.

EPCRA (Emergency Planning and Community Right-to-Know Act): This material contains no extremely hazardous substances.

CERCLA (USA - Comprehensive Response Compensation and Liability Act): None listed.

Clean Water Act (CWA): No listings as Hazardous Substances, Priority Pollutants, or Toxic Pollutants under the CWA.

Clean Air Act (CAA): No listings under the CAA.

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986: No components listed.

State Right to Know Laws: None of the components are listed.

CPR (Canadian Controlled Products Regulations): This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations.

WHMIS Class: Not a controlled substance.

IDL (Canadian Ingredient Disclosure List): None listed.

DSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List): Listed on DSL.

SECTION 16 - OTHER INFORMATION

Legend:

ACGIH American Congress of Government Industrial Hygienists

CAS Chemical Abstracts Service

EINECS European Inventory of Existing Commercial Chemical Substances

HMIS Hazardous Materials Identification System
IARC International Agency for Research on Cancer
NA Not Available ND Not Determined
NE Not Established NR Not Reported
NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

REVISION SUMMARY: New edition authored 1/11/2011. JTV

MSDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com



The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.