

Valvoline™ DAILY PROTECTION SAE-40 Motor Oil

Version: 1.8	Revision Date: 01/03/2023	Print Date: 06/21/2023
SECTION 1. IDENTIFICATION		
Product name	: Valvoline™ DAILY PROTECTION SAE-40 Motor Oil	
Product code	: 822400	
Manufacturer or supplier's	details	
Company name of supplier	: Valvoline LLC	
Address	: 100 Valvoline Way Lexington, KY 40509 United States of America (USA)	
Telephone	: 1-800-TEAMVAL (1-800-832-6825)	
E-mail address	: SDS@valvoline.com	
Emergency telephone number	: +1-800-VALVOLINE (+1-800-825-8654)	

### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)
Not a hazardous substance or mixture.
GHS label elements
Not a hazardous substance or mixture.
Other hazards
None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

Concentration (% w/w)

CAS-No.



/ersion: 1.8	Revi	sion Date: 01/03/2023		Print Dat 06/21/202
DISTILLATES (PETROLEUN HYDROTREATED HEAVY PARAFFINIC	Л),	64742-54-7	>= 80	) - < 90
DISTILLATES (PETROLEUN HYDROTREATED HEAVY PARAFFINIC	Л),	64742-54-7	>= 1.5	i - < 5
Actual concentration is withh	eld as	a trade secret		
ECTION 4. FIRST AID MEASU	RES			
General advice	: [	Do not leave the victim	unattended.	
If inhaled	6	f unconscious, place ir advice. f symptoms persist, ca	n recovery position and see Il a physician.	k medical
In case of eye contact	F	Remove contact lenses Protect unharmed eye. f eye irritation persists		
If swallowed	ם ז	Keep respiratory tract of Do not give milk or alco Never give anything by f symptoms persist, ca	bholic beverages. mouth to an unconscious (	person.
Most important symptoms and effects, both acute and delayed	: 1	No symptoms known o	r expected.	
Notes to physician	: 1	Freat symptomatically.		
	1	No hazards which requ	ire special first aid measure	es.
ECTION 5. FIREFIGHTING ME	ASUR	ES		
Hazardous combustion products	: 1	No hazardous combus	tion products are known	

Further information	:	Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.



Valvoline™ DAILY PROTECTION SAE-40 Motor Oil

Version: 1.8	1.8 Revision Date: 01/03/2023 P 06		
SECTION 6. ACCIDENTAL RELE	EAS	E MEASURES	
Environmental precautions	:	If the product contaminates rivers and lakes or drain respective authorities.	is inform
Methods and materials for containment and cleaning up	:	Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.	
SECTION 7. HANDLING AND ST	OR	AGE	
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.	

Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area.
Conditions for safe storage	:	Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	:	No materials to be especially mentioned.
Further information on storage stability	:	No decomposition if stored and applied as directed.

# SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate	5 mg/m3	ACGIH



ersion: 1.8	Revision Date: 01/03/2023	Print Date 06/21/202
	matter)	
Personal protective equip	ent	
Respiratory protection	: No personal respiratory protective equi required.	pment normally
Eye protection	: Safety glasses	
Skin and body protection	: Protective suit	
Hygiene measures	: General industrial hygiene practice.	
ECTION 9. PHYSICAL AND CH	EMICAL PROPERTIES	
Appearance	: liquid	
Colour	: amber	
Odour	: No data available	
Odour Threshold	: No data available	
рН	: No data available	
Melting point/freezing point	: No data available	
Boiling point/boiling range	: 600.01 °F / 315.56 °C (1,013.333333 hPa) Calculated Phase Transition Liquid/Ga	as
Flash point	: 478 °F / 248 °C	
	Method: Cleveland open cup	
Evaporation rate	: No data available	
Flammability (solid, gas)	: No data available	
Self-ignition	: No data available	
Upper explosion limit / Upper flammability limit	: No data available	
	No data available	
Lower explosion limit / Lower	: No data available	



Valvoline™ DAILY PROTECTION SAE-40 Motor Oil

Version: 1.8	Re	vision Date: 01/03/2023	Print Date: 06/21/2023
flammability limit			
		No data available	
Vapour pressure	:	0.1 hPa (68 °F / 20 °C) Calculated Vapor Pressure	
Relative vapour density	:	No data available	
Relative density	:	No data available	
Density	:	0.8861 g/cm3 (60.01 °F / 15.56 °C)	
Solubility(ies) Water solubility	:	negligible	
Solubility in other solvents	:	No data available	
Partition coefficient: n- octanol/water	:	No data available	
Decomposition temperature	:	No data available	
Viscosity Viscosity, dynamic	:	No data available	
Viscosity, kinematic	:	127 mm2/s (104 °F / 40 °C)	
Oxidizing properties	:	No data available	

## SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: Stable under recommended storage conditions. No hazards to be specially mentioned.
Conditions to avoid	: None known.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.



rsion: 1.8	Revision Date: 01/03/2023	Print Date 06/21/202
CTION 11. TOXICOLOGI		
Acute toxicity Not classified based on a	available information.	
Product: Acute dermal toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method	
Components:		
DISTILLATES (PETRO	_EUM), HYDROTREATED HEAVY PARAFFINIC:	
Acute oral toxicity	: LD50 (Rat): > 15 g/kg	
Acute dermal toxicity	: LD50 (Rabbit): > 5 g/kg	
DISTILLATES (PETRO	_EUM), HYDROTREATED HEAVY PARAFFINIC:	
Acute oral toxicity	: LD50 (Rat): > 15 g/kg	
Acute dermal toxicity	: LD50 (Rabbit): > 5 g/kg	
Skin corrosion/irritatio		
Components:		
DISTILLATES (PETRO	_EUM), HYDROTREATED HEAVY PARAFFINIC:	
Assessment	: Slight, transient irritation	
Result	: Slight, transient irritation	
DISTILLATES (PETRO	_EUM), HYDROTREATED HEAVY PARAFFINIC:	
	: Slight, transient irritation	
Result	: Slight, transient irritation	
Serious eye damage/ey		
Not classified based on	available information.	
<u>Components:</u>		
•	_EUM), HYDROTREATED HEAVY PARAFFINIC:	
Result Assessment	: No eye irritation : No eye irritation	
A3963911611	. No eye initation	
DISTILLATES (PETRO	_EUM), HYDROTREATED HEAVY PARAFFINIC:	
Result Assessment	<ul><li>No eye irritation</li><li>No eye irritation</li></ul>	



Valvoline™ DAILY PROTECTION SAE-40 Motor Oil

Version: 1.8

Revision Date: 01/03/2023

Print Date: 06/21/2023

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Components:

### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity -	:	Classified based on DMSO extract content < 3% (Regulation
Assessment		(EC) 1272/2008, Annex VI, Part 3, Note L)

## DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity -:Classified based on DMSO extract content < 3% (Regulation</th>Assessment(EC) 1272/2008, Annex VI, Part 3, Note L)

- **IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- **OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
- **NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

#### **Reproductive toxicity**

Not classified based on available information.

### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

### Aspiration toxicity

Not classified based on available information.

#### Components:

### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

No aspiration toxicity classification



rsion: 1.8	Revision Date: 01/03/2023		Print Da 06/21/20
Further information			
Product:			
Remarks	No data a	vailable	
CTION 12. ECOLOGICAL INFO	MATION		
Ecotoxicity			
Product:			
Ecotoxicology Assessment			
Acute aquatic toxicity	Not classi	fied based on available information.	
Chronic aquatic toxicity	Not classi	fied based on available information.	
Components:			
DISTILLATES (PETROLEUM	HYDROTRE	EATED HEAVY PARAFFINIC:	
Toxicity to fish		h): > 100 mg/l time: 96 h	
Toxicity to daphnia and other aquatic invertebrates		uatic invertebrates): > 10,000 mg/l time: 48 h	
Toxicity to algae/aquatic plants		ae, algal mat (Algae)): > 100 mg/l time: 72 h	
Toxicity to fish (Chronic toxicity)	NOEC (Fi	sh): 10 mg/l	
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	NOEC (A	quatic invertebrates): 10 mg/l	
Ecotoxicology Assessment			
Acute aquatic toxicity	Not classi	fied based on available information.	
Chronic aquatic toxicity	Not classi	fied based on available information.	
DISTILLATES (PETROLEUM	HYDROTRE	EATED HEAVY PARAFFINIC:	
Ecotoxicology Assessment			
		field be and an ever lable information	



Valvoline™ DAILY PROTECTION SAE-40 Motor Oil

rsion: 1.8	Re	evision Date: 01/03/2023	Print Date 06/21/202
Chronic aquatic toxicity	:	Not classified based on available information.	
<b>Persistence and degradabil</b> No data available	lity		
Bioaccumulative potential			
Components:			
DISTILLATES (PETROLEUN Partition coefficient: n- octanol/water		IYDROTREATED HEAVY PARAFFINIC: log Pow: Expected > 7	
<b>Mobility in soil</b> No data available			
Other adverse effects			
Product: Ozone-Depletion Potential	:	Regulation: 40 CFR Protection of Environment; Pa Protection of Stratospheric Ozone - CAA Section Substances Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as de U.S. Clean Air Act Section 602 (40 CFR 82, Subp B).	602 Class I efined by the
Additional ecological information	:	No data available	

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

#### International Regulations

#### UNRTDG

Not regulated as a dangerous good

# IATA-DGR

Not regulated as a dangerous good

### IMDG-Code

Not regulated as a dangerous good



Valvoline™ DAILY PROTECTION SAE-40 Motor Oil

Version: 1.8

Revision Date: 01/03/2023

Print Date: 06/21/2023

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## **National Regulations**

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

## SECTION 15. REGULATORY INFORMATION

## **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	No SARA Hazards	

SARA 313	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis)
	reporting levels established by SARA Title III, Section 313.

### Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

### Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act



Valvoline™ DAILY PROTECTION SAE-40 Motor Oil

Version: 1.8	Revision Date: 01/03/2023	Print Date: 06/21/2023
US State	e Regulations	
Massac	husetts Right To Know	
	Lubricating oils (petroleum), hydrotreated	64742-58-1
Pennsy	vania Right To Know	
	DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
	DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-62-7
	NAPHTHENIC DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
Maine C	hemicals of High Concern	
	Lubricating oils (petroleum), hydrotreated	64742-58-1
Marraan	PROPRIETARY OF LUBRIZOL 7065C	Not Assigned
vermon	t Chemicals of High Concern Lubricating oils (petroleum), hydrotreated	64742-58-1
	PROPRIETARY OF LUBRIZOL 7065C	Not Assigned
Washing	gton Chemicals of High Concern	
	Lubricating oils (petroleum), hydrotreated PROPRIETARY OF LUBRIZOL 7065C	64742-58-1 Not Assigned
Californ	ia List of Hazardous Substances	rtor / tooignou
	DISTILLATES (PETROLEUM), HYDROTREATED HEAVY	64742-54-7
	PARAFFINIC DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
Californ	ia Permissible Exposure Limits for Chemical Contaminants	
	DISTILLATES (PETROLEUM), HYDROTREATED HEAVY	64742-54-7
	PARAFFINIC DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
The con	nponents of this product are reported in the following invent	ories:
TCSI	: On the inventory, or in compliance with	n the inventory
TSCA	: All substances listed as active on the T	SCA inventory
AIIC	: Not in compliance with the inventory	
DSL	: All components of this product are on t	he Canadian DSL
ENCS	: Not in compliance with the inventory	
ISHL	: Not in compliance with the inventory	
KECI	: On the inventory, or in compliance with	the inventory



Valvoline™ DAILY PROTECTION SAE-40 Motor Oil

Version: 1.8	Revision Date:         01/03/2023         Print Date:           06/21/2023         06/21/2023
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
NZIoC	: On the inventory, or in compliance with the inventory
TECI	: Not in compliance with the inventory

## **TSCA** list


No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

#### Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

### **SECTION 16. OTHER INFORMATION**



### Full text of other abbreviations

ACGIH	:	USA.
OSHA Z-1	:	USA.
		Limits

ACGIH Threshold Limit Values (TLV) Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

1

0

1

0



Valvoline™ DAILY PROTECTION SAE-40 Motor Oil

Version: 1.8

Revision Date: 01/03/2023

Print Date: 06/21/2023

ACGIH / TWA:8-hour, time-weighted averageOSHA Z-1 / TWA:8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL -Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS -Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA -National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD -Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS -Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

Revision Date

: 01/03/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the



Valvoline™ DAILY PROTECTION SAE-40 Motor Oil

Version: 1.8

Revision Date: 01/03/2023

Print Date: 06/21/2023

specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Internal information : R0178051