

Valvoline™ HIGH MILEAGE with MaxLife™
Technology SAE 10W-30 Synthetic Blend Motor
Oil

Version: 2.0 Revision Date: 06/14/2023 Print Date: 06/21/2023

SECTION 1. IDENTIFICATION

Product name : Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE

10W-30 Synthetic Blend Motor Oil

Product code : 881161

Manufacturer or supplier's details

Company name of supplier : Valvoline Global Operations

Address : 100 Valvoline Way

Lexington, KY 40509

United States of America (USA)

Telephone : 1-800-TEAMVAL (1-800-832-6825)

E-mail address : SDS@valvolineglobal.com

Emergency telephone

number

: +1-800-VALVOLINE (+1-800-825-8654)

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture



Valvoline™ HIGH MILEAGE with MaxLife™
Technology SAE 10W-30 Synthetic Blend Motor
Oil

Version: 2.0 Revision Date: 06/14/2023 Print Date: 06/21/2023

Components

Chemical name	CAS-No.	Concentration (% w/w)
DISTILLATES (PETROLEUM),	64742-54-7	>= 50 - < 60
HYDROTREATED HEAVY		
PARAFFINIC		
DISTILLATES (PETROLEUM),	64742-54-7	>= 30 - < 40
HYDROTREATED HEAVY		
PARAFFINIC		
HYDROTREATED LIGHT	64742-55-8	>= 1 - < 1.5
PARAFFINIC DISTILLATE		

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

No symptoms known or expected.

Notes to physician : No hazards which require special first aid measures.

Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

: High volume water jet



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor

Version: 2.0 Revision Date: 06/14/2023 Print Date: 06/21/2023

Hazardous combustion

products

carbon dioxide and carbon monoxide

Further information Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Refer to protective measures listed in sections 7 and 8.

Use personal protective equipment.

Environmental precautions If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Conditions for safe storage Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid No materials to be especially mentioned.

Further information on

storage stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components CAS-No. Value type Control Basis



Valvoline™ HIGH MILEAGE with MaxLife™
Technology SAE 10W-30 Synthetic Blend Motor
Oil

Version: 2.0 Revision Date: 06/14/2023 Print Date: 06/21/2023

		(Form of exposure)	parameters / Permissible concentration	
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Eye protection : Safety glasses

Skin and body protection : Protective suit

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : amber

Odour : mild

Odour Threshold : No data available

pH : No data available



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

Version: 2.0 Revision Date: 06/14/2023 Print Date: 06/21/2023

Melting point/freezing point : No data available

Boiling point/boiling range : $> 424 \, ^{\circ}\text{F} / > 218 \, ^{\circ}\text{C}$

(1013 hPa)

Flash point : $> 390 \, ^{\circ}\text{F} / > 199 \, ^{\circ}\text{C}$

Method: Cleveland open cup

Evaporation rate : < 1

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : < 1.0 mmHg (68 °F / 20 °C)

Relative vapour density : > 1

AIR=1

Relative density : No data available

Density : 0.863 g/cm3 (60.1 °F / 15.6 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : ca. 70 mm2/s (104 °F / 40 °C)

Oxidizing properties : No data available



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

Version: 2.0 Revision Date: 06/14/2023 Print Date: 06/21/2023

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous

reactions

Stable under recommended storage conditions.

No hazards to be specially mentioned.

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Result : Slight, transient irritation

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation Result : Slight, transient irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

Version: 2.0 Revision Date: 06/14/2023 Print Date: 06/21/2023

Assessment : Slight, transient irritation Result : Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment : Slight, transient irritation Result : Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result : Slight, transient irritation

Remarks : Expected based on components.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation
Assessment : No eye irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation
Assessment : No eye irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result : Slight, transient irritation
Assessment : Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

Version: 2.0 Revision Date: 06/14/2023 Print Date: 06/21/2023

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

IARC Group 1: Carcinogenic to humans

Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0

(Mineral oils, untreated or mildly treated)

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP Known to be human carcinogen

Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0

(Mineral Oils: Untreated and Mildly Treated)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

No aspiration toxicity classification

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor

Version: 2.0 Revision Date: 06/14/2023 Print Date: 06/21/2023

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

: NOEC (Fish): 10 mg/l

aquatic invertebrates

(Chronic toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

Version: 2.0 Revision Date: 06/14/2023 Print Date: 06/21/2023

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Persistence and degradability

No data available

Bioaccumulative potential

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n-

octanol/water

: log Pow: Expected > 7

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82

Protection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was

manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +

B).

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG



Valvoline™ HIGH MILEAGE with MaxLife™
Technology SAE 10W-30 Synthetic Blend Motor
Oil

Version: 2.0 Revision Date: 06/14/2023 Print Date: 06/21/2023

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Zinc O,O,O',O'- 2215-35-2 >= 0.1 - < 1 %

tetrakis(1,3dimethylbutyl) bis(phosphorodit

hioate

Zinc, bis[O,O- 4259-15-8 >= 0.1 - < 1 %

bis(2-ethylhexyl) phosphorodithioa to-S,S']-, (T-4)-



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

64742-55-8

Version: 2.0 Revision Date: 06/14/2023 Print Date: 06/21/2023

PHOSPHORODI 84605-29-8 < 0.1 % THIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTY L AND ISO-PR) ESTERS, ZINC SALTS

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

HYDROTREATED LIGHT PARAFFINIC DISTILLATE

US State Regulations

Massachusetts Right To Know

Pennsylvania Right To Know	
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY	64742-54-7
PARAFFINIC `	
PROPRIETARY SUBSTANCE OF HITEC 11188 - 000000276110	Not Assigned
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8
Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl)	2215-35-2
bis(phosphorodithioate	0.1=1.1.00.1
Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Zinc, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-S,S']-, (T-4)-	4259-15-8
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0



TCSI

TSCA

SAFETY DATA SHEET

Valvoline™ HIGH MILEAGE with MaxLife™
Technology SAE 10W-30 Synthetic Blend Motor
Oil

Version: 2.0 Revision Date: 06/14/2023 Print Date: 06/21/2023

	110110111 Date: 00/14/2020		06/21/20
	PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS	84605-29-8	
	DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (<3 % DMSO EXTRACT)	64742-65-0	
	DIPHENYLAMINE	122-39-4	
Maine C	hemicals of High Concern	04740 54 7	
	DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC PHOSPHORODITHIOIC ACID, MIXED 0,0-BIS(1,3-	64742-54-7 84605-29-8	
	DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-	72623-86-0	
	based	12023-00-0	
	DIPHENYLAMINE	122-39-4	
Vermont	Chemicals of High Concern		
	DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	
	PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS	84605-29-8	
	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	
	DIPHENYLAMINE	122-39-4	
Washing	ton Chemicals of High Concern		
	DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	
	PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS	84605-29-8	
	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	
	DIPHENYLAMINE	122-39-4	
Californi	a List of Hazardous Substances		
	DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	
	DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	
Californi	a Permissible Exposure Limits for Chemical Contaminants		
	DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	
	DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	
The com	ponents of this product are reported in the following invent	ories:	

: On the inventory, or in compliance with the inventory

: All substances listed as active on the TSCA inventory



Valvoline™ HIGH MILEAGE with MaxLife™
Technology SAE 10W-30 Synthetic Blend Motor
Oil

Version: 2.0 Revision Date: 06/14/2023 Print Date: 06/21/2023

AIIC : Not in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

ENCS : On the inventory, or in compliance with the inventory

KECI: On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16. OTHER INFORMATION


Further information



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

Version: 2.0 Revision Date: 06/14/2023 Print Date: 06/21/2023

NFPA 704:



Special hazard

HMIS® IV:

HEALTH	1	0
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL -Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS -Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA -National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration;



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

Version: 2.0 Revision Date: 06/14/2023 Print Date: 06/21/2023

NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 06/14/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Internal information: R0355563