



# CYCLO<sup>®</sup> INDUSTRIES, LLC

## MATERIAL SAFETY DATA SHEET

This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this product. Please read the information on these sheets and then provide this information to those people at your company whose responsibility it is to comply with FEDERAL, STATE and COMMUNITY RIGHT TO KNOW regulations. Also, make this information available to any employee who requests it.

If Cyclo Industries, LLC considers the formula of this product to be a trade secret, the exact chemical names of the ingredient(s) and the percentages in which they are combined will not appear in the body of this sheet. The exact composition is available upon request to physicians, industrial hygienists and other health professionals.

### SECTION 1 – PRODUCT & COMPANY IDENTIFICATION

**Product Name:** Cyclo<sup>®</sup> Z•Lube<sup>®</sup> Multi-Purpose Lube, Stock No. C-405

**Product Use:** Displaces moisture, stops squeaks and reduces friction, loosens rusted parts and protects against moisture, rust and corrosion

**Manufactured by:** Cyclo Industries, LLC, 401 Maplewood Drive, Suite 18, Jupiter, FL 33458  
Telephone: (561) 775-9600

**First Aid Emergency:** (800) 752-7869 or (312) 906-6194

**Shipping Emergency:** (800) 424-9300 or (703) 527-3887 (CHEMTREC)

**HMIS Code:** Health = 1      Flammability = 2      Reactivity = 0

### SECTION 2 – COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

CAS Reg. No.	Material	Percentage	Exposure Limits
64742-48-9	Petroleum distillate, odorless mineral spirits	40 – 50	200 ppm = OSHA PEL & ACGIH TLV
64741-44-2	Petroleum distillate	15 – 25	400 ppm = OSHA PEL 200 ppm = ACGIH TLV
64742-52-5	Petroleum oil	10 – 20	5.0 mg/m <sup>3</sup> = OSHA PEL (oil mist)
64742-53-6	Hydrotreated light naphthenic distillate	5 – 10	5.0 mg/m <sup>3</sup> = OSHA PEL (oil mist)
124-38-9	Carbon dioxide	1 – 5	10000 ppm = OSHA PEL 5000 ppm = ACGIH TLV

### SECTION 3 – HAZARDS IDENTIFICATION

#### Effects of Overexposure:

**Skin Contact:** Contact may dry the skin; prolonged contact may cause moderate irritation. Not easily absorbed. Solvent action can dry and defat the skin causing the skin to crack, leading to dermatitis.

**SECTION 3 – HAZARDS IDENTIFICATION continued**

Inhalation: Respiratory irritation, headache nausea, fatigue, drowsiness, impaired co-ordination.  
Eye Contact: Liquid or vapor can cause moderate to severe irritation.  
Ingestion: Not a likely route of exposure. If swallowed, seek immediate medical advice and/or attention.

**Health Hazards:** Acute – eye irritant. Possible skin irritant. Chronic – none known.

**Carcinogenicity:** NTP Carcinogen = No; IARC Monographs = No; OSHA Regulated = No

**Medical Conditions Generally Aggravated By Exposure:** None known.

**SECTION 4 – FIRST AID MEASURES****First Aid Procedures:**

Ingestion: If swallowed, DO NOT induce vomiting. Seek immediate medical advice and/or attention.  
Skin Contact: Wipe off with towel. Wash with soap and water. Get medical attention if irritation persists.  
Inhalation: Remove to fresh air. Administer oxygen if needed. Apply artificial respiration if breathing has stopped. Get medical attention.  
Eye Contact: Wash immediately with large volumes of fresh water for at least 15 minutes. Get medical attention.

**SECTION 5 – FIRE FIGHTING MEASURES**

**Flash Point:** 102°F (39°C)                      **Method Used:** TCC

**Flammable Limits in Air by Volume:** Lower Explosion Limit (LEL) = 0.7 / Upper Explosion Limit (UEL) = 6

**Extinguishing Media:** Foam, CO<sub>2</sub>, dry chemical, water fog.

**Special Fire Fighting Procedures:** Water spray may be ineffective. Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat. If water is used, fog nozzles preferred. Wear goggles and self-contained breathing apparatus.

**Unusual Fire and Explosion Hazards:** Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Vapor accumulation can flash or explode if ignited. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention.

**SECTION 6 – ACCIDENTAL RELEASE MEASURES**

**Spill/Leak Procedures:** Avoid breathing vapors. Ventilate area. Remove all sources of ignition. Clean up area with absorbent material and place in closed containers for disposal.

## SECTION 7 – HANDLING AND STORAGE

**Handling & Storage Procedures:** Store and use in cool, dry, well-ventilated areas. Vapors may cause flash fire. Keep away from heat, sparks and flame. Do not store above 120°F. Do not puncture or incinerate (burn) cans. Do not stick pin, nail or any other sharp object into opening on top of can. Do not spray in eyes. See product label for additional information. **KEEP OUT OF THE REACH OF CHILDREN.**

**Other Precautions:** Use with adequate ventilation. To prevent vapor build-up, open doors and windows or use an explosion-proof exhaust fan to ensure fresh air exchange during and after use. Do not breathe vapor, gas or spray mist. When using, do not eat, drink or smoke. Avoid contact with eyes, skin and clothing. Wear protective equipment. Wash thoroughly after handling. Remove contaminated clothing and wash it before reuse. Empty containers retain product s residues; follow label warnings even after can is emptied. Do not store in basements.

## SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

**Respiratory Protection:** Avoid breathing vapors. Use with adequate ventilation equal to out of doors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use approved air line type respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

**Ventilation:** Sufficient to prevent inhalation of solvent vapors. General dilution and/or local exhaust ventilation in volume or pattern to keep PEL/TLV of most hazardous ingredient below acceptable limit and LEL below stated limit.

**Protective Clothing:** Solvent resistant gloves required for prolonged or repeated use. Solvent resistant aprons or other clothing is recommended.

**Eye Protection:** Safety glasses with splash guards or full face shield is recommended.

**Work/Hygienic Practices:** Eye washes and safety showers in the workplace are recommended.

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

**Boiling Point:** 315°F (157°C)

**Specific Gravity (H<sub>2</sub>O=1):** 0.8

**Vapor Density (Air=1):** Heavier than air

**Solubility in Water:** Nil

**Evaporation Rate (Butyl Acetate = 1):** Slower than ether

**Appearance and Odor:** Aerosol product

**Volatile Organic Compound (VOC) (as packaged minus water):** 49%

## SECTION 10 – STABILITY AND REACTIVITY

**Stability:** Stable

**Conditions to Avoid:** Application to hot surfaces. Storage above 120°F. Exposure to open flame.

### SECTION 10 – STABILITY AND REACTIVITY continued

**Incompatibility (materials to avoid):** Strong oxidizing agents.

**Hazardous Decomposition or Byproducts:** May produce fumes when heated to decomposition. Fumes may contain carbon monoxide and other toxic fumes.

**Hazardous Polymerization:** Will not occur.

### SECTION 11 – TOXICOLOGICAL INFORMATION

**Toxicological Data:** Long-term toxicological studies have not been conducted for this product. See Section 3 of this MSDS for acute symptoms of overexposure and carcinogenicity information.

### SECTION 12 – ECOLOGICAL INFORMATION

**Aquatic/Terrestrial Toxicity Environmental Fate** No data is available at this time.

### SECTION 13 – DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Dispose of in accordance with local, state and federal regulations. Before attempting clean up, refer to other sections of this MSDS for hazard caution information.

### SECTION 14 – TRANSPORT INFORMATION

#### U.S. DOT

**Shipping Description:** Consumer Commodity  
**ID Number:** Not applicable  
**Hazard Class:** ORM-D  
**Packing Group:** Not applicable  
**Label:** Not applicable  
**Placards:** Not applicable

#### IMDG

**Shipping Description:** Aerosols, Ltd. Qty.  
**ID Number:** UN1950  
**Hazard Class:** 2  
**Packing Group:** Not applicable  
**Label:** Not applicable  
**Markings:** Not applicable  
**Placards:** Not applicable

**SECTION 15 – REGULATORY INFORMATION**

**TSCA Inventory:** All components of this product are listed on the Toxic Substance Control Act (TSCA) Inventory of chemical substances maintained by the U.S. Environmental Protection Agency.

**SARA Extremely Hazardous Substances** None

**SARA Section 313** This product does not contain any toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 (SARA 313 – Toxic Chemical Release Reporting)

**CERCLA/Superfund (RQ):** This product is not subject to CERCLA reporting requirements. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

**California Proposition 65:** This product does not contain chemicals known to the State of California to cause cancer, birth defects and other reproductive harm.

**SECTION 16 – OTHER INFORMATION**

**Document Date:** May 20, 2005

**Supersedes:** 10/23/98

**Revisions:** Section 1 – address; Section 2 – component percentages; Section 3 – Flash point and flammable limits; added Sections 11, 12 & 15.

---

Cyclo Industries, LLC provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgement in determining its appropriateness for a particular purpose. Cyclo Industries, LLC makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, LLC will not be responsible for damages resulting from use of or reliance upon this information.