SAFETY DATA SHEET



1. Identification

Product identifier Liquid Wrench Hydraulic Jack Oil

Other means of identification

SDS number M3312

Part No. M3332, M3312
Tariff code 2710.19.3040
Recommended use Hydraulic Fluid
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Blumenthal Brands Integrated, LLC

Address 600 Radiator Road

Indian Trail, NC 28079

Telephone Customer Service/ (704) 821-7643

Technical

Website www.solvewithB.com
E-mail sds@solvewithB.com

Emergency phone number INFOTRAC (United States) (800) 535-5053

INFOTRAC (International) (352) 323-3500

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Reproductive toxicity (fertility, the unborn

child)

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May be harmful if swallowed and enters airways. May damage fertility. May damage the unborn

child.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Category 1A

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information NOTE: This product is a consumer product and is labeled in accordance with the US Consumer

Product Safety Commission regulations which take precedence over OSHA Hazard

Communication labeling. The container label may not include the OSHA label elements listed in this document. Always carefully review the entire SDS and the product label prior to use in the

workplace.

3. Composition/information on ingredients

Mixtures

Chemical name Common name and synonyms		CAS number	%	
Mineral Oil		Mixture	90 - 100	
Calcium Alkaryl Sulfonate		Proprietary	< 0.5	
Calcium Long-chain Alkylphenate Sulfide		Proprietary	< 0.5	
Long-chain Alkenyl Succinimide		Proprietary	< 0.5	
Zinc dialkyldithiophosphate		68649-42-3	< 0.5	
Other components below reportable le	evels		< 1	

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

attendance.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Drink 1 or 2 glasses of water. Do not induce

Direct contact with eyes may cause temporary irritation.

vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and delayed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Indication of immediate medical attention and special treatment needed

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

During fire, gases hazardous to health may be formed.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

General fire hazards

Move containers from fire area if you can do so without risk.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Use standard firefighting procedures and consider the hazards of other involved materials.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Store locked up. Store in tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

JS. OSHA Specifically Regulated S Components	Туре	Value	
CADMIUM (CAS 7440-43-9)	TWA	0.005 mg/m3	
ETHYLENE OXIDE (CAS 75-21-8)	STEL	5 ppm	
,	TWA	1 ppm	
_EAD (CAS 7439-92-1)	TWA	0.05 mg/m3	
US. OSHA Table Z-1 Limits for Air (Contaminants (29 CFR 1910.1	000)	
Components	Туре	Value	
1,4-dioxane (CAS 123-91-1)	PEL	360 mg/m3	
		100 ppm	
PROPYLENE OXIDE (CAS	PEL	240 mg/m3	
75-56-9)		100 ppm	
US. OSHA Table Z-2 (29 CFR 1910.	•		
Components	Туре	Value	Form
CADMIUM (CAS 7440-43-9)	Ceiling	0.6 mg/m3	Dust.
		0.3 mg/m3	Fume.
	TWA	0.2 mg/m3	Dust.
		0.1 mg/m3	Fume.
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
1,4-dioxane (CAS 123-91-1)	TWA	20 ppm	
CADMIUM (CAS 7440-43-9)	TWA	0.01 mg/m3	
		0.002 mg/m3	Respirable fraction.
ETHYLENE OXIDE (CAS 75-21-8)	TWA	1 ppm	
LEAD (CAS 7439-92-1)	TWA	0.05 mg/m3	
PROPYLENE OXIDE (CAS 75-56-9)	TWA	2 ppm	
US. NIOSH: Pocket Guide to Chem			
Components	Туре	Value	
1,4-dioxane (CAS 123-91-1)	Ceiling	3.6 mg/m3	
		1 ppm	
ETHYLENE OVIDE (CAC	Ceiling	9 mg/m3	
		5 ppm	
ETHYLENE OXIDE (CAS 75-21-8)	TWA	5 ppm 0.18 mg/m3	
	TWA		

Material name: Liquid Wrench Hydraulic Jack Oil

SDS US

M3332, M3312 Version #: 04 Revision date: 03-26-2020 Issue date: 05-01-2015

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time	
CADMIUM (CAS 7440-43	-9)5 μg/g	Cadmium	Creatinine in urine	*	
	5 μg/l	Cadmium	Blood	*	
LEAD (CAS 7439-92-1)	200 μg/l	Lead	Blood	*	

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

1,4-dioxane (CAS 123-91-1) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

1,4-dioxane (CAS 123-91-1) Skin designation applies.

US - Tennessee OELs: Skin designation

1,4-dioxane (CAS 123-91-1) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

1,4-dioxane (CAS 123-91-1) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

1,4-dioxane (CAS 123-91-1) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece. Applicable for industrial

settings only.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Applicable for industrial settings only.

Other Use of an impervious apron is recommended. Applicable for industrial settings only.

Chemical respirator with organic vapor cartridge and full facepiece. Chemical respirator with Respiratory protection

organic vapor cartridge and full facepiece if threshold limits are exceeded. Applicable for industrial

settings only.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Liquid Clear. **Appearance**

Physical state Liquid. Liquid. **Form** Color Colorless. Mild Petroleum Odor **Odor threshold** Not available. Not available. Not available. Melting point/freezing point

Initial boiling point and boiling

Not available.

range

> 410.0 °F (> 210.0 °C) Flash point

Evaporation rate Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Material name: Liquid Wrench Hydraulic Jack Oil

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%)

Not available. Explosive limit - upper (%) Not available.

Vapor pressure 0.013 torr @ 25C Vapor density Not available. Not available. Relative density

Solubility(ies)

Solubility (water) Not available. Not available. **Partition coefficient** (n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Viscosity 6.9 cSt

Viscosity temperature 212 °F (100 °C)

Other information

Density 0.9 g/ml @ 15.6 C Not explosive. **Explosive properties**

Flammability class Combustible IIIB estimated

31.7 mm²/s Kinematic viscosity 104 °F (40 °C) Kinematic viscosity

temperature

Oxidizing properties Not oxidizing. Percent volatile 0.3 % estimated -40 °F (-40 °C) Pour point

Specific gravity

VOC 0.35 % estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

M3332, M3312 Version #: 04 Revision date: 03-26-2020 Issue date: 05-01-2015

Species Test Results Components 1,4-dioxane (CAS 123-91-1) **Acute Dermal** LD50 Rabbit 7600 mg/kg Inhalation Rat LC50 46 mg/l, 2 Hours Oral LD50 Rat 5150 mg/kg

CADMIUM (CAS 7440-43-9)

Acute Oral

LD50 Rat 63 - 259 mg/kg

ETHYLENE OXIDE (CAS 75-21-8)

Acute Inhalation

LC50 Rat 1450 ppm, 4 Hours

Oral

LD50 Rat 72 mg/kg

LEAD (CAS 7439-92-1)

Acute Dermal

LD50 Rat > 2000 mg/kg, 24 Hours

Inhalation

LC50 Rat > 5.05 mg/l, 4 Hours

Oral

LD50 Rat > 2000 mg/kg

PROPYLENE OXIDE (CAS 75-56-9)

Acute Dermal

LD50 Rabbit 950 - 1250 mg/kg, 4 Hours

Inhalation

LC50 Mouse 1740 ppm, 4 Hours

Oral

LD50 Rat 380 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. **Serious eye damage/eye** Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

ACGIH sensitization

PROPYLENE OXIDE (CAS 75-56-9)

Dermal sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

1,4-dioxane (CAS 123-91-1) 2B Possibly carcinogenic to humans.

CADMIUM (CAS 7440-43-9)

ETHYLENE OXIDE (CAS 75-21-8)

1 Carcinogenic to humans.

LEAD (CAS 7439-92-1)

PROPYLENE OXIDE (CAS 75-56-9)

2B Possibly carcinogenic to humans.

2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

CADMIUM (CAS 7440-43-9) Cancer ETHYLENE OXIDE (CAS 75-21-8) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

1,4-dioxane (CAS 123-91-1) Reasonably Anticipated to be a Human Carcinogen.

CADMIUM (CAS 7440-43-9) Known To Be Human Carcinogen. ETHYLENE OXIDE (CAS 75-21-8) Known To Be Human Carcinogen.

LEAD (CAS 7439-92-1) Reasonably Anticipated to be a Human Carcinogen. PROPYLENE OXIDE (CAS 75-56-9) Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity May damage fertility. May damage the unborn child.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard**

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results** 1,4-dioxane (CAS 123-91-1) Aquatic Fish LC50 Inland silverside (Menidia beryllina) 6700 mg/l, 96 hours CADMIUM (CAS 7440-43-9) Aquatic Crustacea EC50 Water flea (Daphnia magna) 0.0491 mg/l, 48 hours Fish LC50 Rainbow trout, donaldson trout 0.0024 - 0.0029 mg/l, 96 hours (Oncorhynchus mykiss) ETHYLENE OXIDE (CAS 75-21-8) Aquatic LC50 Fish Fathead minnow (Pimephales promelas) 73 - 96 mg/l, 96 hours

LEAD (CAS 7439-92-1)

Aquatic

Fish LC50 Rainbow trout, donaldson trout 1.17 mg/l, 96 hours

(Oncorhynchus mykiss)

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

1.4-dioxane -0.27ETHYLENE OXIDE -0.3 PROPYLENE OXIDE 0.03

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the Disposal instructions

material under controlled conditions in an approved incinerator. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

D006: Waste Cadmium Hazardous waste code D008: Waste Lead

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Material name: Liquid Wrench Hydraulic Jack Oil

SDS US M3332, M3312 Version #: 04 Revision date: 03-26-2020 Issue date: 05-01-2015

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

1,4-dioxane (CAS 123-91-1)Listed.CADMIUM (CAS 7440-43-9)Listed.ETHYLENE OXIDE (CAS 75-21-8)Listed.LEAD (CAS 7439-92-1)Listed.PROPYLENE OXIDE (CAS 75-56-9)Listed.Zinc dialkyldithiophosphate (CAS 68649-42-3)Listed.

SARA 304 Emergency release notification

ETHYLENE OXIDE (CAS 75-21-8) 10 LBS PROPYLENE OXIDE (CAS 75-56-9) 100 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

CADMIUM (CAS 7440-43-9) Cancer ETHYLENE OXIDE (CAS 75-21-8) Cancer

LEAD (CAS 7439-92-1) Reproductive toxicity

CADMIUM (CAS 7440-43-9) Lung

ETHYLENE OXIDE (CAS 75-21-8)

Reproductive toxicity

LEAD (CAS 7439-92-1)

CADMIUM (CAS 7440-43-9)

ETHYLENE OXIDE (CAS 75-21-8)

LEAD (CAS 7439-92-1)

Central nervous system

Kidney

Mutagenicity

Kidney

CADMIUM (CAS 7440-43-9)

ETHYLENE OXIDE (CAS 75-21-8)

Acute toxicity

Central nervous system

LEAD (CAS 7439-92-1) Blood

ETHYLENE OXIDE (CAS 75-21-8)

LEAD (CAS 7439-92-1)

ETHYLENE OXIDE (CAS 75-21-8)

Skin sensitization
Acute toxicity

Skin irritation
Eve irritation

respiratory tract irritation

Acute toxicity Flammability

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
ETHYLENE OXIDE PROPYLENE OXIDE	75-21-8 75-56-9	10 100	1000 10000		

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
1,4-dioxane	123-91-1	< 0.2	
CADMIUM	7440-43-9	< 0.2	
ETHYLENE OXIDE	75-21-8	< 0.2	
LEAD	7439-92-1	< 0.2	
PROPYLENE OXIDE	75-56-9	< 0.2	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

1,4-dioxane (CAS 123-91-1) CADMIUM (CAS 7440-43-9) ETHYLENE OXIDE (CAS 75-21-8) LEAD (CAS 7439-92-1) PROPYLENE OXIDE (CAS 75-56-9)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

ETHYLENE OXIDE (CAS 75-21-8) PROPYLENE OXIDE (CAS 75-56-9) Safe Drinking Water Act Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

ETHYLENE OXIDE (CAS 75-21-8) Other Flavoring Substances with OSHA PEL's

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including Ethylene Oxide, which are known to the State of California to cause cancer, and Lead, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-dioxane (CAS 123-91-1) Listed: January 1, 1988 CADMIUM (CAS 7440-43-9) Listed: October 1, 1987 ETHYLENE OXIDE (CAS 75-21-8) Listed: July 1, 1987 LEAD (CAS 7439-92-1) Listed: October 1, 1992 Listed: October 1, 1988 PROPYLENE OXIDE (CAS 75-56-9)

California Proposition 65 - CRT: Listed date/Developmental toxin

CADMIUM (CAS 7440-43-9) Listed: May 1, 1997 Ethylene Glycol (CAS 107-21-1) Listed: June 19, 2015 ETHYLENE OXIDE (CAS 75-21-8) Listed: August 7, 2009 Listed: February 27, 1987 LEAD (CAS 7439-92-1)

California Proposition 65 - CRT: Listed date/Female reproductive toxin

ETHYLENE OXIDE (CAS 75-21-8) Listed: February 27, 1987 LEAD (CAS 7439-92-1) Listed: February 27, 1987

California Proposition 65 - CRT: Listed date/Male reproductive toxin

CADMIUM (CAS 7440-43-9) Listed: May 1, 1997 ETHYLENE OXIDE (CAS 75-21-8) Listed: August 7, 2009 Listed: February 27, 1987 LEAD (CAS 7439-92-1)

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,4-dioxane (CAS 123-91-1) CADMIUM (CAS 7440-43-9) ETHYLENE OXIDE (CAS 75-21-8) LEAD (CAS 7439-92-1)

PROPYLENE OXIDE (CAS 75-56-9)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No

Country(s) or region Inventory name On inventory (yes/no)* China Inventory of Existing Chemical Substances in China (IECSC)

Europe European Inventory of Existing Commercial Chemical

Substances (EINECS)

New Zealand Inventory

Europe European List of Notified Chemical Substances (ELINCS) No Japan Inventory of Existing and New Chemical Substances (ENCS) No

Korea Existing Chemicals List (ECL) No New Zealand

Philippines Philippine Inventory of Chemicals and Chemical Substances Nο

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) No Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico No

16. Other information, including date of preparation or last revision

05-01-2015 Issue date 03-26-2020 **Revision date**

Version # 04

HMIS® ratings Health: 2

> Flammability: 0 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 0 Instability: 0

NFPA ratings



Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

> information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Physical & Chemical Properties: Multiple Properties

Material name: Liquid Wrench Hydraulic Jack Oil

SDS US

Nο

No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).