



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/20/2022

 2.2
 03/29/2023
 600000001217
 Date of first issue: 05/09/2016

#### **SECTION 1. IDENTIFICATION**

Product name : CYCLO RED GREASE 6/10.5 OZ

Product code : C123

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 75225

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone num-

ber

1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

Restrictions on use : Use only outdoors or in a well-ventilated area.

#### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable aerosols : Category 1

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ toxicity

- single exposure

Category 3 (Central nervous system)

Aspiration hazard : Category 1

**GHS** label elements

Hazard pictograms :







Signal word : Danger

Hazard statements : Extremely flammable aerosol.

May be fatal if swallowed and enters airways.

Causes skin irritation.

# **CYCLO® RED GREASE**



Version 2.2

Revision Date: 03/29/2023

SDS Number: 60000001217

Date of last issue: 04/20/2022 Date of first issue: 05/09/2016

Causes serious eye irritation.

May cause drowsiness or dizziness.

#### Precautionary statements

#### Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ protective clothing/ eye protection/ face protection.

## Response:

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/ attention.

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

### Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding  $50 \, ^{\circ}\text{C} / 122 \, ^{\circ}\text{F}$ .

## Disposal:

Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards

None known.

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

## **Hazardous components**

Chemical name	CAS-No.	Concentration (% w/w)
Naphtha (petroleum)	64742-49-0	>= 30 - < 50
Acetone	67-64-1	>= 20 - < 30
Xylene	1330-20-7	>= 1 - < 5





Version Revision Date: SDS Number: Date of last issue: 04/20/2022 2.2 03/29/2023 600000001217 Date of first issue: 05/09/2016

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms

and effects, both acute and

delayed

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness.

Suspected of damaging fertility or the unborn child.

Notes to physician : Treat symptomatically.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod: :

ucts

Carbon oxides

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

## CYCLO® RED GREASE



Version Revision Date: SDS Number: Date of last issue: 04/20/2022 2.2 03/29/2023 600000001217 Date of first issue: 05/09/2016

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essarv.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Environmental precautions :

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against :

fire and explosion

: Do not spray on a naked flame or any incandescent material.

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Use only explosion-proof equipment.

Keep away from open flames, hot surfaces and sources of

ignition.

Advice on safe handling : Do not

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Keep container tightly closed in a dry and well-ventilated

olace.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with





Version Revision Date: SDS Number: Date of last issue: 04/20/2022 2.2 03/29/2023 600000001217 Date of first issue: 05/09/2016

the technological safety standards.

Further information on stor-

age stability

: No decomposition if stored and applied as directed.

# **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Naphtha (petroleum)	64742-49-0	TWA	TWA 500 ppm 2,000 mg/m3	
		TWA	400 ppm 1,600 mg/m3	OSHA P0
Acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
Xylene	1330-20-7	TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA 100 ppm		ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m3	OSHA P0
		TWA	100 ppm 435 mg/m3	OSHA P0

# **Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentration	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Xylene	1330-20-7	Methylhip- puric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI

# **CYCLO® RED GREASE**



Version Revision Date: SDS Number: Date of last issue: 04/20/2022 2.2 03/29/2023 600000001217 Date of first issue: 05/09/2016

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES** 

Appearance : aerosol

Colour : red

Odour : solvent-like

Odour Threshold : No data available

pH : No data available

Melting point/range : No data available

Boiling point/boiling range : No data available

Flash point : -97 °C

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

12.8 %(V)

Lower explosion limit / Lower :

flammability limit

1.2 %(V)

Vapour pressure : No data available

Relative vapour density : No data available

Density : 0.745 g/cm3

# **CYCLO® RED GREASE**



Version Revision Date: SDS Number: Date of last issue: 04/20/2022 2.2 03/29/2023 600000001217 Date of first issue: 05/09/2016

Solubility(ies)

Water solubility : slightly soluble

Partition coefficient: n-

octanol/water

: No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Molecular weight : No data available

VOC % By Weight : 49.97 %

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Not applicable

Hazardous decomposition

products

Carbon oxides

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

### Information on likely routes of exposure

Inhalation Eye contact Skin contact Ingestion

## **Acute toxicity**

Not classified based on available information.

#### **Product:**

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 150 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/20/2022

 2.2
 03/29/2023
 600000001217
 Date of first issue: 05/09/2016

Method: Calculation method

**Components:** 

Acetone:

Acute oral toxicity : LD50 (Rat, female): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat, female): 76 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 7,426 mg/kg

Xylene:

Acute oral toxicity : LD50 (Rat): 3,523 - 8,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 6700 ppm

Exposure time: 4 h

Test atmosphere: vapour

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg

Skin corrosion/irritation

Causes skin irritation.

**Product:** 

Remarks: May cause skin irritation in susceptible persons.

**Components:** 

Naphtha (petroleum):

Result: Irritating to skin.

Acetone:

Result: Possibly irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

Xylene:

Assessment: Irritating to skin. Result: Irritating to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

**Product:** 

Remarks: May cause irreversible eye damage.

# **CYCLO® RED GREASE**



Version Revision Date: SDS Number: Date of last issue: 04/20/2022 2.2 03/29/2023 600000001217 Date of first issue: 05/09/2016

### **Components:**

Acetone:

Result: Irritating to eyes. Assessment: Irritating to eyes.

Xylene:

Result: Irritating to eyes.

## Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

**OSHA**No component of this product present at levels greater than or

egual to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

### Reproductive toxicity

Suspected of damaging fertility or the unborn child.

## **Components:**

### Naphtha (petroleum):

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

### STOT - single exposure

May cause drowsiness or dizziness.

### Components:

## Naphtha (petroleum):

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

#### Acetone:

Exposure routes: Inhalation

# **CYCLO® RED GREASE**



Version Revision Date: SDS Number: Date of last issue: 04/20/2022 2.2 03/29/2023 600000001217 Date of first issue: 05/09/2016

Target Organs: Nervous system

Assessment: May cause drowsiness or dizziness.

Xylene:

Assessment: May cause drowsiness or dizziness., May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

**Aspiration toxicity** 

May be fatal if swallowed and enters airways.

**Components:** 

Naphtha (petroleum):

May be fatal if swallowed and enters airways.

Acetone:

May be harmful if swallowed and enters airways.

Xylene:

May be fatal if swallowed and enters airways.

**Further information** 

**Product:** 

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

**SECTION 12. ECOLOGICAL INFORMATION** 

**Toxicity** 

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

**SECTION 13. DISPOSAL CONSIDERATIONS** 

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

# **CYCLO® RED GREASE**



Version Revision Date: SDS Number: Date of last issue: 04/20/2022 2.2 03/29/2023 600000001217 Date of first issue: 05/09/2016

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

#### International Regulations

**IATA-DGR** 

UN/ID No. : UN 1950

Proper shipping name : Aerosols, flammable

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 Packing instruction (cargo : 203

aircraft)

Packing instruction : 203

(passenger aircraft)

**IMDG-Code** 

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

# **National Regulations**

**49 CFR** 

UN/ID/NA number : UN 1950 Proper shipping name : Aerosols

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 ERG Code : 126 Marine pollutant : no

## **SECTION 15. REGULATORY INFORMATION**

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ   Calculated product	
		(lbs)	(lbs)
Acetone	67-64-1	100	100 (F003)
Xylene	1330-20-7	100	100 (F003)
Xylene	1330-20-7	100	*





Version Revision Date: SDS Number: Date of last issue: 04/20/2022 2.2 03/29/2023 600000001217 Date of first issue: 05/09/2016

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

## SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Aspiration hazard

Skin corrosion or irritation

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Reproductive toxicity

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Xylene 1330-20-7 >= 1 - < 5 %


## California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA:



Special hazard

Revision Date : 03/29/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.





Version Revision Date: SDS Number: Date of last issue: 04/20/2022 2.2 03/29/2023 600000001217 Date of first issue: 05/09/2016

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN