



# Material Safety Data Sheet

## Section 1: Product & Company Identification

**Product Name:** Moly-Graph® Extreme Pressure Multi-Purpose Lithium Grease

**Product Number (s):** SL3146

**Manufactured By:**

CRC Industries, Inc.  
885 Louis Drive  
Warminster, PA 18974  
[www.crcindustries.com](http://www.crcindustries.com)

|                            |                |
|----------------------------|----------------|
| General Information        | (215) 674-4300 |
| Technical Assistance       | (800) 521-3168 |
| Customer Service           | (800) 272-8963 |
| 24-Hr Emergency (CHEMTREC) | (800) 424-9300 |

## Section 2: Hazards Identification

### Emergency Overview

Appearance & Odor: Grey semi-solid to solid grease with a faint petroleum odor

As defined by OSHA's Hazard Communication Standard, this product is nonhazardous.

### Potential Health Effects:

**EYE:** May cause irritation.

**SKIN:** Repeated or prolonged contact can result in drying of the skin.

**INHALATION:** Heating can generate vapors that may cause respiratory irritation, nausea and headaches. Inhalation hazard at room temperature is unlikely due to the low volatility of this product.

**INGESTION:** Can cause stomach ache and vomiting. Main hazard, if ingested, is aspiration into the lungs and subsequent pneumonitis.

**CHRONIC EFFECTS:** Unknown

**TARGET ORGANS:** None known

Medical Conditions Aggravated by Exposure:

Skin or respiratory conditions

See Section 11 for toxicology and carcinogenicity information on product ingredients.

**Product Name: Moly-Graph® Extreme Pressure Multi-Purpose Lithium Grease**  
**Product Number (s):**

---

---

**Section 3: Composition/Information on Ingredients**

| COMPONENT                                   | CAS NUMBER | % by Wt.  |
|---|------------|-----------|
| Hydrotreated heavy naphthenic distillates   | 64742-52-5 | 70 - 90   |
| Lithium 12-hydroxystearate                  | 7620-77-1  | 5 – 10    |
| Zinc, dithiophosphate di-C1-14-alkyl esters | 68649-42-3 | 0.5 – 1.5 |
| Molybdenum sulfide                          | 1317-33-5  | 0.2 – 1   |
| Graphite                                    | 7782-42-5  | 0.2 - 1   |

---

**Section 4: First Aid Measures**

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.

Ingestion: Do not induce vomiting. Seek medical attention.

*Note to Physicians:* None available

---

**Section 5: Fire-Fighting Measures**

Flammable Properties: This product is nonflammable.

|                           |               |                        |     |
|---------------------------|---------------|------------------------|-----|
| Flash Point:              | > 400 F (COC) | Upper Explosive Limit: | 7.0 |
| Autoignition Temperature: | ND            | Lower Explosive Limit: | 0.9 |

Suitable Extinguishing Media: CO2, dry chemical, sand, dolomite, alcohol resistant foam, water spray

Products of Combustion: Oxides of carbon. Sulfur.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition. Avoid water in straight hose stream as it will scatter and spread fire.

---

**Section 6: Accidental Release Measures**

Personal Precautions: Use personal protection recommended in Section 8. Minimize skin contact.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush

# Product Name: Moly-Graph® Extreme Pressure Multi-Purpose Lithium Grease

## Product Number (s):

into sewers or storm drains. Advise authorities if product has entered waterways.

Methods for Containment & Clean-up: Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

---

## Section 7: Handling and Storage

Handling Procedures: Keep container away from heat, sparks, and open flame. High temperatures may produce irritating vapors. Eye wash station should be available at work place. Keep containers closed when not in use. Ventilate well, especially in warmer environments.

Storage Procedures: Store in a cool dry area out of direct sunlight. Store separated from acids and oxidizing materials. Store away from sparks and open flame.

Aerosol Storage Level: NA

---

## Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

| COMPONENT   | OSHA |      | ACGIH |      | OTHER |        | UNIT              |
|---|------|------|-------|------|-------|--------|-------------------|
|   | TWA  | STEL | TWA   | STEL | TWA   | SOURCE |                   |
| Hydrotreated heavy naphthenic distillate  | 5*   | NE   | 5*    | 10*  | NE    |        | mg/m <sup>3</sup> |
| Lithium 12-hydroxystearate  | NE   | NE   | NE    | NE   | NE    |        |                   |
| Zinc, dithiophosphate di-C1-14-alkyl esters   | NE   | NE   | NE    | NE   | NE    |        |                   |
| Molybdenum sulfide  | NE   | NE   | 10    | NE   | NE    |        | mg/m <sup>3</sup> |
| Graphite  | 15** | NE   | 2     | NE   | 2.5   | NIOSH  | mg/m <sup>3</sup> |
| N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated * – oil mist ** - mppcf |      |      |       |      |       |        |                   |

Engineering Controls: Area should have ventilation to provide fresh air. Use local exhaust to prevent accumulation of vapors. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations

Respiratory Protection: None required for normal work where adequate ventilation is provided. Use NIOSH-approved self-contained positive pressure respirators in low circulation areas and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as latex or rubber. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

---

## Section 9: Physical and Chemical Properties

**Product Name: Moly-Graph® Extreme Pressure Multi-Purpose Lithium Grease**

**Product Number (s):**

Physical State: semi-solid grease  
Color: grey  
Odor: mild petroleum  
Specific Gravity: 0.90 @ 60 F  
Initial Boiling Point: ND  
Freezing Point: ND  
Vapor Pressure: < 0.1 mmHg @ 68 F  
Vapor Density: > 5 (air = 1)  
Evaporation Rate: < 0.01 (butyl acetate = 1)  
Solubility: Insoluble in water  
pH: NA  
Volatile Organic Compounds: wt %: 0.2 g/L: 1.8 lbs./gal: 0.015

---

**Section 10: Stability and Reactivity**

Stability: Stable  
Conditions to Avoid: None  
Incompatible Materials: Avoid contact with acids and oxidizing substances.  
Hazardous Decomposition Products: Oxides of carbon. Sulfur  
Possibility of Hazardous Reactions: No

---

**Section 11: Toxicological Information**

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

ACUTE EFFECTS

| <u>Component</u>       | <u>Test</u> | <u>Result</u> | <u>Route</u> | <u>Species</u> |
|------------------------|-------------|---------------|--------------|----------------|
| Naphthenic distillates | LD50        | > 5000 mg/kg  | Oral         | Rat            |
| Naphthenic distillates | LD50        | > 2000 mg/kg  | Dermal       | Rabbit         |
| Naphthenic distillates | LC50        | 2.18 mg/L/4H  | Inhalation   | Rat            |

CHRONIC EFFECTS

Carcinogenicity:

|       | <u>Component</u> | <u>Result</u> |
|-------|------------------|---------------|
| OSHA: | None listed      |               |
| IARC: | None listed      |               |
| NTP:  | None listed      |               |

Mutagenicity: None available

Other: Naphthenic distillates Base oils of this product contain < 3% DMSO Extractable total polycyclic aromatic compound (PAC) per IP 346.

**Product Name: Moly-Graph® Extreme Pressure Multi-Purpose Lithium Grease**

**Product Number (s):**

---

**Section 12: Ecological Information**

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: Naphthenic distillates: 48 Hr EC50 Daphnia magna: >1000 mg/L  
Persistence / Degradability: None available  
Bioaccumulation / Accumulation: None available  
Mobility in Environment: None available

---

**Section 13: Disposal Considerations**

Disposal: This product is not a RCRA hazardous waste.

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

---

**Section 14: Transport Information**

Proper shipping description:

US DOT (ground): Not Regulated

Special Provisions: None

---

**Section 15: Regulatory Information**

**U.S. Federal**

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: None

**Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.**

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:

|                       |    |
|-----------------------|----|
| Fire Hazard           | No |
| Reactive Hazard       | No |
| Release of Pressure   | No |
| Acute Health Hazard   | No |
| Chronic Health Hazard | No |

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:  
Zinc compounds (< 1.5%)

**Product Name: Moly-Graph® Extreme Pressure Multi-Purpose Lithium Grease**  
**Product Number (s):**

---

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

**State Regulations**

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: None

State Right to Know:

New Jersey: 1317-33-5  
Pennsylvania: 7782-42-5  
Massachusetts: 1317-33-5, 7782-5  
Rhode Island : 7782-42-5

**Additional Regulatory Information:** None

---

---

**Section 16: Other Information**

NFPA: Health: 1 Flammability: 1 Reactivity: 0  
HMIS: Health: 1 Flammability: 1 Reactivity: 0 PPE: B

Prepared By: Michelle Rudnick  
CRC #: 2127  
Revision Date: 12/05/2006

Changes since last revision: MSDS reformatted in accordance with ANSI Z400.1-2004

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

|       |  |           |                           |
|-------|--|-----------|---------------------------|
| CAS:  | Chemical Abstract Service                                  | NA:       | Not Applicable            |
| ppm:  | Parts per Million  | ND:       | Not Determined            |
| TCC:  | Tag Closed Cup   | NE:       | Not Established           |
| PMCC: | Pensky-Martens Closed Cup                                  | g/L:      | grams per Liter           |
| PPE:  | Personal Protection Equipment                              | lbs./gal: | pounds per gallon         |
| TWA:  | Time Weighted Average                                      | STEL:     | Short Term Exposure Limit |
| OSHA: | Occupational Safety and Health Administration              | COC:      | Cleveland Open Cup        |
| ACGIH | American Association of Governmental Industrial Hygienists |           |                           |
| NIOSH | National Institute of Occupational Safety & Health         |           |                           |
| mppcf | Millions of particles per cubic foot (of air)              |           |                           |