

Safety Data Sheet

Issue Date: 07-May-2018

Revision Date: 24-Aug-20

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Topco Simply Done -20°F Windshield Washer Fluid

Other means of identification

SDS#/Product Code 534526-35

UN/ID No UN1993

Recommended use of the chemical and restrictions on use

Recommended Use Windshield washer fluid.

Details of the supplier of the safety data sheet

Manufacturer Address

FMP
1380 Corporate Center Curve, Suite 200
Eagan, MN 55121
Phone: 888-784-0802

Emergency Telephone Number

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Blue liquid

Physical state Liquid

Odor Alcohol

Classification

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 3
Acute toxicity - Inhalation (Vapors)	Category 3
Specific target organ toxicity (single exposure)	Category 1
Flammable Liquids	Category 3

Signal Word

Danger

Hazard statements

Harmful if swallowed
Toxic in contact with skin
Toxic if inhaled
Causes damage to organs
Flammable liquid and vapor



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Use only outdoors or in a well-ventilated area
 Do not breathe dust/fume/gas/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Keep cool
 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower
 Call a POISON CENTER or doctor if you feel unwell
 Wash contaminated clothing before reuse
 IF INHALED: Remove person to fresh air and keep comfortable for breathing
 Call a POISON CENTER or doctor
 IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell
 Rinse mouth
 IN CASE OF FIRE: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
Methanol	67-56-1	30-32

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First Aid Measures

General Advice	Provide this SDS to medical personnel for treatment.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a poison control center or doctor for treatment advice.
Skin Contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a poison center or doctor/physician if you feel unwell. Wash contaminated clothing before reuse.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.
Ingestion	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Rinse

mouth. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. If large quantities are swallowed, get emergency medical help immediately.

Most important symptoms and effects

Symptoms Harmful if swallowed. Toxic in contact with skin. Toxic if inhaled. Causes damage to organs. Can cause irritation to eyes and mucous membranes. Sore throat, shortness of breath, coughing and congestion. Irritation, itching, dermatitis.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Small Fire Dry chemical. Carbon dioxide (CO₂). Foam.

Large Fire Water spray or fog. Foam.

Unsuitable Extinguishing Media High volume water jet.

Specific Hazards Arising from the Chemical

Flammable liquid and vapor. Vapors may travel to source of ignition and flash back. Closed containers may explode if exposed to extreme heat.

Hazardous Combustion Products Carbon monoxide. Carbon dioxide (CO₂).

Explosion Data

Sensitivity to Static Discharge Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Ventilate area of leak or spill. Use personal protection recommended in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Remove all sources of ignition. No smoking in spill area.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling

Handle in accordance with good industrial hygiene and safety practice. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Keep cool. Wear protective gloves/protective clothing and eye/face protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep container tightly closed and store in a cool, dry and well-ventilated place. Store locked up.

Incompatible Materials

Strong acids. Strong reducing agents. Strong oxidizing agents. Magnesium. Water-reactive materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Methanol 67-56-1	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³

Appropriate engineering controls

Engineering Controls

Apply technical measures to comply with the occupational exposure limits. Showers. Eyewash stations. Local exhaust ventilation recommended.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Wear chemical safety goggles.

Skin and Body Protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory Protection

Under normal conditions, respirator is not normally required. If the exposure limit is exceeded and engineering controls are not feasible, a half face piece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full face piece particulate respirator (NIOSH type N100 filter) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, Glycerin, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full face piece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in Oxygen-deficient atmospheres.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	Odor	Alcohol
Appearance	Blue liquid	Odor Threshold	Not determined
Color	Blue		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	8.0	
Melting point / freezing point	-28.9 °C / -20.02 °F	
Boiling Point / Boiling Range	87 °C / 188.6 °C	
Flash Point	33 °C / 91.4 °F	
Evaporation Rate	2.1	(butyl acetate = 1)
Flammability (Solid, Gas)	Liquid - Not Applicable	
Flammability Limit in Air		
Upper Flammability Limit	6%	
Lower Flammability Limit	36%	
Vapor Pressure	128 hPa	@ 20°C (68°F)
Vapor Density	1.11	(Air=1)
Relative Density	0.952	
Water Solubility	Soluble in water	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Autoignition temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

Other Information

VOC Content	31%
Density	7.9422 lb/gal

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to Avoid

Avoid temperatures exceeding the flash point. Heat, flames and sparks.

Incompatible Materials

Strong acids. Strong reducing agents. Strong oxidizing agents. Magnesium. Water-reactive materials.

Hazardous Decomposition Products

Carbon monoxide. Carbon dioxide (CO₂).

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact	Avoid contact with eyes.
Skin Contact	Toxic in contact with skin.
Inhalation	Toxic if inhaled.
Ingestion	Harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methanol 67-56-1	= 6200 mg/kg (Rat)	= 15800 mg/kg (Rabbit) = 15840 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h = 64000 ppm (Rat) 4 h

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity Based on the information provided, this product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

STOT - single exposure Causes damage to organs.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	331.68 mg/kg
ATEmix (dermal)	995.00 mg/kg
ATEmix (inhalation-dust/mist)	1.66 mg/L
ATEmix (inhalation-vapor)	9.95 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Methanol 67-56-1	-0.77

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

- Disposal of Wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.
- Contaminated Packaging** Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methanol 67-56-1		Included in waste stream: F039		U154

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Methanol 67-56-1	Toxic Ignitable

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT 1 Gallon = Limited Quantity; 55 and 250 Gallon = Fully Regulated (see below)

- UN/ID No** UN1993
- Proper Shipping Name** Flammable liquids, n.o.s. (Methanol)
- Hazard Class** 3
- Packing Group** III

IATA 1 Gallon = Fully Regulated (see below, PI 355); 55 and 250 Gallon = Forbidden

- UN/ID No** UN1992
- Proper Shipping Name** Flammable liquid, toxic, n.o.s. (Methanol)
- Hazard Class** 3
- Subsidiary Hazard Class** 6.1
- Packing Group** III

IMDG 1 Gallon = Limited Quantity; 55 and 250 Gallon = Fully Regulated (see below)

- UN/ID No** UN1992
- Proper Shipping Name** Flammable liquid, toxic, n.o.s. (Methanol)
- Hazard Class** 3
- Subsidiary Hazard Class** 6.1
- Packing Group** III

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
Methanol	X	X	X	X	X	X	X	X

Legend:

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List*
- EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*
- ENCS - Japan Existing and New Chemical Substances*
- IECSC - China Inventory of Existing Chemical Substances*
- KECL - Korean Existing and Evaluated Chemical Substances*
- PICCS - Philippines Inventory of Chemicals and Chemical Substances*
- AICS - Australian Inventory of Chemical Substances*

US Federal Regulations

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Methanol 67-56-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Methanol - 67-56-1	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Methanol 67-56-1	X	X	X

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	Not determined	Not determined	Not determined	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical hazards	Personal Protection
	Not determined	Not determined	Not determined	Not determined

Issue Date: 07-May-2018
Revision Date: 24-Aug-20
Revision Note: Revised Section 14 information

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

ADDITIONAL PRODUCT INFORMATION DISCLOSURE

20 Windshield Washer Fluid

CAS#	Raw Material	Functional Purpose	Lists Of Concern	Links to Lists of Concern
7732-18-5	Water		CA Prop 65 US NTP Reproductive or Developmental Toxicants	https://oehha.ca.gov/proposition-65/proposition-65-list https://ntp.niehs.nih.gov/whatwestudy/assessments/noncancer/completed/index.html
67-56-1	Methanol	Reduces freeze point	CA Non-Cancer Hazards	https://oehha.ca.gov/air/general-info/oehha-acute-8-hour-and-chronic-reference-exposure-level-rel-summary
3734-33-6	Denatonium Benzate	Bittering agent		https://ntp.niehs.nih.gov/ntp/ohat/methanol/methanol_monouraph.pdf
Windshield 1116737*	Patent Blue Dye 18500	Dye/colorant		

*WERKS NUMBER

https://leginfo.ca.gov/faces/jsp/clientsClient.xhtml?_afid=20172018059255