Valvoline.	Page: 1
SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 6/21/2023
	SDS Number: R0074103
Valvoline™ AW 32 HYDRAULIC OIL	Version: 1.3
VV041	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ AW 32 HYDRAULIC OIL

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-VALVOLINE (1-800-825-8654)
Valvoline LLC	, , ,
100 Valvoline Way	Regulatory Information Number
Lexington, KY 40509	1-800-TEAMVAL (1-800-832-6825)
United States of America (USA)	, , ,
1-800-TEAMVAL (1-800-832-6825)	Product Information
,	1-800-TEAMVAL (1-800-832-6825)
	,
SDS@valvoline.com	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	• · · · - • · ·		>=90.00 - <= 100.00
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	>=1.50 - < 5.00

Valvoline	Page: 2
SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 6/21/2023
	SDS Number: R0074103
Valvoline™ AW 32 HYDRAULIC OIL	Version: 1.3
VV041	

SECTION 4. FIRST AID MEASURES

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: No symptoms known or expected.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons

Specific extinguishing

methods

.

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Valvoline	Page: 3
SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 6/21/2023
	SDS Number: R0074103
Valvoline™ AW 32 HYDRAULIC OIL	Version: 1.3
VV041	

for firefighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
HYDROTREATED LIGHT	64742-55-8	TWA	5 mg/m3	OSHA Z-1

Valvoline	Page: 4
SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 6/21/2023
	SDS Number: R0074103
Valvoline™ AW 32 HYDRAULIC OIL	Version: 1.3
VV041	

PARAFFINIC DISTILLATE		Mist	
	TWA	5 mg/m3 Inhalable fraction	ACGIH
	TWA	5 mg/m3 Mist	OSHA P0
	TWA	5 mg/m3 Mist	NIOSH REL
	ST	10 mg/m3 Mist	NIOSH REL
	PEL	5 mg/m3 particulate	CAL PEL

Engineering measures : General room ventilation should be adequate for normal

conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known,

suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear as appropriate:

Safety shoes

Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : amber

Odour : oily

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : > 425 °F / 218 °C

Valvoline	Page: 5
SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 6/21/2023
	SDS Number: R0074103
Valvoline™ AW 32 HYDRAULIC OIL	Version: 1.3
VV041	

(1013 hPa)

Flash point : $> 390 \, ^{\circ}\text{F} / > 199 \, ^{\circ}\text{C}$

Method: Cleveland open cup

Evaporation rate : > 1

Ethyl Ether

Flammability (solid, gas) : No data available

Upper explosion limit : 6 %(V)

Calculated Explosive Limit

Lower explosion limit : 1 %(V)

Calculated Explosive Limit

Vapour pressure : 0.0133333 hPa (21.11 °C)

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 0.863 g/cm3 (15.56 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 30 - 35 mm2/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Valvoline.	Page: 6
SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 6/21/2023
	SDS Number: R0074103
Valvoline™ AW 32 HYDRAULIC OIL	Version: 1.3
VV041	

Conditions to avoid : excessive heat

Incompatible materials : Strong acids

Strong oxidizing agents

Hazardous decomposition

products No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation

Skin contact

Eye Contact

Ingestion

Acute toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation Result : Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment : Slight, transient irritation Result : Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Unlikely to cause eye irritation or injury.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation Assessment : No eye irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result : Slight, transient irritation
Assessment : Slight, transient irritation

Valvoline	Page: 7
SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 6/21/2023
	SDS Number: R0074103
Valvoline™ AW 32 HYDRAULIC OIL	Version: 1.3
VV041	

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

IARC No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

No aspiration toxicity classification

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available

Valvoline.	Page: 8
SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 6/21/2023
	SDS Number: R0074103
Valvoline™ AW 32 HYDRAULIC OIL	Version: 1.3
VV041	

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic

hazard

: Not classified based on available information.

Long-term (chronic) aquatic

hazard

: Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Aquatic invertebrates): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

: NOEC (Fish): 10 mg/l

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment

Short-term (acute) aquatic

hazard

: Not classified based on available information.

Long-term (chronic) aquatic

hazard

: Not classified based on available information.

Persistence and degradability

Components:

No data available

Bioaccumulative potential

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n- : log Pow: Expected > 7

octanol/water

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Valvoline.	Page: 9
SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 6/21/2023
	SDS Number: R0074103
Valvoline™ AW 32 HYDRAULIC OIL	Version: 1.3
VV041	

Product:

Additional ecological

information

: No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods	

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

INTERNATIONAL AIR TRANSPORT ASSOCIATION - LASSENGER				
Not dangerous goods				

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

Valvoline.	Page: 10
SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 6/21/2023
	SDS Number: R0074103
Valvoline™ AW 32 HYDRAULIC OIL	Version: 1.3
VV041	

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
TOLUENE	108-88-3	1000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : No SARA Hazards

California Prop. 65

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" for carcinogenicity as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" for reproductive/developmental toxicity as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory

TSCA list


No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 09/07/2018

Valvoline.	Page: 11
SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 6/21/2023
	SDS Number: R0074103
Valvoline™ AW 32 HYDRAULIC OIL	Version: 1.3
VV041	



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

Valvoline.	Page: 12
SAFETY DATA SHEET	Revision Date: 09/07/2018
	Print Date: 6/21/2023
	SDS Number: R0074103
Valvoline™ AW 32 HYDRAULIC OIL	Version: 1.3
VV041	

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods ISO : International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit P-Statement : Precautionary Statement PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV : Threshold Limit Value TWA : Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System