

# Safety Data Sheet

## SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

### ACDelco Upper Engine and Fuel Injector Cleaner

**Product Use:** Fuel Additive  
**Product Number(s):** 266406

**Company Identification**  
Chevron Products Company  
Global Lubricants  
6001 Bollinger Canyon Rd.  
San Ramon, CA 94583  
United States of America  
www.chevronlubricants.com

#### Transportation Emergency Response

CHEMTREC: (800) 424-9300 or (703) 527-3887

#### Health Emergency

Chevron Emergency Information Center: Located in the USA. International collect calls accepted. (800) 231-0623 or (510) 231-0623

#### Product Information

email : lubemsds@chevron.com

## SECTION 2 HAZARDS IDENTIFICATION

**CLASSIFICATION:** Flammable liquid: Category 4. Aspiration toxicant: Category 1. Eye irritation: Category 2A. Skin irritation: Category 2. Target organ toxicant (central nervous system): Category 3. Target organ toxicant (respiratory irritant): Category 3. Acute aquatic toxicant: Category 3. Chronic aquatic toxicant: Category 3.



**Signal Word:** Danger

**Physical Hazards:** Combustible liquid.

**Health Hazards:** May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.

**Environmental Hazards:** Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS:

**Prevention:** Keep away from heat/sparks/open flames/hot surfaces. -- No smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid release to the environment.

**Response:** IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF SWALLOWED: Immediately call a poison center or doctor/physician. Do NOT induce vomiting. Call a poison center or doctor/physician if you feel unwell. In case of fire: Use media specified in the MSDS to extinguish. Specific treatment (see Notes to Physician on this label).

**Storage:** Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

**Disposal:** Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

### SECTION 3 COMPOSITION/ INFORMATION ON INGREDIENTS

COMPONENTS	CAS NUMBER	AMOUNT
Glycol ether	Trade secret	30 - 60 %weight
Glycol ethers	Trade secret	10 - 30 %weight
01154100-5179P	Trade secret	20 - 30 %weight
01154100-5262P	Trade secret	10 - < 20 %weight

Note that the chemical identity of some or all of the above components is considered confidential business information and is being withheld as permitted by 29 CFR 1910.1200 and various State Right-To-Know Laws.

### SECTION 4 FIRST AID MEASURES

#### Description of first aid measures

**Eye:** Flush eyes with water immediately while holding the eyelids open. Remove contact lenses, if worn, after initial flushing, and continue flushing for at least 15 minutes. Get immediate medical attention.

**Skin:** Wash skin with water immediately and remove contaminated clothing and shoes. Get medical attention if any symptoms develop. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

**Ingestion:** If swallowed, get medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person.

**Inhalation:** Move the exposed person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if breathing difficulties continue.

#### Most important symptoms and effects, both acute and delayed

##### IMMEDIATE SYMPTOMS AND HEALTH EFFECTS

**Eye:** Contact with the eyes causes severe irritation. Symptoms may include pain, tearing, reddening, swelling and impaired vision.

**Skin:** Contact with the skin causes irritation. Skin contact may cause drying or defatting of the skin. Contact with the skin is not expected to cause an allergic skin response. Symptoms may include pain, itching, discoloration, swelling, and blistering. Not expected to be harmful to internal organs if absorbed through the skin. High-Pressure Equipment Information: Accidental high-velocity injection under the skin of materials of this type may result in serious injury. Seek medical attention at once should an accident like this occur. The initial wound at the injection site may not appear to be serious at first; but, if left untreated,

could result in disfigurement or amputation of the affected part.

**Ingestion:** Because of its low viscosity, this material can directly enter the lungs, if swallowed, or if subsequently vomited. Once in the lungs it is very difficult to remove and can cause severe injury or death. May be irritating to mouth, throat, and stomach. Symptoms may include pain, nausea, vomiting, and diarrhea.

**Inhalation:** The vapor or fumes from this material may cause respiratory irritation. Symptoms of respiratory irritation may include coughing and difficulty breathing. Excessive or prolonged breathing of this material may cause central nervous system effects. Central nervous system effects may include headache, dizziness, nausea, vomiting, weakness, loss of coordination, blurred vision, drowsiness, confusion, or disorientation. At extreme exposures, central nervous system effects may include respiratory depression, tremors or convulsions, loss of consciousness, coma or death.

**DELAYED OR OTHER SYMPTOMS AND HEALTH EFFECTS:** Excessive or prolonged exposure to this material may cause central nervous system effects. Symptoms may include headache, dizziness, nausea, vomiting, weakness, loss of coordination, blurred vision, drowsiness, confusion, or disorientation. Extreme exposures may cause respiratory depression, tremors or convulsions, loss of consciousness, coma or death. Contains material that may cause damage to the following organ(s) following repeated exposure based on animal data: Kidney Blood/Blood Forming Organs Risk depends on duration and level of exposure. See Section 11 for additional information.

**Indication of any immediate medical attention and special treatment needed**

**Note to Physicians:** Ingestion of this product or subsequent vomiting may result in aspiration of light hydrocarbon liquid, which may cause pneumonitis. In an accident involving high-pressure equipment, this product may be injected under the skin. Such an accident may result in a small, sometimes bloodless, puncture wound. However, because of its driving force, material injected into a fingertip can be deposited into the palm of the hand. Within 24 hours, there is usually a great deal of swelling, discoloration, and intense throbbing pain. Immediate treatment at a surgical emergency center is recommended.

**SECTION 5 FIRE FIGHTING MEASURES**

Leaks/ruptures in high pressure system using materials of this type can create a fire hazard when in the vicinity of ignition sources (eg. open flame, pilot lights, sparks, or electric arcs). See Section 7 for proper handling and storage.

**EXTINGUISHING MEDIA:** Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

**PROTECTION OF FIRE FIGHTERS:**

**Fire Fighting Instructions:** For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

**Combustion Products:** Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion. Combustion may form oxides of: Nitrogen.

**SECTION 6 ACCIDENTAL RELEASE MEASURES**

**Protective Measures:** Eliminate all sources of ignition in the vicinity of the spill or released vapor. If this material is released into the work area, evacuate the area immediately. Monitor area with combustible gas indicator.

**Spill Management:** Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing

precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. All equipment used when handling the product must be grounded. A vapor suppressing foam may be used to reduce vapors. Use clean non-sparking tools to collect absorbed material. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

**Reporting:** Report spills to local authorities as appropriate or required.

**SECTION 7 HANDLING AND STORAGE**

**Precautionary Measures:** Do not get in eyes, on skin, or on clothing. Liquid evaporates and forms vapor (fumes) which can catch fire and burn with explosive force. Invisible vapor spreads easily and can be set on fire by many sources such as pilot lights, welding equipment, and electrical motors and switches. Fire hazard is greater as liquid temperature rises above 29C (85F). DO NOT USE IN HIGH PRESSURE SYSTEMS in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed.

Do not taste or swallow. Do not breathe vapor or fumes. Wash thoroughly after handling.

**General Storage Information:** DO NOT USE OR STORE near heat, sparks, flames, or hot surfaces . USE AND STORE ONLY IN WELL VENTILATED AREA. Keep container closed when not in use.

**General Handling Information:** Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

**Static Hazard:** Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. For more information, refer to OSHA Standard 29 CFR 1910.106, 'Flammable and Combustible Liquids', National Fire Protection Association (NFPA 77, 'Recommended Practice on Static Electricity', and/or the American Petroleum Institute (API) Recommended Practice 2003, 'Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents'.

**Container Warnings:** Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

**SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

**GENERAL CONSIDERATIONS:**

Consider the potential hazards of this material (see Section 3), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

**ENGINEERING CONTROLS:**

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below the recommended exposure limits.

**PERSONAL PROTECTIVE EQUIPMENT**



**Eye/Face Protection:** Wear protective equipment to prevent eye contact. Selection of protective equipment may include safety glasses, chemical goggles, face shields, or a combination depending on the work operations conducted.

**Skin Protection:** Wear protective clothing to prevent skin contact. Selection of protective clothing may include gloves, apron, boots, and complete facial protection depending on operations conducted. Suggested materials for protective gloves include: Silver Shield, Viton.

**Respiratory Protection:** Determine if airborne concentrations are below the recommended occupational exposure limits for jurisdiction of use. If airborne concentrations are above the acceptable limits, wear an approved respirator that provides adequate protection from this material, such as: Air-Purifying Respirator for Organic Vapors.

Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

**Occupational Exposure Limits:**

Component	Agency	TWA	STEL	Ceiling	Notation
Glycol ethers	ACGIH	20 ppm (weight)	--	--	A3
Glycol ethers	OSHA Z-1	240 mg/m3	--	--	Skin

Consult local authorities for appropriate values.

**SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

**Attention: the data below are typical values and do not constitute a specification.**

- Color:** Green
- Physical State:** Liquid
- Odor:** Amine odor
- Odor Threshold:** No data available
- pH:** No data available
- Vapor Pressure:** No data available
- Vapor Density (Air = 1):** No data available
- Initial Boiling Point:** 315°C (599°F)
- Solubility:** No data available
- Freezing Point:** No data available
- Specific Gravity:** 1.0054 @ 15°C (59°F) (Typical)
- Density:** 1.0098 kg/l @ 15°C (59°F) (Typical)
- Viscosity:** 6.3 cSt @ 40°C (104°F) (Min)
- Coefficient of Therm. Expansion / °F:** 0.00079 (Typical)
- Evaporation Rate:** No data available
- Decomposition temperature:** No Data Available
- Octanol/Water Partition Coefficient:** No data available

**FLAMMABLE PROPERTIES:**

**Flammability (solid, gas):** No Data Available

**Flashpoint:** (Pensky-Martens Closed Cup) 61 °C (141 °F) Minimum

**Autoignition:** No data available

**Flammability (Explosive) Limits (% by volume in air):** Lower: No data available Upper: No data available

**SECTION 10 STABILITY AND REACTIVITY**

**Reactivity:** This material is not expected to react.  
**Chemical Stability:** This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.  
**Conditions to Avoid:** Open flames, sparks, temperatures above the material flash point.  
**Incompatibility With Other Materials:** May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.  
**Hazardous Decomposition Products:** None known (None expected)  
**Hazardous Polymerization:** Hazardous polymerization will not occur.

**SECTION 11 TOXICOLOGICAL INFORMATION**

**Information on toxicological effects**  
**Serious Eye Damage/Irritation:** The eye irritation hazard is based on evaluation of data for product components.  
**Skin Corrosion/Irritation:** The skin irritation hazard is based on evaluation of data for product components.  
**Skin Sensitization:** The skin sensitization hazard is based on evaluation of data for product components.  
**Acute Dermal Toxicity:** The acute dermal toxicity hazard is based on evaluation of data for product components.  
**Acute Oral Toxicity:** The acute oral toxicity hazard is based on evaluation of data for product components.  
**Acute Inhalation Toxicity:** The acute inhalation toxicity hazard is based on evaluation of data for product components.  
**Acute Toxicity Estimate:** Not Determined  
**Germ Cell Mutagenicity:** This product gave negative results in the following mutagenicity assays:  
**Carcinogenicity:** Refer to ADDITIONAL TOXICOLOGY INFORMATION below.  
**Reproductive Toxicity:** The hazard evaluation is based on data for components or a similar material.  
**Specific Target Organ Toxicity - Single Exposure:** The hazard evaluation is based on data for components or a similar material.  
**Specific Target Organ Toxicity - Repeated Exposure:** The hazard evaluation is based on data for components or a similar material.

**ADDITIONAL TOXICOLOGY INFORMATION:**  
This product contains 2-butoxyethanol (2-BE, CAS# 111-76-2). 2-BE is not considered a significant acute or chronic toxicity hazard in humans. A validated physiologically based pharmacokinetic model indicates that humans receiving extensive dermal or inhalation exposure to 2-BE would not receive a toxic dose of

2-butoxyacetic acid (Appl. Occup. Environ. Hyg. 8:580-586, 1993), the metabolite principally responsible for the observed toxicity of 2-BE in laboratory animals.

**SECTION 12 ECOLOGICAL INFORMATION**

**ECOTOXICITY**

This material is expected to be harmful to aquatic organisms and may cause long-term adverse effects in the aquatic environment. The ecotoxicity hazard is based on an evaluation of data for the components or a similar material. The product has not been tested. The statement has been derived from the properties of the individual components.

**MOBILITY**

No data available.

**PERSISTENCE AND DEGRADABILITY**

This material is not expected to be readily biodegradable. The biodegradability of this material is based on an evaluation of data for the components or a similar material. The product has not been tested. The statement has been derived from the properties of the individual components.

**POTENTIAL TO BIOACCUMULATE**

Bioconcentration Factor: No data available.  
Octanol/Water Partition Coefficient: No data available

**SECTION 13 DISPOSAL CONSIDERATIONS**

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by international, country, or local laws and regulations.

**SECTION 14 TRANSPORT INFORMATION**

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

**DOT Shipping Description:** NA1993, COMBUSTIBLE LIQUID, N.O.S. (GLYCOL ETHERS), III

**IMO/IMDG Shipping Description:** NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORTATION UNDER THE IMO/IMDG CODE

**ICAO/IATA Shipping Description:** NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORTATION UNDER ICAO TI / IATA DGR

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code:**  
Not applicable

**SECTION 15 REGULATORY INFORMATION**

<b>EPCRA 311/312 CATEGORIES:</b>	1. Immediate (Acute) Health Effects:	YES
	2. Delayed (Chronic) Health Effects:	NO

- |                                       |     |
|---------------------------------------|-----|
| 3. Fire Hazard:                       | YES |
| 4. Sudden Release of Pressure Hazard: | NO  |
| 5. Reactivity Hazard:                 | NO  |

**REGULATORY LISTS SEARCHED:**

01-1=IARC Group 1	03=EPCRA 313
01-2A=IARC Group 2A	04=CA Proposition 65
01-2B=IARC Group 2B	05=MA RTK
02=NTP Carcinogen	06=NJ RTK
	07=PA RTK

The following components of this material are found on the regulatory lists indicated.

Glycol ether	03, 06, 07
01154100-5262P	05, 07
Glycol ethers	03, 05, 06, 07

**CHEMICAL INVENTORIES:**

All components comply with the following chemical inventory requirements: AICS (Australia), DSL (Canada), EINECS (European Union), KECI (Korea), PICCS (Philippines), TSCA (United States).

One or more components has been notified but may not be listed in the following chemical inventories: ENCS (Japan). Secondary notification by the importer may be required.

**NEW JERSEY RTK CLASSIFICATION:**

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows: PETROLEUM OIL

**SECTION 16 OTHER INFORMATION**

**NFPA RATINGS:** Health: 2 Flammability: 2 Reactivity: 0

**HMIS RATINGS:** Health: 2 Flammability: 2 Reactivity: 0  
 (0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme, PPE:- Personal Protection Equipment Index recommendation, \*- Chronic Effect Indicator). These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or the National Paint and Coating Association (for HMIS ratings).

**REVISION STATEMENT:** This revision updates the following sections of this Safety Data Sheet: 1-16  
**Revision Date:** JULY 22, 2014

**ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:**

TLV - Threshold Limit Value	TWA - Time Weighted Average
STEL - Short-term Exposure Limit	PEL - Permissible Exposure Limit
GHS - Globally Harmonized System	CAS - Chemical Abstract Service Number
ACGIH - American Conference of Governmental	IMO/IMDG - International Maritime Dangerous Goods



Industrial Hygienists	Code
API - American Petroleum Institute	SDS - Safety Data Sheet
HMIS - Hazardous Materials Information System	NFPA - National Fire Protection Association (USA)
DOT - Department of Transportation (USA)	NTP - National Toxicology Program (USA)
IARC - International Agency for Research on Cancer	OSHA - Occupational Safety and Health Administration
NCEL - New Chemical Exposure Limit	EPA - Environmental Protection Agency
SCBA - Self-Contained Breathing Apparatus	

Prepared according to the 29 CFR 1910.1200 (2012) by Chevron Energy Technology Company, 6001 Bollinger Canyon Road San Ramon, CA 94583.

**The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.**